INCH-POUND
MIL-M-24784/11(SH)
6 September 1994
SUPERSEDING
DOD-STD-2139
28 December 1981

ASSOCIATED DETAIL SPECIFICATION

MANUAL, SHIP INFORMATION BOOK (SIB) REQUIREMENTS

This specification is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification contains requirements for the preparation of a Ship Information Book (SIB) that is to be used as a system-level ready reference for use by ship operating, maintenance, and overhaul personnel on board ship and in Navy training schools.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, SEA 03R42, Naval Sea Systems Command, 2531 Jefferson Davis Hwy, Arlington, VA 22242-5160 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N6946 AREA TMSS
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:24Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

MILITARY

MIL-M-24784 - Manual, Technical: General Acquisition and Development Requirements.
MIL-M-24784/1 - Manual, Technical Change Package Requirements.
MIL-M-24784/2 - Manual, Technical Revision Requirements.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Document Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

PUBLICATIONS

DEPARTMENT OF DEFENSE

DoD 5200.1-R - Information Security Program Regulation.
DoD 5220.22-M - Industrial Security Manual for Safeguarding Classified Information.

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for associated detail specifications), the text of this specification shall take precedence. When a generic requirement is in conflict with a unique requirement from the governing associated detail specification, the unique requirement shall take precedence. Nothing in this specification, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General. The Ship Information Book (SIB) shall be developed on an individual ship basis. It shall be complete and detailed as required so that it will serve as the primary intrasystem and intersystem technical publication covering installation and operation of ship systems and equipment. It shall provide a basic reference source, for ships' force, for planning and overhaul yards, for fleet and training commands, and for tenders and other naval activities. Coverage shall include mechanical, heating, ventilation and air conditioning, piping, electrical, and electronics systems and equipment on the ship. It shall provide a thorough understanding of the installations on the ship, together with intrasystem and intersystem capabilities and limitations. It shall contain or provide reference to technical information required by the crew as required for proper operation and maintenance of the systems and equipment covered. Document reference numbers shall be standard throughout all chapters of a volume, that is, reference (1) shall be a reference to the same document throughout the volume. Only very common acronyms shall be used, each of which should be spelled out when first utilized.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:24Z
Check the source to verify that this is the current version before use.

3.1.1 System diagrams. Current system diagrams may be used as the diagrammatics for each chapter. If used, the diagrams shall be revised to remove numbered references, revision symbols, notes that are not applicable, title blocks, and other information extraneous to the SIB. Connection diagrams for connecting major components in a system or plant and other illustrations required shall be prepared. Illustrations shall be neat and legible.

3.1.2 Operating and maintenance instructions. The text shall not include detailed component operating and maintenance instructions which would duplicate those in the system and component technical manuals, but shall instead refer to these technical manuals for operation and maintenance. The text shall, however, include clear instructions relating component operation to the overall system operation [see 3.6.1.3.2g and h and 3.6.2.2]. Reference to the Naval Ships' Technical Manual (NSTM) shall be made where appropriate.

3.2 Security classifications. The overall classification assigned to a technical manual shall agree with the highest classification assigned to any portion within and shall be placed conspicuously at the top and bottom of the Cover/Title page or abbreviated title. Security classification markings shall be in accordance with DoD 5220.22-M and 5200.1-R and shall be placed in accordance with DoD 5220.22-M and 5200.1-R. The security markings shall be the same as for other title pages.

3.3 Deliverable products and data items. The deliverable products and data items shall be specified in the Contract Data Requirements List (CDRL) and shall conform to the requirements specified herein. Data items shall include the following, as applicable:

(a) Outline or book plan.
(b) Review draft copy (RDC).
(c) Preliminary technical manual (PTM).
(d) Final reproducible copy (FRC).
(e) Supplements.
(f) Changes (see 3.3.1).
(g) Revisions (see 3.3.2).
(h) Management data (see 3.3.3).

3.3.1 Change packages. When specified (see 6.2), change packages shall be in accordance with MIL-M-24784/1.

3.3.2 Revisions. When specified (see 6.2), revisions shall be in accordance with MIL-M-24784/2.

3.3.3 Management data. Unless otherwise specified (see 6.2), the following quality assurance data items shall be provided in accordance with MIL-M-24784:

(a) Technical Manual Quality Assurance Program Plan.
(b) Validation Plan.
(c) Validation Certification.
(d) Technical Manual Evaluation Records.
(e) Verification Plan.
(f) Technical Manual Verification Incorporation Certification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:24Z
Check the source to verify that this is the current version before use.

3.4 Arrangement. Unless otherwise specified, the manual shall be arranged in a standardized format (that is, front matter, technical content, appendices, glossaries, indexes and back matter) and appropriately divided by volume, part, chapter and section in accordance with the requirements of MIL-M-24784, Appendix C and the following.

3.4.1 Surface ships.

3.4.1.1 Over 90 meters (300 feet). The SIB shall consist of the following separately bound volumes, or parts of volumes, as applicable, if listed separately below, with the titles as indicated:

(a) Volume 1 - Hull and hull mechanical systems.
(b) Volume 2 - Machinery plant.

(1) Part 1 - Propulsion plant, general design and operating procedures.
(2) Part 2 - Auxiliary machinery, piping, air conditioning, ventilation, and heating systems.

(c) Volume 3 - Power and lighting systems.

(1) Part 1 - General Description and design information of systems.
(2) Part 2 - General description of electrically operated auxiliaries.

(d) Volume 4 - Electronic systems.
(e) Volume 5 - Interior communication systems.

(1) Part 1 - Interior communication systems.
(2) Part 2 - Sound-powered telephone systems, voice tubes, and message passing facilities.

(f) Volume 6 - Weapons control systems.
(g) Volume 7 - Ballasting systems, as applicable.

3.4.1.2 Under 90 meters (300 feet). The SIB may be bound in a single large volume, provided the titles indicated above are clearly separated and indicated (for example, thumb-indexed), and width limitation is not exceeded.

3.4.2 Submarines. The SIB for a submarine shall consist of the following separately bound volumes with titles as indicated:

(a) Volume 1 - General information,
(b) Volume 2 - Tactical facilities,
(c) Volume 3 - Ship control systems,
(d) Volume 4 - Steam and diesel propulsion plant systems,
(e) Volume 5 - Electrical power systems,
(f) Volume 6 - Ship service systems, and
(g) Volume 7 - Hull, mechanical, and ship emergency systems.

Source: https://assist.dla.mil -- Downloaded: 20260-20T02:24Z
Check the source to verify that this is the current version before use.

3.5.3 Axial wire lead terminals. Axial-wire lead terminals shall be as specified

3.4.3 Foreword, preface and introduction. Submittal and routing instructions for reporting of errors and technical manual improvements shall be included in the foreword, preface and introduction in accordance with MIL-M-24784.

3.5 Format and preparation instructions.

3.5.1 Writing style. Unless otherwise specified, the style of writing, level of writing, readability, and referencing shall be in accordance with the requirements of MIL-M-24784, Appendix B.

3.5.2 Safety precautions. Unless otherwise specified, safety and health warnings, cautions and notes shall be in accordance with the requirements of MIL-M-24784, Appendix D.

3.5.3 Tabular material. Unless otherwise specified, the preparation of tables shall be in accordance with the requirements of MIL-M-24784, Appendix E.

3.5.4 Graphics. Unless otherwise specified, the preparation of illustrations, drawings, diagrams and sketches shall be in accordance with the requirements of MIL-M-24784, Appendix F.

3.5.5 Numbering. Unless otherwise specified, the numbering of paragraphs, procedures, divisions, issues, changes, illustrations, tables, and publications shall be in accordance with the requirements of MIL-M-24784, Appendix G.

3.6 Structure of SIB. The SIB shall be arranged in chapters and sections and shall be in accordance with MIL-M-24784. Volumes shall be divided into individually bound parts when required. Content of chapters and sections shall be in accordance with the volume arrangement provided in 3.6.1 and 3.6.2 for surface ships and submarines respectively. Section and subsection content and location may vary within a particular chapter to accommodate necessary or unique data coverage, as specified by the contract.

(a) Data level descriptions. Data presented shall be concise and to the depth necessary for supporting the objectives of the SIB.
(b) Minimum data requirements. The text, illustrations and tables prescribed in this specification reflect minimum SIB requirements. Where the system configuration provides additional capabilities, operating modes or functions, other than covered herein, such additional coverage by text, illustrations and tabulated data shall be provided. Piping system diagrams shall include identification for all valves, either by words or by symbols.

3.6.1 Volume arrangement - Surface ships. Volumes 1 through 7 shall include the following descriptions and guidance:

3.6.1.1 Volume 1. Volume 1 of the SIB shall include a general description of the ship's design characteristics and the major shipboard arrangements and systems. Descriptive material, lists, and illustrations, as applicable, shall be under the appropriate section number and title. Sections shall be in numerical sequence. Each section of the Ship Specification including all drawings and other documents developed therefrom, shall be carefully studied for applicable subject

Source: https://assist.dla.mil -- Downloaded: 20260-20T02:24Z
Check the source to verify that this is the current version before use.

matter for this book. In addition, subjects such as docking and towing, which may not be covered in the Ship Specification but for which specific information is applicable and necessary for ship operation or maintenance, shall be included in the appropriate volume.

3.6.1.2 Volumes 2 through 7. Volumes 2 through 7 of the SIB shall describe ship systems, including design functions, operations, and limitations of each system, interrelationships between systems, troubleshooting, fault-isolation techniques, system check-out, and routine systems maintenance. General or specific information contained in Combat Systems Technical Operations Manual (CSTOM), when prepared, the Naval Ships' Technical Manual (NSTM), and equipment technical manuals, respectively, shall not be repeated in the SIB, except as necessary to fulfill the intent of the text. The following references, if of a permanent nature, shall be provided in the text, where applicable.

(a) Reference to appropriate drawings.
(b) Reference to drawing indices, books, schedules or other manuals such as damage control book, operational station book, schedule of watertight integrity tests and inspections, and equipment manuals.
(c) Cross references between volumes of the SIB, and between sections or chapters within a volume, shall be included only where necessary for continuity, to assist in complete understanding of the text and for avoidance of repetition.

3.6.1.3 Volume 2 - Machinery plant. This volume shall consist of 2 parts.

3.6.1.3.1 Part 1 - Propulsion plant general design and operation procedures. Part 1 shall acquaint and instruct the operators in the operation of the propulsion plant, shall describe the centralized control system, shall contain information and data in appropriate chapters and sections as outlined below, and shall conform, in general, to the sequence of the outline (as applicable to the type of propulsion plant):

(a) List of references including principal equipment manuals or other technical manuals and drawings used in part 1 preparation, table of contents, list of illustrations, and legend of symbols.
(b) Arrangement of machinery, including brief description, arrangement drawings, list of machinery correlated with the arrangement drawings.
(c) Arrangement of operating station enclosure, including associated list of equipment and arrangement drawing.
(d) Machinery components including as a minimum a brief description, design ratings and characteristics including, but not restricted to, the following:

(1) Main boilers:
- Integral accessories such as burners, soot blowers, and safety valves.
- Nonintegral auxiliaries (excluding feedwater and fuel oil) such as forced draft blowers.
- Control systems, including composite diagram of functions such as combustion, feed water, forced draft blower, speed versus air flow, and fuel oil burner characteristic curves.

Source: https://assist.dla.mil -- Downloaded: 2026l0-20T02:24Z
Check the source to verify that this is the currentversion before use.

ccessibility by date code and lot symbol. The manufacturer shall provide for lot tra

(2) Main propulsion turbines:
- Diagram of turbine steam flow and associated valve operation handwheels, and control diagram for one propulsion set.

(3) Propulsion internal combustion engines including control system.
(4) Propulsion electrical system including control system.
(5) Propulsion gas turbines including control system.
(6) Propulsion reduction gear including as applicable:
- Attached lubrication oil pump,
- Shaft turning gear,
- Revolution counter drive,
- Internal instrumentation.

(7) Propulsion shafting and propeller, including as applicable:
- Shaft securing device,
- Shaft brake,
- Uncoupling shaft,
- Thrust bearings,
- Auxiliary thrust device,
- Shaft bearings,
- Fairwaters,
- Rope guards.

(8) Turbine generator (mechanical end only):
- Diagram of turbine steam flow and associated valve operation, handwheels, and control diagram for one turbine generator set.

(9) Distilling plant.
(10) Piping systems, including a brief description, with diagrams and lists of equipment served.
(11) Collecting, holding and transfer system, including a brief description with diagrams.
(12) Main steam:
- List of pressure reducing stations including rating, number, location, equipments served.

(13) Auxiliary steam.
(14) Feed water, including main, booster recirculation control, and differential pressure control.
(15) Main condensate.
(16) Auxiliary condensate.
(17) Other auxiliary systems:
- Lubricating oil,
- Fuel oil service,
- Control air, and Machinery and piping system drainage (LP and HP).

(e) For the above systems and components in part 1, general directions shall be included for operation, with appropriate references to diagrams or other illustrations, for normal operation, split plant operation, emergency operation, and standby operation. These procedures shall be summarized in a condensed manner, for plant-wide operations for the following conditions:

Source: https://assist.dla.mil -- Downloaded: 2026l0-20T02:24Z
Check the source to verify that this is the currentversion before use.

(1) Standby
(2) Warm-up of main propulsion plant
(3) Underway, cruising
(4) Underway, full power
(5) Secure, main propulsion plant
(6) Moored at pier, using shore electric power and steam.

3.6.1.3.2 Part 2 - Auxiliary machinery, piping, environmental pollution control, air conditioning, ventilation and heating systems. The systems and components in part 2 shall be described in a manner to permit understanding of their intended functions, operations, and limitations. A chapter shall be devoted to each piping system, each independent auxiliary machinery plant, each air conditioning, ventilation, and heating system and an overall chapter pertaining to pumps. Wherever reference is made to a piping component, the component designation as specified in the Ships Specification shall be included. An index of all tests, inspections, cleaning requirements, adjustments and safety precautions, referred to in each chapter, shall be included at the end of each chapter, and shall refer to the page of the text where each is used. Tables shall be included showing the time required to flood and drain each damage control void and the time required to ballast and deballast each fuel and ballast tank or both, as applicable to expedite fueling-at-sea. The liquid loading instruction shall describe the manner in which protection against fragment damage can be maintained as ship fuel and aviation fuel are pumped down. The chapter on pumps shall be similar in format to the pump tables in section 503 of the Ship Specification and shall reference, in addition to the information contained in those tables, the applicable technical manual, compartment name and number of space containing each pump, title of system in which pump is located and the applicable SIB chapter number of the system. The chapter shall be categorized into the following subsections, as applicable: centrifugal, rotary, reciprocating, attached, and portable. The schedule for preparation of volume 2, part 2 shall permit issue of approved preliminary chapters at least 1 month prior to the operational check of the associated system. Part 2 shall include, but is not restricted to the following:

(a) Auxiliary machinery plants:

(1) Auxiliary boilers,
(2) Refrigeration machinery,
(3) Air conditioning machinery,
(4) Steering system,
(5) Bow transfer system (where applicable) and,
(6) Fin stabilizer machinery (where applicable).

(b) Air conditioning, ventilation and heating systems - Section 512:

(1) Recirculating,
(2) Supply,
(3) Exhaust,
(4) Maintenance,
(5) Filter locations,
(6) Filter and duct cleaning instructions and,
(7) Collective Protection System (CPS) (where applicable).

Source: https://assist.dla.mil -- Downloaded: 2026l0-20T02:24Z
Check the source to verify that this is the currentversion before use.

(c) Piping systems - One chapter for each type system as described in the noted section of the Ship Specification, as applicable:

(1) Steam - Section 253 and Section 517.
(2) Feed and condensate - Section 255 and/or Section 517.
(3) Sea water cooling - Section 256 and/or Section 521.
(4) Lubricating oil - Section 262.
(5) Fire main and sea water sprinkling - Section 521.
(6) Plumbing drainage, deck drainage, and so forth - Section 528.
(7) Main, secondary and special drainage - Section 529.
(8) Fresh water - Section 532.
(9) Machinery and piping systems drainage - Section 534.
(10) Ship fuel - Section 541.
(11) Aviation fuel and gasoline - Section 542.
(12) Compressed air - Section 551.
(13) Compressed gas - Section 552.
(14) Fire extinguishing - Section 555.
(15) Special - Section 558.

(d) Pumps - Section 503.
(e) Environmental pollution control system - Section 593:

(1) Sewage systems,
(2) Waste water systems,
(3) Solid waste system,
(4) Oil pollution control system,
(5) Air pollution control system, and,
(6) Chemical and industrial waste system.

Except for the chapter on pumps described above, each chapter shall be subdivided into three sections as follows:

(f) Section I - Description and principles of operation. This section shall be further subdivided into the three units described below:

(1) Unit 1 - Introduction. This unit shall cover the purpose, general description and major design characteristics of the system characteristics of the system or independent auxiliary machinery plant, and shall include a diagrammatic, schematic drawing, or both.
(2) Unit 2 - Detailed description. This unit shall discuss the overall system or independent auxiliary machinery plant components, and its controls, instruments and its protective devices. Interrelationship between system components and the overall system or related companion system shall be included.
(3) Unit 3 - Principles of operation. This unit shall describe system or independent auxiliary machinery plant operations, list applicable precautions and discuss applicable operating stations. This unit shall convey information in an explanatory and descriptive manner as to what operations can be performed by or with the system or independent auxiliary machinery plant. Reference shall be made to corresponding

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:24Z
Check the source to verify that this is the current version before use.

operating instructions in section II for detailed step-by-step instructions, as applicable. Operations shall be discussed under the headings of Normal, Starting, Securing, Infrequent, Abnormal and Emergency. Abnormal operation shall be defined as an operation that results when specific equipment or components of a system or independent auxiliary machinery plant is not available for service. Emergency operation shall be defined as that operation performed as a result of a malfunction or maloperation of a system or component, the consequences of which prevent or seriously restrict the operation of the system or independent auxiliary machinery plant or jeopardizes the safety of ship, personnel or both.

(g) Section II - Operating instructions. This section shall be further subdivided into the four units described below:

(1) Unit 1 - Introduction. This unit shall simply describe the content of the section and reference the principles of operation described in section I.

(2) Unit 2 - Initial conditions and precautions. This unit shall specify those initial conditions that provide a starting point for each operating instruction and shall caution and instruct the operator so that he fully understands the extent of the operation to be performed and its effect on system and independent auxiliary machinery plant conditions, and that he shall ascertain whether or not the instruction can be accomplished without conflicting with other operations. Initial conditions shall be based on valve lineup shown on system and independent auxiliary machinery plant diagrams for normal operations.

(3) Unit 3 - Procedures. This unit shall cover detailed step-by-step procedures for performing the operations of the operating instruction under normal conditions. Where necessary, steps or instructions shall be emphasized by the use of "NOTE:" "CAUTION" or "WARNING" to ensure safe procedures (see MIL-M-24784). Each operating instruction shall be provided with a minimum valve lineup- table for performing the instruction or portion thereof. Procedures shall specify which steps may be performed in any sequence or in parallel. Procedures shall also include statements which permit the crew to omit certain steps under certain conditions, while still ensuring that crucial steps are performed in proper sequence. In addition, procedures shall be written to permit the crew to enter a procedure at any point, provided the conditions at that point are the same as they would have been had the procedure been performed starting from the initial condition stated in the procedure. Operating procedures in each chapter shall be based on the following format:

- Initial conditions,
- Precautions,

Source: https://assist.dla.mil -- Downloaded: 20260-20T02:24Z
Check the source to verify that this is the currentversion before use.

- Summary check list (for immediate action on casualties only);
- Operations flow diagrams (for complex evolutions only),
- Detailed procedure, and,
- Notes and references to other operating instructions within the volume shall be minimized. Wherever possible, operating procedures shall be written to cover a single evolution and shall not contain extra steps intended to make the procedure cover more than one evolution.

(4) Unit 4 - Back-up operation. This unit shall be used for those systems and independent auxiliary machinery plants that have back-up methods of operation and shall be addressed as being performed only when the procedures of Unit 3 are not practicable or possible. Back-up operations relating to the failure of any component or system that forms part of the HVAC portion of the Collective Protection System (CPS) shall be exactly delineated, especially with respect to the loss of pressurization in a CPS zone.

(h) Section III - Maintenance. This section shall be further subdivided into the three units described below:

(1) Unit 1 - Principles of maintenance. This unit shall cover and discuss the importance proper maintenance has in retaining system and independent auxiliary machinery plant capability; discuss items which are generally applicable to a wide range of maintenance operations, such as cleanliness, lubrication and isolation criteria; reference sources of additional maintenance information; provide general precautions for performing maintenance; and shall define and briefly discuss maintenance instructions and maintenance procedures.

(2) Unit 2 - Maintenance instructions. This unit shall provide specific maintenance instructions for system-independent subsystems and independent auxiliary machinery plant. Each instruction shall have breakdowns on general information, precautions, preventive maintenance, troubleshooting and corrective maintenance. A preventative maintenance summary table shall be provided for each instruction. Preventive maintenance instructions shall be retained in this unit until formal implementation of the 3-M planned maintenance system (PMS).

(3) Unit 3 - Maintenance procedures. This unit shall contain maintenance operations of a general nature, such as hydrostatic testing, component handling, routinely performed tests, and adjustment procedures for special system cleaning and preventative maintenance operations.

3.6.1.4 Volume 3 - Power and lighting systems. This volume shall consist of two parts.

3.6.1.4.1 Part 1 - General description and design information of systems. The following shall be a guide for format and applicable subject matter:

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:24Z
Check the source to verify that this is the current version before use.

(a) Generating plant - A description shall be given, including tables and illustrations included where necessary, of ship service, emergency, and special systems:

(1) Type, size, and location of generators,
(2) Temperature rises to be expected at various points in the generator during normal operation, and methods of measuring temperature by use of the thermocouples in the stator of the generator.
(3) Use of space heaters within the generator during periods of shutdown,
(4) Type of voltage regulator, method of regulation, and degree of voltage regulation.
(5) Prime mover information including kind, rating, speed, reduction gear data, and manufacturer,
(6) Type of governor and method of regulation, degree of frequency regulation, and generator load balancing features,
(7) Overload and unbalance ratings of the generators including the short time overload ratings and special overload requirements, if any, the allowable phase unbalance for three phase generators, and allowable unbalance for three wire, dc generators.
(8) Brief power analysis to show what loads may be expected during various conditions of operation including the event of loss of part of the generating capacity, and
(9) Instructions for operating the system under split plant or parallel conditions, proper bus tie connections for the various shipboard conditions, and the number of ship service generators which may be operated safely in parallel without exceeding the interrupting capacity of the circuit breakers shall be specified. A note shall be added that this will not limit the number of ship service generators which may be paralleled momentarily for transfer of load or synchronizing. It is not intended that detail instructions be included for the operation of the generator itself such as method of starting, controlling, and paralleling.

(b) Distribution system - A description shall be given and illustrations included where specified, for ship's service emergency, special, power and lighting systems.
(c) Type of distribution.

(1) A statement of the method of distributing the electric power, covering for example, that the system is of the radial type consisting of switchboards, load centers and power panels, bus ties, feeders, mains, and submains.
(2) A schematic wiring diagram as well as written descriptive material of the ship service, emergency and special electric power distribution systems, and including the following but showing nothing beyond the power panel or individual load supplies by each feeder emanating from the ship service switchboards, emergency switchboards, or load center switchboard:

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:24Z
Check the source to verify that this is the current version before use.

- Switchboard bus arrangement,
- Generators (ship service, emergency, and special), motor generator sets, solid state frequency changers (including electronics, aircraft servicing, interior communication, and weapons control),
- Bus ties and bus feeders,
- Shore power connections,
- Line voltage regulators,
- Voltage and frequency monitors,
- Rectifiers,
- No break power supplies,
- Feedback circuits,
- Transformers (lighting and interior communication),
- Circuit breakers, (types, size, and element ratings),
- Feeder designation with name and designation of load centers, power panels, transformers, or individual loads served, and
- Generator prime mover types.

(3) A diagram showing the normal, alternate, and emergency feeders to the following loads:

- Steering gear,
- Weapons systems,
- Electronic systems,
- Main drainage pumps and fire pumps, and
- Interior communication switchboards.

(4) In addition, bus ties and other interconnections shall be shown. For special types of ships, other loads shall be shown that are considered of the same order of importance as those listed above. This diagram shall show the loads, switchboards, and generators in block form with no interior connections or details such as circuit breakers or bus arrangements and shall show each of these elements at their approximate frame location. No effort shall be made to differentiate between different deck levels. The cables shall be shown in their actual location only insofar as they are to port, center, or starboard. For ships with three decks or platform levels or less (excluding superstructure), a wiring deck plan of the power systems shall be included. For all other ships, an isometric diagram of the power systems shall be provided.

(d) Switchboard - A description shall be given and illustrations included, where specified.

(1) Number and location.
(2) Use of each unit or section, for example, whether for generator, bus tie, or distribution.
(3) Any special features applying to switchboards, such as: Automatic operation of the emergency generating plant, Feedback arrangements, and Current controlled contactors.

Source: https://assist.dla.mil -- Downloaded: 20260-20T02:24Z
Check the source to verify that this is the current version before use.

(4) Precautions to prevent paralleling of emergency generators with each other or with other generators, or the requirements for paralleling, if so specified.
(5) Requirements for paralleling with shore power.

(e) Central Control Console (where applicable) - A description shall be given and illustrations included, where specified.

(1) Location.
(2) Use of the unit (equipment or systems controlled or monitored).
(3) Any special features, such as:

- Relinquishing control to a local switchboard, automatic paralleling.

(4) Requirements for paralleling operating generators with shore power.
(5) Precautions to prevent loss of electrical plant if the Central Control Console is lost.

(f) Protective devices - A description shall be given and the following illustrations included:

(1) A circuit breaker coordination chart shall be prepared showing the time-current characteristics of all the circuit breakers used in series from the generator to the load on a representative feeder. The bus tie circuit breakers plotted on log-log paper and shall cover the complete range from the long time delay pick-up value of current of the smallest breaker to the instantaneous trip point of the breaker with the highest setting.
(2) The short circuit current characteristics of the generator shall also be shown on this chart. Following are typical examples of the types, sizes, element ratings, and settings of the breaker circuits to be covered for selective tripping:

- Generator connection to switchboard,
- Bus tie,
- Feeder,
- Main and branch,
- Uses of fuses (on both power and lighting circuits),
- Design characteristics of controllers such as:

  - Manual operation,
  - Magnetic operation,
  - Low voltage protection (LVP), and
  - Low voltage release (LVR).

(g) Lighting systems - A description shall be given and illustrations included as applicable:

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:24Z
Check the source to verify that this is the current version before use.

(1) For ships with three decks or platform levels or less (excluding superstructure), a wiring deck plan of the lighting systems shall be included.
(2) For all other ships, an isometric diagram of the lighting distribution system shall be included.
(3) Door switches and light traps for darkened ship operation.
(4) Red illumination, description of its operation and use.
(5) Relay and portable lanterns, description of its operation and use.
(6) Broad band blue illuminations, description of its operation and use.
(7) Navigation and signal light:

- Elementary wiring diagram,
- Outboard profile of the ship showing locations of the lights, and
- Operational procedures.

(8) Lights for night flight operations:

- Elementary wiring diagram,
- Equipment and light location, and
- Operational procedures.

(h) Other systems and miscellaneous - A description shall be given and illustrations included:

(1) Shore power connections:

- Location,
- Reference to power system diagrams,
- Current capacity, and
- Hook-up procedures.

(2) Receptacles for portable connections for portable submersible pumps and portable welding sets:

- An illustration to show the locations and rating of outlets on the plan views of each deck on which outlets are located. In addition, an elevation view at the centerline shall be shown with all outlets as projected on the center plane. Sufficient compartmentation shall be shown to indicate accurately the location of outlets.

(3) Indication of length of cables supplied.
(4) How many cable types and in which repair station they are stowed.
(5) Arrangements for placing in simultaneous operation in each machinery room the maximum number of submersible pumps using the specified number and lengths of portable cables supplied. This shall be shown on both plan and elevation views.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:24Z
Check the source to verify that this is the current version before use.

(6) A drawing showing the location of main wireways on all decks.
(7) Casualty power system: A description of the purpose, scope, limitations, and proper use of this system. An isometric diagram of the complete casualty power system (showing terminals) shall be included.
(8) Degaussing system: A general description of the system with instructions for operation. A sketch illustrating the approximate location of the coils.
(9) Isolated receptacle circuits: A general description of this system including its purpose and need for maintaining high insulation resistance to ground.
(10) Electrical schematic of lighting and outlet circuits and a table showing electrical feeders and breakers by compartment.

3.6.1.4.2 Part 2 - General description of electric equipment and electrically-operated auxiliaries.

(a) This part shall be divided into four chapters as follows:

(1) Chapter 1 - Power equipment,
(2) Chapter 2 - Electric-operated auxiliaries,
(3) Chapter 3 - Lighting equipment, and
(4) Chapter 4 - Miscellaneous equipment (test panels, storage batteries, instruments, and related equipment).

(b) Data, as applicable, for each item of power and lighting equipment, exclusive of power equipment tabulated in Chapter 2, shall be tabulated under the following headings in Chapters 1, 3, and 4:

(1) Name of equipment.
(2) Name of manufacturer.
(3) Number of units.
(4) Location (designating number in accordance with the ship specification).
(5) Electrical data (brief).
(6) Controlling equipment (type and manufacturer).
(7) Reference to applicable technical manuals.
(8) For electric-operated auxiliaries, data shall be tabulated as follows:

- Name of auxiliary,
- Name of manufacturer of electric equipment,
- Number of units,
- Size (power of electric equipment),
- Location (designating number in accordance with the Ship Specification),
- Electrical data (state source of type of electric power supply),
- Controlling equipment (type and manufacturer),
- Reference to applicable technical manuals (electric and mechanical).

Source: https://assist.dla.mil -- Downloaded: 2026l0-20T02:24Z
Check the source to verify that this is the currentversion before use.

(c) Where no technical manual has been provided for an item of equipment, a brief description shall be given in addition to tabulated data relative to the function, purpose, and general features of the equipment. A wiring diagram shall also be included for such equipment.

3.6.1.5 Volume 4 - Electronic systems. Many of the systems or equipment will be included in CSTOM in similar format if prepared for the ship. Information in the CSTOM shall not be repeated in the SIB, except as necessary to fulfill the intent of the text.

3.6.1.5.1 Text. The text shall present a general overall description of the electronic systems installations so that those whose duties require a knowledge of the broad phases, purposes, and functions of the various electronic systems may quickly and easily familiarize themselves with operational capabilities and general characteristics of the installations. The text shall be divided into chapters, each covering a logical grouping of electronic equipment, units, and accessories comprising a particular system installed. Chapters shall be arranged in alphabetical order by system title. Each chapter shall begin with a general discussion of the system. The major emphasis of each chapter, however, shall be on operating capabilities and limitations. Each chapter shall include sufficient description concerning other systems that supply information to or receive information from electronic systems, to permit an understanding of the relationship between the described electronic system and other associated systems.

3.6.1.5.2 Illustrations. Drawings required for clarification shall be included as one of the last chapters.

3.6.1.5.3 Drawings. The following drawings shall be included:

(a) Antenna arrangement (locating all installed antennas and antenna space reservations).
(b) Antenna system (including retractable or tilting masts, mast controls and indicators, transmission lines, connectors, and operating limitations).
(c) Power supply system between distribution centers and electronic equipment and between units of electronic equipment (block diagram).
(d) Radar and IFF system design drawing (block diagram).
(e) Radio communication system design drawing (block diagram).
(f) Sonar system drawing (block diagram).
(g) ECM system design drawing (block diagram).
(h) Navigation system design drawing (block diagram).
(i) Radiac system design drawing (block diagram).
(j) Waveguide isometric wiring diagrams (other isometric wiring diagrams are not required).

3.6.1.5.4 Tables. Table I shall be titled "List of Electronic Equipment Installed" and shall contain data under the following heading:

(a) Model or type number or both.
(b) Location (compartment designation number).

Source: https://assist.dla.mil -- Downloaded: 20260-20T02:24Z
Check the source to verify that this is the current version before use.

3.6.1.6 Volume 5 - Interior communication systems. This volume shall present a general overall description of the interior communication systems and related equipment so that those whose duties require a knowledge of the various installations may easily familiarize themselves with the principal installation and the operational features. The volume shall be divided into two separately bound parts as follows:

3.6.1.6.1 Part 1. Interior communication (IC) systems shall be divided into applicable chapters as follows:

- Chapter 1 - IC switchboards (including IC test switchboards).
- Chapter 2 - Ship control consoles and ship control indicators.
- Chapter 3 - Telephone system, dial.
- Chapter 4 - Amplified voice communications, recording, television, and entertainment systems.
- Chapter 5 - Electrical alarm, safety, and warning systems.
- Chapter 6 - Indicating, order, and metering systems. Throughout part 1, where applicable, systems shall be arranged and listed in alphabetical order according to circuit designations. Circuit designations shall appear to the left of system titles. The description of each installation shall include the following information, as applicable:

(a) Purpose - The text shall describe the basic purpose for which the subject system is installed.
(b) System classification - Importance and readiness classification shall be designated for each system.
(c) Equipment description - A listing of principal system equipments, including switching, shall be provided. The list shall denote equipment type, quantity, location, and the functional end use of each. Where equipments or components (such as loudspeakers and high temperature thermostats), are associated with a specific group or area, they shall be categorized accordingly.
(d) Operation - The system operational capabilities and limitations shall be described in consonance with the applicable shipboard installation drawings. Input and output characteristics of major equipments shall be defined where they affect overall system operation. Special emphasis shall be devoted to modes of operation, transfer, and action-cutout switching to facilitate expedient operational decisions during damage emergencies, equipment failure, and changing requirements in system loads. A single line flow diagram shall be provided to supplement the written text for all systems having complex switching arrangements. Following is a list of systems having complex switching arrangements either singularly or in combination with other systems. The list is not intended to preclude diagrams for other systems, where required, to simplify the operational description:

Source: https://assist.dla.mil -- Downloaded: 20260-20T02:24Z
Check the source to verify that this is the current version before use.

Circuit	System title
HD-HE	Wind direction and speed system
L	Rudder order system
LB	Steering emergency signal system
LC	Gyro compass system
XLC	Auxiliary gyro compass system
LN	Ships inertial navigation system
LV	Ships aircraft inertial automatic navigator alignment system
M	Propeller order system
MB	Engine or motor order system
3MB	Engine control order system
4MB	Propulsion control order system
1MC	General announcing systems
3MC	Aviators' announcing systems
4MC	Damage control announcing system
MS	Remote switching control system
N	Rudder angle indicator system
5N-6N	Emergency rudder angle indicator systems
RC	Catapult signal system
TL	Dead reckoning system
VP	Controllable pitch propeller indicating system
Y	Underwater log system

(e) Flow diagrams - Flow diagrams shall depict transmission of signals from source or origin to destination. Typical flow diagrams, with appropriate reference to tables, may be used for systems containing duplicate subsystems. Directional flow diagrams shall be marked to indicate the specific electrical and mechanical signal characteristics being transmitted. The text, in conjunction with supporting diagrams, shall define the interrelationships between the systems being described and associated systems.

(f) System check-out - System check-out procedures shall be provided to enable periodic evaluation of the system's operational status. A systematic approach shall be included for isolating equipment failure, open circuits, shorts, and grounds in system cabling. Check-out procedures in equipment technical manuals and test memoranda shall be referenced to supplement the description as required.

(g) Power supplies - Voltage, frequency, phase, source, and location of power supply (switch and fuse size not required) shall be identified. A schematic wiring diagram showing switchboard power supplies, bussing, and interties shall be included in the section covering IC switchboards.

(h) Referenced material - Principal installation drawings, technical manuals, and other data pertaining to the installation shall be referenced, where applicable.

3.6.1.6.2 Part 2. Sound-powered telephone systems, voice tubes, and message-passing facilities shall be divided into applicable chapters as follows:

Source: https://assist.dla.mil -- Downloaded: 2026l0-20T02:24Z
Check the source to verify that this is the currentversion before use.

- Chapter 1 - General information
- Chapter 2 - Ship control circuit
- Chapter 3 - Engineers' and damage control circuits
- Chapter 4 - Armaments control and associated circuits
- Chapter 5 - Miscellaneous circuits (not included in above categories)
- Chapter 6 - Voice tubes and message-passing facilities

(a) Chapter 1 shall include information on the telephone systems and types of circuits installed, and the function and use of associated equipment such as plotter's transfer switchboard, amplifiers, tie switches, untie switches, tie lines, and selective switches. A complete list of the telephone circuits (in alphabetical order) and a list of the selective switches shall be included.

(b) Each chapter, 2 through 5, shall describe the function of the associated circuits, and shall include a list of telephones by circuit, and a list of telephones by station. Sound-powered telephone calls provided shall be included in the list of telephones by circuit. A comprehensive description and schematic wiring diagrams shall be provided for those circuits which incorporate special transfer switching.

(c) Chapter 6 shall contain a description and list (including calls) of the voice tubes, and a description and list of the message-passing facilities.

3.6.1.7 Volume 6 - Weapons. All of the systems and equipment shall be in the CSTOM, if prepared for the ship. This volume shall present a general overall description of the weapons control system and special equipment, so that those whose duties require a knowledge of the various installations, may easily familiarize themselves with the principal installation and operational features. The volume shall be divided into chapters as follows:

- Chapter 1 - Weapons control systems.
- Chapter 2 - Weapons control switchboards.

(a) Throughout Chapters 1 and 2, where applicable, systems shall be arranged and listed in alphabetical order according to circuit designations. Circuit designations shall appear to the left of system titles. In general, the description of each installation shall include the following information, as applicable:

(1) Purpose,
(2) Type and location of major units,
(3) Principal features, method of operation (refer to applicable technical manual for detailed descriptions), and transfer and action cutout switching,
(4) Power supplies (switch and fuse sizes not required),
(5) Reference technical manuals,
(6) Reference drawings (principal installation drawings).

Source: https://assist.dla.mil -- Downloaded: 20260-20T02:24Z
Check the source to verify that this is the current version before use.

(b) For a system having an extensive switching arrangement, a simplified schematic wiring diagram shall be provided to supplement the switching description. A schematic wiring diagram showing switchboard power supplies, bussing, and interties shall be included.

3.6.1.8 Volume 7 - Ballasting systems. This volume shall present a comprehensive description, including basic drawings, diagrams, and tabulations, of the arrangement, functions, operational sequences, and limitations of the ballasting systems for ships having extensive ballasting systems, such as LSD and LPD. Where volume 7 is required, a sample volume will be provided for guidance.

3.6.2 Volume Arrangement - Submarines. The SIB for submarines shall be developed on an individual ship basis. The design yard shall prepare the books for the lead ship of the class. Copies shall be made available for use by the fellow yards in indicating individual ship differences. Volumes 1 through 7 shall include the following system descriptions and guidance:

3.6.2.1 Volume 1 - General information. This volume shall provide direct and concise descriptions of the basic design characteristics of the class and shall summarize the purpose and limitations of the major installations, arrangements and systems. Specific operational discussions and details of systems or components shall not be included but shall be referenced to the applicable systems manuals (volumes 2 through 7). Illustrations, in general, shall not duplicate information contained in the Booklet of General Drawings, but may be developed from these drawings where necessary to present simplified arrangement and schematic drawings to supplement the text.

3.6.2.2 Volumes 2 through 7. These volumes shall provide detailed system or component descriptions, including function, design characteristics, principles of operation, modes of operation, maintenance, troubleshooting guides, and system tests, checkouts, and adjustments. Reference lists, instrumentation requirements, and system diagrams shall be included, as necessary, to define or supplement the text. The volumes shall include the following systems:

3.6.2.3 Volume 2 - Tactical facilities:

(a) Torpedo weapons systems,
(b) Periscope systems,
(c) Radar systems,
(d) Sonar systems,
(e) Navigational aid systems,
(f) Radio system,
(g) Teletype system,
(h) Underwater telephone system,
(i) Signaling equipment, and
(j) Signal ejector system.

Source: https://assist.dla.mil -- Downloaded: 20260-20T02:24Z
Check the source to verify that this is the currentversion before use.

3.6.2.4 Volume 3 - Ship control system:

(a) Ballasting including trim and drain,
(b) Hovering and depth control system,
(c) Steering and diving control,
(d) Interior communication, and
(e) Navigation.

3.6.2.5 Volume 4 - Steam and diesel propulsion plant systems:

(a) Steam plant support, and
(b) Diesel plant support.

3.6.2.6 Volume 5 - Electrical power systems:

(a) Electric power sources,
(b) Electric power distribution,
(c) Electric plant control, and
(d) Miscellaneous electrical loads.

3.6.2.7 Volume 6 - Ship service systems:

(a) Compressed air,
(b) Compressed gas,
(c) Hydraulic,
(d) Fresh water,
(e) Air conditioning, ventilation, and atmospheric life support,
(f) Refrigeration,
(g) Snorkel,
(h) Habitability,
(i) Diesel generator support, and
(j) Fuel and compensating water.

3.6.2.8 Volume 7 - Hull, mechanical, and ship emergency systems:

(a) Capstans and anchor handling,
(b) Docking, mooring, and towing,
(c) Rigging,
(d) Handling, and mine clearance,
(e) Outboard lighting,
(f) Lubrication, and
(g) Ships emergency systems.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026l0-20T02:24Z
Check the source to verify that this is the currentversion before use.

4.2 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.3 Quality control. Unless otherwise specified (see 6.2), the quality conformance inspection, Government inspection, validation, verification, technical manual quality assurance (TMQA) program reviews, technical manual evaluation records and rejection requirements shall be in accordance with MIL-M-24784.

5. PACKAGING

5.1 Packaging requirements. Unless otherwise specified (see 6.2), the packaging and preservation requirements for delivery of book plans, review draft copies, preliminary technical manuals, final reproducible copy, technical manuals, replenishment materials, changes and revisions shall be in accordance with MIL-M-24784.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The SIB is intended to be used as a basic reference for ship force; for building, planning and overhaul yards; for fleet and training commands; and for tenders and other Naval activities. It is the primary information source concerning shipboard arrangements and systems.

6.2 Acquisition requirements. Acquisition documents must specify the following:

(a) Title, number, and date of this specification (or any TMCR referencing this specification).
(b) Type of ship.
(c) Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.1.2).
(d) Applicable publication number, classification, and distribution statement (see 3.2).
(e) An outline or book plan must be specified whenever a technical manual is required for a new equipment or system (see 3.3a).
(f) Double column text shall normally be specified. When increased effectiveness of presentation results, a single column format is also acceptable.
(g) A review draft copy (RDC) must always be specified for every new technical manual (see 3.3b). For change procurement, unless changes to the technical manual have been pre-approved (TMDER, ECP, and so forth) by the Government, RDC must be specified.

Source: https://assist.dla.mil -- Downloaded: 2026l0-20T02:24Z
Check the source to verify that this is the currentversion before use.

(h) Specify the number of weeks required for Government review of technical manual deliverables.
(i) Specify a preliminary technical manual when an extended period of use is required prior to Government verification (normally applies to complex equipment and systems only), (see 3.3c).
(j) Final reproducible copy (see 3.3d).
(k) Supplement manuals (see 3.3e) must be specified when:

(1) The classified information can be confined to the supplement manual such that its basic technical manual will be routed as "unclassified".
(2) It augments a technical manual to provide for a different model and can be justified as a cost effective method of promulgation.
(3) It can be justified as a practical method of promulgation.

(l) Changes must be specified only when they pertain to technical manual corrections resulting from a hardware change or modification. They may also be specified if it has been determined that significant omissions of technical data or information has been identified. Do not specify a change to correct minor or editorial corrections. When changes are justified on the above basis, the change package must include the correction of all outstanding temporary or interim changes and may include minor changes (see 3.3f). The change package must be developed in accordance with MIL-M-24784/1.
(m) Whenever the number of change pages is estimated to exceed approximately 25 percent of the total number of pages in the manual, an update revision must be specified (see 3.3g) and developed in accordance with MIL-M-24784\2.
(n) When the total number of pages requiring change exceed approximately 50 percent of the total number of pages in the manual, a complete revision must be specified (see 3.3g) and developed in accordance with MIL-M-24784/2.
(o) What quality assurance and management data items are to be delivered (see 3.3.3, 4.2, 6.4 and MIL-M-24784):

(1) TMQA program.
(2) Validation plan.
(3) Validation certification.
(4) Evaluation records.
(5) Verification plan.
(6) Verification incorporation certification.

(p) When preservation, packing, and marking are other than as specified (see Section 5. PACKAGING).
(q) For classified equipment, attach a DD Form 254 specifying the following:

(1) Security classification.
(2) Downgrading and declassification notification.
(3) Areas requiring security protection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:24Z
Check the source to verify that this is the current version before use.

6.3 Technical manual acquisition. This specification (or a TMCR based on this specification) must be listed on the Contract Data Requirements List (DD Form 1423) in order to acquire the technical manuals described by this specification, except where DoD FAR Supplement 27.475-1 exempts the requirement for a DD Form 1423.

6.4 Consideration of data requirements. The following data requirements should be considered when this specification is applied on a contract. The applicable Data Item Descriptions (DID's) should be reviewed in conjunction with the specific acquisition to ensure that only essential data are requested/provided and that the DID's are tailored to reflect the requirements of the specific acquisition. To ensure correct contractual application of the data requirements, a Contract Data Requirements List (DD Form 1423) must be prepared to obtain the data, except where DoD FAR Supplement 27.475-1 exempts the requirement for a DD Form 1423.

Reference Paragraph	DID Number	DID Title
3.3.3	DI-M-6158	Manual, Technical: Data Research and Analysis Source Data
3.3.3	DI-M-2194	Manual, Technical: Quality Assurance Program Plan
3.3.3	DI-M-2195	Manual, Technical: Validation Plan
3.3.3	DI-M-2196	Manual, Technical: Validation Certification
3.3.3	DI-M-2197	Manual, Technical: Evaluation Record
3.3.3	DI-M-2198	Manual, Technical: Verification Plan
3.3.3	DI-M-2201	Technical Manual Verification Incorporation Certification

The above DID's were those cleared as of the date of this specification. The current issue of DoD 5010.12-L, Acquisition Management Systems and Data Requirements Control List (AMSDL), must be researched to ensure that only current, cleared DID's are cited on the DD Form 1423.

6.5 Definitions. The words or phrases used throughout this specification are defined in MIL-M-24784.

6.6 Subject term (key word) listing.

Maintenance
Operating
Overhaul personnel
Training schools

Review activity:
Navy - EC

Preparing activity:
Navy - SH
(Project TMSS-N242-11)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:24Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:24Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the comment number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of this form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-M-24784/11(SH)	2. DOCUMENT DATE (YYMMDD) 940906

3. DOCUMENT TITLE
MANUAL, SHIP INFORMATION BOOK (SIB) REQUIREMENTS

4. NATURE OF CHANGE (identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) DSN (if applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME Technical Point of Contact (TPOC) MR. MICKEY ANDER, SEA 04TD3 ADDRESS ALL CORRESPONDENCE AS FOLLOWS:	b. TELEPHONE (Include Area Code) (1) Commercial: DSN: TPOC: 703-602-8701 8-332-8701
c. ADDRESS (Include Zip Code) COMMANDER, NAVAL SEA SYSTEMS COMMAND ATTN: SEA 03R42 2531 JEFFERSON DAVIS HIGHWAY ARLINGTON, VA 22242-5160	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403 Falls Church, VA 22041-3466 Telephone 703-756-2340 DSN 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026l0-20T02:24Z
Check the source to verify that this is the currentversion before use.