INCH-POUND

MIL-F-24787/2(SH)
3 September 1993

MILITARY SPECIFICATION

FITTINGS, END, TYPE A, 37° FLARE, REUSABLE FOR FLEXIBLE HOSE ASSEMBLIES

This specification is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers reusable SAE 37° flare end fittings for use with wire or synthetic fiber reinforced rubber hose.

1.2 Classification. The 37° fittings shall be type A (straight nipple). See MIL-F-24787, table III for identification of corresponding hose type (MIL-H-24135 and MIL-H-24136 specification sheet number) for each group number specified herein.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, SEA 03Q42, Naval Sea Systems Command, 2531 Jefferson Davis Hwy, Arlington, VA 22242-5160 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 4730
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:39Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

QQ-N-281 - Nickel-Copper Alloy Bar, Rod, Sheet, Strip, Wire, Forgings, and Structural and Special Shaped Sections.
QQ-N-286 - Nickel-Copper-Aluminum Alloy, Wrought (UNS N05500).
QQ-N-288 - Nickel-Copper Alloy and Nickel-Copper-Silicon Alloy Castings.
QQ-S-633 - Steel Bar, Carbon, Cold Finished and Hot Rolled (General Purpose)

MILITARY

MIL-F-24787 - Fittings, End, Reusable for Flexible Hose Assemblies, General Specification For.
MIL-H-24135 - Hose Synthetic Rubber, Wire Reinforced, for Flexible Hose Assemblies, General Specification for.
MIL-H-24136 - Hose, Synthetic Rubber, Synthetic Fiber Reinforced, for Flexible Hose Assemblies, General Specification for.

(Unless otherwise indicated, copies of the federal and military specifications, standards and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of DoDISS cited in the solicitation. Unless otherwise specified, the issues of the documents not listed in the DoDISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 304 - Standard Specification for Steel Bars, Alloy, Subject to End-Quench Hardenability Requirements (DoD adopted)

A 582 - Standard Specification for Free-Machining Stainless and Heat-Resisting Steel Bars, Hot-Rolled or Cold Finished. (DoD adopted)

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

SOCIETY OF AUTOMOTIVE ENGINEERS (SAE)

AMS 6381 - Steel Tubing, Mechanical 0.95Cr - 0.20Mo. (0.38 - 0.43C (SAE 4140). (DoD adopted)

(Application for copies should be addressed to the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15096.)

(Non-Government standards and other publications are normally available from the organizations which prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:39Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated detail specifications, specification sheets, or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 SAE 37° fittings furnished under this specification shall conform to the requirements of MIL-F-24787 and as specified herein.

3.1.1 Fitting availability. Types A and AL SAE 37° flare fittings are available in the groups and sizes indicated in table I.

TABLE I. SAE 37° flare fitting by group.

Fitting size (hose dash no.)	Fitting group										
	I	II	III	IV	V	VI	VII	VIII	IX	X	XI
4	X							X			X
5								X			
6	X	X						X			X
8	X	X				X		X			X
10	X							X			X
12	X	X				X		X			X
16	X	X	X			X		X			X
20	X		X		X	X		X			X
24	X		X		X	X		X			X
32	X		X		X	X		X			X

Note: X's denote where SAE 37° end fittings are available by group and size.

3.2 Dimensions. Fitting dimensions shall be in accordance with figure 1 and the tables thereto.

3.3 Materials. Fitting materials shall be in accordance with figure 1 and the tables thereto.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:39Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Quality assurance provisions shall be in accordance with MIL-F-24787.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of the manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Sampling for qualification testing.

4.2.1 End fittings. Qualification testing of end fittings shall consist of end fitting samples as specified in table II. For qualification testing, end fittings shall be attached to the appropriate hose indicated in table II.

4.2.1.1 Use on multiple hoses. Where end fittings are indicated for use on multiple hose associated detail specifications, the basic qualification shall be to the associated detail specification having the highest pressure rating. At least one hose sample shall be selected from each additional associated detail specification for the hydraulic impulse test.

Source: https://assist.dla.mil -- Downloaded: 202610-20T02:39Z
Check the source to verify that this is the current version before use.

TABLE II. End fitting samples required.

Group no.	Size hose (dash no.)	No of end fitting samples required	Appropriate hose military specification
I	-8 -32	8 10	MIL-H-24135/1,/5,/6 and /13
II	-8 -16	8 10	MIL-H-24135/2 and /8
III	-16 -32	8 10	MIL-H-24135/3
V	-8 -32	8 10	MIL-H-24135/7
VI	-16 -32	8 10	MIL-H-24135/9
VIII	-8 -32	8 10	MIL-H-24135/10 (-4 TO -32) /12 and MIL-H-24136/3
XI	-8 -32	8 10	MIL-H-24136/2

*If a size larger than -128 is to be offered than that size shall be represented by 6 sample end fittings.

4.2.3 Hose qualification. Hose samples used for the qualification of fittings to this specification shall be qualified to the appropriate associated detail specification and shall be not less than 15 inches long. Where there are no previously qualified hose, the prospective fitting supplier shall work together with a prospective hose supplier to qualify their respective products. (The hose supplier and fitting supplier may be a single source).

4.2.3.1 The quantity of hose samples (15 inch minimum length) required shall be in accordance with table III.

TABLE III. Hose samples required.

Hose size (table II)	No. of hose samples to be provided
Smallest Largest	4 5

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:39Z
Check the source to verify that this is the current version before use.

4.2.4 Hose and end fitting mix. Where there are two or more qualified suppliers of hose to the associated detail specification required for hose samples for the group being qualified, the hose mix shall be in accordance with table IV. Where there is only one previously qualified supplier, the "previously qualified" samples shall come from that supplier.

TABLE IV. Hose and fitting mix when there is one or more qualified suppliers for combined qualification test.

One approved source				
Sample size (dash no.) 4/	No. of hose samples to be provided 1/		No. of end fittings to be provided	
	Qualifier 2/	Appvd 3/ source	Qualifier 2/	Appvd 3/ source
Smallest	2	2	4	4
Largest	3	2	5	5

Two or more approved sources			
Sample size (dash no.)	No. of fittings to be provided by		
	Qualifier 2/	Approved 3/ source #1	Approved 3/ source #2
Smallest	4	2	2
Largest	5	3	2
Sample size (dash no.)	Number of hoses to be provided by		
	Qualifier 2/	Approved 3/ source #1	Approved 3/ source #2
Smallest	2	1	1
Largest	3	1	1

(Hose samples shall be not less than 15 inches in length and shall be coupled on one end with the fitting being submitted for qualification and on the other end with a previously qualified end fitting.)

1/ See table II for appropriate hose sample.
2/ Offeror of hose and fittings or fittings to be qualified.
3/ Approved source - Previously qualified fitting and hose, or fitting or hose.
4/ Satisfactory completion of qualification testing of the samples selected in accordance with tables II, III and IV will qualify the manufacturer for all sizes in this associated detail specification for the group qualified. Qualification will be extended to all fittings under the same group no. under different associated detail specifications.

Source: https://assist.dla.mil -- Downloaded: 202610-20T02:39Z
Check the source to verify that this is the current version before use.

4.2.5 No previously qualified source. Where there is no previously qualified source, all samples for qualification shall come from the prospective qualifier(s).

4.2.6 Sequence of tests on sample hose assemblies shall be as specified in table V. If hoses are being qualified at the same time, the sequence of tests shall be in accordance with the applicable associated detail specification for the hose being qualified. Whichever sequence is used, only those tests in table V below shall apply to end fittings.

TABLE V. Sequence of qualification tests on sample assemblies.

Test sequence (see MIL-F-24787)	Assembly sample numbers								
	Smallest size				Largest size				
	1	2	3	4	5	6	7	8	9
Proof pressure (see 4.6.1)	X	X	X	X	X	X	X	X	X
Hydraulic fluid circulation (see 4.6.2)		X					X		
Impulse test (see 4.6.3) 1/				X	X		X		
Burst test (see 4.6.4)	X		X			X		X	

1/ Were the end fitting group being qualified is used on multiple hoses (see table II), qualification will be extended to the use of the fitting on additional hoses provided at least one sample hose assembly from each of the other group(s) is made up and submitted to the hydraulic impulse test.

5. PACKAGING

5.1 Packaging requirements shall be in accordance with MIL-F-24787.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. End fittings to this specification are intended for use in shipboard or shore to ship piping systems where pressures do not exceed the flange rated working pressure, and temperatures do not exceed that of the applicable hose.

6.2 Acquisition requirements. Acquisition documents should specify the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:39Z
Check the source to verify that this is the current version before use.


(a) Title, number and date of this specification sheet.
(b) Fitting type designation.
(c) Fitting group designation, see table I.
(d) Fitting size, hose X pipe or tube.
(e) Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1 and 2.1.1).
(f) Quantity.

6.3 Subject term (key word) listing.


SAE 37°
Group no.

Preparing activity:
Navy - SH
(Project 4730-N086-2)


Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:39Z
Check the source to verify that this is the current version before use.



TYPE A-----SOLID SOCKET



TYPE A-----RING AND BAND



TYPE A-----BOLT TOGETHER

FIGURE 1. Type A end fittings.

Source: https://assist.dla.mil --Downloaded: 2026-10-20T02:39Z
Check the source to verify that this is the current version before use.

TABLES FOR SOLID SOCKET FITTINGS

TABLE VI. Dimensions for groups I and II solid socket type A.

Hose (dash no.)	Tube size (nom)	T Thread Cl-2B	A max	C nom	G max	M ref
-4	1/4	5/16-20 UNF	2.75	0.563	1.00	0.37
-4	5/16	1/2-20 UNF	2.75	0.625	1.00	0.40
-4	3/8	9/16-18 UNF	3.00	0.688	1.25	0.40
-6	3/8	9/16-18 UNF	3.00	0.688	1.25	0.40
-6	1/2	3/4-16 UNF	3.21	0.875	1.25	0.44
-8	1/2	3/4-16 UNF	3.50	0.875	1.50	0.44
-8	5/8	7/8-14 UNF	3.50	1.000	1.50	0.52
-8	3/4	1-1/16-12 UNF	3.50	1.250	1.50	0.57
-10	5/8	7/8-14 UNF	3.50	1.000	1.50	0.52
-12	3/4	1-1/16-12 UN	4.00	1.250	1.75	0.57
-12	7/8	1-3/16-12 UN	4.00	1.375	1.75	0.58
-12	1	1-5/16-12 UN	4.00	1.500	1.75	0.60
-16	1	1-5/16-12 UN	4.50	1.500	2.25	0.60
-16	1-1/4	1-5/8-12 UN	4.75	2.000	2.25	0.64
-20	1-1/4	1-5/8-12 UN	5.25	2.000	2.75	0.74
-20	1-1/2	1-7/8-12 UN	5.25	2.250	2.75	0.74
-24	1-1/2	1-7/8-12 UN	5.75	2.250	3.00	0.74
-32	2	2-1/2-12 UN	6.75	2.875	3.50	0.93

TABLE VII. Dimensions for group III solid socket type A (-16 size only).

Hose (dash no.)	Tube size (nom)	T Thread CL-2B	A max	C nom	G max	M ref
-16	1	1-5/16-12 UN	5.00	1.50	2.00	0.60

TABLE VIII. Dimensions for group VIII solid socket type A.

Hose (dash no.)	Tube size (nom)	T Thread CL-2B	A max	C nom	G max	M ref
-4	1/4	7/16-20	1.75	0.56	0.62	0.35
-5	5/16	1/2-20	1.90	0.62	0.69	0.38
-6	3/8	5/16-18	2.05	0.69	0.81	0.38
-8	1/2	3/4-16	2.52	0.88	0.94	0.43
-10	5/8	7/8-14	2.80	1.00	1.12	0.51
-12	3/4	1-1/16-12	3.15	1.25	1.25	0.57
-16	1	1-5/16-12	2.28	1.50	1.44	0.60
-20	1-1/4	1-5/8-12	3.00	2.00	1.75	0.64
-24	1-1/2	1-7/8-12	3.28	2.25	1.94	0.74
-32	2-1/2	1-7/8-12	3.88	2.88	2.44	0.76
-40	2-1/2	3- 12	4.16	4.38	3.25	0.80
-48	3	3-1/2-12	4.28	5.00	3.85	0.87

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:39Z
Check the source to verify that this is the current version before use.

Notes for tables VI, VII and VIII.

1. Dimensions are in inches.
2. Fitting assembly materials for swivel nut, socket and hose nipple shall conform to QQ-N-281 or QQ-N-286.
3. Socket (body) alternate material shall conform to QQ-N-288.
4. Socket shall be a one-piece design.

TABLE IX. Dimensions for group III, ring and band socket, type A.

Hose (dash no.)	Tube size (nom)	T thread CL-2B	A max	B nom	C max	M ref
-20	1-1/4	1-5/8-12 UN	6.50	2.00	4.00	0.64
-24	1-1/2	1-7/8-12 UN	7.25	2.25	4.25	0.74
-32	2	2-1/2-12 UN	8.25	2.88	5.25	0.93

NOTES:

1. Dimensions are in inches.
2. Fitting assembly materials for the swivel nut and hose nipple shall conform to QQ-N-281 or QQ-N-286.
3. Socket may be one-piece or multiple segment design, not exceeding the envelope dimensions.
4. Socket alternate materials shall conform to QQ-N-288 or steel conforming to AISI 1035 (segments) or SAE-AISI 4140 (ring and band) in accordance with AMS 6381 as applicable.

TABLE X. Dimensions for group V, ring and band socket, type A.

Hose (dash no.)	Tube size (nom)	T thread CL-2B	A max	B nom	C max	M ref
-20	1-1/4	1-5/8-12 UN	4.95	2.00	4.20	0.64
-24	1-1/2	1-7/8-12 UN	5.60	2.25	4.25	0.74
-32	2	2-1/2-12 UN	6.36	2.88	5.25	0.93

NOTES:

1. Dimensions are in inches.
2. Material for the nipple shall conform to AISI 1137 or AISI 11L37.
3. Material for the socket segments shall conform to AISI 1035 or AISI 1040-1045.
4. Material for the ring and bands shall conform to AISI 4140.
5. Material for the swivel nut shall conform to AISI 11L37 or AISI 1110.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:39Z
Check the source to verify that this is the current version before use.

TABLE XI. Dimensions for group VI, ring and band socket, type A.

Hose (dash no.)	Tube size (nom)	T thread CL-2B	A max	B nom	C max	M ref
-8	1/2	3/4-16	3.87	0.88	1.60	0.44
-12	3/4	1-1/16-12	4.95	1.25	1.78	0.57
-16	1	1-5/16-12	5.39	1.50	2.16	0.60
-20	1-1/4	1-5/8-12	5.10	2.00	2.88	0.64
-24	1-1/2	1-7/8-12	5.63	2.25	3.16	0.74
-32	2	2-1/2-12	6.45	2.88	3.75	0.93

NOTES:
1. Dimensions are in inches.
2. Fitting assembly materials for the swivel nut and hose nipple shall conform to QQ-N-281 or QQ-N-286.
3. Sockets for sizes -8, -12 and -16 shall be a one-piece design. Sockets for sizes -20 and larger may be one-piece design or multiple segment, not exceeding the envelope dimensions.
4. Materials for the sockets shall be QQ-N-281, QQ-N-286, QQ-N-288 or, for sizes -20 and larger steel conforming to AISI-SAE 4140 in accordance with AMS 6381, as applicable.

TABLE XII. Dimensions for group XI, bolt together socket, type A.

Hose (dash no.)	Tube size (nom)	T thread CL-2B	A max	B nom	C max	M ref	X max	W nom
-4	4	7/16-20 UNF	2.75	0.56	1.00	0.37	2.25	0.94
-4	5	1/2-20 UNF	2.75	0.62	1.00	0.40	2.25	0.94
-4	6	9/16-18 UNF	3.00	0.68	1.38	0.40	2.35	0.94
-6	6	9/16-18 UNF	3.25	0.68	1.38	0.40	2.47	0.94
-6	8	3/4-16 UNF	3.25	0.87	1.25	0.44	2.47	0.94
-8	8	3/4-16 UNF	3.50	0.87	1.50	0.44	3.00	1.00
-8	10	7/8-14 UNF	3.50	1.00	1.50	0.52	3.00	1.00
-10	10	7/8-14 UNF	3.75	1.00	1.50	0.52	3.00	1.25
-8	12	1-1/16-12 UN	3.75	1.25	1.50	0.57	3.00	1.25
-12	12	1-1/16-12 UN	4.00	1.25	2.05	0.57	3.50	1.31
-12	14	1-3/16-12 UN	4.00	1.37	2.00	0.58	3.50	1.25
-12	16	1-5/16-12 UN	4.25	1.50	2.00	0.60	3.50	1.62
-16	16	1-5/16-12 UN	4.50	1.50	2.25	0.60	4.81	1.62
-16	20	1-5/8-12 UN	4.75	2.00	2.25	0.64	4.81	1.62
-20	20	1-5/8-12 UN	5.25	2.00	2.75	0.64	4.81	2.00
-20	24	1-7/8-12 UN	5.25	2.25	2.75	0.74	4.81	2.25
-24	24	1-7/8-12 UN	5.75	2.25	3.00	0.74	5.38	2.25
-32	32	1-1/2 12 UN	6.75	2.87	3.50	0.93	5.81	2.88

NOTES:
1. Dimensions are in inches.
2. Fitting assembly materials shall be in accordance with QQ-N-281 or QQ-N-286.
3. Swivel nut may be ASTM A 304 or QQ-S-633.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T02:39Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the comment number and revision letter should be given.

2. The submitter of this form must complete blocks 4, 5, 6, and 7.

3. The preparing activity must provide a reply within 30 days from receipt of this form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-F-24787/2(SH)	2. DOCUMENT DATE (YYMMDD) 930903

3. DOCUMENT TITLE
FITTINGS, END, TYPE A, 37^0 FLARE, REUSABLE FOR FLEXIBLE HOSE ASSEMBLIES

4. NATURE OF CHANGE (identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) DSN (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME Technical Point of Contact (TPOC) MR. CARL BANKS, SEA 03Y23 ADDRESS ALL CORRESPONDENCE AS FOLLOWS:	b. TELEPHONE (Include Area Code) (1) Commercial: DSN: TPOC: 703-602-0367 8-332-0367
c. ADDRESS (Include Zip Code) COMMANDER, NAVAL SEA SYSTEMS COMMAND ATTN: SEA 03Q42 2531 JEFFERSON DAVIS HIGHWAY ARLINGTON, VA 22242-5160	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403 Falls Church, VA 22041-3466 Telephone 703-756-2340 DSN 289-2340

DD FORM 1426, OCT 89 Previous editions are obsolete. 198/290

Source: https://assist.dla.mil -- Downloaded: 20260-20T02:39Z
Check the source to verify that this is the current version before use.