C-B-801H
September 26, 1974
SUPERSEDING
Fed. Spec. C-B-801G
November 18, 1970

FEDERAL SPECIFICATION

BUTTER

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers the requirements for butter for use by agencies of the Federal Government.

1.2 Classification. Butter covered by this specification shall be of the following grades, styles, and classes as specified (see 6.1):

1.2.1 Grades. The butter shall conform to the requirements of the following grades in accordance with the United States Standards for Grades of Butter as specified (see 6.1):

U. S. Grade AA or 93 Score
U. S. Grade A or 92 Score
U. S. Grade B or 90 Score

1.2.2 Styles. The butter shall be of the following styles as specified (see 6.1):

(a) One-pound solid prints (individually wrapped and cartoned).
(b) One-pound solid prints (individually wrapped, uncartoned).
(c) Quarter-pound prints (individually wrapped, 4 per carton).
(d) Quarter-pound prints (individually wrapped, 4 per overwrap).
(e) Patties:
Cuts per pound: 72 or 90
(f) Bulk (60, 64 or 68 pounds net).

1.2.3 Classes. Butter purchased shall be of the classes defined below, as specified (see 6.1):

1.2.3.1 Class 1, fresh, straight lot. Class 1 shall be a shipment of butter of one grade, uniformly packed and marked, manufactured by one creamery and from current production which has not been held more than 30 days from date of churning to date for delivery under the contract. The product shall be held at a temperature not exceeding 40°F. If printed and held more than 10 days after printing, it shall be held at a temperature below 30° F.

FSC 8910

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.

1.2.3.2 Class 2, storage, straight lot. Class 2 shall be a shipment of butter of one grade, uniformly packed and marked, manufactured by one creamery and has been held more than 30 days but not more than 12 months from date of churning to date for delivery under the contract. The butter shall move into storage as soon as possible after date of manufacture but in no case shall the time exceed 15 days, during which time the temperature shall not exceed 40° F. The storage temperature, after the 15 days, shall not be higher than -5°F., although it is recommended that the storage be maintained at -10°F. or lower.

1.2.3.3 Class 3, fresh, miscellaneous lot. Class 3 shall be a shipment of butter of one grade, manufactured by more than one creamery but which otherwise conforms to the requirements of 1.2.3.1.

1.2.3.4 Class 4, storage, miscellaneous lot. Class 4 shall be butter of one grade, manufactured by more than one creamery but which otherwise conforms to the requirements of 1.2.3.2

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

L-C-110	-	Cellophane (Coated and Noncoated, Regenerated Cellulose Film).
L-P-378	-	Plastic Sheet and Strip, Thin Gauge, Polyolefin.
PPP-B-636	-	Boxes, Shipping, Fiberboard.
PPP-B-1163	-	Box, Corrugated Fiberboard, High Compression Strength, Weather Resistant, Wax-Resin Impregnated.

Federal Standards:

Fed. Test Method Std. No. 101	-	Preservation, Packaging, and Packing Materials: Test Procedures.
Fed. Std. No. 123	-	Marking for Domestic Shipment (Civil agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, DC 20402.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.

(Single copies of this specification and other Federal specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.
MIL-STD-1482	-	Sanitary Standards for Butter (and Related Products) Plants.

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

LAWS AND REGULATIONS

U. S. Department of Health, Education and Welfare

Federal Food, Drug, and Cosmetic Act and Regulations Promulgated Thereunder.

(Copies may be obtained from the Superintendent of Documents, U. S. Government Printing Office, Washington, DC 20402. Prices may be obtained from the Superintendent of Documents.)

U. S. Department of Agriculture

U. S. Standards for Grades of Butter.

General Specifications for Dairy Plants Approved for USDA Inspection and Grading Service.

Dairy Plants Surveyed and Approved for USDA Grading Service.

Directory of Consumer Protection Programs, Establishments, Circuits and Officials.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.

(Copies may be obtained from the Dairy Division, Agricultural Marketing Service, U. S. Department of Agriculture, Washington, DC 20250.)

Brucellosis Eradication - Recommended Uniform Methods and Rules, Agricultural Research Service, U. S. Department of Agriculture, Bulletin ARS 91-79.

(Copies may be obtained from U. S. Department of Agriculture, Agricultural Research Service, Washington, DC 20250.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

National Motor Freight Traffic Association, Inc., Agent

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Materials.

3.1.1 Milk. The raw milk used in the preparation of this product shall comply with the quality requirements specified in the General Specifications for Dairy Plants Approved for USDA Inspection and Grading Service. The milk shall be drawn from cows in herds accredited as tuberculosis-free and certified brucellosis-free by the U. S. Department of Agriculture, or herds that have passed an annual tuberculosis test and meet USDA requirements for an individually certified herd, or from cows in herds located in:

(1) A Modified Accredited Tuberculosis Area; and
(2) Either (a) A Certified Brucellosis Area; or
(b) Modified Certified Brucellosis Area; or
(3) An area in the process of being certified by the USDA in accordance with USDA Agricultural Research Service Bulletin 91-79. The milk shall be practically free from colostrum, fresh, wholesome, and normal in appearance and odor and shall be subject to inspection by the procuring agency or duly authorized representative.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.

3.1.2 Cream.

3.1.2.1 Cream separated at an approved plant shall be derived from milk meeting the requirements of 3.1.1.

3.1.2.2 Cream not separated at an approved plant (i.e., farm separated cream) shall comply with the applicable referenced requirements of 3.1.1.

3.1.3 Water. Water used in the processing of butter shall be of a safe sanitary quality and shall be approved by the appropriate State or local authority. The water may be treated by acidification with edible acids, chlorination or heat, but shall not impart undesirable flavors, odors, or microorganisms to the finished product.

3.1.4 Salt. Salt when used (see 6.1), shall be crystalline, refined sodium chloride of the type used in butter manufacture.

3.1.5 Color. Coloring, when used (see 6.1), shall be annatto or any color which is approved by the US Food and Drug Administration.

3.2 Processing. Processing shall be in accordance with the requirements stated in General Specifications for Dairy Plants Approved for USDA Inspection and Grading Service; Section: Supplemental Specifications for Plants Manufacturing, Processing and Packaging Butter and Related Products.

3.3 Rooms, compartments, equipment and utensils. Rooms, compartments, equipment and utensils shall be in accordance with the quality requirements and specifications stated in the publication referenced in 3.2.

3.4 Finished product. The finished butter shall comply with the requirements cited in the publication referenced in 3.2.

3.5 Plant qualification. The product shall originate, be processed, handled, and packaged in plants which are approved under the USDA General Specifications for Dairy Plants Approved for USDA Inspection and Grading Service, and listed by the U. S. Department of Agriculture in the document titled 'Dairy Plants Surveyed and Approved for USDA Grading Service', and approved for the finished product described in this specification, or in plants meeting the requirements of MIL-STD-1482. Unless otherwise specified (see 6.1), storage and shipping facilities shall meet the sanitary requirements of MIL-STD-1482.

3.6 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and Regulations Promulgated Thereunder.

3.7 Intransit handling temperature. Unless otherwise specified (see 6.1), the intransit handling temperature shall be such that the maximum internal temperature of the butter at time of delivery shall not exceed 45°F.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements (except for determining grade of final product) as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling. Procedures for sampling for microbiological and analytical analysis shall be in accordance with the publication referenced in 3.2.

4.3 Inspections.

4.3.1 Grading prior to printing. Bulk butter may be presented for grading prior to printing but shall be re-graded after printing and packaging.

4.3.2 Factory and printing inspection and survey. Butter produced or printed in a plant found on inspection to be using unsatisfactory practices, equipment or facilities or to be operating under unsanitary conditions will not be accepted. The passing as satisfactory of any detail of processing or materials shall not relieve the supplier of responsibility for faulty workmanship or materials which may be discovered at any time prior to final acceptance.

4.3.2.1 In addition to the physical inspection of plant equipment and review of operating procedures, examination of processing and manufacturing records, including pasteurization (time and temperature) records and testing cream or butter for phosphatase within 24 hours after processing, as tested by a Government designated laboratory, shall constitute criteria upon which to determine proper pasteurization, efficiency of pasteurization, and plant sanitation. Establishment of this information may be obtained from records covering routine current commercial production of the processor.

4.3.3 USDA certificate of quality and condition. When specified by the procuring agency (see 6.1)the supplier shall furnish a U.S. Department of Agriculture inspection or grading certificate, evidencing quality and condition, as outlined in procurement documents.

4.3.4 Plant qualification conditions. The product furnished under this document shall be unacceptable if not produced and, when applicable, stored in plants which currently meet the qualification conditions of 3.5.

4.3.5 Sampling for inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except as otherwise indicated hereinafter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.

4.3.6 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with requirements of referenced specifications, drawings and standards unless otherwise excluded, amended, modified or qualified, in this specification or applicable purchase document.

4.3.6.1 Inspection of milk and cream.

4.3.6.1.1 Animal sources. Inspection shall be made to determine that cows supplying the milk used in the preparation of this product are in disease-free herds as specified in 3.1.1. Determination of herd status regarding tuberculosis and brucellosis shall be made by contacting the nearest office of the Agricultural Research Service of the Animal Health Division. (Location of this office may be ascertained by consulting the publication entitled Directory of Consumer Protection Programs, Establishments, Circuits and Officials.)

4.3.6.2 Examination of milk. The raw milk shall be examined and tested upon receipt at the processing plant(s) in accordance with the quality requirements for raw milk specified in 3.1.1. Records of results of such examination and testing shall be maintained and made available for review. Failure to comply with the above referenced requirements, reflected by actual examination or by examination of records, shall be cause for rejection of the finished product made therefrom.

4.3.6.2.1 Examination of cream. Cream separated at an approved plant shall be examined to determine compliance with the quality requirements for cream specified in 3.1.2. If the cream is farm-separated, the examination and tests shall be made for organoleptic properties and sediment to determine compliance with the above referenced requirements. Records of results of such examinations and testing shall be maintained and made available for review. Failure to comply with the referenced requirements, reflected by actual examination and testing or by examination of records, shall be cause for rejection of the finished product made therefrom.

4.3.6.2.2 Establishment sources. Inspection shall be made to determine that all processed milk and cream (except as stated in 4.3.6.2.1) shipments received by the supplier have been processed, packaged and shipped by establishments approved as military sources of supply as listed in the Directory of Sanitarily Approved Food Establishments for Armed Forces Procurement or from plants listed by the U.S. Department of Agriculture in the document entitled "Dairy Plants Surveyed and Approved for USDA Grading Service" and approved for the specific product shipped. Nonconformance to the above requirements shall be cause for rejection of the involved quantity of finished product made therefrom.

4.3.6.3 Examination of salt and color. Examination shall be made of labels, invoices, plant or laboratory records or other valid documents to determine conformance of those components, as applicable, to the identity requirements referenced in 3.1. Nonconformance shall be cause for rejection of the involved finished product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.

4.3.6.4 Examination of water. Water shall be examined to determine compliance with the requirements of 3.1.3 as concerns potability, approval source, treatment and condition. This determination shall be performed by examination of current approval source document(s) from the state or local authority. In addition, plant records shall be maintained to indicate the type and frequency of water treatment used, if any, and to include the examination and test results as concerns condition and microbiological counts as they may affect the quality of the end item. Adequate testing frequency shall be maintained to assure acceptability of the water supply, but in no instance shall the frequency be less than one test every six months in accordance with approved testing procedures. Nonconformance to an approval source or to one or more requirements of 3.1.3 shall be cause for rejection of the finished product produced in association with the water supply in question.

4.3.7 Testing of components. Testing of components described in this specification shall be as shown in table I. Results shall apply to lot average requirements. Nonconformance to one or more test requirements shall be cause for rejection of the lot.

TABLE I. Testing of components (see 4.3.6)

Component	Sample unit	Lot size expressed in	Inspection level	Characteristics	Results reported	Test ref & rqmt par
Dry waxed vegetable parchment, or waxed paper as applicable	3 sq. yds. of cut sheets	Number of reams	S-1	Basis weight of paper	Nearest pound/ ream	5.2.1.1 4.4.1
Case lining (kraft or sulphite paper) or, (vegetable parchment), as applicable	3 sq. yds. of cut sheets	Number of reams	S-1	Basis weight of paper (waxed & dewaxed)	Nearest pound per ream	5.3.1.1.1 4.4.1
				Bursting strength (after waxing)	Nearest pound per sq. in.	
				Tearing resistance	Nearest gram per sheet	
				Melting point of wax	Nearest degree F.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.

TABLE I. Testing of components (see 4.3.6) (cont'd)

Component	Sample unit	Lot size expressed in	Inspection level	Characteristics	Results reported	Test ref & rqmt par
Fiberboard box pads and liners	Two 12-inch x 12-inch panels or equivalent in total area	Box pads and liners	S-1	Melting point of wax	Nearest degree F.	5.3.1 4.4.1
Polyethylene	1 Bag	Number of bags	S-1	Thickness	Nearest 0.0001 in.	5.3.1.1.1 4.4.2

4.3.8 Process examination. Examination shall be made during preprocessing and processing to determine compliance with the referenced requirements of 3.2 as concerns time and temperature and of 3.3 as concerns facilities, equipment and utensils. Records shall be maintained of preprocessing storage temperature of all milk products used in the manufacture of the end item, pasteurization times and temperatures with their respective controls required by local or state regulatory agencies and the results of the phosphatase test run at least once daily. (See 4.3.2.1). The cream sample to be tested shall be taken from a single batch or shall represent a composite of all batches or tanks of cream processed daily. Failure to comply with one or more of the above requirements, reflected by actual examination or by examination of records, shall be cause for rejection of the involved finished product made therefrom.

4.3.9 Finished product inspection.

4.3.9.1 Lot size. An inspection lot for examination or testing shall be one style and class. The size shall be expressed in pounds. More than one day's production may be included in the lot if the number of cases from each churning or production code represented in the lot is recorded on a manifest.

4.3.9.2 Examination of end item for the net weight, patty count and packaging characteristics shall be in accordance with the following procedures. The appropriate minimum sample size shall be a one-pound portion of the primary container designated in table II or III, as applicable; shall be formed by drawing one sample unit per shipping case selected proportionately from the production codes represented in the inspection lot. The applicable acceptance (AC) and rejection (RE) numbers are given in table II. Classification of defects found during the examination shall be in accordance with tables IV and V. AQLs shall be expressed as percent defective for table IV and as defects per hundred units for table V.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.

TABLE II. Plans for end-item examination (civil agencies)

Lot Size in Pounds	Minimum Sample Size for Prints and Patties 1/	Major (Major and Minor) Ac	Major (Major and Minor) Re	Total Ac	Total Re
2-150	5	2/	2/	0	1
151-500	13	0	1	1	2
501-35,000	20	1	2	2	3
35,001-500,000	32	2	3	3	4

1/ Sample size for bulk butter shall be one container per each churning or 5,000 pounds, whichever is smaller.

2/ A lot with one or more defects shall be rejected.

TABLE III. Plans for end-item examination (military agencies)

Table	Inspection level	Sample unit 1/ 2/	Lot size expressed in	AQLs Major	AQLs Minor	AQLs Total
IV	S-3	A packaged 1 pound print, a pound package of quarter pound prints, two 1/2-pound trays of patties or 5 pounds of packaged patties	Pounds	-	2.5	-
V	S-3	A packaged 1 pound print, a pound package of quarter pound prints, two 1/2-pound trays of patties or 5 pounds of packaged patties	Pounds	2.5	-	4.0

1/ One sample unit per shipping container shall be selected.

2/ Sample size for bulk butter shall be one container per each churning or 5,000 pounds, whichever is smaller.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.

TABLE IV. Examination of net weight and patty count per pound 1/

Category	Defect
Minor	
201	Net weight more than 1/4-ounce under specified weight (1 pound packages). (Report to nearest 1/8-ounce).
202	Net weight more than 3/4-ounce under specified weight (packages of more than 1 pound, but not more than 10 pounds). (Report to nearest 1/4-ounce).
203	Net weight more than 2-ounces under specified weight (bulk butter, style (f)). (Report to nearest 1-ounce).
204	Patty count not as specified. 2/

1/ The lot shall be rejected if sample data indicate lot average net weight and lot average patty count, as applicable, are less than specified net weight and count. Except ready-to-serve patties cut 90 to the pound and placed individually on chips shall average not more than 95 nor less than 85 patties per pound. For applicable net weights and patty counts, see 5.2.1.1 and 5.2.1.2.

2/ One pound of product from each sample unit shall be examined for this defect. This defect is not applicable to ready-to-serve patties placed individually on chips.

TABLE V. Examination of packaging

Category		Defect	Wrappers	Cartons	Applicable to waxed or parchment paper separators and waxed paper packaging, chips, covers, trays, or cartoning of patties only
Major	Minor				
101 1/		Not type specified	X	X	X
102		Missing	X	X	X

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.

TABLE V. Examination of packaging (cont'd)

Category		Defect	Wrappers	Cartons	Applicable to waxed or parchment paper separators and waxed paper packaging, chips, covers, trays, or cartoning of patties only
Major	Minor				
103		Objectionable odor	X	X	X
104		Any surface contacting product not clean	X	X	X
105		Not packaged in layers as specified			X 2/
106		Nomenclature missing, incorrect or illegible	X	X	X 3/
107		Not completely wrapped or inclosed	X	X	
	201	Exterior not clean	X	X	X
	202	Not completely overwrapped or cartoned			X 2/
	203	90-count style patties not placed on coated side of chips			X
	204	More than 1 patty placed on chip for 90-count style			X

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.

TABLE V. Examination of packaging (cont'd)

Category		Defect	Wrappers	Cartons	Applicable to waxed or parchment paper separators and waxed paper packaging, chips, covers, trays, or cartoning of patties only
Major	Minor				
	205	Labeling information other than nomenclature missing, incorrect or illegible	X	X	X 3/

1/ Applicable to packaging level B only.

2/ Applicable to 5-pound packages or cartons.

3/ Applicable to cartons or outer waxed paper wrapper of 5-pound packages.

4.3.10 Examination of butter for grade.

4.3.10.1 Examination of bulk butter for grade prior to printing. When bulk butter prior to printing is examined for grade, the determination for U. S. grade shall be in accordance with 1.2.1. If so graded, the butter shall be re-graded after printing and packaging, see 4.3.10.2. The sample unit and size for examination shall be 1 bulk primary container. Lot size shall be expressed in terms of pounds and the lot identified by churn number. Each churn number shall represent 1 lot. When lot identification cannot be made according to churn number marked on each container, sample size shall be the number of primary containers indicated by inspection level S-2. In no instance shall a lot size exceed 60,000 pounds. Butter shall be tempered so as to have an internal temperature of 45° - 55°F. at the time of examination for grade. No bulk butter shall be examined for U. S. Grade until 48 hours after churning. A standard butter trier plug from one sample unit shall be examined for U. S. Grade. If any sample unit does not meet the specified grade requirement, it shall be cause for rejection of the entire lot.

4.3.10.2 Examination of prints or patties for grade. Prints of butter or patty style butter shall be examined for U. S. Grade after packaging in accordance with 1.2.1 and with procedures, churn and lot identification and lot size

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.

and internal temperature requirements as in 4.3.10.1. The sample unit for examination shall be a single 1-pound print or its equivalent in quarter-pound prints or patties. When butter has been examined in the bulk or pre-printing state, the same lot identity shall be maintained in the finished product presented for examination. If any sample unit does not meet the specified grade requirement, it shall be cause for rejection of the entire lot.

4.3.11 Examination of butter for style or class. Examination shall be made at origin or at time of delivery as applicable to determine compliance with the requirements of 1.2.2 or 1.2.3, as may be specified in 6.1 and as concerns uniformity of grade and pack, creamery origin, churning date, temperature and time intervals. Determination of compliance shall be ascertained by marked date of churning (or printing) as applicable, grade, or other valid means. Ten percent of the number of shipping containers in the lot shall be examined. Noncompliance to the above referenced class requirements or absence of required markings on one or more containers shall be cause for rejection of the involved lot(s).

4.3.12 Examination of intransit handling temperature. Examination shall be made at time of delivery of product to determine compliance with the internal temperature requirements of 3.7 (see 6.1 for exception, if specified). The sample unit shall be one primary container for bulk or 1 intermediate package for prints or patties. Lot size shall be expressed in terms of pounds and the sample size for examination shall be 1/4 the number of sample units indicated by table II or III, as applicable, selected at random points in the delivery vehicle and taken from different shipping containers. No less than 3 shipping containers shall be taken for examination for any given shipment. Finding of any temperature not in accordance with the specification requirement shall be cause for rejection of the lot.

4.3.13 Examination of the filled and sealed shipping container. Examination of the filled and sealed shipping container and fiberboard liners and pads, as applicable, for level B pack shall be in accordance with the examination criteria of PPP-B-636 or PPP-B-1163, as applicable. In addition, the following defects shall be included in the table for examination: Major: Marking missing, incorrect or illegible; Minor: (1) Pads and liners missing or not waxed as specified; (2) Net weight exceeds 68 pounds or exceeds 30 pounds of patties packed in W5c or W5s fiberboard boxes as indicated by marked net weight. When the product is not packaged in intermediate cartons, the following defects shall be included in the examination, as applicable:

Major:

(1) Waxed paper liner or gusset plastic bag missing or not completely protecting product from shipping container.

(2) Waxed paper liner or gusseted bag has odor.

(3) Gusseted plastic bag closure not heat sealed or taped.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.

Minor:

(1) Waxed paper liner or gusseted plastic bag torn.

(2) Waxed paper liner or gusseted plastic bag unclean.

(3) Gusseted plastic bag not fitting contents snugly.

(4) Dimensions of pads not as specified.

(5) Pads or liners missing or not as specified.

(6) Pads or liners not waxed when applicable.

Examination of level C packing shall be in accordance with the examination criteria of the aforementioned specification except that only the defects pertaining to marking shall apply.

4.3.14 Examination of cellophane. Examination of cellophane shall be in accordance with L-C-110 for type III.

4.4 Tests. Test procedures and controls which differ from those specified herein, may be used by the supplier if they provide a quality assurance equivalent to that specified. If the Government inspection activity determines that such procedures and controls do not provide, as a minimum, such quality assurance, the supplier will use the test procedures set forth herein. In case of dispute as to test results, the test methods specified herein shall govern.

4.4.1 Paper tests. Paper shall be tested in accordance with the following methods of Fed. Test Method Std. No. 101:

Test	Method No.
Basis weight of paper and paperboard	5022
Melting point of wax	4017
Bursting strength of sheet materials	2007
Tearing resistance (Elmendorf)	2036

4.4.2 Polyethylene thickness. Polyethylene thickness shall be determined in accordance with L-P-378.

5. PREPARATION FOR DELIVERY

5.1 Materials. No materials shall be used in the packaging or packing of this product which will impart an odor or flavor to the product. If mold-inhibiting materials are incorporated in the wrappers such materials shall comply in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and Regulations Promulgated Thereunder.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.

5.2 Packaging. The product shall be packaged in accordance with level B or level C as specified (see 6.1).

5.2.1 Level B.

5.2.1.1 Wrapper for prints (style (a), (b), (c) or (d)). One quarter-pound prints or 1-pound prints of the product, shall be properly wrapped with a single sheet of dry waxed vegetable parchment paper or wet-strength paper, having a basis weight of 30 pounds ± 5 percent per ream (24 x 36-500) or with a wet-strength paper waxed, having a basis weight of 20 pounds ± 5 percent per ream (24 x 36-500), with a blend of polyethylene and microcrystalline or paraffin waxes. Alternatively, the prints may be wrapped in a commercial foil-paper combination wrapper. Four individually wrapped one-quarter-pound prints shall be overwrapped with one of the materials listed in this paragraph.

5.2.1.2 Patties (style (e)). The butter patties, cut 72 or 90 to the pound, as specified (see 6.1), shall be packaged in layers in 5-pound units and placed in commercially acceptable waxed wrapper or commercial, coated carton. The layers shall be separated by a sheet of waxed, parchment paper or cellophane conforming to type III of L-C-110.

5.2.1.2.1 Alternatively, when specified (see 6.1), patties cut 90 to the pound shall be individually placed on chips made from plastic or bleached sulphite paperboard. Paperboard chips shall be coated on one side with polyethylene, and the patties shall be placed on the coated side. Patties shall be covered with a piece of waxed, parchment paper or cellophane conforming to type III of L-C-110. One-half pound of patties shall be placed on a tray. When specified (see 6.1), trays shall be packaged in 5-pound units and wrapped in commercially acceptable waxed wrapper or commercially-coated carton. The material for chips, covers, and trays shall be that which is normally used for good commercial practice.

5.2.1.3 Intermediate package for prints.

5.2.1.3.1 Styles (a) and (c). Four wrapped 1/4-pound prints or one wrapped 1-pound print shall be packed in a commercial coated intermediate carton.

5.2.1.3.2 Style (d). Four wrapped 1/4-pound prints shall be overwrapped in a material commercially acceptable for the product.

5.2.2 Level C. Unless otherwise specified (see 6.1), commercial packaging shall be acceptable for all styles except (e) which shall be packaged as specified in 5.2.1.2. All bulk butter (style (f)) shall be solid packed.

5.3 Packing. The product shall be packed in accordance with level B or level C as specified (see 6.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.

5.3.1 Level B. Not more than 68 pounds of the product shall be packed into a fiberboard container constructed, closed, and reinforced in accordance with style RSC-L, V3c, V3s, or V4s of PPP-B-636. Alternatively, the shipping container shall be a wax-impregnated fiberboard box constructed in accordance with style RSC-L, class I, type SWCFI, grade 275 of PPP-B-1163. Closure shall be with hot melt adhesive in accordance with the appendix of PPP-B-636. The style RSC container shall be reinforced with two lengthwise bands and one girthwise band in accordance with the appendix of PPP-B-636. The box shall have a liner of one-piece construction covering the sides and ends of the box, and shall be provided with top and bottom pads not more than 1/16-inch smaller than the length and width of the box. The pads and liner shall be made from fiberboard of the same grade specified for the box. The inside surfaces of the pads and liners shall be waxed with a fully refined paraffin wax having a melting point of not less than 128°F, when tested in accordance with Method 4017 of Federal Test Method Standard No. 101. Shipping containers with cartoned product do not require pads or liners.

5.3.1.1 Patties. Thirty pounds of patties shall be packed into a snug-fitting fiberboard box constructed, closed and reinforced in accordance with RSC-L, W5c or W5s of PPP-B-636. Alternatively, the shipping container may be a snug-fitting wax-impregnated fiberboard box constructed in accordance with style RSC-L, class I, type SWCFI, grade 200 of PPP-B-1163. Closure shall be with hot melt adhesive in accordance with the appendix of PPP-B-636. The wax-impregnated container shall be reinforced with two lengthwise bands and one girthwise band in accordance with the appendix of PPP-B-636. The box shall have top and bottom pads in accordance with 5.3.1. Liners and pads shall be waxed in accordance with 5.3.1.

5.3.1.1.1 Fiberboard box liner. The boxes containing uncartoned prints or patties shall be completely lined inside with a 1- or 2-piece liner of waxed paper so placed as to separate the product from the top, bottom, sides, and ends of the container. The lining material shall be bleached or semi-bleached deodorized kraft or sulphite paper or parchmentized paper having a minimum basis weight (see 4.4.1) of 25 pounds (±5 percent) per ream (24 by 36-500) before waxing. The sheet shall be wet waxed on both sides with not less than 9 pounds (± 5 percent) per ream of fully refined parafin wax having an average melting point of not less than 125°F. (see 4.4.1). The waxed paper shall have an average bursting strength of not less than 22 points (see 4.4.1) and an average tearing resistance in any direction of not less than 27 grams except that the parchmentized paper shall have an average tearing resistance of not less than 18 grams (see 4.4.1). Alternatively, a gusseted plastic bag constructed of 0.002-inch thick polyethylene shall be used in lieu of waxed paper. The bag shall fit the contents snugly and shall be closed by heat sealing or taping. When the plastic bag is used, the fiberboard pads and liners need not be waxed.

5.3.1.2 When specified (see 6.1 and 6.3) the shipping containers specified in 5.3.1 and 5.3.1.1 shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive, filament reinforced tape in accordance with the appendix of PPP-B-636, except that for V3c, V3s, V4s, W5c and W5s boxes two reinforcing bands may be used, one lengthwise and one girthwise.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.

5.3.2 Level C. Not more than 68 pounds of the product shall be packed in a snug-fitting fiberboard box constructed, closed, and reinforced in accordance with style RSC, class domestic, type CF or SF, method II closure of PPP-B-636. The boxes containing uncartoned prints (style (b) or (d)) or patties (style (e)) shall be lined as specified in 5.3.1.1.1.

5.3.2.1 When specified (see 6.1) the shipping container shall be in accordance with the Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.4 Labeling and marking.

5.4.1 Wrappers and intermediate cartons for prints. Any labeling that complies with the Federal Food, Drug, and Cosmetic Act and Regulations Promulgation Thereunder will be acceptable.

5.4.1.1 Patties. The commercial waxed wrapper or carton containing 5-pound unit of patties shall be labeled as indicated in 5.4.1.

5.4.2 Shipping containers.

5.4.2.1 For civil agencies. Shipping containers shall be marked in accordance with Federal Standard No. 123 and as specified in 5.4.2.3.

5.4.2.2 For military agencies. Shipping containers shall be marked in accordance with MIL-STD-129 and as specified in 5.4.2.3.

5.4.2.3 Additional markings. In addition to the markings specified in 5.4.2.1 or 5.4.2.2, as applicable, the name and address of the plant of origin (if different from that of the prime contractor) manufacturer's lot number or churn number shall appear below the contractor's name, unless otherwise specified (see 6.1) for LCL shipments. Also, the following information shall be printed (in 2 lines) on top of the shipping container in bold capital letters between 1 and 1-1/2 inches high, all letters being of the same height:

BUTTER

KEEP REFRIGERATED

45°F. or LOWER

6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Grade, style and class required (see 1.2.1, 1.2.2 and 1.2.3).
(b) Whether salt is to be added to the finished product (see 3.1.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.

(c) Whether coloring is to be added to the finished product (see 3.1.5).
(d) When storage and shipping facilities are not required to comply with MIL-STD-1482 (see 3.5).
(e) Maximum internal temperature permitted at time of delivery if other than 45° F. (see 3.7).
(f) When USDA inspection or grade certificate is required (see 4.3.3.)
(g) Levels of packaging and packing required (see 5.2 and 5.3).
(h) Number of patties per pound required (see 5.2.1.2).
(i) When patties cut 90 to the pound are to be packaged in accordance with 5.2.1.2.1.
(j) When trays are to be packaged in 5-pound units (see 5.2.1.2.1).
(k) If other than commercial packaging is required for styles (a), (b), (c) and (d) in level C packaging (see 5.2.2).
(l) When packing specified in 5.3.1.2 or 5.3.2.1 is required.
(m) Shipping container markings required for LCL shipments (see 5.4.2.3).

6.2 Destination inspection (for civil agencies only). When the finished product has been inspected and passed at point other than destination, the contract should require that the product be inspected at destination for condition and quantity only. Unless otherwise specified, such inspection should be made by the receiving facility.

6.3 Packing specified in 5.3.1.2 is intended for transfer at sea operations and specific overseas operations.

6.4 Military agencies. Based on conditions known or expected to be encountered during shipping, handling, and storage of the specific item being procured, the contracting officer should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.14D/DSAR 4145.7.

Custodians:

Army - GL
Navy - SA
Air Force - 45

Review activities:

Army - MD
Navy - MC, MS
DP - SS

Preparing activity:

Army - GL

Civil Agency Coordinating Activities:

USDA - AMS
GSA - FSS
HEW - FDA
VA - DMS

Project No. 8910-0355

U. S. GOVERNMENT PRINTING OFFICE : 1974 - 585-644/1358

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 45 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.

FOLD

US Army Natick Laboratories
Natick, MA 01760

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

U.S.MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

STSNL-TD

Commander
US Army Natick Laboratories
ATTN: STSNL-TD
Natick, MA 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

C-B-801H - BUTTER

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:05Z
Check the source to verify that this is the current version before use.