AMENDMENT

TO

INTERIM FEDERAL SPECIFICATION

CLEANING COMPOUND, ENGINE COOLING SYSTEM

This amendment was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, D. C. 20406, based upon currently available technical information. The General Services Administration has authorized this amendment as a part of Interim Federal Specification O-C-00432 (GSA-FSS), dated October 23, 1964.

PAGE 1

Paragraph 2.1: Delete "O-O-690 - Oxalic acid, Dihydrate, Technical".

PAGE 2

Paragraph 2.2: Update "ASTM D 501-58" to "ASTM D 501-67".

Paragraph 3.1.1. line 2: Delete "98-percent" and substitute "93-percent".

Paragraph 3.1.2: Delete and substitute:

3.1.2 Minor component. The minor component shall consist of sodium carbonate and a wetting agent. The minor component shall consist of not less than 93-percent anhydrous sodium carbonate in powder or granular form, after removing absorbed moisture and shall meet the test specified in 4.4.2.

PAGE 3

Paragraph 4.4.1: Delete and subtitute:

4.4.1 The major component when tested by the sodium hydroxide titration shall meet the requirement of 3.1.1. Set up a pH meter for an electrometric titration. Check the meter with a series of standard buffer solutions. Weigh to the nearest 0.1 milligram (mg) about 0.25 grams (g.) of the material into a 150-milliliter (ml.) beaker. Add 40 ml. of water and when the material has dissolved completely titrate with 0.1 N sodium hydroxide to a pH of 8.5 calculate the purity as percent oxalic acid dihydrate as follows:

$$\text{Percent purity} = \frac{6.304\ V\ N}{W}$$

Where:
V = volume of sodium hydroxide used, in ml.
N = normality of sodium hydroxide solution.
W = weight of specimen, in g.

Paragraph 4.4.2: Delete and substitute:

4.4.2 The minor component, having been oven-dried for 1 hour at 105° C., shall be tested in accordance with ASTM method D 501-67, sections 19, 20, and 21 to determine compliance with 3.1.2.

PAGE 5

Paragraph 5.4.1. Instructions for use: Fifth sentence of instruction for use: Delete "180-190 degrees F" and substitute "160-190 degrees F".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:13Z
Check the source to verify that this is the current version before use.