O-C-430A
July 9, 1975
SUPERSEDING
Int. Fed. Spec. O-C-00430(GSA-FSS)
July 28, 1964

FEDERAL SPECIFICATION

CLEANING COMPOUND, PAINT BRUSH

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE

1.1 This specification covers a brush cleaner in powder form for cleaning brushes hardened with paint (oil base) (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

TT-E-489 - Enamel, Alkyd, Gloss (For Exterior and Interior Surfaces).
PPP-B-636 - Boxes, Shipping, Fiberboard.

Federal Standards:

Fed. Std. No. 123 - Marking for Shipment (Civil Agencies).
Fed. Std. No. 536 - Soap and Soap Products (Including Synthetic Detergents): Sampling and Testing.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

FSC 6850

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:13Z
Check the source to verify that this is the current version before use.

American Society for Testing and Materials (ASTM) Standard:

E 70 - Method of Test of pH of Aqueous Solutions with the Glass Electrode.

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza., Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Material. The compound shall be uniformly compounded, homogeneous, and a free-flowing powder.

3.1.1 Excluded ingredients. The compound shall not contain acid or lye. A certificate of compliance that caustic alkali agents are excluded from the finished product shall be furnished by the contractor to the contracting officer at the time bids are submitted (see 4.1.1).

3.2 Cleaning efficiency. A 10.0 percent solution of the compound in water shall effectively loosen hard (oil base) paint, varnish, shellac, enamel within 48 hours to permit easy removal of paint from brush, when tested as specified in 4.5.1.

3.3 Solubility. The compound shall be completely soluble in water when tested as specified in 4.5.2.

3.4 Deleterious action on brush. The compound, when used according to directions, shall not be harmful to the brush, when tested as specified in 4.5.3.

3.5 Particle size. The particle size of the compound shall be generally uniform to mimimize segregation of the ingredients. Not less than 85 percent shall pass through a size no. 10 (2.00 mm) sieve when tested as specified in 4.5.4.

3.6 pH. The pH of a one percent solution of the compound shall be 7.0 to 12.0 when tested as specified in 4.5.5.

3.7 Stability. The compound shall maintain a stability for a period of not less than one year after receipt and shall show no tendency to cake under normal shipping and storage conditions.

3.8 Workmanship. The compound shall be a free-flowing powder. It shall contain no foreign or lumpy material.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Certificates. Where certificates are submitted, the Government reserves the right to check-test such items to determine the validity of the certification.

4.2 Sampling for inspection and acceptance. Sampling for inspection and acceptance shall be performed in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated herein.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:13Z
Check the source to verify that this is the currentversion before use.

4.2.1 Lot. For purposes of sampling, a lot shall consist of all the containers of the compound offered for delivery at one time.

4.3 Examination for net content and testing of end item. Failure of the end item to comply with the content specified or failure to meet the laboratory test requirements shall be cause for rejection.

4.4 Examination of preparation for delivery. An examination shall be made to determine that markings, materials, workmanship, and contents comply with the requirements of section 5. Defects shall be scored in accordance with table I. The sample unit shall be one shipping container fully prepared for delivery. Sampling shall be in accordance with MIL-STD-105. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and AQL hall be 4.0 defects per hundred units.

TABLE I. Classification of preparation for delivery defects

Examine	Defects
Markings	Omitted; incorrect; illegible; improper size, location, sequence, or method of application.
Materials	Any component missing, or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose stapling. Distortion of container.
Contents	Not as specified.

4.5 Test methods.

4.5.1 Cleaning efficiency.

4.5.1.1 Preparation of brush. Saturate a clean brush (natural, nylon, or other synthetic bristles) with an oil-base paint (class A of TT-E-489 or equal) and allow the brush to dry for 48 hours.

4.5.1.2 Procedure. Prepare a 10.0 percent solution of the compound. Allow the paint hardened brush (see 4.5.1.1) to remain in solution for a period of 48 hours. Wash the brush thoroughly with soap and water, rinse with water, and inspect the brush for removal of paint.

4.5.2 Solubility. Add 9.0 grams of compound to 100 ml. of water maintained at approximately 120°F (40°C), stir vigorously for 5 minutes, and observe immediately for undissolved material.

4.5.3 Deleterious action on paint brush. The compound shall not be harmful to the natural, nylon, or other synthetic bristles of the brush. After treatment (see 4.5.1) follow manufacturer's direction (see 5.3.3.1) for preservation of the brush while drying. Allow the brush to dry and inspect. There shall be no deleterious effect on the brush filaments and the setting compound. The brush shall remain soft and pliable and usable for the purpose intended.

4.5.4 Sieve test. The sieve test shall be run in accordance with the applicable test procedures outlined in test method 2101 of Fed. Test Method Std. No. 536.

4.5.5 pH. Determine the pH of a one percent solution of the compound in distilled water at 25° ± 1°C. using a pH meter with an alkali-resistant glass electrode in accordance with ASTM E 70.

5. PREPARATION FOR DELIVERY

5.1 Packaging.

5.1.1 Level C. The compound furnished in 3, or 9-ounce quantities shall be packaged in plastic containers or folding cartons, as applicable, in accordance with the industry standard practice.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:13Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be A, B, or C as specified (see 6.2).

5.2.1 Level A. The compound packaged as specified in 5.1.1 shall be packed in quantities shown in table II, in a box conforming to PPP-B-636, class weather-resistant. Closure shall be in accordance with the appendix to the box specification.

5.2.2 Level B. The compound packaged as specified in 5.1.1 shall be packed in quantities shown in table II, in a box conforming to PPP-B-636, class-domestic. Closure shall be in accordance with Method I of the appendix to the box specification.

TABLE II. Packing quantities

Size	Shipping containers
3-ounce	72
9-ounce	36

5.2.3 Level C. The compound packaged as specified in 5.1.1 shall be packed in containers to assure carrier acceptance and safe arrival at destination. The containers shall conform to the National Motor Freight Classification or Uniform Freight Classification Rules, as applicable.

5.3 Marking.

5.3.1 Civil agencies. In addition to markings required by contract or order, the packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. In addition to markings required by contract or order, the packages and shipping containers shall be marked in accordance with MIL-STD-129.

5.3.3 Labeling.

5.3.3.1 Direction for use. The manufacturer shall mark each package with instructions for use and preservation of the brush after the use of the compound.

5.3.3.2 Based on the manufacturer's formulation, warning or other information as may be required by applicable Federal laws shall be included.

6. NOTES

6.1 Intended use. The cleaning compound is intended for use in the cleaning of brushes hardened with (oil base) paint.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Size of container (see 5.1.1).
(c) Level of packing required (see 5.2).
(d) Marking required (see 5.3).

6.3 Basis of purchase. The compound shall be purchased by net weight.

Military Interests:

DoD has waived coordination interest in this Federal Specification until further notice.

Preparing activity:

GSA-FSS

CIVIL AGENCY COORDINATING ACTIVITIES:

CPSC
GSA-FSS, PBO
VA-DMS

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See Section 2 of this specification to obtain extra copies and other documents referenced herein. Price 25 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:13Z
Check the source to verify that this is the current version before use.