O-I-518a
APRIL 26, 1957
SUPERSEDING
Int. Fed. Spec. O–I–00518(GSA–FSS)
September 30, 1955

FEDERAL SPECIFICATION

INSECTICIDE, CHLORDANE AND INSECTICIDE, DIELDRIN LIQUID, RESIDUAL, ROACH AND ANT CONTROL

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope.—This specification covers two types of kerosene-base liquid insecticide suitable for use as residual-type spray for roach and ant control.

1.2 Classification.

1.2.1 *Types.*—Liquid insecticide shall be of the following types, as specified (see 6.1):

Type C.—2 percent chlordane

Type D.—0.5 percent dieldrin

2. APPLICABLE SPECIFICATIONS, STANDARDS, AND OTHER PUBLICATIONS

2.1 The following specifications and standards, of the issues in effect on date of invitation for bids, form a part of this specification.

Federal Specifications:

TT–P–141 — Paint, Varnish, Lacquer, and Related Materials; Methods of Inspection, Sampling, and Testing.

PPP–C–96 — Cans, Metal, 28-Gage and Lighter.

PPP–P–31 — Preservation, Packaging, Packing and Marking of Material; and Shipping Instruction (Domestic Shipment and Storage).

Federal Standards:

Fed. Std. No. 102—Preservation, Packaging, and Packing Levels.

Fed. Test Method Std. No. 791—Lubricants, Liquid Fuels, and Related Products; Methods of Testing.

(Activities outside the Federal Government may obtain copies of Federal Specifications and Standards as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington 25, D. C.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, Seattle, and Washington, D. C.

(Federal Government activities may obtain copies of Federal Specifications and Standards and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specifications:

JAN–P–108—Boxes, Fiberboard, Corrugated and Solid (Military Type).

MIL–K–3128 — Kerosene, Water-White (For Use in Insecticide).

402174/57/No. 333

FSC Class 6840

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:14Z
Check the source to verify that this is the current version before use.

Military Standards:

MIL–STD–105 — Sampling Procedures and Tables for Inspection by Attributes.

MIL–STD–129 — Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by the contractor in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. — The following documents form a part of this specification. Unless otherwise indicated, the issues in effect on date of invitation for bids, shall apply:

Code of Federal Regulations:

49 CFR 71–78 — Interstate Commerce Commission Rules and Regulations for the Transportation of Explosives and Other Dangerous Articles.

U. S. Coast Guard Regulations for Explosives and Other Dangerous Articles on Board Vessels.

(Copies of the Code of Federal Regulations may be obtained from the Superintendent of Documents, Government Printing Office, Washington 25, D. C. Application for copies should cite title number.)

Service and Regulatory Announcement No. 166:

Federal Insecticide, Fungicide and Rodenticide Act.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington 25, D. C.)

Official Methods of Analyses of the Association of Official Agricultural Chemists (Seventh Edition—1950).

(Application for copies should be addressed to the Association of Official Agricultural Chemists, Post Office Box 540, Benjamin Franklin Station, Washington 25, D. C.)

Consolidated Freight Classification Rules.

(Application for copies should be addressed to the Consolidated Classification Committee, 202 Chicago Union Station, Chicago 6, Ill.)

3. REQUIREMENTS

3.1 Composition.—Liquid insecticide shall have the following compositions in the indicated proportions per 100 milliliters of the finished formulation at 77°F. (25°C.):

Type C:

Chlordane ___2.0 ± 0.1 gm.
Kerosene ____Sufficient to make 100 ml.

Type D:

Dieldrin ____0.55 ± 0.05 gm.
Kerosene ____Sufficient to make 100 ml.

3.2 Ingredients.

3.2.1 *Chlordane ingredient.* — The chlordane ingredient used in formulating type C insecticide shall contain not less than 98.0 percent by weight of clarified technical chlordane (comprising not less than 60.0 percent by weight of 1, 2, 4, 5, 6, 7, 8, 8-octachloro-4 7-methano-3a, 5, 7, 7a-tetrahydroindane and not more than 40.0 percent by weight of related active compounds formed in the manufacturing process) and not more than 2.0 percent by weight of stabilizers or odorants. The ingredient shall conform to table I, when tested as specified in 4.4.1.

3.2.2 *Dieldrin ingredient.* — The dieldrin ingredient used in formulating type D insecticide shall be a light tan solid containing by weight not less than 85 percent of 1, 2, 3, 4, 10, 10 hexachlor - 6, 7 epoxy - 1, 4, 4a, 5, 6, 7, 8, 8a octahydro - 1, 4 endo exo- 5, 8 dimethanonapthalene, hereinafter referred to as HEOD. The ingredient shall conform to table I, when tested as specified in 4.4.2.

3.2.3 *Kerosene.*—The kerosene shall conform to Military Specification MIL–K–3128.

3.3 Finished insecticide.—When tested as specified in 4.4.3, the insecticide shall conform to table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:14Z
Check the source to verify that this is the current version before use.

TABLE I.—*Chemical and physical requirements for chlordane and dieldrin ingredients*

Property	Requirement			
	Chlordane		Dieldrin	
	Minimum	Maximum	Minimum	Maximum
Chlorine content (percent by weight)	64	67	54	57
Kerosene insolubles (ml. / 10 ml.)	--	0.05	--	0.02
Color (number)	--	4	--	--
Specific gravity (at 60°/ 60° F.)	1.630	1.670	--	--

TABLE II.—*Chemical and physical requirements for finished insecticides*

Property	Requirement		Applicable test paragraph
	Type C	Type D	
Organically bound chlorine content (gm. per 100 ml.)	1.22 to 1.41	0.27 to 0.34	4.4.3.1
Qualitative color test	To equal standard (min.)	--------	4.4.3.2
Active component, HEOD (gm. per 100 ml.)	--------	.42 (min.)	4.4.3.3
Appearance	Slight haze (max.)	Slight haze (max.)	4.4.3.4
Residual odor	Mild, characteristic	Sensibly none	4.4.3.5
Staining properties	No staining	No staining	4.4.3.6
Flash point, (°F.)	125 (min.)	125 (min.)	4.4.3.7
Corrosion	No discoloration or etching	No discoloration or etching	4.4.3.8

3.4 Labeling.—The labeling shall be registered under the Federal Insecticide, Fungicide and Rodenticide Act and in compliance with its requirements. The following label data shall be durably and legibly marked on the main panel of the body by lithographing, stenciling or printing with a noncorrosive, weather-resistant, waterproof ink which will not smear nor rub off during handling. If all of the label data cannot be applied due to being too voluminous, that portion, such as the mixing instructions and directions for use may be placed on a label made of white paper containing not more than 15 percent unbleached or ground wood pulp and having a smooth finish:

For type C insecticide:

INSECTICIDE, CHLORDANE, LIQUID, RESIDUAL, ROACH AND ANT CONTROL

Type C—Federal Specification O–I–518

Active ingredients ____100.0 percent
Technical chlordane[1] ____ 2.0 percent
Kerosene (odorless) ____98.0 percent

[1] Consists of octachloro—4, 7 methane tetrahydroindane and related compounds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:14Z
Check the source to verify that this is the current version before use.

For type D insecticide:

INSECTICIDE, DIELDRIN, LIQUID, RESIDUAL, ROACH AND ANT CONTROL

Type D—Federal Specification O–I–518

Active ingredients ____100.0 percent
Dieldrin[1] _____ 0.5 percent
Kerosene (odorless) ____99.5 percent

[1] Consists of 85 percent hexachloro epoxy octahydro-endo, exo-dimethano naphthalene and 15 percent related compounds.

For both type C and type D insecticide:

Stock number
Manufacturer's name and address
Date of pack
Lot number
Contract number
Net contents

READ INSTRUCTIONS BEFORE USING

CAUTION: Toxic when taken internally or spilled on skin. In case of spillage on skin, wash immediately with soap and water. DO NOT USE IN SPACES WHERE FOOD IS HANDLED OR STORED UNLESS PRECAUTIONS ARE OBSERVED TO PREVENT CONTAMINATION OF FOODSTUFFS. FOOD, DISHES, COOKING UTENSILS, AND TABLE TOPS MUST BE PROTECTED FROM THE SPRAY BY SUITABLE COVERING.

FLAMMABLE LIQUID
DO NOT USE NEAR AN OPEN FLAME

BANK OR EXTINGUISH ALL FIRES BEFORE START OF SPRAY PROCEDURES.

This material WILL NOT be used as a space spray or for residual treatments which cover extensive indoor surfaces, such as entire bulkheads and overheads. Do not use in rooms occupied by children under 1 year of age.

DIRECTIONS FOR USE AS RESIDUAL SPRAY

Apply spray at the rate of 1 gallon per 1,000 or 1 pint per 125 lineal feet to cracks, crevices, and other harborages of roaches, and to the runways of ants. The best way to gage the proper amount is to spray until surfaces are wet. Use sprayer with nozzle adjusted for coarse, wet spray to insure that all the spray will strike the surface being treated. One thorough application should remain effective for several weeks, depending upon the degree of infestation from outside sources. Operators should wear a respirator approved by the U. S. Bureau of Mines for use around organic vapors when applying the insecticide. The respirator should be similar to Mine Safety Appliances Company chemical cartridge respirator (Catalogue No. ED43798).

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 Sampling. — Each container shall be carefully identified by manufacturer's batch (or control lot) number until ultimate action is taken as to acceptance or rejection of material offered for delivery. Individual samples shall not be mixed and shall be placed in separate airtight and watertight containers which shall be nearly filled. Containers shall be covered, sealed to prevent atmospheric effects, and labeled completely with information on the lot and batch number, date of sampling, contract number, and applicable specification.

4.1.1 *Sampling lot.*—For purposes of sampling, a lot shall consist of not more than 10,000 gallons of liquid insecticide of one type prepared from one manufactured batch in a single production and offered for delivery at one time.

4.1.2 *Sampling procedure for lot acceptance.*

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:14Z
Check the source to verify that this is the current version before use.

4.1.2.1 *Sampling for visual inspection of filled containers.* — Sampling shall be conducted in accordance with Military Standard MIL–STD–105 utilizing inspection level I and acceptable quality level = 2.5 percent defective.

4.1.2.2 *Sampling for lot acceptance tests.*— From each lot offered for Government inspection three 1-pint specimens of the finished insecticide shall be selected from separate containers selected at random. One 4 ounce sample of either chlordane ingredient (for type C insecticide) or dieldrin ingredient (for type D insecticide) used in formulating that lot shall also be sampled. Each specimen thus selected shall be placed in separate, clean, dry, amber glass containers which shall be tightly sealed and carefully marked. Each specimen shall be tested as specified in 4.3.

4.2 Inspection.

4.2.1 *Visual inspection of filled containers.* —Each of the sample filled containers selected in accordance with 4.1.2.1 shall be visually inspected to verify compliance with this specification in regard to marking, packing, and other requirements not involving tests. Any filled container in the sample containing one or more defects shall be rejected, and if the number of defective filled containers in any sample exceeds the acceptance number for the appropriate sampling plan of Military Standard MIL–STD–105, the lot represented by the sample shall be rejected.

4.3 Lot acceptance tests. — Each of the separate sample specimens selected in accordance with 4.1.2.2 shall be subjected to the tests specified in 4.4.

4.3.1 *Place of test.*—Unless otherwise specified in the contract or order, lot acceptance tests shall be conducted at the contractor's plant by the contractor under the supervision of the Government inspector. Contractors shall provide the necessary laboratory facilities satisfactory to the inspector or shall engage the services of a commercial testing laboratory acceptable to the activity concerned.

4.3.2 *Action in case of failure.*—If any one of the samples tested is found to be not in conformance with this specification, the lot which it represents shall be rejected.

4.4 Test procedures. — Where applicable, the methods of testing specified in Federal Specification TT–P–141 and Federal Test Method Standard No. 791 shall be followed as indicated herein.

4.4.1 *Tests of chlordane ingredient (type C).*

4.4.1.1 *Specific gravity.* — The specific gravity shall be determined with a pycnometer by method 418 of Federal Specification TT–P–141, using 10 to 15 gm. of chlordane concentrate and using water as a solvent instead of kerosene.

4.4.1.2 *Color.* — Determine color value of chlordane concentrate by use of the Union Colorimeter in accordance with method 102 of Federal Test Method Standard No. 791.

4.4.1.3 *Kerosene insolubles.* — Dissolve 10 gm. of the concentrate in sufficient kerosene to make a final volume of 50 ml. Shake thoroughly to insure that the sample has been dissolved completely and store solution at room temperature for 5 days. After this period, reagitate the sample thoroughly to obtain a uniform distribution of any sediment that has formed (swabbing the walls of the container if the precipitate adheres to them)and transfer 10 ml. to a calibrated centrifuge tube and spin for 10 minutes at 1,700 revolutions per minute, approximately. Record the volume of sediment in the tube.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:14Z
Check the source to verify that this is the current version before use.

4.4.1.4 *Organically bound chlorine content.*[1]—Weigh accurately[2] a 0.15 ± 0.02 gm. sample of the concentrate into a clean, dry 300-ml. standard, tapered-neck flask. Add 20 ml. of isopropyl alcohol (99 percent) and 2½ gm. of freshly cut sodium (cut into small pieces) and swirl the flask to mix its contents. Connect the flask to a water-cooled reflux condenser having a corresponding standard tapered male fitting and boil gently for 2½ hours, swirling occasionally. Destroy the excess sodium by adding 15 ml. of isopropyl alocohol followed by the cautious addition of 10 ml. of 50-percent isopropyl alcohol. Transfer the contents of the flask quantitatively to a 600-ml. beaker; rinse the flask, condenser, and glass joint thoroughly with water, catching the washings in the beaker. Add a few glass beads, cover with a watch glass and boil gently on a hot plate until the volume is 75 to 100 ml. Cool, add a few drops of phenolphthalein, neutralize with nitric acid (1:1) and add 5 ml. of the acid in excess. Transfer the solution to a 500-ml. separatory funnel, rinsing the beaker a few times with distilled water. Wash down the sides of the beaker with two successive 20-ml. portions of a mixture consisting of ethyl ether and isoamyl alcohol (2:1), transferring the washings successively to the funnel. Finally, rinse the beaker three times with distilled water, adding these washings successively to the funnel. Shake the funnel vigorously for 1 minute, and let stand until a clean separation of phases occurs. Draw off the aqueous layer into a 600-ml. beaker; wash the organic layer in the funnel with 10 ml. of distilled water, shaking vigorously for 1 minute. Again let the phases separate cleanly and add the wash water to the beaker. Repeat the washing with a second 10-ml. portion of water. Add slowly, with stirring, an accurately measured volume of standard 0.1*N* silver nitrate solution (40 ml. approx.). Coagulate the precipitate by heating on a steam bath for 4 hours, cool and filter through a No. 42 Whatman paper. Wash thoroughly with cold distilled water, receiving the filtrate and washings in a 500-ml. Erlenmeyer flask. Add 5 ml. of ferric ammonium sulfate indicator[3] and titrate with 0.1*N* ammonium thiocyanate solution. Compute the net number of milliliters of silver nitrate solution used by the sample. Then compute the percentage chlorine in the sample by the equation:

$$a = \frac{b \times 0.3547}{\text{weight of sample grams}}$$

where:

a = percentage chlorine

b = net number of milliliters of 0.1000*N* silver nitrate used.

4.4.2 *Tests of dieldrin ingredient (type D).*

4.4.2.1 *Organically bound chlorine content.*—Weigh accurately a 1.5-gm. sample of the dieldrin ingredient into a 100-ml. volumetric flask and make to volume with benzine (thiophene free). Dissolve completely and pipette a 10-ml. sample into a 300-ml. standard tapered neck flask; proceed as specified in 4.4.1.4.

4.4.2.2 *Kerosene insolubles.*—Dissolve (by warming) 0.5 gm. of dieldrin ingredient in sufficient kerosene to make a final volume of 50-ml. Proceed as specified in 4.4.1.3.

[1] The decomposition of the sample by sodium is recommended. However, it is permissible to use the Parr bomb method using sodium peroxide as the fusion material for dechlorination. If the latter method is used, the subsequent procedure shall be as specified in 4.4.1.4 starting with the instructions for transferring the material to the separatory funnel and extracting with the ether-isoamyl alcohol mixture. In the event of dispute, the results obtained by the sodium decomposition method specified shall govern.

[2] The use of a small dropping bottle (15-ml. capacity) with a ground-in pipette having a rubber bulb is convenient for the accurate weighing of the concentrate sample taken for test.

[3] Ferric ammonium sulfate indicator is prepared by dissolving 125 gm. of the salt in 300 ml. of distilled water, adding 25 ml. of freshly boiled concentrated nitric acid (cooled before addition) and diluting with distilled water to 500 ml.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:14Z
Check the source to verify that this is the current version before use.

4.4.3 *Tests of liquid insecticide.*

4.4.3.1 *Organically bound chlorine content.*

4.4.3.1.1 *For type C.*—With the sample at 77°F., accurately pipette an 8-ml. portion into a 300-ml. standard tapered-neck flask. Proceed at this point as specified in 4.4.1.4.

4.4.3.1.2 *For type D.*—With the sample at 77°F., accurately pipette a 25-ml. portion into a 300-ml. standard tapered-neck-flask. Proceed as specified in 4.4.1.4.

4.4.3.2 *Qualitative color test.*—Pipette accurately a 0.25-ml. sample of the liquid insecticide into a small test tube (15 to 20-ml. capacity), add 3 ml. of a solution containing diethanolamine and 1*N* methanolic potassium hydroxide (two parts of the amine and one part of the caustic). Add 7 ml. of isopropyl alcohol (99 percent), stir to mix contents and place on a steam bath for 30 minutes. A 0.25-ml. sample from a 2-percent comparison solution shall be tested in the same manner along with the test sample. This comparison solution shall be prepared by dissolving 2 ± 0.1 gm. of the technical refined grade chlordane that was submitted with the material offered for inspection (see 4.1.2.2) in sufficient kerosene conforming to Military Specification MIL–K–3128 to make an accurate volume of 100 ml. After the 30-minute heating period the tubes shall be cooled and the intensity and type of red color developed shall be compared visually. If a precipitate or haze occurs, the solutions shall be filtered before the comparison.

4.4.3.3 *Active component, HEOD (for type D only) (by partition chromatography).*

4.4.3.3.1 *Apparatus and reagents.* — The apparatus and reagents to be used are as described in sections 5. 149 and 5. 150 of the Official Methods of Analysis of the Association of Official Agricultural Chemists, Seventh Edition (1950), except that the dye solution described shall contain 50 mg. D and C red No. 18 and 100 mg. D and C violet No. 2 per 100 ml. of mobile solvent.

4.4.3.3.2 *Preparation of sample.*—With the sample of type D insecticide at 77°F., pipette 50 ml. into a 100-ml. volumetric flask, add 2 ml. of the dye solution and dilute to the mark with mobile solvent. Mix thoroughly.

4.4.3.3.3 *Preparation of column.*—Transfer 80-gm. of silicic acid to the blendor, add 225 ml. of mobile solvent, mix by means of blendor and while mixing add 40 ml. of nitromethane. Continue mixing for 15 seconds and quickly pour mixture (use 6-inch funnel) into the partition column. Wash down walls of column with 5 ml. of mobile solvent and apply 3 to 5 pounds pressure of nitrogen to force liquid into silicic acid. Allow about 1½ inches of liquid to remain above the top of the acid. If necessary, tap column to insure top of acid is level. Close regulator on nitrogen tank and relieve pressure in the column by cautiously removing the rubber stopper.

4.4.3.3.4 *Determination.* — With the prepared sample at 77°F., pipette 20 ml. and allow to flow very slowly down the walls of the column (a burette may be substituted for the pipette), taking care not to disturb the top of the acid. Wash down column walls with 10 ml. of mobile solvent. Reapply 3 to 5 pounds pressure of nitrogen and maintain until the sample (as indicated by the dye colors) has been forced completely into the acid. Do not allow liquid level to fall below the top of the acid column. Cautiously release pressure and add 100 ml. of mobile solvent. Reapply pressure (see note 1). Immediately before the red color is about to leave the column release pressure and add an additional 100 ml. of mobile solvent. Reapply pressure. As the red colored solution reaches the bottom of the column collect the eluent alternately using two 10-ml. graduated cylinders. First collect four 5-ml. fractions transferring each to a consecutively numbered 50-ml. flask. Retain these (see note 2). Then continue collecting 2½ ml. portions transferring

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:14Z
Check the source to verify that this is the current version before use.

each to individually consecutively numbered 50 ml. flasks. Place each flask on steam bath as collection is made. Continue collection until the last of the red colored solution has been eluted. Then collect 5-ml. portions until the blue colored solution is obtained. Finally, collect three or four 5-ml. portions of the blue colored eluent. Retain (see note 2). Evaporate all flasks to dryness and examine. The appearance of a solid film indicates that HEOD is being obtained. Examine in consecutive order those flasks showing this film. Stoppage of film formation in flasks shows termination of HEOD elution. To each of those flasks showing the film add 7 or 8 ml. of n hexane. Warm flasks to dissolve HEOD and transfer to a tared 250-ml. flask. Wash consecutively each of the 50-ml. flasks with 15 ml. of n hexane, adding the hexane to the first flask, pouring the hexane into the second etc., until all have been washed. Add washings to the tared flask. Repeat washing with another 15 ml. of hexane and again add washings to the tared flask. Evaporate hexane from the 250-ml. flask on a steam bath until a solid film appears. Remove from bath and evacuate the flask for 2 minutes on a vacuum pump. Cautiously allow air to enter flask several times during this evacuation. Place the flask in a desiccator for several minutes. Weigh and calculate the amount of HEOD obtained.

Note 1: Care must be taken to obtain a level acid column so that the absorption of the sample (as indicated by the dyes) is uniform. Failure to obtain this is shown either by the formation of isolated colored areas or the boundary formed between the two dyes is ragged. If either or both conditions exist discord column (since poor results will be obtained) and restart assay.

Note 2: These flasks are retained for insurance purposes and are kept until the initial and final appearance of HEOD has been observed.

4.4.3.4 *Appearance.*—Examine the liquid insecticide visually by transmitted light for clarity, sedimentation and haze.

4.4.3.5 *Residual odor.*—Dip strips of No. 40 Whatman filter paper of uniform shape and size into the liquid. Remove and allow to dry for 4 hours in a well-ventilated room. Examine for residual odor.

4.4.3.6 *Staining properties.* — Place three drops of the liquid insecticide upon an 11-centimeter No. 40 Whatman filter paper supported so that the area treated shall be free of contact with any under surface. Allow the liquid to evaporate from the paper and after 4 hours examine for staining.

4.4.3.7 *Flash point.*—The flash point shall be determined using the tag closed tester in accordance with method 1101 (flash point of volatile flammable liquids) of Federal Test Method Standard No. 791.

4.4.3.8 *Corrosion test.*—Place a clean strip of mechanically polished mild steel (SAE 1020) about ½ inch in width and 3 inches in length in a clean dry test tube. Add sufficient liquid insecticide to completely immerse the test strip. Stopper the tube, place in an oven maintained at 50°C. for 4 hours. After that time remove the strip and compare with a similar strip of freshly polished steel.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.

5.1.1 *Levels A and B.*—One gallon of insecticide of one type only shall be filled into a square or rectangular base, one-gallon capacity metal can. The can, equipped with handle and fabricated from Special Can Manufacturer's terneplate, 1.25 pound hot-dip tinplate or 0.50 pound electrolytic tinplate, shall conform to type V, class 4 or 5, Federal Specification PPP–C–96 with exterior protective coating conforming to Plan B. Each closure shall be provided with inner seals.

5.1.2 *Level C.*—One gallon of insecticide of one type only shall be packaged in accordance with the manufacturer's commercial practice.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:14Z
Check the source to verify that this is the current version before use.

5.2 Packing.

5.2.1 *Level A.*—Six one-gallon cans of insecticide of one type only, packaged by level A or C as specified shall be packed in accordance with the Appendix of Federal Specification PPP–C–96 except that, in addition to the cushioning specified, half slotted partitions and box liners shall be used. Partitions and liners shall be fabricated from fiberboard conforming to compliance symbol W6c of Military Specification JAN–P–108. The height of the partitions shall be equal to the height of the can, exclusive of the handle and shall form an individual snug-fitting cell for each can. The box liners shall be of one-piece construction. The height for the liner shall be equal to the inside depth of the box, less the thickness of the top and bottom pads and shall cover the sides and ends of the box. The ends of the liner shall abut at the center of a side panel and the seam formed shall be taped full length with pressure-sensitive tape. The top and bottom pads shall be not more than one-sixteenth of an inch smaller than the inside length and width of the box.

5.2.2 *Level B.*—Six one-gallon cans of insecticide of one type only, packaged by level A or C as specified shall be packed in accordance with the Appendix of Federal Specification PPP–C–96.

5.2.3 *Level C.* — The insecticide shall be packed in containers, which (together with packaging, wrapping, and inner packing) are acceptable by common or other carriers for safe transportation to point of destination specified in shipping instructions at the lowest transportation rate for such supplies.

5.3 Compatibility of containers.—The container, closure, lining, on space fillers shall not interact physically or chemically with the contents of the container so as to be altered or to alter the strength, quality, or purity of the container contents for at least 1 year from the date of shipment.

5.4 Marking.

5.4.1 *For Military shipments.*—In addition to the marking specified in 3.4 and any special marking required by the contract or order, marking shall be in accordance with Military Standard MIL–STD–129. In addition, shipping containers shall be marked to insure safe handling as required by the Code of Federal Regulations and Regulations for Explosives or Other Dangerous Articles on Board Vessels.

5.4.1.1 *Labels.* — Labels specified in 3.4 shall be securely affixed in place with water-resistant label adhesive as specified in section 3 of Military Standard MIL–STD–129 and shall be waterproofed by coating the entire outer surface of the label with the same adhesive.

5.4.2 *For nonmilitary shipments.*—In addition to the marking specified in 3.4 and any special marking required by the contract or order, marking shall be in accordance with Federal Specification PPP–P–31. In addition, shipping containers shall be marked to insure safe handling as required by the Code of Federal Regulations and Regulations for Explosives or Other Dangerous Articles on Board Vessels.

6. NOTES

6.1 Federal Standard No. 102 should be referred to for definitions and applications of the various levels of packaging protection for supplies and equipment.

6.2 Ordering data. — Procurement documents should specify the following:

(a) Title, number, and date of this specification.

(b) Type required (see 1.2).

(c) Applicable levels of preservation, packaging, and packing required (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:14Z
Check the source to verify that this is the current version before use.

6.3 Liquid insecticide is purchased by volume, the unit being a U. S. gallon at 25°C. (77°F.).

Patent notice.—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

MILITARY INTERESTS:

Army—Q M
Navy—Sh MC Y
Air Force.

★ U. S. GOVERNMENT PRINTING OFFICE: 1957

Copies of this specification may be purchased for 10 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:14Z
Check the source to verify that this is the current version before use.