MIL-B-17089A(Aer)
Amendment - 1
26 September 1957

MILITARY SPECIFICATION

BAROMETER, ANEROID ML-448( )UM

This amendment forms a part of Military Specification MIL-B-17089A(Aer) of 18 April 1957, and has been approved by the Bureau of Aeronautics, Department of the Navy.

Page 2 Paragraph 3.4.4 Delete the entire paragraph and substitute the following:

"Crystal. The crystal shall be flat clear glass free of bubbles or flaws. It shall show no warpage that will interfere with the assembly or operation of barometer. It shall be entirely suitable for intended use and capable of withstanding normal handling and use aboard ship."

Page 3 Paragraph 3.5.1 Delete sentence:

"A removable mounting base of a design suitable to permit standing the barometer on a horizontal surface, shall be attached to the case."

Line 18: Delete "500 millibars" and substitute "30 millibars".

Page 7 Paragraph 4.2.3 Delete "10 millibars and substitute " 30 millibars".

Page 8 Paragraph 4.2.8 Delete "0.3 millibars" and substitute "0.4 millibars".

Page 8 Paragraph 4.2.11 Delete the entire paragraph and substitute the following:

"Friction. Test shall be made with dial vertical and again with dial horizontal. The barometer shall be isolated from appreciable vibration and reading noted. Change pressure approximately 3 millibars and read barometer. Tap sharply; the change in reading shall not exceed 0.5 millibars. Repeat at least at three separate pressure test points."

Page 8 Paragraph 4.2.12 Delete "0.4 millibars and substitute "0.5 millibars".

Page 9 Paragraph 4.2.14.1 Delete "(a) -20°F ±2°F
Delete "0.0090 millibars" and substitute "0.0150 millibars".

Page 9 Paragraph 4.2.17 Delete entire paragraph.

Source: https://assist.dla.mil -- Downloaded: 202610-18T09:44Z
Check the source to verify that this is the current version before use.