NOT MEASUREMENT SENSITVE

MIL-DTL-11484/353B(IH)
10 March 2023
SUPERSEDING
MIL-DTL-11484/353A(IH)
15 November 2017

DETAIL SPECIFICATION SHEET

# LAPEL BUTTON, STRATEGIC MISSION, DEFENSE INTELLIGENCE AGENCY

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-11484.

**All lettering and discs between phrases shall be epoxied BLUE #20**




MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

DIMENSIONS:
HEIGHT: 11/16 inch
WIDTH: 11/16 inch
THICKNESS (along bottom scroll): 0.075 inch ± 0.010 inch

FINISH: 24K Gold Plated, Matte Finish, Polished Highlights and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 8.

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T02:31Z
Check the source to verify that this is the current version before use.

EPOXY: Epoxy shall be applied where indicated, and shall match TIOH Hard Enamel Color Chip Number listed:

| TIOH HARD ENAMEL COLOR CHIP NUMBER | LOCATION(S) |
|---|---|
| Blue #20 | All letters and the discs between phrases |

ATTACHING DEVICE: Attaching device shall be prong with pick and wing type clutch. The prong shall be centered on the reverse side and either fused or soldered to the lapel button.

ITEM CASE: Lapel buttons to be presented in a case shall be mounted and centered on a polyethylene pad and placed in a rigid hinged plastic box having a transparent lid and opaque bottom section. The box shall have two plastic hinges and catches and shall be approximately 1-1/8 inches square and 5/8 inch in overall depth. The pad shall be of sufficient depth to restrict movement of the lapel button.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished obverse hub or die.

2. The manufacturer may deviate from MIL-DTL-11484 by applying a nickel underplating prior to applying the requisite 24K gold plating.

3. Hard cloisonné enamel may be used in lieu of epoxy enamel. If hard cloisonné enamel is used, the requisite base material for this item is Gilding Metal 95/5 (UNS Alloy No.C-210).

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review Activity:
DLA - CT

(Project No. 8455-2023-113)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T02:31Z
Check the source to verify that this is the current version before use.