INCH-POUND

MIL-B-16029G
14 August 1989
SUPERSEDING
MIL-B-16029F
19 April 1974

MILITARY SPECIFICATION

BUCKETS, DRAGLINE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This document covers dragline buckets for earth and rock excavation.

1.2 Classification. Buckets will be one of the following types, classes, and sizes as specified (see 6.2):

1.2.1 Part or identifying number (PIN). (see 6.1.5)	(PIN Code)
Type I - Light duty.	- A
Type II - Medium duty.	- B
Type III - Heavy duty.	- C
Class P - Perforated plate.	- P
class S - Solid plate.	- S
Size 37 - 3/8 cubic yard (cu yd).	- 1
Size 50 - 1/2 cu yd.	- 2
Size 75 - 3/4 cu yd.	- 3
Size 100 - 1-1/2 cu yd.	- 4

Beneficial cements (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 3815

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:10Z
Check the source to verify that this is the current version before use.

Size 150 - 1-1/2 cu yd. - 5
Size 200 - 2 cu yd. - 6
Size 250 - 2-1/2 cu yd. - 7
Size 300 - 3 cu yd. - 8
Size 350 - 3-1/2 cu yd. - 9

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications. The following specifications form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

RR-W-410 - Wire Rope and Stand.

MILITARY

MIL-T-704 - Treatment and Painting of Material.
MIL-C-3580 - Cranes and Crane-Shovels, Truck, Crawler and Wheel Mounted, Full-Revolving and Their Attachments, Packaging of.
MIL-S-17249 - Steel Casting, Hadfield Manganese (Low Magnetic Permeability).
MIL-C-46168 - Coating, Aliphatic Polyurethane, Chemical Agent Resistant.
MIL-T-52176 - Teeth, Surface Ripping; (Points, Shanks, Keepers, and Keeper Locks), Bucket and Dipper, Crane-Shovel.
MIL-C-53039 - Coating, Aliphatic Polyurethane, Single Component, Chemical Agent Resistant.

(Unless otherwise Indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents which is current on the date of the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM A 27 - Standard Specification for Steel Castings, Carbon.
ASTM A 36/A 36M - Specification for Structural Steel.

Source: https://assist.dla.mil -- Downloaded: 202610-18T08:10Z
Check the source to verify that this is the current version before use.

ASTM A 148	Standards Specification for Steel Castings High Strength.
ASTM A 391	Specification for Alloy Steel Chain.
ASTM A 514/A 514M -	Specification for Alloy Steel Plate.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. The bucket unit shall include the bucket body, hoist and drag chains, spreader bar, dump block, dump rope, teeth, sheaves, and all necessary sockets, links, shackles, rings, and pins. The bucket unit shall be delivered complete and ready for use.

3.2 First article. When specified in the contract or purchase order, a sample shall be subjected to first article Inspection (see 4.2.1 and 6.2).

3.3 Standard bucket. components and accessories. Except as modified by this specification, the bucket components, and accessories shall be the manufacturer's standard or optional items, which meet or exceed the requirements of this specification.

3.4 Materials. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose In commercial practice. Unless otherwise specified herein, all equipment, material, and articles incorporated In the work covered by this specification are to be new and fabricated using materials produced from recovered materials to the maximum extent possible without jeapordizing the intended use. The term recovered materials means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. Unless otherwise specified, none of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this specification.

3.5 Capacity and weight. The struck level capacity of the bucket shall be within 2 percent of that specified in table I, and shall be established by taking the actual side area, with the forward line delineated by the angle of repose of the material assumed at 90 degrees from the deepest part of the

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:10Z
Check the source to verify that this is the current version before use.

cutting edge, multiplied by the average inside bucket width, which is determined by measurements of the top and bottom of both the front and rear reference points of the bucket. The weight of class S buckets, as delivered, shall be not less than specified for the respective size in table I. In addition, the delivered weight of class S buckets of size 37 through size 100 shall not exceed the respective specified weight by more than 10 percent, and the delivered weight of class S buckets of size 150 through size 350 shall not exceed the respective specified weight by more than 12 percent. The delivered weight of class P buckets shall be not less than 97 percent of the weight specified in table I, for the respective size of class S buckets. The bucket body, including teeth, hitch, plate pines, trunnion pins, and anchor pins shall be not less than 70 percent of the total weight of the bucket.

TABLE I. Capacitiies and weights (weights based on class S buckets).

	37	50	75	100	150	200	250	300	350
Struck capacity (cu ft)	11.25	15	22.5	30	45	60	75	90	105
Type I, weight (lb)	875	1,000	1,420	1,720	2,550	3,200	3,620	4,120	4,650
Type II, weight (lb)	900	1,150	1,550	1,830	2,930	3,550	4,100	4,800	5,350
Type III, weight (lb)	1,120	1,350	1,850	2,260	3,220	4,100	4,850	5,500	6,150

3.6 Components.

3.6.1 Bucket body. The bucket body shall include bottom, side, and back plates, with partial or complete lip and bottom, dependent on manufacturer's commmercial practice. Method of connecting bucket body assembly of arch, lip or complete bottom, hoist trunnions, hitch plates, runner bars, heel plates, and comer wearing shoes shall be either cast integral or welded, or combination of both. The body shall be designed in accordance with best commercial practice to handle the class of excavation for which it is intended. The inside surfaces shall be smooth and free from projections. The connections between the bottom and side plates shall have a radius and the back plates shall be curved sufficiently to provide satisfactory loading and dumping performance. Cast lips or cast bottoms and connections to body and side plates, shall provide a firm joint that is consistent with industry practice for weldments or riveted components. Inside clear width at the lip shall be slightly larger than at the heel to facilitate the discharge of adhesive material. The plates for the bottom, sides, and back of the bucket shall be of steel which meets or exceeds the requirements of ASTM designation A 36. The back and side plates of class P buckets shall be perforated in a manner that will not impair or weaken the bucket strength.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:10Z
Check the source to verify that this is the current version before use.

3.6.2 Arch. The front end components shall be of cast or rolled plate steel construction. The arch shall be designed so that it will withstand its proportionate share of the load during all operation cycles without defomation or failure, provided it is not subjected to loading or digging forces in excess of four times the breaking strength of the size dump rope specified In table II. Ample clearance shall be provided for the flow excavated material in and out of the bucket.

TABLE II. Dump rope size (inches).

	Bucket size								
	37	50	75	100	150	200	250	300	350
Rope size	1/2	5/8	5/8	5/8	3/4	3/4	7/8	1	1-1/8

3.6.3 Lip. The lip shall be cast manganese steel conforming to MIL-S-17249, cast steel conforming to ASTM A 27 and ASTM A 148, or alloy steel plate conforming to ASTM Designation A 514, or better. The lip shall form the cutting edge. The extent of the lip shall conform to the manufacturer's standard practice, and shall accommodate the teeth as specified (see 3.6.4). All lips or cutting edges shall enable replacement of expendable components.

3.6.4 Teeth. Unless otherwise specified (see 6.2), manufacturer’s standard bucket teeth shall be furnished. When specified (see 6.2), teeth shall conform to MIL-T-52176. The teeth shall be readily replaceable by the use of standard tools.

3.6.5 Hitch plates. The hitch plates for attaching the drag chains to the bucket shall be of one of the steels specified in 3.6.3 except for types I and II buckets of size 100 and smaller, the steel may conform to ASTM A 27 and ASTM A 148. The hitch plates shall provide not less than two positions for the attachment of the drag chains as an aid in controlling the digging depth. The plates shall be either riveted or welded to the bucket body.

3.6.6 Trunnion brackets. The trunnion brackets shall be of one of the steels specified in 3.6.3. The trunnion brackets shall be accurately located on the bucket body to provide proper balance, and shall be either riveted or welded in place.

3.6.7 Runners. Renewable runners shall be provide and shall be either riveted or welded to the heel of the bucket. The runners shall be of one of the steels specified in 3.6.3.

3.6.8 Heel plates. Renewable or integral cast type heel plates shall be provided. Renewable heel plates shall be either riveted or welded between the runner bars at the heel of the bucket. The plates shall be of one of the steels specified in 3.6.3.

3.6.9 Corner wearing shoes. All buckets shall have renewable cast corner wearing shoes of the material specified in 3.6.3. Renewable wearing shoes shall be bolted, riveted, or welded to the bottom corner.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:10Z
Check the source to verify that this is the current version before use.

3.6.10 Chains. Unless otherwise specified (see 6.2), all buckets shall be furnished with the manufacturer's standard hoist and drag chains, links, rings, and shackles. When specified (see 6.2), chains shall meet or exceed the requirements of ASTM A 391.

3.6.11 Spreader bar. Spreader bar shall be of rolled or cast steel with a minimum safety factor of 3, based on yield strength, using a static struck bucket loaded with material weighing 100 pounds per cubic foot.

3.6.12 Dump block. The dump block assembly shall include the frame, sheave, axle, and lubrication fittings. The frame shall be of cast or rolled steel. The sheave shall be made of steel conforming to one of the steels specified in 3.6.3 and shall have smooth grooves with a pitch diameter of not less than 16 times the diameter of the dump rope. The sheave shall be furnished with lubricated roller type bearings, or needle bearings as normally provided an commercial buckets of the size indicated. The sheave pin shall be of cold rolled or forged steel.

3.6.13 Dump rope. The dump rope shall be 6 by 19 improved plow steel, uncoated, preformed, independent wire rope core conforming to RR-W-410, type I, class 2, construction 3. Size of dump rope shall be not less than specified in table II (see 3.6.2). Sockets shall be of steel conforming to one of the steels specified in 3.6.3.

3.7 Cleaning. treatment, and painting. Surfaces normally painted in good commercial practice shall be cleaned, treated, and painted as specified herein. The color of the finish coat shall be as specified (see 6.2). Surfaces to be painted shall be cleaned and dried to insure that they are free from contaminants such as soil, grease, welding slag and spatter, loose mill scale, water, dirt, corrosion product, or any other contaminating substances. As soon as practicable after cleaning, and before any corrosion product or other contamination can result, the surfaces shall be prepared or treated to insure the adhesion of the coating system. The painting shall consist of at least one coat of primer and one finish coat. The primer shall be applied to a clean, dry surface as soon as practicable after cleaning and treating. Painting shall be with manufacturer's current materials according to manufacturer's current processes and the total dry film thickness shall be not less than 2.5 mils over the entire surface. The paint shall be free from runs, sags, orange peel, or other defects. ("When specified see 6.2"), the portions of the (item) normally painted internally and externally shall be cleaned, treated and painted in accordance with MIL-T-704, type F or G, as applicable. Top coat color shall be green 383 conforming to MIL-C-46168 or MIL-C-53039 as applicable.

3.8 Identification plate. The contracting officer will furnish to the Government inspector the required identification plates. The contractor will be required to stamp the necessary data in the blank spaces thereon and securely affix said plates in a conspicuous place on each unit, assembly or subassembly, and parts as directed by the Government inspector. Nonferrous screws, rivets, or bolts of not less than l/8-inch in diameter shall be used to affix the plates. Nomenclature contained in contract item description shall be placed in the top blank.

Source: https://assist.dla.mil -- Downloaded: 202610-18T08:10Z
Check the source to verify that this is the current version before use.

3.9 Lubrication. Means for lubrication shall be in accordance with the manufacturer's standard practice. The lubricating points shall be easily visible and accessible. Where use of high pressure lubricating equipment, 1,000 pounds-force per square inch or higher, will damage grease seals or other parts, a suttable warning shall be affixed to the equipment in a conspicuous location.

3.10 Workmanship. All parts, components, and assemblies of the bucket, Including castings, forgings, molded parts, stamping, bearings, seals, machined surfaces, and welded parts, shall be clean and free from sand, dirt, fins, pits, sprues, scale, flux, and other harmful extraneous material. External surfaces shall be free from burrs, sharp edges, and corners except when sharp edges and comers are required.

3.11 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to insure uniformity of size and shape.

3.12 Bolted connections. Bolt holes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

3.13 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape and of uniform size for the same diameter of rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

3.14 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

3.15 Castings. All castings shall be sound and free from patching, misplaced coring, warping, or any other defect which reduces the castings ability to perfom its intended function.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:10Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Examination. Each bucket shall be examined. for compliance with the requirements specified in section 3 of this specification. Any redesign or modification of the suppliers standard product to comply with specified requirements, or any necessary redesign or modification following failure to meet specified requirements, shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirements or presence of one or more defects preventing or lessening maximum efficiency shall constitute cause for rejection.

4.2.1 First article inspection. The first article inspection shall be performed on buckets when a first article is required (see 3.2 and 6.2}. This inspection shall include the examination of 4.2.1 and the tests of 4.3. The first article may be either a first production item or a standard production item from the supplier's current inventory provided the item meets the requirements of the specification and is representative of the design, construction, and manufacturing technique applicable to the remaining items to be furnished under the contract.

4.3 First article tests. When first article is required, the first article bucket of each type, class, and size shall be subjected to the tests specified in 4.3.1 and 4.3.2. The first article tests shall be performed by the supplier. The supplier shall provide all material and equipment to perform all testing specified. Failure to pass any phase of the required tests shall be cause for the Government to refuse acceptance of all buckets until corrective action has been taken.

Source: https://assist.dla.mil -- Downloaded: 202610-18T08:10Z
Check the source to verify that this is the current version before use.

4.3.1 Material rehandling test. Bucket shall be tested for rehandling of materials. Materials for testing shall be loose or stockpiled earth, rock, or a combination thereof. The bucket shall scoop up a load, raise, and dump contents completely. This test cycle shall be repeated not less than 10 times and the average load shall be not less than the stuck capacity required in 3.5.

4.3.2 Digging test. Bucket shall be subjected to a digging test. Materials for testing shall be in-place moist earth, reck, or combination of earth and rock. Bucket shall be set down or dropped on the materials at the proper angle to dig and scoop a load immediately. The bucket shall be raised and conveyed to the proper location where material shall be completely dumped. This test cycle shall be repeated not less than 10 times and the average load shall be not less than the struck capacity of the bucket as required in 3.5. The loading and dumping of arty materials being tested shall not be retarded by protrusions or projections inside the bucket.

4.4 Production unit tests. The contractor's testing procedures shall, as a minimum, assure that each bucket is capable of meeting the requirements of this specification.

4.5 Packaging inspection. The preservation, packing, and marking of the item shall be inspected to verify cmformance to the requirements of section 5.

5. PACKAGING

5.1 Preservation, packing, and marking. Preservation, packing, and marking shall be in accordance with the requirements of MIL-C-3580 with the level of preservation and the level of packing as specified (see 6.2).

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. Dragline buckets covered by this specification are intended for excavating earth and loose rock.

6.1.1 Type I. The type I, light duty bucket is Intended for excavating sand, loose earth, loam, moist and wet clay, and loose small gravel.

6.1.2 Type II. The type II, medium duty bucket is intended for excavating dry clay, loose boulders, coal, gravel, and soft shale.

6.1.3 Type III. The type III, heavy duty bucket is intended for excavating average cemented gravel, hard shale, conglomerate hardpan, claiche, and broken rock.

6.1.4 Class P. The class P perforated bucket is intended for excavating wet material that is not too fluid. This class bucket has less weight than the class S solid plate bucket.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:10Z
Check the source to verify that this is the current version before use.

6.1.5 Part or identifying numbers (PIN). The PINs were developed to identify items covered by this specification for cataloging purposes. The PIN consist of this specification identifier (M16029), the type, class, and size specified herein.

Example - Heavy Duty, perforated plate 2 cubic yards.

	M	16029	C	4
Military specification				
Specification number				
Type				
Size				

TABLE III. Bucket type, class, and size.

Type	Class		Size							
	P	S	1	2	3	4	5	6	7	8
A										
B										
C	X							X		

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Type, class, and size of bucket required (see 1.2).
c. Issue of DODlSS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
d. When first article is required for inspection and approval (see 3.2, 4.2.1, and 6.3).
e. When teeth shall confomr to MIL-T-52176 (see 3.6.4).
f. When chains shall meet or exceed the requirements ASTM Designation A 391 (see 3.6.10).
g. When cleaning, treatment, and painting in accordance with MIL-T-704, type A is required (see 3.7).
h. For Army procurements specify MIL-T-704, Type F or G paint (see 3.7).
i. Finish coat color required (see 3.7).
j. Level of preservation and level of packing required (see 5.1).

6.3 First article. When a first article inspection is required, the item will be tested and should be (a first article sample), {a first production item) (a sample selected from the first bucket production items) or it may be a standard production item from the contractor's current inventory as specified in 4.2.1. The first article should consist of (one), (two), etc unit(s). The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test, and approval of the first article.

Source: https://assist.dla.mil -- Downloaded: 202610-18T08:10Z
Check the source to verify that this is the current version before use.

6.4 Subject term (keyword) listing.

Solid plate.
Perforated.
Cable operated.

6.4.1 Changes from previous issue. Marginal notations are not used fn this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:
Army - ME
Navy - YD
Air Force - 99

Preparing Activity:
Navy - YD

(Project 3815-0100)

Review Activities:
Air Force - 84
DLA - CS

User Activity:
Navy - MC

Source: https://assist.dla.mil -- Downloaded: 202610-18T08:10Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

Commanding Officer (Code 156)
Naval Construction Battalion Center
Port Hueneme, CA 93043-5000

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer
Code 156
Naval Construction Battalion Center
Port Hueneme, CA 93043-5000

Source: https://assist.dla.mil -- Downloaded: 202640-18T08:10Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-B-16029G	BUCKETS, DRAGLINE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*:
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 202610-18T08:10Z
Check the source to verify that this is the current version before use.