	MILLIVOLTS, D. C.	VOLTS, D. C.	
	Single range	Single range	Multiple range
FULL-SCALE RANGES	50 100 200 500	3 150 800 30 300 50 500	300/30

ITEM	REQUIREMENT
Scale length	5 inches min.
Position influence (balance)	1 percent of scale length, max. change.
Initial accuracy	.25 percent max. error.
Damping factor	5 min.
Response time	2 seconds max.
Power consumption	30 ma. max. : millivoltmeters. 20 ma. max. : voltmeters.
External-field influence	.75 percent max. change in 5-oersted field.
Heat effect at 65° C.	1 percent max. change at 65° C. : voltmeters. 2 percent max. change at 65° C. : millivoltmeters. .5 percent max permanent change.
Temperature influence	.25 percent max. change: voltmeters. .5 percent max. change: millivoltmeters.
Low-temperature exposure	.63 percent max. change at 0° C. : voltmeters. 1.25 percent max. change at 0° C. : millivoltmeters. .5 percent max. permanent change.
Sustained overload	1 percent of scale length, max. temporary zero shift. .5 percent of scale length, max. permanent zero shift. .33 percent max. permanent change in indication.
Vibration	1 percent max. change.
Friction effect	2 percent max change.
Humidity resistance	1 percent max. change.

NOTES:

1. Percentages are based on full-scale value unless otherwise indicated herein.
2. Referenced specifications shall be of the issue in effect on date of invitation for bids.

APPROVED 2 Jan 1953 REVISED

NOTICE When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation or conveying any rights or permission to manufacture use, or sell any patented invention that may in any way be related thereto

CUSTODIANS:
Army–Signal Corps
Navy–Bureau of Ships
Air Force

PROCUREMENT SPECIFICATION
MIL-M-16034

MS Form 233 1 Oct 52

SPECIFICATION SHEET

VOLTMETERS, D.C., PORTABLE,
0.25-PERCENT ACCURACY CLASS

MIL-M-16034/11

SHEET 1 OF 1

Other interest Army - EOT, Navy - MCorSY

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:14Z
Check the source to verify that this is the current version before use.