


* THIS DIMENSION HAS BEEN CHOSEN TO ALLOW THE MOUNTING OF ACCESSORIES ON INSTRUMENT PROPER

PANEL DRILLING PLAN

ALL DIMENSIONS IN INCHES

	MILLIAMPERES, A. C. 1/	AMPERES, A. C. 1/	KILOAMPERES, A. C. 1/
FULL-SCALE RANGES 2/	100 200 500	5 50 200 600 10 75 300 800 20 100 400 30 150 500	1 3 1.2 4 1.5 2

1/ Alternating current (60, 400, or 800 cycles per second).

2/ Ammeters above 50 amperes and all kiloammeters are calibrated for use with external transformers. Current through meter at full-scale deflection is 5 amperes.

APPROVED 2 Jan 1953 REVISED

NOTICE When Government drawings specifications or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever and the fact that the Government may have formulated, furnished or in any way supplied the said drawings, specifications or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto

CUSTODIANS
Army-Signal Corps
Navy-Bureau of Ships
Air Force

PROCUREMENT SPECIFICATION
MIL-M-16034

SPECIFICATION SHEET

AMMETERS, A. C., SWITCHBOARD
6-INCH, 90-DEGREE SCALE

MIL-M-16034/8

SHEET 1 OF 2

MS Form 233, 1 Oct 52

Other interest: Army - EOT, Navy - MCOrSY

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:13Z
Check the source to verify that this is the current version before use.

ITEM	REQUIREMENTS
Scale length	5 inches min.
Position influence (balance)	1 percent of scale length, max. change.
Initial accuracy	1 percent max. error.
Damping factor	3 min.
Response time	2.5 seconds max.
Power consumption	5 va. max.
Frequency range	60-cycle meters; 25 to 125 cycles, 2 percent max. change.
Frequency influence	.5 percent max. change for 60-cycle meters. 2 percent max. change for 400- and 800-cycle meters.
External field influence	3 percent max. change in 5-oersted field.
Heat effect at 65° C.	2 percent max. change at 65° C. .5 percent max. permanent change.
Temperature influence	.5 percent max. change.
Low-temperature exposure	1.25 percent max. change at 0° C. .5 percent max. permanent change.
Momentary overload	1 percent max. change.
Sustained overload	1 percent of scale length, max. temporary zero shift. .5 percent of scale length, max. permanent zero shift. .33 percent max. permanent change in indication
Vibration	1 percent max. change.
Friction effect	2 percent max. change.
Humidity resistance	2 percent max. change.

NOTES:

1. Percentages are based on full-scale value unless otherwise indicated herein.

2. Referenced specification shall be of the issue in effect on date of invitation for bids.

APPROVED 2 Jan 1953 REVISED

NOTICE When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture use, or sell any patented invention that may in any way be related thereto

Downloaded from http://www.everyspec.com on 2026-01-18T08:13Z
Check the source to verify that this is the current version before use.