MILITARY SPECIFICATION

CONTAINER, WEAPON SECURITY: XH4289

This specification is approved for use by U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Department and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This military specification covers one type of container, designated Container, Weapons Security: XH4289, which is used as a security container, for various weapons systems, in the WADS program.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

*2.1.1 Specification and standards.
Specification and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

MIL-W-21157 - Weldment, Steel, Carbon and Low Alloy.

*2.1.2 Other Government documents, drawings and publications.
Other Government documents, drawings and publications. The following other Government document forms a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament,Munitions and Chemical Command, Attn. AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8140
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:06Z
Check the source to verify that this is the current version before use.

PRODUCT DRAWINGS

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT CENTER

9349591 - Container, Weapon Security: XH4289.
9349592 - Cage-Pallet Weldment.
9349593 - Cage Weldment.
9349945 - Tang.
9378072 - Gas Spring.
9352729 - Caster, Swivel, Heavy Duty.
9354410 - Handle, Wrench.
9354411 - Wrench, Caster Fork.
9369974 - Plunger.
9369978 - Housing, Plunger.
9369979 - Spacer, Lock.
9369980 - Plate, Lock Mount.
9369984 - Plate, Deck.
9369993 - Top Section, Cage, Pallet.
9378258 - Shipping Configuration, Container, Weapon Security: XH4289
9381474 - Tool, Clamp.
9381668 - Packing and Marking for Swivel Casters.

INSPECTION EQUIPMENT DRAWINGS

U.S. ARMY ARMAMENT, RESEARCH, DEVELOPMENT AND ENGINEERING CENTER

9354610 - Functional Gage, Weapon Security Container.
9395733 - Functional Gage, Slider, Deck Plate.

Copies of specifications, standards, drawings, and publications required by manufacturers in connection with specific acquisition functions, should be obtained from the contracting activity or as directed by the contracting officer.

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specification sheets of MS standards) the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials and components. Materials shall conform to applicable specifications and drawings. Each component shall conform to all dimensions and tests specified on the component drawing. The contractor shall have available verifiable proof (i.e., objective evidence (see 6.2)) that materials and components were fabricated, inspected, and tested under controllable conditions as set forth in the contractor's quality control or inspection procedures.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:06Z
Check the source to verify that this is the current version before use.

3.2 Assembly. The security container shall comply with all requirements specified on drawings (dwg.) 9349591, with all requirements specified herein, and with the requirements of applicable specifications to the extent specified on the drawings and herein.

3.3 First article. When specified, a sample security container shall be subjected to first article inspection (see 4.3 and 6.1.1).

3.4 Compression test on gas spring. The gas spring (dwg. 9378072) shall be subjected to a compression test to ensure that it is in proper operating condition before it is installed in the security container. The force required to compress the piston of the gas spring 0.20 ± 0.05 inch, shall be 480 ± 65 pounds. Testing shall be as specified in 4.5.1.

3.5 Plunger pull test. The wire rope, crimped to each of the two plungers of the security container, shall be capable of withstanding a minimum pull force of 75 pounds for a minimum period of 5 seconds. After this test, there shall be no evidence of deterioration or damage to the wire rope, or to any visible crimped connection, that may impair its intended operation. In addition, the plunger face shall not be displaced from its original position by more than 0.030 inch. Testing shall be as specified in 4.5.2.

3.6 Load test on handle. Prior to installation of the two gas springs, the center handle of the security container shall be tested to ensure that it is capable of supporting the weight of the container lid when the lid is lifted without the gas spring assist. The handle shall support the weight of the lid for a minimum period of 60 seconds, and there shall be no evidence of cracked welds, abnormal distortion to the handle, or other damage. Testing shall be as specified in 4.5.3.

3.7 Functioning test of container lid. The lid of the security container shall be raised to its full-open position, and the force required to raise the lid shall not exceed 50 pounds. While at its full-open position, the lock pin shall be capable of being inserted into the struts without binding or use of undue force and without failure of the pin to lock in place. During this test, the lid shall operate smoothly, during opening and closing, without evidence of binding. Testing shall be as specified in 4.5.4.

3.8 Serialization. A serial number shall be assigned by the contractor to each security container produced. In no event, shall serial numbers be duplicated, nor shall they give any indication of classified production quantities. Six-letter serial codes (e.g., VIN SAR) shall not be used on these containers.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:06Z
Check the source to verify that this is the current version before use.

3.9 Welding. All welding of the security container shall be in accordance with MIL-W-21157.

3.10 Workmanship. All parts and accessories shall be constructed, assembled, and finished in a thoroughly workmanlike manner. Particular attention shall be given to neatness, marking, cleaning, and freedom of the parts from burrs and sharp edges which may affect performance or result in injury during handling. All parts shall be free of chips, dirt, grease (unless specified on the drawing), rust, and other foreign material. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agents.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.3).

(b) Quality conformance inspection (see 4.4).

4.3 First article inspection.

4.3.1 Submission. When the contract requires first article inspection, one security container, produced by the contractor, shall be submitted to the testing facility designated in the invitation for bids or request for proposal. The two gas springs may be unassembled, for submission, to facilitate load testing on the handle (see 3.6).

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:06Z
Check the source to verify that this is the current version before use.

4.3.2 Inspection and testing to be performed. The first article inspection sample shall be inspected for the defects specified in 4.4.2.1, using inspection methods contained therein, and for all the requirements of Section 3. The test requirements of Section 3 are listed in Table I, and the tests shall be performed in the listed sequence. The plunger pull test shall be performed during production of the security container. The container shall be tested using the test methods specified in 4.5. Inspection and testing shall be performed with the acceptance inspection equipment specified in 4.4.4. If the container fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspections upon any failure of the first article sample to comply with the stated requirements. None of these tests is considered destructive, and the sample so tested shall be returned to the lot.

TABLE I. First article tests.

Test	Requirement paragraph
a. Plunger pull test	3.5
b. Load test on handle	3.6
c. Functioning test of container lid	3.7

4.4 Quality conformance inspection.

4.4.1 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot, and a batch shall mean an inspection batch for the purposes of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor shall bedesignated or approved by the Government representative.

4.4.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the major defect or minor defect table as applicable, (see Table II). Any defect found in the sample, selected for the major or minor classification, shall reject the lot. Inspection of major defects 102, 103, 104, 105, and 106 of the weapon security container (see 4.4.2.1.10) shall be conducted on a 100 percent basis. If any container fails to comply with any of the requirements of major defect 102, 103, 104, 105, or 106, the container shall be removed from the lot. The sequence of inspections for the classification of defects need not be followed so long as all the defect inspections are performed. The term "TMC", when used, shall mean tool manufacture control (see 6.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

TABLE II. Inspection lot sampling.

Major defect table		Minor defect table	
Lot size	Sample size	Lot size	Sample size
1-5	all	1-5	all
6-10	5	6-10	4
11-15	10	11-15	8
16-25	15	16-25	11
26-35	22	26-35	14
36-50	26	36-50	16
51 and over	30	51 and over	18

4.4.2.1 Classification of defects. Critical, major, and minor defects are defined in MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63955(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1.1	Spacer, Lock				9369979
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined.				
Major:					
101.	Thickness, max		Table II	3.2	Gage
102.	Diameter of counterbore, min. (2 places)		Table II	3.2	Gage
103.	Depth of counterbore, min. (2 places)		Table II	3.2	Gage
104.	Location of three attached holes		Table II	3.2	Gage
105.	Diameter of smaller attached hole, min. (2 holes)		Table II	3.2	Gage
Minor:					
201.	Evidence of poor workmanship		Table II	3.10	

NOTES:

Source: https://assist.dla.mil - Downloaded: 2022-10-23T03:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63955(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1.2	Plate, Lock Mount				9369980
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined.				
Major:					
101.	Thickness, max.		Table II	3.2	Gage
Minor:					
201.	Evidence of poor workmanship		Table II	3.10	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63955(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1.3	Tang	1 OF 1	9349945
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined.				
Major:					
101.	Thickness, min.		Table II	3.2	Gage
102.	Location of cutout in angled portion		Table II	3.2	Gage
103.	Depth of cutout in angled portion, min		Table II	3.2	Gage
104.	Distance from base of slot, between bore holes, to right side, max.		Table II	3.2	Gage
105.	Depth of vertical groove on right side (near bore holes), min.		Table II	3.2	Gage
Minor:					
201.	Configuration of tang improper (including slots and radii)		Table II	3.2	Visual
202.	Evidence of poor workmanship		Table II	3.10	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-01-23T03:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63955(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1.4	Plunger	1 OF 1	9369974
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined.				
Major:					
101.	Length, max.		Table II	3.2	Gage
102.	Diameter of flange, max.		Table II	3.2	Gage
Minor:					
201.	Chamfer on edge of flange missing or improper (2 places)		Table II	3.2	Visual
202.	Countersink in rear surface missing or improper		Table II	3.2	Visual
203.	Protective finish inadequate or improper		Table II	3.2	Visual
204.	Evidence of poor workmanship		Table II	3.10	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T13:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1.5	Top Section, Cage, Pallet				9369993
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined.				
Major:					
101.	Location of hole in top surface (2 holes)		Table II	3.2	Gage
102.	Diameter of hole in top surface, min. (2 holes)		Table II	3.2	Gage
Minor:					
201.	Evidence of poor workmanship (see 3.10)		Table II	3.10	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63955(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1.6	Housing, Plunger				9369978
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined.				
Major:					
101.	Diameter of cavity, min.		Table II	3.2	Gage
102.	Depth of cavity, min.		Table II	3.2	Gage
103.	Configuration of hole, in right side, improper		Table II	3.2	Visual
Minor:					
201.	Evidence of poor workmanship		Table II	3.10	Visual

NOTES:

Source: https://assist.dla.mil Downloaded: 2026-02-10T03:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63955(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1.7	Plate, Deck				9369984
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined.				
Major:					
101.	Thickness, min.		Table II	3.2	Gage
102.	Diameter of hole, min. (11 holes)		Table II	3.2	Gage/TMC
103.	Location of hole (11 holes)		Table II	3.2	Gage/TMC
104.	Location of slot (5 slots)		Table II	3.2	Gage/TMC
Minor:					
201.	Evidence of poor workmanship		Table II	3.10	Visual

NOTES:

Source: https://assist.dla.mil-Downloaded: 2026-01-20-23T03:06Z
Check the source to verify that the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63955(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.1.8	Cage Weldment				9349593
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major:					
101.	Location of beam (-5) on top of weldment (10 beams)		Table II	3.2	Gage
102.	Inspection hole in beam (-12) missing or improper (2 places)		Table II	3.2	Visual
103.	Inspection hole in beam (-13) missing or improper (2 places)		Table II	3.2	Visual
104.	Inspection hole in beam (-6) missing or improper		Table II	3.2	Visual
105.	Any beam missing, improper, or improperly assembled (44 beams)		Table II	3.2	Visual
106.	Tubing (-15) missing or improper in beam (-13) (2 places)		Table II	3.2	Visual
107.	Drill rod missing or improper in tubing (-15) (2 places) (inspect prior to assembly)		Table II	3.2	Visual
108.	Filler (-14) missing or improper in beam (-12) (2 places)		Table II	3.2	Visual
109.	Filler (-19) missing, improper, or improperly assembled in beam (-6) (2 places)		Table II	3.2	Visual
110.	Tang plate missing, improper, or improperly assembled (4 places)		Table II	3.2	Visual

NOTES:

Source: https://assist.dla.mil Downloaded: 2020-10-27T03:39Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1.8	Gage Weldment (continued)	2 OF 2	9349593
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
111.	Tie-down ring missing, improper, improperly located, or improperly installed (4 places)		Table II	3.2	Visual
112.	Pipe (-20) missing, improper, improperly located, or improperly attached (2 places)		Table II	3.2	Visual
113.	Expanded metal missing, cut, damaged, or improperly assembled		Table II	3.2	Visual
114.	Cover plate (tang shield) missing, improper, or improperly attached (2 places)		Table II	3.2	Visual
115.	Welding cracked, defective, or improper		Table II	3.9	Visual
Minor:					
201.	Protective finish inadequate or improper		Table II	3.2	Visual
202.	Protective finish on tang inadequate or improper		Table II	3.2	Visual
203.	Evidence of poor workmanship		Table II	3.10	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-01-23T13:06
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63955(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.1.9	Cage-Pallet Weldment				9349592
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined.				
Major:					
101.	Location of fork-lift tube underneath center of weldment (2 places from front to back; 2 places from side to side)		Table II	3.2	Gage
102.	Diameter of hole in towing hitch, min. (2 holes; 2 places)		Table II	3.2	Gage
103.	Location of hole in towing hitch (2 holes; 2 places)		Table II	3.2	Gage
104.	Location of flat hook tiedown in deck plate (4 places)		Table II	3.2	Gage
105.	Location of keepered hook in deck plate (4 places)		Table II	3.2	Gage
106.	Filler (-18) missing or improper in beam (-2) (3 places)		Table II	3.2	Visual
107.	Inspection hole in beam (-2) missing or improper (3 places)		Table II	3.2	Visual
108.	Expanded metal screen missing, cut, damaged, or improperly assembled		Table II	3.2	Visual
109.	Tie-down ring missing, improper, improperly located, or improperly installed (8 places)		Table II	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2024-10-03T03:10:06Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE		SHEET	DRAWING NUMBER
4.4.2.1.9	Cage-Pallet Weldment (continued)		2 OF 2	9349592
				NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
110.	Frame plate missing, improper, or improperly installed (8 places)		Table II	3.2	Visual
111.	Towing hitch improper, improperly located, or improperly attached (2 places)		Table II	3.2	Visual
112.	Welding cracked, defective, or improper (see 3.9)		Table II	3.9	Visual
Minor:					
201.	Protective finish inadequate or improper		Table II	3.2	Visual
202.	Evidence of poor workmanship		Table II	3.10	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2024-10-23T03:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63955(AR)

PARAGRAPH	TITLE		SHEET 1 OF 4		DRAWING NUMBER
4.4.2.1.10	Container, Weapon Security: XH4289				9349591
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major:					
101.	Alignment of hole in tang with shoulder screw hole (2 holes) (2 places)		Table II	3.2	Gage
102.	Ability of an MMC functional gage (see dwg. 9354610), simulating base of combination lock assembly with bolt, to be fully engaged to lock mount plate (dwg. 9369980) without binding or use of undue force [to check location of 4 mounting holes, locating-pin hole, alignment of rectangular bolt slot with tang slot, and location of plate shield (2 places)]		100%	3.2	Gage
103.	Ability of a functional gage, simulating mounting holes of caster, to be fully engaged to ribbed shoulder bolts without binding or use of undue force (4 places)		100%	3.2	Gage
104.	Ability of a functional fixture, simulating minimum interior clearance dimensions to be installed into the container, without interference with any component, when the container lid is completely closed and latched		100%	3.2	Gage

NOTES:

Source: https://assist.dla.mil - Downloaded: 20260-23103:06Z
Check the source verify that this is the current version before use.

PARAGRAPH	TITLE		SHEET 2 OF 4		DRAWING NUMBER
4.4.2.1.10	Container, Weapon Security: XH4289 (continued)				9349591
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
105.	Ability of a functional fixture, simulating maximum exterior dimensions, to be completely installed over the container without interference		100%	3.2	Gage
106.	Ability of slider to move freely, without binding and use of undue force, and lock in place, with front sliders, when proper number of gages [simulating base of support (dwg. 9395733) are installed in the deck plate support holes for each slider (5 sliders; 1 to 3 holes)]		100%	3.2	Manual/Gage
107.	Ability of latch to function properly (latch and unlatch) (2 latches)		Table II	3.2	Manual
108.	Ability of caster wheel to swivel, with proper quick-release pin operation, and to rotate freely without binding (4 casters, unassembled)		Table II	3.2	Manual
109.	Ability of caster wheel (dwg. 9352729-1) to lock and unlock when the wing-nut brake is operated (2 casters, unassembled)		Table II	3.2	Manual
110.	Gas spring improper or improperly attached (including nuts and shoulder studs) (2 places) 1/		Table II	3.6	Visual

NOTES:
1/ To be inspected when gas springs are installed after the load test on handle.

Source: https://assist.dla.mil - Downloaded: 20260103T0806Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE		SHEET	DRAWING NUMBER
4.4.2.1.10	Container, Weapon Security: XH4289 (continued)		3 OF 4	9349591
				NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
111.	Strut assembly improper or improperly assembled (including nuts, shoulder studs, washers, cotter pin, and quick-release pin (2 places)		Table II	3.2	Visual
112.	Wrench handle or clamp tool missing, improper, or improperly secured		Table II	3.2	Visual/Manual
113.	Fork caster wrench missing, improper, or improperly secured (including ability of lock pin to be secured in place)		Table II	3.2	Visual/Manual
114.	Spring in plunger housing missing or improper (inspect during assembly)		Table II	3.2	Visual
115.	Plunger wire strands nicked or cut		Table II	3.2	Visual
Minor:					
201.	Position of plunger face with plunger housing (flush or below) (2 places)		Table II	3.2	Visual
202.	Grease fitting on caster missing, damaged, or improper (2-3 fittings/ caster) (see dwg. 9352729)		Table II	3.2	Visual
203.	Chain-base assembly (for quick-release pin on strut assembly) missing, damaged, or improperly attached (2 places)		Table II	3.2	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2025-10-27T03:06Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1.10	Container, Weapon Security: XH4289 (continued)	4 OF 4	9349591
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
204.	Identification plate missing, loose improper, damaged, or improperly marked		Table II	3.2	Visual
205.	Serial number missing, improper, or illegible (2 places) (see 3.8)		Table II	3.8	Visual
206.	Marking missing, improper, or illegible		Table II	3.2	Visual
207.	Evidence of poor workmanship (see 3.10)		Table II	3.10	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63955(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1.1	Shipping Configuration, Container Weapon Security: XH4289				9378258
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined.				
Major:					
101.	Any caster missing, damaged, improper or improperly packaged (4 casters) (see dwg. 9381668) (inspect prior to strapping carton in container)		Table II	3.2	Visual
102.	Cast or carton improperly located or improperly strapped in interior of container		Table II	3.2	Visual
103.	Container improperly strapped and sealed (including cover (2), spacer (6), corner board (8), strapping (2), and seal (2)		Table II	3.2	Visual
104.	Skid assembly improper, or improperly assembled (2 places)		Table II	3.2	Visual
Minor:					
201.	Skid marking missing, improper, or illegible		Table II	3.2	Visual
202.	Evidence of poor workmanship		Table II	3.10	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-10-23T03:06Z
Check the source to verify that this is the current version before use.

4.4.3 Quality conformance inspection testing. The contractor shall perform all of the tests specified in Table III. Tests b, c, and d shall be performed in the listed sequence.

TABLE III. Quality conformance tests.

Test	Test classification
a. Compression test of gas spring	Major
b. Plunger pull test	Major
c. Load test on handle	Major
d. Functioning test of container lid	Major

4.4.3.1 Compression test of gas spring (see dwg. 9378072 and 3.4). Each gas spring shall be subjected to this test (see 4.5.1). If any gas spring fails to comply with the applicable requirements, it shall be classified defective and be removed from the lot.

4.4.3.2 Plunger pull test (see 3.5), load test on handle (prior to installing gas spring) (see 3.6), and functioning test of container lid (see 3.7). Each security container shall be subjected to these tests (see applicable paragraph in 4.5). If any container fails to comply with the applicable requirements, it shall be classified defective and be removed from the lot.

4.4.4 Acceptance inspection equipment (AIE).

4.4.4.1 Major defects and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration procedures designed or specified by the contractor (see 6.1.2). The contractor shall obtain approval of such equipment designs, operating instructions, and calibration procedures prior to use on the contract (see 6.3). The contractor may, at his discretion, perform the inspection of major defect 102, of 4.4.2.1.10, using the AIE designed and specified by the procuring agency (see dwg. 9354610).

4.4.4.2 Minor defects and tests. Not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

4.5 Methods of inspection. The tolerances specified in this specification are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less than accuracy tolerances of the test equipment used. Unless otherwise specified, the tests shall be conducted at room temperature (77° ± 10°F).

4.5.1 Compression test of gas spring. The gas spring shall b securely attached to a Government-approved test fixture, in the vertical position, with piston uppermost. The gas spring shall be cycled once by fully compressing and releasing the piston, and the period of this cycle shall be not less than six seconds. A suitable force gauge shall be used in conjunction with the test fixture to measure the force exerted by the piston when it is compressed 0.20 inch from its free state. The gas spring shall comply with the requirements of 3.4 during this test.

4.5.2 Plunger pull test. The security container shall be positioned in such a manner to ensure that the plunger face is accessible for testing and that sufficient clearance is provided for the test fixture/equipment. Before performing this test, measure the position of the plunger face with reference to the plunger housing. Using a suitable marker, place a reference mark on the plunger face and on the plunger housing, in line with each other. Fasten a 0.190-24 UNC eyebolt to the plunger for a minimum engagement of 0.125 inch. NOTE: When installing eyebolt, do not permit the plunger to rotate in the plunger housing (as evidenced by movement of the plunger reference mark). Apply the 75-pound force, to the eyebolt, perpendicular to the force, inspect the wire ropes and crimped connections (where accessible), and measure the position of the plunger face with reference to the plunger housing. The plunger assembly shall comply with the requirements of 3.5 during this test.

4.5.3 Load test on handle. Before performing this test, ensure that no gas spring is installed. A suitable lifting device (strap, rope, hook, etc.) shall be attached to the center handle of the container lid. The lid shall be raised 12 to 18 inches by the lifting device, using any convenient method (hoist, pulley, etc.), and the lid shall be held at this position for a minimum period of 60 seconds. After this test, the lid shall be lowered to its closed position, and the handle shall be inspected and shall comply with the requirements of 3.6.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

4.5.4 Functioning test of container lid. Release both hold-down latches and allow the container lid to come to equilibrium. Attach a suitable force measuring scale to the middle handle of the lid. The lid shall then be opened by raising the scale in a smooth, even manner, and the maximum force required to start the lid rising shall be recorded. The lid shall then be manually raised to its full open position (after removing the scale), and the lock pin shall be fully inserted into the strut on each side of the container. The lock pins shall then be removed from the struts, and the lid shall be lowered and latched in the closed position. The lid shall comply with the requirements of 3.7 during this test.

5. PACKAGING

5.1 Packing. The security container shall be completely assembled (except for the four casters), latched, and prepared for shipment as specified on dwg. 9378258. The wooden skids shall be assembled to the container as specified on dwg. 9378258. The four casters (P/N 9352729) shall be packaged as specified on dwg. 9381668 and shall be securely strapped to the container for shipment (see dwg. 9378258). The wrench handle (P/N 9354410), the caster fork wrench (P/N 9354411), and the clamp tool (P/N 9381474) shall be securely mounted in place as specified on dwg. 9349591.

6. NOTES

6.1 Ordering data.

6.1.1 Acquisition requirements. Acquisition documents should specify (a) the title, number, and date of this specification, and (b) first article sample requirements.

6.1.2 Contract data requirements. Contractor engineering documentation shall be developed as specified by an approved Data Item Description (DID) (DD Form 1664) when specified on a Contract Data Requirements List (DD Form 1423) incorporated into the contract or purchase order. Deliverable data required by this specification is cited in the following paragraph:

Paragraph No.	Data requirement	Applicable DID No.
4.4.4.1	Quality Engineering Acceptance Inspection Equipment Descriptive Documentation.	DID-R-1714

Copies of data item descriptions, required by the contractor in connection with specific acquisition functions, should be obtained from the procuring activity or as directed by the contracting officer.

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:06Z
Check the source to verify that this is the current version before use.

6.2 Objective Evidence.

6.2.1 General. Contractors inspection records and documents verifying compliance with applicable dwg. and specification requirements.

6.2.2 Materials. A statement (certification), supported by test data, that all materials produced or purchased by the contractor meets all requirements when such material is controlled by Government or commercial specifications referenced in contractual documents.

6.3 Acceptance inspection equipment. The contractor shall obtain approval of equipment designs, operating instructions, and calibration procedures from Commander, U.S. Army Armament, Munitions, and Chemical Command, ATTN: AMSMC-QAN-I(D), Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract. Unless otherwise specified, Data Item DI-R-1714 will apply.

6.4 Tool manufacture control (TMC). When TMC is specified as a method of inspection, it shall mean that the manufacturing tool setup (e.g., stamping die, automatic tape control machine, etc.) may be used to accept the parts being manufactured. Two consecutive parts, which comply with drawing dimensions, shall constitute proper initial tool control acceptance. In addition, two consecutive parts shall be examined, as specified in the applicable paragraph in the classification of defects, whenever the manufacturing tool requires maintenance.

6.5 Changes from previous issue. The margins of this standard are marked with asterisks to indicate where significant changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations.

6.6 Subject term (key word) listing.

Security container	Acceptance equipment
Weldment	Load test
Compression test	Functional gage
Plunger	Tool manufacturing control

6.7 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under cognizance of ARRADCOM.

Custodian:
Army-AR

Preparing activity:
Army-AR

Project 8140-A773

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-63955 (AR)	CONTAINER, WEAPON SECURITY: XH4289

3a. NAME OF SUBMITTING ORGANIZATION

b. ADDRESS *(Street, City, State, ZIP Code)*

4. TYPE OF ORGANIZATION *(Mark one)*

- ☐ VENDOR
- ☐ USER
- ☐ MANUFACTURER
- ☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament Munitions &
Chemical Command
ATTN: AMSMC-QA
Picatinny Arsenal, NJ 07806-5000

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.