INCH-POUND

MIL-P-48188A (AR)
24 April 1992
SUPERSEDING
MIL-P-48188 (AR)
01 March 1976

MILITARY SPECIFICATION

Projectiles, 155MM, HE, M692 AND M731 Metallic Hardware for

This specification is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the Metallic Hardware for Projectiles, 155MM, HE: M692 and M731 (See 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. The following specifications, standards and handbooks forms a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (See 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document, should be addressed to: Commander U.S. Army ARDEC, ATTN: SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil - Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

QQ-P-416 - Plating, Cadmium (Electrodeposited)

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-1169-Packaging, Packing and Marking for Shipment of Inert Ammunition Components.
MIL-STD-1190-Packaging, Packing and Marking for Shipment of Inert Ammunition Components

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Ave, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS (See 6.5)

U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

9298331 -Plate, Shelf
9298336 -Pad, Base
9298337 -Column, Segment
9298339 -Shim, Ogive
9298361 -Sleeve, Expulsion Charge
9298371 -Cup, Spotting Charge
9298373 -Cup, Closure
9298391 -Rod, Battery Activation
9298392 -Piston, Battery Initiator
9298393 -Plate, Pusher

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

PUBLICATIONS

Title 49 - Code of Federal Regulations

(Copies of drawings, publications and other Government documents required by the contractor in connection with specific acquisition functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.1.3 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (See 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM-E-18-67 Standard Methods of Test for Rockwell Hardness and Rockwell Superficial Hardness for Metallic Materials

ASTM-B-117-73 Standard Method of Salt Spray (Fog) Testing

ASTM-B-633 Specification for Electro Deposited Coatings of Zinc on Iron and Steel

(Application for copies should be addressed to: American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

2.1.4 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with applicable drawings, specifications.

3.2 Hardware. The Hardware shall comply with all requirements specified on drawings (dwgs) referenced in Section 2 and with all requirements specified in applicable specification.

NOTE: The specific type of Column Segment design to be selected (9298337) shall be determined by contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

3.3 Workmanship. All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents.

3.4 Mechanical properties. Cold-working or heat-treating (including quenching-and-tempering, normalizing, normalizing-and-termpering, annealing, and stress-relieving) operations, shall be performed in such a manner as to produce the specified properties uniformly throughout the entire lot. The contractor shall determine the detailed procedures to produce parts meeting the required mechanical properties. These procedures shall be documented and submitted with the first article sample to the Contracting Officer. Changes in these procedures shall also be documented and submitted to the contracting Officer.

3.5 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspection. The following types of inspection shall be conducted on this item:

a. First Article Inspection.

b. Quality Conformance Inspection.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated below:

Part Description	Drawings	Quantity
Plate, Shelf	9298331	25
Pad, Base	9298336	25
Column, Segment	9298337	25
Shim, Ogive	9298339-1	5
Shim, Ogive	9298339-2	5
Shim, Ogive	9298339-3	5
Shim, Ogive	9298339-4	5
Shim, Ogive	9298339-5	5
Sleeve, Expulsion Charge	9298361	25
Cup, Spotting Charge	9298371	25
Rod, Battery Activation	9298391	25
Piston, Battery Initiator	9298392	25
Plate, Pusher	9298393	25

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:17Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

MIL-P-48188A (AR)

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE Metallic Hardware	SHEET 1 OF 2		DRAWING NUMBER NEXT HIGHER ASSEMBLY See below
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Shim, Column (see dwg. 9298362)			
	Examination for defects	20	3.2	4.4.2.2
	Material Certification		3.1	
	Pad, Base (see dwg. 9298336)			
	Examination for defects	25	3.2	4.4.2.2
	Hardness Test	10	3.2	4.5.2
	Salt Spray Test	5	3.2	4.5.3
	Plate, Shelf (see dwg. 9298331)			
	Examination for defects	25	3.2	4.4.2.4
	Hardness Test	10	3.2	4.5.2
	Salt Spray Test	5	3.2	4.5.3
	Rod, Battery Activation (see dwg. 9298391)			
	Examination for defects	25	3.2	4.4.2.5
	Plate, Pusher (see dwg. 9298393)			
	Examination for defects	25	3.2	4.4.2.6
	Sleeve, Expulsion Charge (see dwg. 9298361)			
	Examination for defects	25	3.2	4.4.2.7

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:17Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE Metallic Hardware	SHEET 2 OF 2	DRAWING NUMBER NEXT HIGHER ASSEMBLY See below
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Piston, Battery Initiator (See Dwg. 9298392			
	Examination for defects	25	3.2	4.4.2.7
	Shim, Ogive (See dwg. 9298339)			
	Examination for defects	25	3.2	4.4.2.8
	Hardness test	5	3.2	4.5.2
	Column, Segment (see dwg 9298337)			
	Examination for defects	25	3.2	4.4.2.9
	Hardness test	10	3.2	4.5.2
	Salt Spray Test	5	3.2	4.5.3
	Cup, Spotting Charge (See dwg. 9298371)			
	Examination for defects	25	3.2	4.4.2.10

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:17Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination and tests.

a. Classification of characteristics. Quality conformance examinations and tests are specified in the following Classification of Characteristics paragraphs. The contractor's quality program or detailed inspection system shall provide assurance of compliance of all characteristics with the applicable drawing and specification requirements utilizing as a minimum the conformance criteria specified. Where cited herein, attributes sampling inspection shall be conducted in accordance with Table II below, using the inspection levels stated in the Classification of Characteristics paragraphs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

TABLE II Attributes sampling inspection.

Lot Size	Inspection Level			
	I	II	III	IV
2 to 8	*	*	*	*
9 to 15	*	*	*	13
16 to 25	*	*	*	13
26 to 50	*	*	32	13
51 to 90	*	*	32	13
91 to 150	*	125	32	13
151 to 280	*	125	32	32
281 to 500	*	125	32	32
501 to 1200	*	125	80	50
1201 to 3200	1250	125	80	50
3201 to 10000	1250	125	125	50
10001 to 35000	1250	315	125	80
35001 to 150000	1250	315	125	80

Numbers under inspection levels indicate sample size; asterisks indicates one hundred percent inspection. If sample size exceeds lot size, perform one hundred percent inspection. Accept on zero and reject on one or more for all inspection levels.

b. Alternative quality conformance provisions. Alternative quality conformance procedures, methods, or equipment, such as statistical process control, tool control, other types of sampling procedures, etc., may be used by contractor when they provide, as a minimum, the level of quality assurance required by the provisions specified herein. Prior to applying such alternative procedures, methods, or equipment, the contractor shall describe them in a written proposal submitted to the Government for evaluation (see 6.4). When required, the contractor shall demonstrate that the effectiveness of each proposed alternative is equal to or better than the specified quality assurance provisions herein. In cases of dispute as to whether the contractor's proposed alternative(s) provides equivalent assurance the provisions of this specification shall apply. All approved alternative provisions shall be specifically incorporated into the contractors quality program or detailed inspection system, as applicable.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:17Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Shim, Column		9298338
			NEXT HIGHER ASSEMBLY N/A

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major A				
101	Thickness	Level II	3.2	Gage
Minor				
201	Angle of sides	Level IV	3.2	Gage
202	Large radius	Level IV	3.2	Gage
203	Width at narrow end	Level IV	3.2	Gage
204	Distance from narrow end to large radius	Level IV	3.2	Gage
205	Poor workmanship	Level IV	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:17Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.2	Pad, Base	1	1	9298336
				NEXT HIGHER ASSEMBLY: N/A

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major A				
101	Thickness	Level II	3.2	Gage
102	Diameter	Level II	3.2	Gage
103	Parallelism of Faces	Level II	3.2	Gage
104	Flatness of faces	Level II	4.3	Gage
105	Hardness Test		3.2	4.5.2
106	Salt Spray Test		3.2	4.5.3
Minor				
201	Surface finish of faces	Level IV	3.2	Visual/Tactile
202.	Poor workmanship	Level IV	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:17Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-48188A (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Plate, Shelf		9298331
			NEXT HIGHER ASSEMBLY N/A

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major A				
101	Thickness	Level II	3.2	Gage
102	Diameter	Level II	3.2	Gage
103	Diameter of hole	Level II	3.2	Gage
104	Parallelism of faces	Level II	4.3	Gage
105	Hardness Test		3.2	4.5.2
106	Salt Spray Test		3.2	4.5.3
Minor				
201	Chamfer missing	Level IV	3.2	Visual
202	Surface finish improper	Level IV	3.2	Visual/Tactile
203	Protective finish missing	Level IV	3.2	Visual
204	Poor workmanship	Level IV	3.3	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89

Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:17Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH 4.4.2.4	TITLE Rod, Battery Activation	SHEET 1 OF 2		DRAWING NUMBER 9298391
				NEXT HIGHER ASSEMBLY ---
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major A				
101	Largest diameter (16 places)	Level II	3.2	Gage
102	Straightness	Level II	3.2	Gage
103	Total length	Level II	3.2	Gage
104	Major diameter of external thread	Level II	4.3	Gage
105	Pitch diameter of external thread	Level II	3.2	Gage
106	Length to end of thread, min	Level II	3.2	Gage
107	Diameter between steps (15 places)	Level II	3.2	Gage
108	Length from threaded end to basic diameter of first conical surface	Level II	3.2	Gage
109	Length from threaded end to basic diameter on second conical surface	Level II	3.2	Gage
110	Length from threaded end to basic diameter on third conical surface	Level II	3.2	Gage
111	Length from threaded end to basic diameter on fourth conical surface	Level II	3.2	Gage
112	Length from threaded end to basic diameter on fifth conical surface	Level II	3.2	Gage
113	Length from threaded end to basic diameter on sixth conical surface	Level II	3.2	Gage
114	Length from threaded end to basic diameter on seventh conical surface	Level II	3.2	Gage
115	Length from threaded end to basic diameter on eighth conical surface	Level II	3.2	Gage

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Rod, Battery Activation	2 OF 2	9298391
			NEXT HIGHER ASSEMBLY ---

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
116	Distance between basic diameter on conical surface and second shoulder (7 places)	Level II	3.2	Gage
117	Distance between basic diameter on conical surface and third shoulder (7 places)	Level II	3.2	Gage
118	External thread damaged	Level II	3.2	Visual
119	Radius, max (8 places)	Level II	3.2	Gage
120	True position pitch diameter to datum A only at right end segment	Level II	3.2	Gage
Minor				
201	True position of pitch diameter of thread with larger diameter	Level IV	3.2	Gage
202	True position of smaller diameter with larger diameter (15 places)	Level IV	3.2	Gage
203	Distance between basic diameter on conical surface and nearest shoulder (8 places) Detail A of Drawing	Level IV	3.2	Comparison Specimens
204	Surface finish	Level IV	3.2	Visual
205	Radius or chamfer missing or excessive	Level IV	3.2	Visual
206	Poor workmanship	Level IV	3.3	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89

Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:17Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Plate, Pusher	1 OF 1	9298393
			NEXT HIGHER ASSEMBLY: N/A

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major A				
101	Largest diameter	Level II	3.2	Gage
102	Diameter of hole	Level II	3.2	Gage
103	Chamfer on largest diameter, min	Level II	3.2	Gage
104	Total height	Level II	3.2	Gage
105	Height of threaded projection	Level II	3.2	Gage
106	True position of hole with largest diameter	Level II	3.2	Gage
107	Pitch diameter of thread	Level II	3.2	Gage
108	Major diameter of thread	Level II	3.2	Gage
109	True position of pitch diameter with largest diameter	Level II	3.2	Gage
110	Thread damaged	Level II	3.2	Gage
Minor				
201	Width of groove on largest diameter	Level IV	3.2	Gage
202	Depth of groove	Level IV	3.2	Gage
203	Thread undercut excessive	Level IV	3.2	Gage
204	Surface finish improper	Level IV	3.2	Visual/Tactile
205	Poor workmanship	Level IV	3.3	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89

Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Sleeve, Expulsion Charge	1 OF 2	9298361
			NEXT HIGHER ASSEMBLY: N/A

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major A				
101	Length from shoulder to face at smaller end	Level II	3.2	Gage
102	Depth to bottom of larger inside diameter at smaller end, min.	Level II	3.2	Gage
103	Diameter of larger inside diameter at smaller end	Level II	3.2	Gage
104	Smaller outside diameter	Level II	3.2	Gage
105	Diameter of flange (larger outside diameter)	Level II	3.2	Gage
106	True position of flange diameter at smaller outside diameter	Level II	3.2	Gage
107	True position of larger inside diameter at smaller end with smaller outside diameter	Level II	3.2	Gage
Major B				
131	Width of flange	Level II	3.2	Gage
132	Inside diameter at larger end, max	Level II	3.2	Gage
133	True position of inside diameter at larger end with smaller outside diameter	Level II	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-48188A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Sleeve, Expulsion Charge	2 OF 2	9298361
			NEXT HIGHER ASSEMBLY: N/A

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Minor				
201	Smallest inside diameter	Level IV	3.2	Gage
202	Depth from face at smaller end to second shoulder	Level IV	3.2	Gage
203	True position of smallest inside diameter with smaller outside diameter	Level IV	3.2	Gage
204	Chamfer or radius missing	Level IV	3.2	Visual
205	Poor workmanship	Level IV	3.3	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89

Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:17Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Piston, Battery Initiator	1 OF 2	9298392
			NEXT HIGHER ASSEMBLY: N/A

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major A				
101	Outside diameter at solid end	Level II	3.2	Gage
102	Largest outside diameter.	Level II	3.2	Gage
103	Thickness through bottom of larger cavity	Level II	3.2	Gage
104	Smallest outside diameter	Level II	3.2	Gage
105	True position of largest outside diameter with diameter at solid end	Level II	3.2	Gage
106	True position of smallest outside diameter with diameter at solid end	Level II	3.2	Gage
107	Minor diameter of larger thread	Level II	3.2	Gage
108	Pitch diameter of larger thread	Level II	3.2	Gage
109	Minor diameter of smaller thread	Level II	3.2	Gage
110	Pitch diameter of smaller thread	Level II	3.2	Gage
111	True position of larger thread with diameter at solid end	Level II	3.2	Gage
112	True position of smaller thread with diameter at solid end	Level II	3.2	Gage
113	Radius behind solid end, max	Level II	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:17Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-48188A (.AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Piston, Battery Initiator	2 OF 2	9298392
			NEXT HIGHER ASSEMBLY N/A

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Minor				
201	Distance from face at solid end to bottom of large cavity	Level IV	3.2	Gage
202	Distance from face at solid end to beginning of radius behind solid end	Level IV	3.2	Gage
203	Minimum threads in smaller cavity	Level IV	3.2	Gage
204	Depth from face at open end to bottom of large cavity	Level IV	3.2	Gage
205	Depth from bottom of large cavity to bottom of small cavity	Level IV	3.2	Gage
206	Poor workmanship	Level IV	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.8	Shim, Ogive	1 OF 1	9298339
			NEXT HIGHER ASSEMBLY: ---

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Thickness	Level II	3.2	Gage
102	Outside diameter	Level II	3.2	Gage
103	Hardness		3.2	Certification Note 1
Minor				
201	Inside diameter, max.	Level IV	3.2	Gage
202	True position of inside diameter with outside diameter	Level IV	3.2	Gage
203	Poor workmanship	Level IV	3.3	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89

Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.9	Column, Segment	1 OF 1	9298337
			NEXT HIGHER ASSEMBLY: ---

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Height	Level II	3.2	Gage or SMI/See Note
102	Parallelism of end faces	Level II	3.2	Gage or SMI
103	Perpendicularity of large radius face with end face	Level II	3.2	Gage or SMI
104	Perpendicularity of slant faces with end face	Level II	3.2	Gage or SMI
105	Distance from large radius face to largest basic width between slant faces	Level II	3.2	Gage or SMI
106	Distance between faces formed by large and small radii	Level II	3.2	Gage or SMI
107	Angle between slant faces	Level II	3.2	4.5.2
108	Hardness test		3.2	4.5.3
109	Salt spray test	Level II	3.2	Gage
110	Depth of circular cutouts, 2 places	Level II	3.2	Gage
111	Radius of circular cutout, 2 places	Level II	3.2	Gage
112	Location of circular cutout, 2 places	Level II	3.2	Gage
Minor				
201	Surface finish improper	Level IV	3.2	Visual/Tactile
202	Any corner not removed	Level IV	3.2	Visual
203	Poor workmanship	Level IV	3.3	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.10	Cup, Spotting Charge	1 OF 1	9298371
			NEXT HIGHER ASSEMBLY: N/A

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major A				
101	Largest outside diameter	Level II	3.2	gage
102	Smaller outside diameter	Level II	3.2	Gage
103	Thickness of sidewall under shoulder, min.	Level II	3.2	Gage
104	Thickness through bottom, min.	Level II	3.2	Gage
105	Cup deformed, or punctured	Level II	3.3	Visual
Major B				
131	True position of smaller outside diameter with larger outside diameter	Level II	3.2	Gage
Minor				
201	Overall height	Level IV	3.2	Gage
202	Distance from shoulder to bottom of cup	Level IV	3.2	Gage
203	Any radius missing	Level IV	3.2	Gage
204	Surface finish improper	Level IV	3.2	Visual/Tactile
205	Poor workmanship	Level IV	3.3	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 — Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the Paragraph Reference/Inspection Method column in the tables starting with 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See MIL-A-48078.

4.5 Methods of inspection.

4.5.1 Dimensional control of stamped parts. In place of the normal sampling and inspection associated with the Classification of Defects, and with the approval of the Contracting Officer a sample of at least ten (10) parts shall be dimensionally inspected to qualify the tool used in the stamping process for use in production (See Note 1). In addition, a random sample of five (5) parts shall be selected from the last portion of each hour's production for dimensional inspection as a control of the tool during production.

If any defective parts are found during qualification of the tool, the tool producing the defective part(s) shall not be used in production.

If any defective parts are found when inspection is performed for control of the tool, the tool producing the defective part(s) shall be removed from production. Further, the portion of production since the last tool control check, it shall be checked and if defective parts are found, returned to the contractor for corrective action.

All tools removed from production because of some fault, may after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he presents objective evidence to the Contracting Officer to substantiate the request.

NOTE 1: Those features of a part which are subsequently machined or otherwise worked upon to meet its drawing requirements shall be inspected in accordance with the classification of defects. A list of these features shall be supplied with the first article sample.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

4.5.2 Hardness test of steel components.

a. For parts heat treated during manufacture.

Ten (10) of each applicable part shall be selected from the heat-treatment batch and shall be subjected to this test. A heat-treatment batch is herein defined as parts that have been heat-treated at the same time, for the same time durations, in the same furnaces and quench batch for each of all phases of the entire heat-treatment process.

b. For parts produced from hardened materials and not heat-treated during manufacture.

Ten (10) of each applicable part shall be selected from those parts produced from each lot or mill heat of material and complying with the lot formation provisions of MIL-A-48078.

The test shall be conducted as specified in ASTM E 18-67 using the applicable penetrator and load for the hardness scale specified on the drawing for the component. Three readings approximately equally spaced shall be taken on any acceptable surface. The average of the three readings shall be determined.

If the average hardness of any part fails to comply with the equipment specified on the applicable drawing, the batch or lot represented by the failing part shall be rejected. (Non-destructive test).

4.5.3 Salt spray test of protective finish. Five parts of each part number shall be selected from each lot in accordance with the lot formation provisions of specification QQ-P-416. The test shall be tested as specified in ASTM B 117-73. The parts shall be tested for the duration specified on the applicable drawing. At the end of the required time, the parts shall be examined for evidence of white corrosion products (See section 3 of QQ-P-416).

If any part shows any evidence of corrosion the lot represented by the sample shall be rejected. This is a destructive test. Parts so tested shall not be returned to the lot.

5. PACKAGING

5.1 Preservation.

5.1.1 Level B. The hardware shall be preserved and packaged as in accordance with MIL-STD-1169. Each package shall contain only one part number.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

5.2 Packing.

* 5.2.1 Level B. The hardware, preserved and packaged as specified in 5.1.1, shall be packed for shipment in accordance with MIL-STD-1169. Each pack shall contain only one part number.

5.3 Marking. Marking of the carton shall comply with MIL-STD-1169.

5.4 Shipping. When components from more than one lot are shipped at one time, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, is not mandatory.)

6.1 Intended use. The components covered by the specification are intended for use on the M692 and M731 Projectiles.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of the specification.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced in section 2.1.

6.3 Submission of inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs as required to Commander: USARDEC, ATTN: SMCAR-QAT-I, Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

6.4 Submission of alternative quality conformance procedures. Unless otherwise specified in the contract, proposed alternative quality conformance provisions will be submitted by the contractor to the procuring contracting officer.

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development and Engineering Center (ARDEC) may also include drawings prepared by and identified as, US Army Armament Research and Development Command, Edgewood Arsenal, Frankfort Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.6 Subject term (keyword) listing.

Plating
Cadmium
Ammunition

6.7 Changes from previous issues. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project Number: 1320-AC82)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.