INCH-POUND

A-A-51164A
November 10, 1993
SUPERSEDING
A-A-51164
November 4, 1986

COMMERCIAL ITEM DESCRIPTION

CRIMPING AND BEADING MACHINES, SHEET METAL, MANUALLY OPERATED, ROTARY TYPE, THROATLESS STYLE

The General Services Administration has authorized the use of this Commercial Item Description.

1. SCOPE

1.1 Scope. This Commercial Item Description (CID) covers throatless, rotary type, manually operated, sheet metal, crimping and beading machines.

1.2 Classification. The crimping and beading machines shall be of one type and of the following sizes. The size to be furnished shall be as specified (see 6.1).

Size 24 - 24 gauge capacity	Size 20 - 20 gauge capacity
Size 22 - 22 gauge capacity	Size 18 - 18 gauge capacity

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may improve this document should be addressed to: Defense General Supply Center (DGSC), ATTN: DGSC-SSA, 8000 Jefferson Davis Highway, Richmond, VA 23297-5678, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document.

AMSC N/A

FSC 3441

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:52Z
Check the source to verify that this is the current version before use.

2. SALIENT CHARACTERISTICS

2.1 Design. The machines furnished shall be new and of the manufacturer's current production models capable of performing crimping, beading, or crimping and beading operations. The machine's function is determined by the type of rolls being used. When fitted with crimping rolls, the machines shall perform crimping operations. When fitted with beading rolls, the machines shall perform beading operations, and when fitted with crimping and beading rolls, the machines shall perform crimping and beading operations. The machines shall include all components, parts, and features necessary to meet the above operations.

2.2 Frame. The frame shall be an iron or steel casting, and shall withstand all forces encountered during operation of the machine to maximum capacity without permanent distortion.

2.3 Mounting. The machine shall be furnished with provisions for bench mounting. This may be accomplished by the use of an integral frame and stand or by providing a stand which may be clamped to a bench. When specified (see 6.1), a floor stand shall be furnished.

2.4 Gears. All gears shall be cast iron or machine cut steel and shall be totally enclosed or guarded to protect the operator.

2.5 Rolls. The rolls shall have a hardness of between 52 and 62 on the Rockwell "C" scale when tested in accordance with ASTM E 18. Unless otherwise specified (see 6.1), the following rolls shall be furnished:

a. Sizes 18, 20, 22 machines
   (1) One pair of 3/8 inch single beading rolls.
   (2) One pair of 3/4 inch ogee (OG) beading rolls.

b. Size 24 machines
   (1) One pair of 1/4 or 5/16 inch single beading rolls.
   (2) One pair of 3/4 inch OG beading rolls.

c. Sizes 18, 20, 22, 24 machines
   (1) One pair of crimping rolls.
   (2) One pair crimping and beading rolls.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:52Z
Check the source to verify that this is the current version before use.

2.6 Hand crank. The machine shall be furnished with a hand crank which shall be of sufficient length to allow normal and smooth operation of the machine.

2.7 Upper roll adjustment. The upper roll shall be adjustable by means of a quick-acting crankscrew.

2.8 Gauge. The machine shall be provided with an adjustable gauge to govern the head placement on the workpiece.

2.9 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest revision of FED-STD-376, and all other requirements of this Commercial Item Description are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request shall be made to the contracting officer to determine if the product is acceptable. The contracting officer has the option of accepting or rejecting the product.

3. REGULATORY REQUIREMENTS

3.1 Environmental protection. During the manufacture of the machine, materials hazardous to the ecological system as prohibited by Federal, state, or local statutes in effect on the date of the contract shall not be used.

3.2 Reference documents. The documents referenced in this document shall be the issues in effect on the date of issuance of the invitation for bid or request for proposal.

3.3 Recovered materials. The contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent possible.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery, and thereafter, as may be otherwise provided under the provisions of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:52Z
Check the source to verify that this is the current version before use.

5. PRESERVATION, PACKING, LABELING, AND MARKING

5.1 Preservation, packing, labeling, and marking. Preservation, packing, labeling, and marking shall be as specified in the contract order.

6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

a. Title, number, and date of this CID.
b. Size and quantity required (see 1.2).
c. Floor stand, if required (see 2.3).
d. Rolls, if different (see 2.5).

6.2 Part identification number (PIN). The following part identification numbering procedure is for Government purposes only and does not constitute a requirement for contractor.

A51159-XX
- ____ Size 1 (see 1.2)
- ____ CID number

6.3 Sources for documents referenced in this CID.

FED-STD-376 is available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19120-5099.

ASTM E 18 is available from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.

MILITARY INTERESTS:

Custodians:
Army - AL
Air Force - 99

Review Activity:
Air Force - 84

CIVIL AGENCY COORDINATION ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

DLA - GS

Project 3441-0152

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:52Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
A-A-51164A	Crimping and Beading Machines, Sheet Metal, Manually Operated

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:52Z
Check the source to verify that this is the current version before use.

DD FORM 1426 PREVIOUS EDITION IS OBSOLETE.