COMMERCIAL ITEM DESCRIPTION

FORMING MACHINE, DOUBLE SEAM, HAND OPERATED

The General Services Administration has authorized the use of this commercial item description in preference to type III of military specification MIL-F-23243A.

1. SCOPE

1.1 Scope. This description covers hand operated, bench mounted, sheet metal, double seam, forming machines of the standard, heavy duty, commercial type, that are used in a production environment for finish seaming flat bottoms on straight or flared sheet metal cylinders after the edges have been flared and set down. The machines are intended for use in sheet metal shops and repair units for fabrication of cylindrical containers, covers, and like cylindrical items.

1.2 Classification. The double seam forming machines shall be of the following sizes. The size to be furnished shall be as specified (see 6.1).

Size 20 - 20 gauge (0.0359 inch) capacity.
Size 24 - 24 gauge (0.0239 inch) capacity.
Size 26 - 26 gauge (0.0179 inch) capacity.

2. APPLICABLE DOCUMENTS

2.1 Documents. The following documents of the issue in effect on the date of invitation for bids or request for proposals form a part of this description to the extent specified herein.

Military Specification MIL-M-18058	- Machinery, Metal and Woodworking, Packaging of.
Federal Standard FED-STD-376	- Preferred Metric Units for General Use by the Federal Government.
American Society for Testing and Materials ASTM D 3951	- Standard Practice for Commercial Packaging.

AMSC N/A FSC 3441

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:52Z
Check the source to verify that this is the current version before use.

3. SALIENT CHARACTERISTICS

3.1 Design. The double seam forming machine shall be new and of the manufacturer's standard design in effect on the date of the solicitation. The machine shall be capable of performing finish seaming operations of flat bottoms on straight or flared sheet metal cylinders of the rated thickness capacity specified in table I for the size machine specified. The machine shall meet the requirements specified herein and shall conform to current commercial industrial practice.

TABLE I. Double seam forming machine sizes and capacities.

Size	Gauge number	Maximum rated capacity in mild steel: Manufacturer's standard gauge (inches)	Throat depth (maximum) (inches)	Lower seam roll diameter (inches)
20	20	0.0359	16	6
24	24	0.0239	15	2-3/4
26	26	0.0179	15	2-3/4

NOTE: Unless otherwise specified value shall be not less than the value specified.

3.2 Frame. The frame shall be constructed of steel or cast iron capable of supporting the shafts and drive mechanism and shall provide a suitable base connection for mounting.

3.3 Shafts. The shafts shall be of high grade machine finished steel. The shafts shall be driven by hand crank and gears and shall be fitted to bearings to provide smooth and easy operation at rated capacity.

3.4 Bearings. The bearings shall conform to standard commercial bearings used in forming machines of this type furnished to the industrial market.

3.5 Gears. The gears shall be machine cut steel or a good grade of cast iron and shall be totally enclosed or guarded to protect the operator.

3.6 Rolls. The rolls shall be machine finished steel and shall be of sufficient hardness to perform the operations for which designed. Lower seam roll shall conform to the diameter requirement of table I for the size machine furnished. Each machine shall be furnished with a set of rolls. When specified (see 6.1) extra rolls shall be furnished as described.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:52Z
Check the source to verify that this is the current version before use.

3.6.1 Roll adjustment. Fast adjustment of top roll and angular wheel shall be provided to move from first operation to second operation. The upper roll shall be provided with a quick acting screw adjustment to provide the necessary pressure to the rolls to perform the double seaming operations.

3.7 Hand crank. The hand crank shall be of sufficient length to ensure operation of the machine without undue strain to the operator.

3.8 Stand. Unless otherwise specified (see 6.1), each double seam forming machine shall be provided with a clamp-on offset stand for bench mounting. The stand offset shall be shaped to bring the machine forward to provide ease of operation.

3.9 Measurement system. All dimensions in this description are given in US units. These dimensions may be converted to SI units through the use of conversion factors and methods specified in FED-STD-376.

3.10 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials to the maximum extent practical.

3.11 Workmanship. Workmanship of the double seam forming machine shall be of a quality equal to that of comparable products furnished to the commercial market.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection, examination, and test requirements specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections, examinations, or tests set forth in this description where such inspections, examinations, and tests are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Examination. Each double seam forming machine shall be visually examined to determine conformance with all requirements of this description.

4.3 Operational test. Each double seam forming machine shall be operated without performing metal forming operations to ensure freedom of movement of the gears, adjusting mechanisms, and changeability of rolls.

4.4 Packaging inspection. Packaging shall be inspected to determine compliance with the requirements of section 5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:52Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation, packing, and marking. Unless otherwise specified in the contract or purchase order, preservation, packing, and marking shall be in accordance with ASTM D 3951. When specified (see 6.1), level A preservation, level A or level B packing, and marking shall be in accordance with MIL-M-18058.

6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

a. Title, number, and date of this commercial item description.
b. Size, of double seam forming machine required (see 1.2).
c. Specify and describe extra rolls, if required (see 3.6).
d. Type of stand, if different (see 3.8).
e. Packaging in accordance with MIL-M-18058,if required specify level of preservation and packing (see 5.1).

6.2 Cross reference data. Items covered by Military Specification MIL-F-23243A are cross referenced to items covered by this description as follows:

MIL-F-23243A	A-A-51168
Type III	(Deleted) Size 20 (New size) Size 24 (New size) Size 26 (New size)

MILITARY INTERESTS:

Custodians

Army - AL
Air Force - 99

Review Activities

Air Force - 84
DLA - GS

User Activity

Navy - YD

CIVIL AGENCY COORDINATION ACTIVITY

GSA - FSS

PREPARING ACTIVITY:

DLA - IP

Project 3441-0129

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:52Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
A-A-51168	Forming Machine, Double Seam, Hand Operated

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION (Mark one)
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER (Specify): _____
b. ADDRESS (Street, City, State, ZIP Code)	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER (Last, First, MI) – Optional	b. WORK TELEPHONE NUMBER (Include Area Code) – Optional
c. MAILING ADDRESS (Street, City, State, ZIP Code) – Optional	8. DATE OF SUBMISSION (YYMMDD)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:52Z
Check the source to verify that this is the current version before use.