INCH-POUND

MS27501G
12 July 2002
SUPERSEDING
MS27501F
31 March 1988

DETAIL SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, CIRCULAR, COVER, PROTECTIVE, PLUG, BAYONET COUPLING, SERIES I

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-DTL-38999.



FIGURE 1. Cover.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:42Z
Check the source to verify that this is the current version before use.



STYLE C

Shell size	A dia +.001 -.005	F max dia	H +.500 -.250 Standard chain length	J +.010 -.015	L max	M min	X	Y	LL max
9	.572	.82	3.0	.567	.9	.58	77°	113°	1.16
11	.700	.94					67°	123°	
13	.850	1.07	3.5				63°	127°	
15	.975	1.19					61°	129°	
17	1.100	1.32					65°	125°	
19	1.207	1.44							
21	1.332	1.57	4.0				69°	121°	
23	1.457	1.69							
25	1.582	1.82							

FIGURE 1. Cover – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:42Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm	Inches	mm
.001	0.03	.567	14.40	1.075	27.2	1.57	39.9
.005	0.13	.572	14.53	1.100	27.94	1.582	40.18
.010	0.25	.58	14.7	1.16	29.5	1.69	42.9
.015	0.38	.700	17.78	1.19	30.2	1.82	46.2
.047	1.19	.82	20.8	1.207	30.66	3.0	76.0
.063	1.60	.850	21.59	1.32	33.5	3.5	89.0
.167	4.24	.9	22.9	1.332	33.83	4.0	102.0
.250	6.35	.94	23.9	1.44	36.6	5.0	127.0
.500	12.70	.975	24.76	1.457	37.01	6.0	152.0
						7.0	178.0

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Finish: See MIL-DTL-38999.
4. BSC dimensions apply at Maximum Material Condition (MMC).
5. The gauge features for GG shall be .004 inches (0.10 mm) smaller than MMC size at basic location.
6. Not for space born applications.

FIGURE 1. Cover – Continued.

REQUIREMENTS:

Dimensions and configuration: See figure 1.
Interface dimensions shall conform to MIL-DTL-38999.
Material:
Cap - Impact extruded or machined aluminum alloy.
Disk - Silicone or fluorosilicone elastomer.
Chain - Stainless steel, passivated.
Fastener - Stainless steel, passivated.

Mating connectors: MIL-DTL-38999 Series I, and MIL-C-27599 Series I.
Disk shall be bonded to cover, or mechanically retained.
Chain shall rotate freely on fastener.
The protective cover and chain assembly shall withstand a static tensile load of 35 pounds applied along the B reference line for 5 minutes.
Fastener tensile strength: Both axial and longitudinal directions shall be 25 pounds. The load shall be applied to the end of the chain.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:42Z
Check the source to verify that this is the current version before use.

Qualification:

Examination of product.
Mating and unmating forces.
Humidity.
Salt spray (corrosion).
Fastener tensile strength (see requirement).
Altitude immersion.

Group A sampling inspection. 100% inspection is not applicable. Sampling inspection shall be in accordance with table I:

TABLE I. Group A sampling plan.

Lot size	Sample size
1 to 13	100 percent
14 to 150	13 units
151 to 280	20 units
281 to 500	29 units
501 to 1,200	34 units
1,201 to 3,200	42 units

Part or Identifying Number (PIN) example:



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:42Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - AS
Air Force - 11
DLA - CC

Review activities:
Army - AR, MI
Navy - EC, MC, OS
Air Force - 19, 99

Preparing activity:
DLA - CC

(Project 5935-4400)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:42Z
Check the source to verify that this is the current version before use.