COMMERCIAL ITEM DESCRIPTION

TAP, THREAD CUTTING
(REGULAR, FRACTIONAL INCH SIZES)

The General Services Administration has authorized the use of this commercial item description in preference to Type I of Federal Specification GGG-T-70.

This commercial item description covers general purpose, ground thread, high-speed steel taps with straight flutes for use in hand and machine tapping operations.

Salient characteristics:

Design. Taps shall be of the regular hand type with straight flutes, and be in accordance with the latest revision of American National Standard ANSI B94.9, except as otherwise indicated by an asterisk in the table below.

Material. Material shall be high-speed steel of the same grade used for taps supplied to the commercial market for general purpose applications.

Hardness. Taps shall be hardened and tempered so as to indicate a Rockwell C62-66 hardness in at least eighty percent of the threaded section from the threaded end. The shank and square drive end may have other suitable heat treatment characteristics to prevent twisting and breaking of the tap.

Finish. Threads shall have a ground finish. Other areas shall be finished in accordance with commercial practice. Coatings or surface treatments, if provided, shall be suitable for general purpose tapping applications.

Thread size, type of chamfer, pitch diameter, and number of flutes. Shall be as shown in the following table for the National Stock Number (NSN) specified. Except as indicated, threads shall be right hand direction.

NATIONAL STOCK NUMBER	SIZE, SERIES, DIRECTION	CHAMFER TYPE	P.D. LIM. SYM.	PITCH DIAMETER MIN. (INCH)	PITCH DIAMETER MAX. (INCH)	NUMBER OF FLUTES
5136-00-203-6213	1/4-28UNFLH	BOTTOMING	H1	0.2268	0.2273	4
5136-00-203-6215	1/2-20UNFLH	BOTTOMING	H1	0.4675	0.4680	4
5136-00-203-6216	3/8-24UNFLH	BOTTOMING	H1	0.3479	0.3484	4
5136-00-203-6220	1/4-28UNFLH	PLUG	H1	0.2268	0.2273	4
5136-00-203-6222	5/16-24UNFLH	PLUG	H1	0.2854	0.2859	4
5136-00-203-6226	1/2-20UNFLH	PLUG	H1	0.4675	0.4680	4
5136-00-203-6228	3/8-24UNFLH	PLUG	H1	0.3479	0.3484	4
5136-00-203-6504	3/8-16UNC	BOTTOMING	H1	0.3344	0.3349	4
5136-00-203-6510	1/4-20UNC	PLUG	H1	0.2175	0.2180	4
5136-00-203-6511	5/16-18UNC	PLUG	H1	0.2764	0.2769	4
5136-00-203-6513	9/16-18UNF	PLUG	H2	0.5269	0.5274	4
5136-00-203-6621	7/8-9UNC	PLUG	H5*	0.8048	0.8053	4
5136-00-203-6626	3/8-16UNC	TAPER*	H2	0.3349	0.3354	4
5136-00-203-6635	9/16-18UNFLH	BOTTOMING	H3	0.5274	0.5279	4
5136-00-203-6647	1/4-20UNC	TAPER	H1	0.2175	0.2180	4
5136-00-203-9468	7/16-28UNS*	PLUG	H2	0.4153	0.4158	4
5136-00-203-9501	5/16-32UNS*	BOTTOMING	H3	0.2932	0.2937	4
5136-00-221-7040	1-1/8-7UNC	PLUG	H4	1.0332	1.0342	4
5136-00-221-7041	1-1/4-7UNC	PLUG	H4	1.1582	1.1592	4
5136-00-223-6228	5/8-11UNC	PLUG	H3	0.5670	0.5675	4
5136-00-227-7260	1-8UNC	PLUG	H4	0.9203	0.9208	4
5136-00-227-8609	1/4-28UNF	TAPER*	H1	0.2268	0.2273	4
5136-00-227-8611	3/8-24UNF	TAPER*	H1	0.3479	0.3484	4

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:09Z
Check the source to verify that this is the current version before use.

NATIONAL STOCK NUMBER	SIZE, SERIES, DIRECTION	CHAMFER TYPE	P.D. LIM. SYM.	PITCH MIN. (INCH)	DIAMETER MAX. (INCH)	NUMBER OF FLUTES
5136-00-227-8612	7/16-20UNF	TAPER	H1*	0.4050	0.4055	4
5136-00-227-8613	1/2-20UNF	TAPER*	H1	0.4675	0.4680	4
5136-00-227-8618	1/4-28UNF	PLUG	H1	0.2268	0.2273	4
5136-00-227-8619	5/16-24UNF	PLUG	H1	0.2854	0.2859	4
5136-00-227-8620	3/8-24UNF	PLUG	H1	0.3479	0.3484	4
5136-00-227-8621	7/16-20UNF	PLUG	H1*	0.4050	0.4055	4
5136-00-227-8622	1/2-20UNF	PLUG	H1	0.4675	0.4680	4
5136-00-227-8625	7/8-14UNF	PLUG	H2	0.8291	0.8296	4
5136-00-227-8627	1/4-28UNF	BOTTOMING	H1	0.2268	0.2273	4
5136-00-227-8628	5/16-24UNF	BOTTOMING	H1	0.2854	0.2859	4
5136-00-227-8629	3/8-24UNF	BOTTOMING	H1	0.3479	0.3484	4
5136-00-227-8631	1/2-20UNF	BOTTOMING	H2*	0.4680	0.4685	4
5136-00-227-8633	3/4-16UNF	BOTTOMING*	H2	0.7099	0.7104	4
5136-00-228-0995	7/16-20UNF	TAPER	H3	0.4060	0.4065	4
5136-00-228-0996	1/2-20UNF	TAPER	H3	0.4685	0.4690	4
5136-00-228-0998	5/8-18UNF	TAPER	H3	0.5899	0.5904	4
5136-00-228-0999	3/4-16UNF	TAPER	H3	0.7104	0.7109	4
5136-00-228-1001	1-1/4-12UNF	TAPER	H4	1.1969	1.1979	6
5136-00-228-1014	1-1/4-12UNF	PLUG	H4	1.1969	1.1979	6
5136-00-228-1015	1-1/2-12UNF	PLUG	H5*	1.4474	1.4484	6
5136-00-228-1023	3/4-16UNF	BOTTOMING	H3	0.7104	0.7109	4
5136-00-228-1024	1-14UNS	BOTTOMING	H4	0.9551	0.9556	4
5136-00-228-1025	1-1/4-12UNF	BOTTOMING	H4	1.1969	1.1979	6
5136-00-228-1031	1-8UNC	TAPER	H4	0.9203	0.9208	4
5136-00-228-1032	1-1/8-7UNC	TAPER	H4	1.0332	1.0342	4
5136-00-228-1033	1-1/4-7UNC	TAPER	H4	1.1582	1.1592	4
5136-00-228-1034	1-1/2-6UNC	TAPER	H4	1.3927	1.3937	4
5136-00-228-1046	1-1/2-6UNC	PLUG	H4	1.3927	1.3937	4
5136-00-228-1054	7/8-9UNC	BOTTOMING	H4	0.8043	0.8048	4
5136-00-228-1055	1-1/8-7UNC	BOTTOMING	H4	1.0332	1.0342	4
5136-00-228-1056	1-1/4-7UNC	BOTTOMING	H4	1.1582	1.1592	4
5136-00-228-1057	1-1/2-6UNC	BOTTOMING	H4	1.3927	1.3937	4
5136-00-239-2174	7/8-9UNC	TAPER	H4	0.8043	0.8048	4
5136-00-254-4518	5/8-18UNF	PLUG	H3	0.5899	0.5904	4
5136-00-262-2195	5/8-18UNF	BOTTOMING	H3	0.5899	0.5904	4
5136-00-262-2200	1-3/8-12UNF	BOTTOMING	H4	1.3219	1.3229	6
5136-00-276-1031	5/16-18UNC	PLUG	H3	0.2774	0.2779	4
5136-00-276-1032	3/8-16UNC	PLUG	H3	0.3354	0.3359	4
5136-00-277-6709	5/8-18UNF	PLUG	H2	0.5894	0.5899	4
5136-00-293-0711	1/4-20UNC	BOTTOMING	H3	0.2185	0.2190	4
5136-00-293-0712	5/16-18UNC	BOTTOMING	H3	0.2774	0.2779	4
5136-00-293-0715	3/8-16UNC	BOTTOMING	H3	0.3354	0.3359	4
5136-00-516-3368	9/16-18UNF	TAPER*	H2	0.5269	0.5274	4
5136-00-516-3371	7/8-14UNF	TAPER*	H2	0.8291	0.8296	4
5136-00-516-4118	5/16-18UNC	BOTTOMING	H2	0.2769	0.2774	4
5136-00-517-5561	1/4-20UNC	BOTTOMING	H1	0.2175	0.2180	4
5136-00-517-5563	5/16-18UNC	BOTTOMING	H1	0.2764	0.2769	4
5136-00-555-3177	5/8-18UNF	PLUG	H4*	0.5904	0.5909	4
5136-00-555-8910	3/8-24UNF	PLUG	H3	0.3489	0.3494	4
5136-00-555-9203	3/8-24UNF	TAPER	H3	0.3489	0.3494	4
5136-00-555-9205	3/8-16UNC	TAPER	H3	0.3354	0.3359	4
5136-00-555-9206	1/4-20UNC	TAPER	H3	0.2185	0.2190	4
5136-00-580-7156	7/16-20UNF	BOTTOMING	H3	0.4060	0.4065	4
5136-00-580-7158	9/16-18UNF	BOTTOMING	H3	0.5274	0.5279	4
5136-00-580-7162	3/4-16UNF	BOTTOMING	H4*	0.7109	0.7114	4
5136-00-580-7163	7/8-14UNF	BOTTOMING	H4	0.8301	0.8306	4
5136-00-580-7166	1-12UNF	BOTTOMING	H4	0.9474	0.9479	4
5136-00-580-7169	9/16-12UNC	TAPER	H3	0.5094	0.5099	4
5136-00-580-7170	9/16-18UNF	TAPER	H3	0.5274	0.5279	4
5136-00-580-7175	7/8-14UNF	TAPER	H4	0.8301	0.8306	4

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:09Z
Check the source to verify that this is the current version before use.

Sequence of qualification tests on sample assemblies TABLE VI

NATIONAL STOCK NUMBER	SIZE, SERIES, DIRECTION	CHAMFER TYPE	P.D. LIM. SYM.	PITCH MIN. (INCH)	DIAMETER MAX. (INCH)	NUMBER OF FLUTES
5136-00-580-7177	1-12UNF	TAPER	H4	0.9474	0.9479	4
5136-00-580-7182	7/16-20UNF	PLUG	H3	0.4060	0.4065	4
5136-00-580-7184	1/2-20UNF	PLUG	H3	0.4685	0.4690	4
5136-00-580-7186	9/16-18UNF	PLUG	H3	0.5274	0.5279	4
5136-00-580-7188	7/8-14UNF	PLUG	H4	0.8301	0.8306	4
5136-00-580-7333	5/16-18UNC	TAPER	H3	0.2774	0.2779	4
5136-00-580-7334	1/2-13UNC	TAPER	H3	0.4510	0.4515	4
5136-00-580-7335	7/16-14UNC	TAPER	H3	0.3921	0.3926	4
5136-00-580-7342	3/4-16UNF	PLUG	H4*	0.7109	0.7114	4
5136-00-580-7343	1-14UNS	PLUG	H4	0.9551	0.9556	4
5136-00-580-7353	7/16-14UNC	BOTTOMING	H3	0.3921	0.3926	4
5136-00-580-7354	1/4-28UNF	BOTTOMING	H3	0.2278	0.2283	4
5136-00-580-7355	5/16-24UNF	BOTTOMING	H3	0.2864	0.2869	4
5136-00-580-7356	1/2-20UNF	BOTTOMING	H3	0.4685	0.4690	4
5136-00-580-7359	5/16-24UNF	PLUG	H3	0.2864	0.2869	4
5136-00-580-7360	1/4-28UNF	PLUG	H3	0.2278	0.2283	4
5136-00-580-7364	5/16-24UNF	TAPER	H3	0.2864	0.2869	4
5136-00-580-7365	1/4-28UNF	TAPER	H3	0.2278	0.2283	4
5136-00-708-0088	3/4-16UNF	PLUG	H3	0.7104	0.7109	4
5136-00-729-5682	3/4-10UNC	TAPER	H3	0.6860	0.6865	4
5136-00-729-5683	5/8-11UNC	TAPER	H3	0.5670	0.5675	4
5136-00-729-5688	1/2-13UNC	BOTTOMING	H3	0.4510	0.4515	4
5136-00-729-5690	9/16-12UNC	PLUG	H3	0.5094	0.5099	4
5136-00-729-5691	7/16-14UNC	PLUG	H3	0.3921	0.3926	4
5136-00-729-5692	1/2-13UNC	PLUG	H3	0.4510	0.4515	4
5136-00-729-5693	1/4-20UNC	PLUG	H3	0.2185	0.2190	4
5136-00-729-5696	1-3/8-12UNF	TAPER	H4	1.3219	1.3229	6
5136-00-729-5701	7/8-9UNC	PLUG	H4	0.8043	0.8048	4
5136-00-729-5702	3/4-10UNC	PLUG	H3	0.6860	0.6865	4
5136-00-729-5703	1/4-32UNS*	PLUG	H2	0.2307	0.2312	4
5136-00-729-5706	1-1/2-12UNF	BOTTOMING	H5*	1.4474	1.4484	6
5136-00-729-5709	1-1/8-12UNF	BOTTOMING	H4	1.0719	1.0729	4
5136-00-729-5710	3/8-24UNF	BOTTOMING	H3	0.3489	0.3494	4
5136-00-729-5715	1-8UNC	BOTTOMING	H4	0.9203	0.9208	4
5136-00-729-5716	3/4-10UNC	BOTTOMING	H3	0.6860	0.6865	4
5136-00-729-5717	5/8-11UNC	BOTTOMING	H3	0.5670	0.5675	4
5136-00-729-5718	9/16-12UNC	BOTTOMING	H3	0.5094	0.5099	4
5136-00-841-2837	1-12UNF	PLUG	H4	0.9474	0.9479	4
5136-00-865-2178	2-12UN*	TAPER	H5	1.9474	1.9489	6 OR 8
5136-00-865-2179	1-3/4-12UN*	TAPER	H5	1.6974	1.6989	6 OR 8
5136-00-865-2229	5/16-24UNF	TAPER*	H1	0.2854	0.2859	4
5136-00-865-2232	1-1/8-12UNF	PLUG	H4	1.0719	1.0729	4
5136-00-889-5828	1/4-20UNC	PLUG	L1*	0.2170	0.2175	4
5136-00-889-6621	1-3/8-6UNC	PLUG	H4	1.2677	1.2687	4
5136-00-889-6625	1/4-20UNC	PLUG	H2	0.2180	0.2185	4
5136-00-889-6966	1-14UNS	TAPER	H4	0.9551	0.9556	4
5136-00-889-6970	11/16-11UNS	PLUG	H3	0.6295	0.6300	4
5136-00-889-6971	11/16-16UNS	PLUG	H3	0.6479	0.6484	4
5136-00-889-6973	11/16-16UNS	TAPER	H3	0.6479	0.6484	4
5136-00-889-7007	11/16-11UNS	BOTTOMING	H3	0.6295	0.6300	4

* Exception to ANSI B94.9

Workmanship. All taps shall be free from imperfections which may affect their appearance, serviceability or durability.

Quality assurance provisions. Sampling for inspection shall be in accordance with MIL-STD-105, Sampling Procedures and Tables for Inspection by Attributes, except where otherwise indicated herein. The lot size shall consist of all taps with the same NSN offered for acceptance at one time. A sample unit shall be one tap.

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T08:09Z
Check the source to verify that this is the currentversion before use.

Visual and dimensional requirements. Each sample unit shall be examined and measured for compliance with applicable requirements of ANSI B94.9, and for workmanship as specified above. The inspection level shall be S-3 with an AQL of 1.5 percent defective.

Hardness test. Hardness testing shall be in accordance with ASTM E 18. The inspection level shall be S-2 with an AQL of 1.5 percent defective.

Performance test. When specified in the contract or purchase order, a sample consisting of three taps of the same manufacturing design shall be tested to demonstrate the ability of the tap to perform in various metals.

Each tap shall be tested by tapping ten through holes into one of three metal bars or plates, each composed of a different composition (one copper alloy, one carbon steel, and one corrosion resisting steel) of the suppliers option. The bars or plates shall have a minimum thickness equal to the major diameter of the tap, and the hole diameters shall be such as to produce a theoretical 75% thread height. Other test factors not specified shall be at the manufacturer's option. Failure of any of the three taps to produce smooth, well-defined Unified National Form threads of a size which is consistent from the first to the last tapped hole shall be considered cause for rejection of the entire preproduction sample.

Packaging inspection. An examination shall be made to determine compliance with all preservation, packaging, packing, labeling, and marking requirements as specified in the contract or purchase order. The inspection level shall be S-2 with an AQL of 2.5 defects per hundred units.

Regulatory requirements. In accordance with the section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing suppliers' employees to undue hazards from the recovered materials.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

Notes:

Copies of American National Standard ANSI B94.9, Taps, Cut and Ground Threads may be obtained from the American National Standards Institute, 1430 Broadway, New York, New York 10018.

Copies of ASTM Standard E 18, Tests for Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials may be obtained from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

Copies of Military Standards are available from the Naval Publication and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 19120.

MILITARY INTERESTS:

Military Coordinating Activity

Army - GL

Custodians

Army - GL
Air Force - 99

Review Activity

Air Force - 84

PREPARING ACTIVITY:

GSA-FSS

Project 5136-0042

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:09Z
Check the source to verify that this is the current version before use.

| Hose size | No. of hose samples |