MILITARY SPECIFICATION SHEET

SCALE, GRAPHICAL SITE, HE M650,
(8-S-1), (P/N 11785434-88)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring this item described herein shall consist of this document and the latest issue of Specification MIL-S-64045

ACCURACY DATA

| Charge | T.A.G.[1] | Ranqe[2] | T.A.G.[1] | Range[2] | T.B.G.[3] | Range4 | T.B.G.[3] | Range[4] |
|---|---|---|---|---|---|---|---|---|
| 1 | 2430±10 | 2500 | 3375±10 | 4500 | 2415±10 | 2500 | 3660±10 | 5000 |
| 2 | 2820±10 | 2900 | 3970±10 | 5500 | 2890±10 | 3000 | 4225±20 | 6000 |
| 3 | 3385±10 | 3500 | 4460±20 | 7000 | 3370±10 | 3500 | 4460±20 | 7000 |
| 4 | 4080±20 | 4200 | 5750±20 | 8000 | 4085±20 | 4200 | 5980±20 | 8500 |
| 5G | 5050±20 | 5200 | 7250±25 | 10000 | 5055±20 | 5200 | 7760±25 | 10000 |
| 5W | 5525±20 | 5700 | 7850±25 | 10500 | 5540±20 | 5700 | 8100±25 | 11000 |
| 6 | 6940±20 | 7200 | 9500±25 | 13000 | 5960±20 | 7200 | 9725±25 | 13500 |
| 7 | 10045±50 | 10600 | l2060±50 | 15500 | 10040±50 | 10500 | 12700±50 | 15000 |
| 8 | 11800±50 | 12000 | 16150±50 | 19000 | 11900±50 | 12000 | 15600±50 | 20500 |
| 9 | 13405±50 | 13500 | 18050±0 | 22000 | 1305560 | 13500 | 18070±50 | 22000 |
| 7R | 10325±50 | 10500 | 16500±50 | 20000 | 10350±50 | 10500 | 16450±50 | 19000 |
| 8R | 13550±50 | 13500 | 18925±50 | 25000 | 13610±50 | 13500 | 2225O±1OO | 23000 |
| 9R | 15410±50 | 15000 | 26010±100 | 28000 | 15400±50 | 15000 | 25450±100 | 28000 |

1. Target. above gun in meters on C scale.
2. Range in meters on T.A.G.scale for specified charge.
3. Target below gun in meters on C scale.
4. Range in meters cm T.B.G. scale for specified charge.

Custodian:
ARMY-AR

Preparing Activity
ARMY-AR



Project No. 1220-A293

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T03:16Z
Check the source to verify that this is the current version before use.