DOD-C-85050(AS)
Amendment 2
8 July 1983

MILITARY SPECIFICATION

CHARGES, BATTERY, NICKEL-CADMIUM, AIRCRAFT,
GENERAL SPECIFICATION FOR

This Amendment forms a part of Military Specification DOD-C-85050(AS) dated 25 June 1982 and is approved for use by the Naval Air Systems Command, Department of The Navy, and is available for use by all Departments and Agencies of the Department of Defense.

Page 1

Delete "FSC 6140" and substitute "FSC 6130

Page 8

Change paragraph 3.5.1.4.5 to read:

Charging time. The maximum time required for the battery charger to charge the specified battery, when all conditions of charge initiation are met, to 80 percent and 100 percent state-of-charge (SOC) shall be as shown in Table I. This requirement applies to batteries that contain actual capacities of up to 125 percent of rated capacities that have been discharged to 0.95 volts/
cell prior to each charge test.

Page 9

Paragraph 3.5.1.6 (a) change 26.0 ± .3 volts to 24.75 ± 0.25 volts in 3 places.

Page 11

Change paragraph 3.8.1 to read:

Nameplate. The nameplate on all chargers shall be metal in accordance with MIL-P-15024 Type A, B or H.

Change Data MFG. to Date MFG.

Page 18

b. Line 2, change 26.3V to 25.0V
Line 5, change to read ± 2.5 seconds, regardless of input voltage, then reopen.

c. Line 4, change 26.0 ± 0.3V to 24.75 ± 0.25V

Preparing activity
Navy - AS
(Project No. 6130-N239)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:04:42
Check the source to verify that this is the current version before use.