INCH-POUND

MIL-DTL-27434/5A
22 May 2008
SUPERSEDING
MIL-A-27434/5
10 May 1960


DETAIL SPECIFICATION SHEET

ADAPTER, CONNECTOR, COAXIAL, RADIOFREQUENCY, BETWEEN SERIES, SERIES C to SERIES UHF TYPE UG-637/U

Inactive for new design after 19 February 1982

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-27434.




Inches	mm
.812	20.62
1.375	34.92

NOTES:
1. All dimensions are in inches.
2. Metric equivalents are given for information only.


FIGURE 1. Type UG – 637/U connector adapter.

AMSC N/A FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:51Z
Check the source to verify that this is the current version before use.



1 CENTER CONTACT



2 BODY

FIGURE 2. Type UG – 637/U connector adapter detail dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:51Z
Check the source to verify that this is the current version before use.




FIGURE 2. Type UG – 637/U connector adapter detail dimensions – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:51Z
Check the source to verify that this is the current version before use.






FIGURE 2. Type UG – 637/U connector adapter detail dimensions – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:51Z
Check the source to verify that this is the current version before use.



8 COUPLING NUT



9 CENTER CONTACT

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.

FIGURE 2. Type UG – 637/U connector adapter detail dimensions – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:51Z
Check the source to verify that this is the current version before use.

Item	Description	Material	Quantity
1	Center contact	Copper beryllium	1
2	Body	Brass	1
3	Insulator	Polytetrafluoroethylene	1
4	Ring	Copper wire	1
5	Insulator	Polytetrafluoroethylene	1
6	Ring	Phosphor bronze	1
7	Body	Brass	1
8	Coupling nut	Brass	1
9	Center contact	Brass	1

Inches	mm	Inches	mm
.001	0.03	.307	7.80
.002	0.05	.310	7.87
.003	0.08	.312	7.92
.004	0.10	.322	8.18
.005	0.13	.335	8.51
.008	0.20	.343	8.71
.010	0.25	.378	9.60
.011	0.28	.382	9.70
.014	0.36	.400	10.16
.015	0.38	.402	10.21
.016	0.41	.413	10.49
.020	0.51	.445	11.30
.028	0.71	.468	11.89
.030	0.76	.479	12.17
.045	1.14	.490	12.45
.065	1.65	.500	12.70
.086	2.18	.550	13.97
.089	2.26	.535	13.59
.093	2.36	.593	15.06
.096	2.44	.595	15.11
.100	2.54	.602	15.29
.120	3.05	.611	15.52
.121	3.07	.625	15.88
.125	3.18	.628	15.95
.140	3.56	.635	16.13
.156	3.96	.660	16.76
.163	4.14	.671	17.04
.184	4.67	.687	17.45
.187	4.75	.697	17.70
.205	5.21	.708	17.98
.210	5.33	.737	18.72
.250	6.35	.781	19.84
.260	6.60	.937	23.80
.274	6.96	1.273	32.33

FIGURE 2. Type UG – 637/U connector adapter detail dimensions – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:51Z
Check the source to verify that this is the current version before use.

ENGINEERING DATA:

Impedance: 50 ohms, nominal.

Frequency range: 0 to 300 MHz

Voltage rating: 500 V rms maximum at sea level.
125 V rms maximum, at 70,000 feet.

Temperature rating: -65º C to +165º C.

REQUIREMENTS:

Dimensions and configuration: See figure 1 and figure 2.

Mating characteristics: Series C interface shall be in accordance with MIL-STD-348 and series UHF shall be in accordance with MIL-DTL-27434 and shall meet the interface dimensions after assembly.

Dielectric withstanding voltage: Method 301 of MIL-STD-202, 1,500 V rms minimum applied instantaneously at sea level.

Corrosion: Applicable.

Vibration: Applicable.

Shock: Applicable.

Part or Identifying Number (PIN): UG-637/U.

Supersession: This document supersedes Navy drawing MS35282 (Sig C).

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Referenced documents. In addition to MIL-DTL-27434, this document references the following:

MIL-STD-202
MIL-STD-348

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:51Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Review activities:
Navy - SH
Air Force - 99

Preparing activity:
DLA - CC

(Project 5935-2007-001)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:51Z
Check the source to verify that this is the current version before use.