The documentation and process conversion measures necessary to comply with this amendment amendment shall be completed by 7 November 2000.

INCH- POUND

MIL-PRF-19500/356F
AMENDMENT 1
7 August 2000

PERFORMANCE SPECIFICATION

SEMICONDUCTOR DEVICE, DIODE, SILICON, VOLTAGE REGULATOR
TYPES 1N4954 THROUGH 1N4996, 1N5968, 1N5969, AND 1N6632 THROUGH 1N6637,
1N4954US THROUGH 1N4996US, 1N5968US, 1N5969US, AND 1N6632US THROUGH 1N6637US,
AND C AND D TOLERANCE SUFFIX DEVICES
JAN, JANTX, JANTXV, JANJ, JANS, JANHC, AND JANKC

This amendment forms a part of MIL-PRF-19500/356F, dated 10 August 1999 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

3.4.1. Construction. Delete “A.3.15.1, A.3.15.2, A.3.15.3, A.3.15.6, A.3.15.7, A.3.15.8” in it’s entirety.

PAGE 3

Figure 1 Dimension table, Delete the metric measurements of BD “2.92 min and 4.70 max” and replace with “2.29 min and 3.68 max”.

Figure 1 Dimension table, Ltr, LD, Delete note 3.

Figure 1 Dimension table, Ltr, BD, Add note 3.

PAGE 9

4.3. Screening table, JANTX and JANTXV, level 1a, Add “unless specified for JANTXV.”

4.3. Screening table, JANS, JANJ, JANTX, and JANTXV, level 2, Delete “Not Required” and replace with “Optional”

4.3. Screening table, JANS, level 10, Delete “Not Applicable” and replace with “100 percent”.

4.3. Screening table, JANTX and JANTXV, level 13, Delete “Required Subgroups 2 of table I herein; ΔI_{R1} (max) $\leq \pm 100$ percent of initial reading or 250 nA, greater; $\Delta V_Z \leq \pm 2.5$ percent of initial reading.” and replace with

“Required, Subgroups 2 of table I herein; ΔI_{R1} (max) = 100 percent of initial reading or 25 percent of column 12 of table IV (1N6632 - 1N4964), 250 nA (1N4965 - 1N4996), whichever is greater, $\Delta V_Z \leq \pm 2.5$ percent of initial reading.”

4.3. Screening table, level 13, Delete note 3.

4.3. Screening table, level 17, Delete in its entirety.

Screening Table, below the notes, Remove the “Leaded devices equations” and place them in 4.4 Power burn-in section just below the “$I_Z \geq 25$ percent of column 8 (I_{ZM}) of table IV.”

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:45Z
Check the source to verify that this is the current version before use.

PAGE 10

4.5.2.1. Group B inspection, table VIa (JANS) of MIL-PRF-19500. Subgroup B5, delete the second paragraph of,

"I_Z = 40 percent of column 8 of table IV for 1000 hours. T_J = +175°C (min). T_A = +30°C ±5°C (frequency is per inspection lot). Leaded samples from the same lot may be used in lieu of the U suffix sample life test."

and substitute the following,

"I_Z = 40 percent of column 8 of table IV for 1000 hours. T_J = +175°C (min) at double the sample size. T_A = +30°C ±5°C (frequency is per inspection lot). Leaded samples from the same lot may be used in lieu of the U suffix sample life test."

PAGE 15

Table II, Subgroup 2, Electrical measurements, Delete " See table III, steps 2, 3, 4, 5, and 6'
and replace with "See table III, steps 1, 2, 3, 4, 5, and 6'

PAGE 16

Table III, note 1c, Delete "steps 2, 3, 4, and 5" and replace with "steps.1, 2, 3, 4, and 5

Table III, note 2a, b, and c, Delete "steps 2, and 3" and replace with "steps 1, 2, and 3"

PAGE 17

Table IV, Type 1N6633, column 12, Delete "500" and replace with "250"

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC
NASA - NA

Review activities:
Army - AR, AV, MI, SM
Navy - AS
Air Force - 13, 19, 99

Preparing activity:
DLA - CC

(Project 5961-2251)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:45Z
Check the source to verify that this is the current version before use.