MILITARY SPECIFICATION

CUTTER, POWDER ACTUATED, M8 REMANUFACTURED METAL PARTS ASSEMBLY

This amendment forms a part of Military Specification MIL-C-60593(MU), dated 20 September 1966, and is approved for use within the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1 Delete: "MIL-STD-693 . . ."in its entirety.

PAGE 2

2.2 Delete in its entirety and substitute:

"2.2 Other publications. The following document forms a part of this specification to the extent specied herein. Unless otherwise specified, the issues of the document which are DOD adpoted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

ASTM D149 Insulating Material, Electrical, at Commercial Power Frequencies, Dielectric Breakdown Voltage and Dielectric Strength of.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer, Naval Ordnance Station, Documentation Division (370), Indian Head, MD 20640-5000.

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:47Z
Check the source to verify that this is the current version before use.

(Application of copies should be addressed to the American Society for Testing Materials, 1916 Race Street, Philadelphia, PA 19103.)

ANSI B46.1 Surface Texture (Surface Roughness, Waviness and Lay)

(Application for copies should be addressed to the American National Standards Institute (ANSI), 1430 Broadway, NY 10018.)

(Nongovernment standards and other publications are normally available from the organization which prepares or which distributes the documents. These documents also may be available in or through libraries or other informational services.)"

PAGE 5

4.2.2 Delete "The ordnance standard finish blocks prescribed in MIL-STD-639 . . ." and substitute "The roughness comparison standards prescribed in ANSI B46.1 . . . ".

PAGE 13

4.3.6.2 Change ". . . ASTM Standard - D149-61 . . ."to read". . . ASTM D149 . . .".

Preparing Activity:
Navy - OS
Project No. 1377-N875

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:47Z
Check the source to verify that this is the current version before use.