INCH-POUND

MIL-C-48669(AR)
AMENDMENT 3
18 April 1991
SUPERSEDING
AMENDMENT 2
30 September 1988

MILITARY SPECIFICATION

CARTRIDGE, 40MM, M918TP; ESCAPEMENT ASSEMBLY
FOR
METAL PARTS AND LOADING, ASSEMBLING AND PACKAGING

This Amendment forms a part of Military Specification MIL-C-48669(AR), dated 1 April 1986, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Change "FSC 1310" to "FSC 1390".

PAGE 2

2.1.2, Add the following under list of drawings:

"8886327 -Cartridge Case Assembly 40MM, M169
9399395 -Anti-Creep Spring
12589941 -Test Vehicle Projectile
12902879 -Inert M918 Projectile Assembly Less Escapement Assembly
12598456 -Packing and Marking for Escapement Assemblies"

2.1.3, Delete:

"CODE OF FEDERAL REGULATIONS

TITLE 49 -Transportation, Parts 100-199

(The Code of Federal Regulations is available from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20315. Orders should specify "49 CFR 100-199 (Latest revision))."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

PAGE 4

Add:

"3.9 Functioning. The projectile, on impact, shall produce sufficient sound, smoke and flash under atmospheric conditions. There shall be no evidence of an air burst. (see 6.9).

3.10 Non-functioning. The projectile shall not lodge in bore of the weapon and there shall be no evidence of a premature burst. (See 6.10)."

Add to Table I under Escapement Assembly (Dwg. 8886357):

"Functioning	150	5-6	3.9	4.5.18
Non-Functioning	100	3-4	3.10	4.5.19"

PAGE 15

4.4.2.7, Critical 2, 4, 5, 6, and 7, Under Paragraph Reference/Inspection Method, Delete "Visual/Probe" and substitute "Probe, 4.5.17".

* 4.4.2.7, Delete critical 8 in its entirety.

* 4.4.2.7, Add Major 105:

"105. Static Pull Test of Setback Spring	.25	3.2	4.5.12"

4.4.2.7, Add the following:

"103. Functioning	100	3-4	3.9	4.5.18
104. Non-Functioning	10	0-1	3.10	4.5.19"

PAGE 18

* Delete paragraph 4.5.12 in its entirety and substitute:

"4.5.12 Static pull test. The escapement assembly shall be placed in an approved fixture and the force specified on the applicable drawing shall be applied. Assemblies subjected to this test shall have their setback springs replaced and be reinspected in accordance with 4.4.2.7, Criticals 6 and 7."

Source: https://assist.dla.mil -- Downloaded: 20260-22T19:36Z
Check the source to verify that this is the current version before use.

Add the following:

"4.5.17 Probe inspection. This inspection shall be performed using automatic inspection equipment designed by the contractor and approved by the Government."

Add the following:

"4.5.18 Functioning. The Escapement Assembly (Dwg. 8886357) shall be inserted into a Test Vehicle Projectile (Dwg. 12589941) and assembled to M169, 40MM cartridge case assembly (Dwg. 8886327) resulting in a M918 TP cartridge (Dwg. 9399372). The cartridge shall be fired from a launcher from which it is standard to impact at approximately 200 meters from the launcher onto coarse sand, ten inches minimum thickness at point of impact. Angle of firing shall be adjusted to give an impact of approximately 25 degrees. Rake sand after every round or traverse weapon between shots so that impacts are not overlapping. If a round falls outside the specified area, it shall be declared a "no-test" round. When results for functioning are reported, the number of "no-test" rounds shall also be reported."

Add the following:

"4.5.19 Non-Functioning. After completion of the transportation-vibration test, the escapement assemblies shall be removed from their regular shipping containers and subjected to this test. The Escapement Assembly (Dwg. 9996327) shall be inserted into a Test Vehicle Projectile (Dwg. 12589941) and assembled to M169, 40mm Cartridge Case Assembly (Dwg. 8886327) resulting in a M918 TP Cartridge (Dwg. 9399372). The cartridge shall be fired from the launcher for which it is standard to impact at 20 feet from the launcher against a vertical celotex target."

5.1.1, Change "Code of Federal Regulations, Tile 49, Part 100-199" to 'Dwg. 12598456".

6.2.d, Delete and substitute the following:

"d. Responsibility for furnishing inert M918 Projectile Assembly Less Escapement Assembly (Dwg. 129002879), Anti-Creep Spring (Dwg. 9399395), Test Vehicle Projectile (Dwg. 12589941) and M169, 40MM Cartridge Case Assembly (Dwg. 8886327)."

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:36Z
Check the source to verify that this is the current version before use.

Add the following:

"6.2i Responsibility for furnishing a Grenade Launcher."

PAGE 20

Add the following:

"6.9 Premature burst. A premature burst is considered to have occurred if the projectile functions in the weapon bore or in flight up to 20 feet from the muzzle.

6.10 Air burst. A projectile that functions inflight further than 20 feet from the weapon muzzle."

The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of the document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1390-A688)

Source: https://assist.dla.mil -- Downloaded: 20260410-22T19:36Z
Check the source to verify that this is the current version before use.