MILITARY SPECIFICATION
CARRIERS, FULL-TRACKED: M548A1 and M730A1

This amendment forms a part of Military Specification MIL-C-62013C(AT), dated 11 August 1982, and is approved for use within the US Army Tank-Automotive Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

*Delete "FSC 2320" and substitute: "FSC 2350".

PAGE 3

*3.1, delete the first sentence and substitute: "Unless otherwise specified (see 6.2), the contractor shall furnish sample vehicles for first article inspection and approval (see 4.3 and 6.3)."

PAGE 4

3.2.4, delete the "Note" in its entirety and substitute: "NOTE: When vehicle is to be operated as a prime mover (equipped with air brake kit), mileage during operation on hard-surfaced roads and cross country shall include 200 miles in each mode towing a 14,000 pound GVW trailer for M548A1 only."

PAGE 5

3.4.2.1, in the second sentence delete: "beyond the extent commensurate with the design characteristics".

3.4.2.3, in the second sentence delete: "beyond the extent commensurate with the design characteristics".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:09Z
Check the source to verify that this is the current version before use.

PAGE 8

*3.4.8.5, line 3, delete "class A3 and C1" and substitute: "parts 4 and 8".

3.4.11, delete in its entirety and substitute:

"3.4.11 Stowed material. All interior and exterior basic issue items (BII) when stowed on the vehicle in the spaces provided shall fit properly and not interfere with the operation of vehicle and components in any manner."

PAGE 9

*3.6, line 2, delete "3.5.1" and substitute: "4.6.4".

PAGE 10

3.6.4, line 2, delete "42 mph" and substitute: "38 mph".

*3.6.5, delete paragraph in its entirety and substitute:

"3.6.5 Acceleration. With the vehicle at a standstill, transmission in the 1-3 range and engine at idle speed, the vehicle shall accelerate from 0 to 20 mph in not more than 18 seconds with rated payload or 11 seconds without load on a smooth, level, hard-surfaced road."

PAGES 11 AND 12

3.6.14 through 3.6.14.2, delete paragraphs in entirety and substitute the following:

"3.6.14 Winch system. The winch system shall withstand an increasing load with an 11 to 12 foot cable (total length), including three to four wraps of cable on a bare drum. The load shall be gradually increased until the shear pin fails or the load reaches 24,000 pounds. The load must exceed 14,000 pounds. Failure load shall be recorded.

3.6.14.1 Winch operation. Starting with the fifth to tenth wrap on a bare drum, tension shall be applied to provide even distribution of the cable until the cable has been completely reeled in.

3.6.14.2 Winch structural integrity. The winch system structural integrity shall be verified by pulling the winch cable with a 20,000 pound load. During the test, the engine power takeoff shall be disengaged. Three to six wraps of cable shall be wrapped on the bare drum. The rope length is optional.

3.6.14.3 Winch controls. The cab-mounted controls shall engage the power takeoff drive for operation of the winch. The manually operated device furnished shall permit free spooling of the winch drum."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:09Z
Check the source to verify that this is the current version before use.

PAGE 21

*4.6.4, line 10, delete "4.6.23" and substitute: "4.7.23".

PAGE 24

TABLE VI, line 1, Folding blast covers (M730A1): Under Control Test column, add: "4.7.13". Line 2, Tailgate (M730A1): Under Control Test column, add: "4.7.14".

Add "system" to winch and additional information as shown in Table VI.

TABLE VI. Classification and location of inspections and tests. - Continued

Title	Requirement	First Article	Acceptance	Control
"Winch system	3.6.14	4.7.31		4.7.31
Winch operation	3.6.14.1	4.7.31	4.7.31	
Winch structural integrity	3.6.14.2	4.7.31		4.7.31
Winch controls	3.6.14.3	4.7.31	4.7.31"	

PAGE 30

4.7.31, delete "3.6.14.2" and substitute: "3.6.14.3".

PAGE 31

*6.2, item e, delete "3.4.2.2" and substitute: "3.4.2".

*6.3, lines 2 and 3, delete "7-104.55 of the Defense Acquisition Regulation" and substitute: "52.209-3 and 52.209-4 of the Federal Acquisition Regulation".

PAGE 33

*Add the following paragraph:

"6.12 Subject term (key word) listing.

Full-Tracked Carriers, M548A1 and M730A1.
M548A1 and M730A1 Full-Tracked Carriers."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - AT

Preparing activity:
Army - AT

(Project 2350-A356)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:09Z
Check the source to verify that this is the current version before use.