INCH-POUND
MIL-DTL-70951A (AR)
28 NOVEMBER 2007
SUPERSEDING
MIL-P-70951 (AR)
24 MARCH 1992

DETAIL SPECIFICATION

PALLET, FIELD ARTILLERY PROJECTILE

This specification is approved for use by the U.S. Army Armament Research Development and Engineering Center (ARDEC), and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers requirements and provisions for the manufacturing and assembly of field artillery projectile pallets (FAPP) for use in unitizing 155MM projectiles (see 6.1).

1.2 Classification. The field artillery projectile pallet shall be classified as follows (see 6.1 and 6.2):

1.2.1 Type I - FAPP with latch rod assembly having rod length of 23.66 inches.

1.2.2 Type II - FAPP with latch rod assembly having rod length of 31.49 inches.

Comments, suggestions, or questions on this document should be addressed to the Commander, U.S. Army ARDEC, ATTN: AMSRD-AAR-QES-E, Picatinny, NJ 07806-5000 or emailed to ardecstdzn@conus.army.mil . Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at http://assist.daps.dla.mil.

AMSC N/A FSC 8140

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to assure the completeness of this list, document users are cautioned that they must meet all requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

FEDERAL SPECIFICATIONS

TT-C-490 - Chemical Conversion Coatings and Pretreatments for Ferrous Surfaces (Base for Organic Coatings)

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-1916 - DoD Preferred Methods for Acceptance of Product
MIL-STD-171 - Finishing of Metal and Wood Surfaces
MIL-STD-1660 - Design Criteria for Ammunition Unit Loads

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-W-21157 - Weldment, Steel, Carbon and Low Alloy (Yield Strength 30,000 – 60,000 PSI)
MIL-W-12332 - Welding, Resistance, Spot, Seam, and Projection; for fabricating assemblies of Low-Carbon Steel

(Unless otherwise indicated, Copies of these documents are available online at http://assist.daps.dla.mil/quicksearch/ or http://assist.daps.dla.mil from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.2.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation or contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

US ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC) DRAWINGS

12914619 – Packing and Marking 155mm projectile pallet
12552040 – Chemical Agent Resistant Coating (CARC) Finishing Requirements for Ferrous and non Ferrous Containers.
12914630 – Latch-rod Assembly
12914623 – Base Panel
12914620 – Base Assembly
12914625 – Cover Panel
12914626 – Cover Panel – End Cap
12914624 – Cover Assembly
12926863 – Cover Liner
12914629 – Spacer
12914628 – Latch-Handle Assembly
12934728 – Base Panel – End Cap
12934729 – Trunnion
12914621 – Base Doubler
12914622 – Forkwell
12914627 – Pivot pin

(Copies of these drawings may be requested online at Pica.drawing.request@conus.army.mil or from U.S. Army ARDEC, ATTN: AMSRD-AAR-AIS-TD, Picatinny, NJ 07806-5000.)

2.3 Non-Government Publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM) INTERNATIONAL

ASTM B 117 - Standard Practice for Operating Salt Spray (Fog) Apparatus
ASTM D 610 - Standard Test Method for Evaluating Degree of Rusting on Painted Steel Surfaces
ASTM B 633 - Standard Specification for Electrodeposited Coatings of Zinc on Iron and Steel
ASTM D 4169 - Standard Practice for Performance Testing of Shipping Containers and Systems
ASTM D 6179 - Standard Test Methods for Rough Handling of Unitized Loads and Large Shipping Cases and Crates
ASTM D 880 - Standard Test Method for Impact Testing for Shipping Containers and Systems

(Copies of these documents are available online at http://www.astm.org or ASTM International, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

AMERICAN WELDING SOCIETY

AWS B 1.10 - Guide for Non-destructive Inspection of Welds
AWS B 4.0 - Standard Methods for mechanical testing of welds
AWS D 9.1 - Sheet metal welding code

(Copies of AWS standards are available online at http://www.aws.org or AWS 550 N.W. LeJeune Road, Miami, Florida 33126.)

2.4 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article inspection. When specified (see 6.2) a sample shall be subjected to first article inspection in accordance with 4.2.

3.2 Components and assemblies. The components and assemblies shall comply with all requirements specified on drawing 12914619.

3.2.1 Latch-rod assembly. The components and assemblies shall comply with all requirements specified on drawing 12914630.

3.2.2 Latch-rod assembly, painted. The components and assemblies shall comply with all requirements specified on drawing 12914630.

3.2.3 Panel, base. The components and assemblies shall comply with all requirements specified on drawing 12914623.

3.2.4 Base assembly. The components and assemblies shall comply with all requirements specified on drawing 12914620.

3.2.5 Base assembly, painted. The components and assemblies shall comply with all requirements specified on drawing 12914620.

3.2.6 Panel, cover. The components and assemblies shall comply with all requirements specified on drawing 12914625.

3.2.7 Cover assembly. The components and assemblies shall comply with all requirements specified on drawing 12914624.

3.2.8 Cover assembly, painted. The components and assemblies shall comply with all requirements specified on drawing 12914624.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

3.2.9 Liner, cover. The components and assemblies shall comply with all requirements specified on drawing 12926863.

3.2.10 Spacer. The components and assemblies shall comply with all requirements specified on drawing 12914629.

3.2.11 Latch-handle assembly. The components and assemblies shall comply with all requirements specified on drawing 12914628.

3.2.12 End cap, cover panel. The components and assemblies shall comply with all requirements specified on drawing 12914626.

3.2.13 End cap, base panel. The components and assemblies shall comply with all requirements specified on drawing 12934728.

3.2.14 Trunnion. The components and assemblies shall comply with all requirements specified on drawing 12934729.

3.2.15 Doubler, base. The components and assemblies shall comply with all requirements specified on drawing 12914621.

3.2.16 Forkwell. The components and assemblies shall comply with all requirements specified on drawing 12914622.

3.2.17 Pin, pivot. The components and assemblies shall comply with all requirements specified on drawing 12914627.

3.2.18 Packing and marking 155mm projectile pallet (Field Artillery Projectile Pallet assembly). The pallet assemblies shall comply with all requirements specified on drawing 12914619.

3.3 Stacking strength. The pallets shall withstand a 5,000 pound minimum (min.) stacking load.

3.4 Welding. The welding shall comply with the requirements of MIL-W-12332 or MIL-W-21157 and weld callouts in the applicable drawings.

3.5 Weld integrity.

3.5.1 Visual inspection. The load bearing surface welds (forkwell welded to base panel) of the base assembly (see dwg. 12914620) shall be free of the following defects:

a. Undercut
b. Overlap

c. Surface cavities
d. Surface cracks in weld metal or in heat affected zone of base metal

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

e. Lack of weld penetration
f. Slag
g. Incomplete fusion
h. The requirement for porosity shall be in accordance with AWS D9.1. The visual inspection of welds shall be in accordance with AWS B1.10.

3.5.2 Weld coupon bend test. The guided specimens shall have no open discontinuities exceeding 1/8 in. (3.2mm) measured in any direction on the convex surface of the specimen after bending, except that cracks occurring on the corners shall not be considered, unless there is definite evidence that they result from slag inclusions or other internal discontinuities.

3.6 Unit load tests. The unit loaded pallets shall conform to the requirements specified in MIL-STD-1660 with the following exceptions:

3.6.1 Repetitive shock test. Damage including dents, paint chipping, or the crushing of members which do not impair the function of the container are not causes for rejection. However, all damage shall be noted for information purposes. The pallets shall not exhibit the following:

a. Functional or physical damage to the contents.
b. Functional damage to the container.
c. Shock forces on the contents (or dummy load) which exceeds the established fragility of the contents.
d. Structural damage to the container which may result in damage to the contents during subsequent shipping, handling, or storage. Substantial spillage, exposure, or shifting of the contents are examples of such damage.

3.6.2 Edgewise drop (rotational) test. Minor damage such as dents, paint chipping, or the crushing of members which do not impair the function of the container are not causes for rejection. However, all damage shall be noted for information purposes. The pallets shall not exhibit the following:

a. Functional or physical damage to the contents.
b. Internal and/or external functional damage to the container.
c. Shock forces on the contents (or dummy load) which exceeds the established fragility of the contents.
d. Structural damage to the container which may result in damage to the contents during subsequent shipping, handling, or storage. Substantial spillage, exposure, or shifting of the contents are examples of such damage.

3.6.3 Incline impact test. Minor damage such as dents, paint chipping, or the crushing of members which do not impair the function of the container are not causes for rejection. However, all damage shall be noted for information purposes. The pallets shall not exhibit the following:

a. Functional or physical damage to the container and/or contents (except a dummy load).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

b. Damage to exterior container which is the result of improper interior packaging, blocking, or bracing.

c. Structural damage to the exterior of container which would result in either spilling of contents or failure of the container in subsequent handling.

d. Evidence of substantial amount of shifting of the contents that would create conditions likely to cause damage during shipment, storage, and reshipment of container.

3.7 Workmanship. The requirements for workmanship are as follows:

3.7.1 Pallets. The pallets shall be regular, smooth, free from wrinkles, cracks, rough spots, burrs, sharp edges and any other defect that might affect the serviceability, durability and safety of the pallets. Weld splatter is permissible on non-load bearing surfaces provided it is firmly attached.

3.7.2 Paint coating. The painted surfaces of the pallets shall comply with the requirements of TT-C-490, applicable drawings and with instructions specified in MIL-STD-171.
The finished coat shall cover all the required surfaces and be continuous. Paint runs are permissible provided they are not more than 3 inches in length, solid, and free from cracks and blisters. Excess thickness is acceptable in areas where multiple passes of the paint gun are required to obtain total coverage. Paint chips which expose primer or bare metal are acceptable provided they are not more than 0.25 inches in diameter and no more than two such paint chips on a pallet. Scratches which expose primer or bare metal are permissible provided they are no more than 1.5 inches in length and no more than 10 inches total on a pallet. Bare metal on contact surfaces of bottom of skids and in areas inaccessible to paint is permissible.

3.7.3 Parts. All parts shall be free of chips, dirt, grease, rust and foreign material. The cleaning method used shall not be injurious to any of the parts nor shall any of the parts be contaminated by the cleaning agents used.

3.7.4 Protective coating thickness. The components and assemblies shall comply with all requirements specified on drawing 12552040.

3.8 Salt spray test for painted base and cover assemblies. When tested as specified in 4.4.5, the painted base and cover assemblies shall be examined immediately after removal from the test and show no more than a trace of rusting per ASTM D 610, and no blister larger than one millimeter in diameter.

3.9 Salt spray test for latch-rod assembly. The painted latch-rod assembly shall show neither corrosion products of zinc nor basis metal corrosion products at the end of the 96 hours when tested by continuous exposure to salt spray in accordance with 4.4.6.

3.10 Latch handle pull test. The force required to release the latch handle from its locking position shall be 20 +/- 5 lbs when determined in accordance with 4.4.7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

4. VERIFICATION

TABLE I. Requirement/Verification Cross Reference Matrix.

Methods of Verification N/A – Not Applicable 1 – Analysis 2 – Demonstration 3 – Examination 4 - Test							Classes of Verification A- First Article B- Conformance		
Section 3 Requirements	Description	Verification Method					Verification Class		Section 4 Verification
		N/A	1	2	3	4	A	B	
3.1	First Article Test				X	X	X		4.2
3.2	Components and assemblies				X	X	X	X	4.3
3.2.1	Latch-rod assembly				X	X	X	X	4.3.2.1
3.2.2	Latch-rod assembly, painted				X	X	X	X	4.3.2.2
3.2.3	Panel, base				X	X	X	X	4.3.2.3
3.2.4	Base assembly				X	X	X	X	4.3.2.4
3.2.5	Base assembly, painted				X	X	X	X	4.3.2.5
3.2.6	Panel, cover				X	X	X	X	4.3.2.6
3.2.7	Cover, assembly				X	X	X	X	4.3.2.7
3.2.8	Cover assembly, painted				X	X	X	X	4.3.2.8
3.2.9	Liner, cover				X	X	X	X	4.3.2.9
3.2.10	Spacer				X	X	X	X	4.3.2.10
3.2.11	Latch-handle assembly				X	X	X	X	4.3.2.11
3.2.12	End cap, cover panel				X	X	X	X	4.3.2.12
3.2.13	End cap, base panel				X	X	X	X	4.3.2.13
3.2.14	Trunnion				X	X	X	X	4.3.2.14
3.2.15	Doubler, base				X	X	X	X	4.3.2.15
3.2.16	Forkwell				X	X	X	X	4.3.2.16
3.2.17	Pin, pivot				X	X	X	X	4.3.2.17
3.2.18	Packing and marking 155mm projectile pallet (Field Artillery Projectile Pallet assembly)				X	X	X	X	4.3.2.18
3.3	Stacking strength					X	X	X	4.4.1/4.4.1.1
3.4	Welding				X		X	X	4.4.1
3.5	Weld integrity				X	X	X	X	4.3.2.4
3.5.1	Visual inspection				X	X	X	X	4.3.2.4
3.5.2	Weld coupon bend test				X	X	X	X	4.4.2/4.4.2.1
3.6	Unit load tests				X	X	X		4.4.4

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

TABLE I. Requirement/Verification Cross Reference Matrix – Continued

Section 3 Requirements	Description	Verification Method					Verification Class		Section 4 Verification
		N/A	1	2	3	4	A	B	
3.7	Workmanship								
3.7.1	Pallets				X	X	X	X	4.3.2.3-4.3.2.4/ 4.3.2.6-4.3.2.7/ 4.3.2.18
3.7.2	Paint coating				X	X	X	X	4.3.2.2/4.3.2.5/ 4.3.2.8/4.3.2.18
3.7.3	Parts				X	X	X	X	4.3.2.1-4.3.2.18
3.7.4	Protective coating thickness				X	X	X	X	4.3.2.2/4.3.2.5/ 4.3.2.8/4.3.2.18
3.8	Salt spray test for painted base and cover assemblies				X	X	X		4.4.5
3.9	Salt spray test for latch-rod assembly				X	X	X		4.4.6
3.10	Latch handle pull test				X	X	X		4.4.7

4.1 Classification of verification. The verification requirements specified herein are classified as follows:

a. First article inspection (see 4.2).

b. Conformance inspection (see 4.3).

4.2 First article inspection.

4.2.1 First article quantity. First article verification shall be performed on the quantity of items as indicated in Table II.

4.2.2 Inspections to be performed. The first article verification shall be performed in accordance with Table II.

4.2.3 First article rejection. If any item fails to comply with requirements, the first article sample shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

TABLE II. First Article Inspection

EXAMINATION OR TEST	NUMBER OF SAMPLES	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Latch-rod assembly (Dwg. 12914630)			
Examination for defects	6	3.2.1	4.3.2.1
Latch-rod assembly, painted (Dwg. 12914630)			
Examination for defects	3	3.2.2	4.3.2.2
Salt spray test	3	3.9	4.4.6
Panel, Base (Dwg. 12914623)			
Examination for defects	6	3.2.3	4.3.2.3
Base assembly (Dwg. 12914620)			
Examination for defects	8	3.2.4	4.3.2.4
Base assembly, painted (Dwg. 12914620)			
Examination for defects	3	3.2.5	4.3.2.5
Salt spray test	3	3.8	4.4.5
Panel, cover (Dwg. 12914625)			
Examination for defects	3	3.2.6	4.3.2.6
Cover assembly (Dwg. 12914624)			
Examination for defects	6	3.2.7	4.3.2.7

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

TABLE II. First Article Inspection - Continued

EXAMINATION OR TEST	NUMBER OF SAMPLES	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Cover assembly, painted (Dwg. 12914624)			
Examination for defects	3	3.2.8	4.3.2.8
Salt spray test	3	3.8	4.4.5
Liner, cover (Dwg. 12926863)			
Examination for defects	6	3.2.9	4.3.2.9
Spacer (Dwg. 12914629)			
Examination for defects	6	3.2.10	4.3.2.10
Latch-handle assembly (Dwg. 12914628)			
Examination for defects	6	3.2.11	4.3.2.11
End cap, cover panel (Dwg. 12914626)			
Examination for defects	6	3.2.12	4.3.2.12
End cap, base panel (Dwg. 12914728)			
Examination for defects	6	3.2.13	4.3.2.13
Trunnion (Dwg. 12934729)			
Examination for defects	6	3.2.14	4.3.2.14

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

TABLE II. First Article Inspection - Continued

EXAMINATION OR TEST	NUMBER OF SAMPLES	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Doubler, base (Dwg. 12914621)			
Examination for defects	6	3.2.15	4.3.2.15
Forkwell (Dwg. 12914622)			
Examination for defects	6	3.2.16	4.3.2.16
Pin, pivot (Dwg. 12914627)			
Examination for defects	6	3.2.17	4.3.2.17
Packing and marking 155mm projectile pallet (Field Artillery Projectile Pallet assembly, painted) (Dwg. 12914619)			
Examination for defects	8 (See Note 1)	3.2.18	4.3.2.18
Stacking strength	8 (See Note 1)	3.3	4.4.1.1
Unit load tests	3 (See Note 1)	3.6	4.4.4
Latch handle pull test	8 (See Note 1)	3.10	4.4.7

Note 1. Samples used in their individual inspections such as painted latch rod assemblies, painted over assemblies, painted base assemblies, cover liners, spacers and latch handle assemblies may be used to make up some of the samples which will be needed for Field Artillery Projectile Pallet assembly inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

4.3 Conformance inspection.

4.3.1 Lot formation. Lot formation shall be in accordance with lot formation requirement of MIL-STD-1916 (Formation and identification of lots or batches).

4.3.2 Classification of characteristics.

a. Sampling requirements. Inspection sampling requirements for critical, major and minor characteristics are defined in MIL-STD-1916. Unless specified otherwise, inspection Level IV shall be used for all characteristics defined as Majors and inspection Level II for all Minor characteristics; Critical characteristics shall be addressed in accordance with MIL-STD-1916.

b. Conformance inspection. Conformance inspection shall be performed in accordance with paragraph 4.3.2.1 through 4.3.2.18. For all conformance inspections the same sample specimen may be used for all non-destructive examinations or tests.

c. Alternative Inspections. Alternative conformance inspections may be submitted and approved in accordance with MIL-STD-1916.

d. Tool control. Dimensions marked tool control should be gaged at the beginning of production and whenever tooling is replaced. Where destruction of components is necessary to inspect these dimensions, measurements of the tool may be substituted provided there is an established correlation between the tool dimensions and the component dimensions prior to the start of production. There should be adequate surveillance to assure that the drawing requirements are being met throughout the life of the tool.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.1	**TITLE** Latch-rod assembly	**SHEET** 1 **OF** 1	**DRAWING NUMBER** 12914630
			NEXT HIGHER ASSEMBLY 12914619

CLASSIFICATION	**EXAMINATION OR TEST**	**CONFORMANCE CRITERIA**	**REQUIREMENT PARAGRAPH**	**INSPECTION METHOD REFERENCE**
Critical	None defined			
Major				
101	Material certification for rod	See Note 1	3.2.1	Certification
102	Pitch diameter of thread on stud end	Level IV	3.2.1	AIE
103	Major diameter of thread on stud end	Level IV	3.2.1	AIE
104	Pitch diameter of thread on nut end	Level IV	3.2.1	AIE
105	Major diameter of thread on nut end	Level IV	3.2.1	AIE
106	Rod not threaded properly into stud	Level IV	3.2.1	Visual/Manual
107	Outside diameter of stud bottom	Level IV	3.2.1	AIE
108	Thickness of stud bottom	Level IV	3.2.1	AIE
109	Total length of rod (Dimension A)	Level IV	3.2.1	AIE
110	Outside diameter of upper part of nut	Level IV	3.2.1	AIE
111	Outside diameter of retainer	Level IV	3.2.1	AIE
112	Primer thickness	4.4.3	3.2.1	4.4.3.1
113	Weld missing or incomplete	Level IV	3.2.1	Visual
Minor				
201	Evidence of poor workmanship	Level II	3.7.3	Visual

Note 1: A certificate of material conformance shall be submitted by the contractor for each lot utilized. The submission of the documentation shall be specified in the contract. Non-conformance with 3.2.1 is grounds for rejection of the lot represented by the certification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.2	**TITLE** Latch-rod assembly, painted		**SHEET** 1 **OF** 1	**DRAWING NUMBER** 12914630
				NEXT HIGHER ASSEMBLY 12914619
CLASSIFICATION	**EXAMINATION OR TEST**	**CONFORMANCE CRITERIA**	**REQUIREMENT PARAGRAPH**	**INSPECTION METHOD REFERENCE**
Critical	None defined			
Major				
101	Paint thickness, min	Level IV	3.2.2	AIE
102	Part missing or incorrectly assembled	Level IV	3.2.2	Visual
Minor				
201	Evidence of poor workmanship	Level II	3.7.3	Visual
202	Protective finish missing incorrect or incorrectly applied	Level II	3.7.2	Visual/Measure
203	Protective coating thickness	Level II	3.7.4	Visual/Measure

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.3	**TITLE** Panel, base	**SHEET** 1 **OF** 1	**DRAWING NUMBER** 12914623
			NEXT HIGHER ASSEMBLY 12914620

CLASSIFICATION	**EXAMINATION OR TEST**	**CONFORMANCE CRITERIA**	**REQUIREMENT PARAGRAPH**	**INSPECTION METHOD REFERENCE**
Critical	None defined			
Major				
101	Material certification	See Note 1	3.2.3	Certification
102	Diameter (8 cups)	Level IV	3.2.3	AIE
103	Position of cups (8)	Level IV	3.2.3	AIE
104	Panel length	Level IV	3.2.3	AIE
105	Panel width	Level IV	3.2.3	AIE
106	Panel height	Level IV	3.2.3	AIE
107	Position of latch-rod assembly hole (2 places)	Level IV	3.2.3	AIE
108	Diameter of large latch-rod assembly hole (2 places)	Level IV	3.2.3	AIE
109	Diameter of small latch-rod assembly hole (2 places)	Level IV	3.2.3	AIE
Minor				
201	Evidence of poor workmanship	Level II	3.7.1/3.7.3	Visual

Note 1: A certificate of material conformance shall be submitted by the contractor for each lot utilized. The submission of the documentation shall be specified in the contract. Non-conformance with 3.2.1 is grounds for rejection of the lot represented by the certification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.4	**TITLE** Base assembly		**SHEET** 1 **OF** 1	**DRAWING NUMBER** 12914620
				NEXT HIGHER ASSEMBLY 12914619
CLASSIFICATION	**EXAMINATION OR TEST**	**CONFORMANCE CRITERIA**	**REQUIREMENT PARAGRAPH**	**INSPECTION METHOD REFERENCE**
Critical	None defined			
Major				
101	Alignment of double hole with base panel (2 places)	Level IV	3.2.4	AIE
102	Distance of forkwell centerline from base panel center (2 places)	Level IV	3.2.4	AIE
103	Mating surface of weld (16 places, see Note 1)	Level IV	3.5.1	Visual/AIE
104	Weld missing or incomplete	Level IV	3.2.4	Visual
105	Primer thickness	4.4.3	3.2.4	4.4.3.1
106	Weld coupon bend test	4.4.2	3.5.2	4.4.2.1
Minor				
201	Evidence of poor workmanship	Level II	3.7.1/3.7.3	Visual

Note 1: This inspection pertains to welds joining the forkwell to the bottom of the base panel.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.5	**TITLE** Base assembly, painted	**SHEET** 1 **OF** 1	**DRAWING NUMBER** 12914620
			NEXT HIGHER ASSEMBLY 12914619

CLASSIFICATION	**EXAMINATION OR TEST**	**CONFORMANCE CRITERIA**	**REQUIREMENT PARAGRAPH**	**INSPECTION METHOD REFERENCE**
Critical	None defined			
Major				
101	Top coat paint thickness, min	Level IV	3.2.5	AIE
Minor				
201	Evidence of poor workmanship	Level II	3.7.3	Visual
202	Protective finish missing incorrect or incorrectly applied	Level II	3.7.2	Visual/Measure
203	Protective coating thickness	Level II	3.7.4	Visual/Measure

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.6	**TITLE** Panel, cover	**SHEET** 1 **OF** 1	**DRAWING NUMBER** 12914625
			NEXT HIGHER ASSEMBLY 12914626

CLASSIFICATION	**EXAMINATION OR TEST**	**CONFORMANCE CRITERIA**	**REQUIREMENT PARAGRAPH**	**INSPECTION METHOD REFERENCE**
Critical	None defined			
Major				
101	Material certification	See Note 1	3.2.6	Certification
102	Position of holes (8)	Level IV	3.2.6	AIE
103	Panel length	Level IV	3.2.6	AIE
104	Panel width	Level IV	3.2.6	AIE
105	Panel height around edges	Level IV	3.2.6	AIE
106	Position of outside holes in side of trough (4 holes)	Level IV	3.2.6	AIE
107	Position of inner holes in side of trough (4 holes)	Level IV	3.2.6	AIE
108	Width of trough (entire length)	Level IV	3.2.6	AIE
109	Position of elongated holes (2)	Level IV	3.2.6	AIE
Minor				
201	Evidence of poor workmanship	Level II	3.7.1/3.7.3	Visual

Note 1: A certificate of material conformance shall be submitted by the contractor for each lot utilized. The submission of the documentation shall be specified in the contract. Non-conformance with 3.2.1 is grounds for rejection of the lot represented by the certification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.7	**TITLE** Cover assembly		**SHEET** 1 **OF** 1	**DRAWING NUMBER** 12914624
				NEXT HIGHER ASSEMBLY 12914619
CLASSIFICATION	**EXAMINATION OR TEST**	**CONFORMANCE CRITERIA**	**REQUIREMENT PARAGRAPH**	**INSPECTION METHOD REFERENCE**
Critical	None defined			
Major				
101	Weld missing or incomplete	Level IV	3.2.7	Visual
102	Part missing or incorrectly assembled	Level IV	3.2.7	Visual
103	Primer thickness	4.4.3	3.2.7	4.4.3.1
Minor				
201	Evidence of poor workmanship	Level II	3.7.1/3.7.3	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.8	**TITLE** Cover assembly, painted		**SHEET** 1 **OF** 1	**DRAWING NUMBER** 12914624
				NEXT HIGHER ASSEMBLY 12914619
CLASSIFICATION	**EXAMINATION OR TEST**	**CONFORMANCE CRITERIA**	**REQUIREMENT PARAGRAPH**	**INSPECTION METHOD REFERENCE**
Critical	None defined			
Major				
101	Top coat paint thickness, min	Level IV	3.2.8	AIE
Minor				
201	Evidence of poor workmanship	Level II	3.7.3	Visual
202	Protective finish missing incorrect or incorrectly applied	Level II	3.7.2	Visual/Measure
203	Protective coating thickness	Level II	3.7.4	Visual/Measure

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.9	**TITLE** Liner, cover		**SHEET** 1 **OF** 1	**DRAWING NUMBER** 12926863
				NEXT HIGHER ASSEMBLY 12914619
CLASSIFICATION	**EXAMINATION OR TEST**	**CONFORMANCE CRITERIA**	**REQUIREMENT PARAGRAPH**	**INSPECTION METHOD REFERENCE**
Critical	None defined			
Major				
101	Small outside diameter (slot diameter) (Section A-A)	Level IV	3.2.9	AIE
102	Middle outside diameter (Section A-A)	Level IV	3.2.9	AIE
Minor				
201	Evidence of poor workmanship	Level II	3.7.3	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.10	**TITLE** Spacer	**SHEET** 1 **OF** 1	**DRAWING NUMBER** 12914629
			NEXT HIGHER ASSEMBLY 12914619

CLASSIFICATION	**EXAMINATION OR TEST**	**CONFORMANCE CRITERIA**	**REQUIREMENT PARAGRAPH**	**INSPECTION METHOD REFERENCE**
Critical	None defined			
Major				
101	Material certification	See Note 1	3.2.10	Certification
102	Radius from center line to tab (3 places) (Section A-A)	Level IV	3.2.10	AIE
103	Location of tabs (3 places)	Level IV	3.2.10	AIE
104	Wall thickness of sides and bottom	Level IV	3.2.10	AIE
105	Outside diameter	Level IV	3.2.10	AIE
106	Inside diameter of cup (Dimension B)	Level IV	3.2.10	AIE
107	Distance from bottom surface of spacer to beginning of tab extension (3 places)	Level IV	3.2.10	AIE
108	Drain slots on bottom of spacer missing	Level IV	3.2.10	Visual
Minor				
201	Evidence of poor workmanship	Level II	3.7.3	Visual

Note 1: A certificate of material conformance shall be submitted by the contractor for each lot utilized. The submission of the documentation shall be specified in the contract. Non-conformance with 3.2.1 is grounds for rejection of the lot represented by the certification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.11	**TITLE** Latch-handle assembly	**SHEET** 1 **OF** 1	**DRAWING NUMBER** 12914628
			NEXT HIGHER ASSEMBLY 12914624

CLASSIFICATION	**EXAMINATION OR TEST**	**CONFORMANCE CRITERIA**	**REQUIREMENT PARAGRAPH**	**INSPECTION METHOD REFERENCE**
Critical	None defined			
Major				
101	Material certification	See Note 1	3.2.11	Certification
102	Location of detents from large hole (2 places)	Level IV	3.2.11	AIE
103	Width at open end of handle	Level IV	3.2.11	AIE
104	Diameter of small hole (2 places)	Level IV	3.2.11	AIE
105	Diameter of large hole (2 places)	Level IV	3.2.11	AIE
106	Height of embossment on large and small holes	Level IV	3.2.11	AIE
107	Distance from center line of small hole center line raised circular section	Level IV	3.2.11	AIE
108	Radius of circular section	Level IV	3.2.11	AIE
Minor				
201	Evidence of poor workmanship	Level II	3.7.3	Visual

Note 1: A certificate of material conformance shall be submitted by the contractor for each lot utilized. The submission of the documentation shall be specified in the contract. Non-conformance with 3.2.1 is grounds for rejection of the lot represented by the certification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.12	**TITLE** End cap, cover panel		**SHEET** 1 **OF** 1	**DRAWING NUMBER** 12914626
				NEXT HIGHER ASSEMBLY 12914624
CLASSIFICATION	**EXAMINATION OR TEST**	**CONFORMANCE CRITERIA**	**REQUIREMENT PARAGRAPH**	**INSPECTION METHOD REFERENCE**
Critical	None defined			
Major 101	Height	Level IV	3.2.12	AIE
Minor 201	Evidence of poor workmanship	Level II	3.7.3	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.13	**TITLE** End cap, base panel		**SHEET** 1 **OF** 1	**DRAWING NUMBER** 12934728
				NEXT HIGHER ASSEMBLY 12914620
CLASSIFICATION	**EXAMINATION OR TEST**	**CONFORMANCE CRITERIA**	**REQUIREMENT PARAGRAPH**	**INSPECTION METHOD REFERENCE**
Critical	None defined			
Major 101	Height	Level IV	3.2.13	AIE
Minor 201	Evidence of poor workmanship	Level II	3.7.3	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.14	**TITLE** Trunnion	**SHEET** 1 **OF** 1	**DRAWING NUMBER** 12934729
			NEXT HIGHER ASSEMBLY 12914628

CLASSIFICATION	**EXAMINATION OR TEST**	**CONFORMANCE CRITERIA**	**REQUIREMENT PARAGRAPH**	**INSPECTION METHOD REFERENCE**
Critical	None defined			
Major				
101	Material certification	See Note 1	3.2.14	Certification
102	Overall width at locking studs	Level IV	3.2.14	AIE
103	Inner radius at cup	Level IV	3.2.14	AIE
104	Outer radius at cup	Level IV	3.2.14	AIE
105	Diameter of locking studs (2 places)	Level IV	3.2.14	AIE
106	Length of stud (2 places)	Level IV	3.2.14	AIE
Minor				
201	Evidence of poor workmanship	Level II	3.7.3	Visual

Note 1: A certificate of material conformance shall be submitted by the contractor for each lot utilized. The submission of the documentation shall be specified in the contract. Non-conformance with 3.2.1 is grounds for rejection of the lot represented by the certification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.15	**TITLE** Doubler, base		**SHEET** 1 **OF** 1	**DRAWING NUMBER** 12914621
				NEXT HIGHER ASSEMBLY 12914620
CLASSIFICATION	**EXAMINATION OR TEST**	**CONFORMANCE CRITERIA**	**REQUIREMENT PARAGRAPH**	**INSPECTION METHOD REFERENCE**
Critical	None defined			
Major				
101	Diameter of hole	Level IV	3.2.15	AIE
102	Distance from end of slot to center line of hole	Level IV	3.2.15	AIE
103	Width of slot	Level IV	3.2.15	AIE
Minor				
201	Evidence of poor workmanship	Level II	3.7.3	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.16	**TITLE** Forkwell		**SHEET** 1 **OF** 1	**DRAWING NUMBER** 12914622
				NEXT HIGHER ASSEMBLY 12914620
CLASSIFICATION	**EXAMINATION OR TEST**	**CONFORMANCE CRITERIA**	**REQUIREMENT PARAGRAPH**	**INSPECTION METHOD REFERENCE**
Critical	None defined			
Major				
101	Overall height	Level IV	3.2.16	AIE
102	Width of formed box	Level IV	3.2.16	AIE
103	Weld missing or incomplete	Level IV	3.2.16	Visual
Minor				
201	Evidence of poor workmanship	Level II	3.7.3	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.17	**TITLE** Pin, pivot		**SHEET** 1 **OF** 1	**DRAWING NUMBER** 12914627
				NEXT HIGHER ASSEMBLY 12914624
CLASSIFICATION	**EXAMINATION OR TEST**	**CONFORMANCE CRITERIA**	**REQUIREMENT PARAGRAPH**	**INSPECTION METHOD REFERENCE**
Critical	None defined			
Major				
101	Small diameter	Level IV	3.2.17	AIE
102	Length of small section	Level IV	3.2.17	AIE
Minor				
201	Evidence of poor workmanship	Level II	3.7.3	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

Conformance inspection by classification of characteristics

PARAGRAPH 4.3.2.18	**TITLE** Packing and marking 155mm projectile pallet (Field Artillery Projectile Pallet assembly)	**SHEET** 1 **OF** 1	**DRAWING NUMBER** 12914619
			NEXT HIGHER ASSEMBLY -

CLASSIFICATION	**EXAMINATION OR TEST**	**CONFORMANCE CRITERIA**	**REQUIREMENT PARAGRAPH**	**INSPECTION METHOD REFERENCE**
Critical	None defined			
Major				
101	Latch handle, when in closed position, does not engage (in hole) completely	Level IV	3.2.18	Visual/Manual
102	Part missing or incorrectly assembled (see Note 1)	Level IV	3.2.18	Visual
103	Protective coating thickness, min. (see Dwg. 12552040)	See Note 2	3.2.18/3.7.4	AIE
104	Stacking strength	4.4.1	3.3	4.4.1.1
Minor				
201	Protective finish missing incorrect or incorrectly applied	Level II	3.7.2	Visual/Measure
202	Evidence of poor workmanship (other than protective coating)	Level II	3.7.1/3.7.3	Visual

Note 1: Inert projectiles shall be used during inspection of assembly.
Note 2: Three samples each shall be submitted for the cover assembly, the base assembly and the latch-rod assembly. Rejection of one sample is grounds for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

4.4 Testing.

4.4.1 Stacking strength sampling. The pallet, assembled with the prototype unit load, shall be stacked with the required stacking load for a period of one (1) hour minimum. After that time, the pallet shall not have any evidence of breaking, bending, buckling or failure of any of the welds. The pallets shall be selected in accordance with the appropriate random sampling plan as follows in Table III:

Table III. Sampling Matrix

Lot Size	Sample Size
1-200 pallets	2
201-500 pallets	5
501-1500 pallets	8
1501-or more pallets	12

4.4.1.1 Stacking strength. The samples shall be tested in accordance with 4.4.1. If any sample fails to meet the requirement, the lot shall be rejected. After three (3) consecutive lots have been found acceptable, every third lot shall be tested thereafter. If any of these lots are rejected, testing must be returned to three (3) consecutive lots. After three consecutive lots pass, return to testing every third lot.

4.4.2 Weld coupon bend test sampling. During the first half of the production shift and during the last half of the production shift and whenever the electrodes are changed or dressed and when any changes are made in the control of the machine, two weld coupons shall be prepared by the welder in accordance with AWS B4.0. If any test coupon fails to meet the requirements of 3.5.2, when tested in accordance with 4.4.2.1, the quantity of pallets welded during that shift and after the earlier weld coupon test (if applicable) shall be rejected.

4.4.2.1 Weld coupon bend test. A guided bend test, as specified in AWS B4.0, shall be performed on the coupons.

4.4.3 Primer thickness of base assembly, cover assembly and latch rod assembly sampling. (See Dwg. 12914620, 12914624 and 12914630, as applicable). Three test specimens (see TT-C-490), at the conclusion of each four (4) hours of primer application, shall be selected for this inspection. The primer thickness, of the specimens, shall be determined as specified in 4.4.3.1. If one or more specimen fails to meet the requirement, the four hour production shall be reworked and corrective action taken until production is acceptable again.

4.4.3.1 Primer thickness of base assembly, cover assembly and latch rod assembly. The primer thickness shall be measured by a suitable instrument.

4.4.4 Unit load test. (First article inspection only) Prototype unit loads for the pallets shall be fabricated in accordance with MIL-STD-1660 with the following exceptions. The gross weight of the ammunition load shall be 900 pounds minus 50 pounds, evenly distributed over the

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

eight (8) cups of the base assembly and shall obtain a height as specified in Dwg. 12914619 (± 2 inches) for the assembled pallet. The following tests, on the loaded pallets, shall be performed in the order specified. If any pallet fails to meet the requirements of 3.6, the first article sample shall be rejected.

4.4.4.1 Repetitive shock test. The test method specified in section 3 /schedule F of ASTM D 4169 shall apply.

4.4.4.2 Edgewise drop (rotational) test. The test method specified in ASTM D 6179 shall apply.

4.4.4.3 Incline impact test. The test method specified in ASTM D 880 procedure B shall apply.

4.4.4.4 Sling compatibility test. The test method and acceptance/rejection criteria specified in section 5 of MIL-STD-1660 shall apply.

4.4.5 Salt spray test for pallet. The painted pallet assembly shall be subjected to 5 percent salt spray for a minimum of 336 hours in accordance with ASTM B 117. Upon removal, wash the pallet gently in warm running water until free from any visible salt deposits and examine immediately in accordance with 3.8.

4.4.6 Salt spray test for latch-rod assembly. The painted latch-rod assembly shall be subjected to 5 percent salt spray for 96 hours in accordance with ASTM B 633.

4.4.7 Latch handle pull test (non-destructive test). While the latch handle engages in a locking position, hook force gage onto the latch handle and pull upward. Make sure the force gage is zeroed out prior to the test. Observe for minimum force required to release latch handle from its locking position.

5. PACKAGING

5.1 Preservation. None required.

5.2 Packing. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of materiel is to be performed by DOD personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point’s packaging activity within the Military Department of Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The Pallet is intended for use in utilizing 155MM projectiles. Latch rod assemblies of two different sizes can be used to accommodate projectiles of different sizes. The M107, M110, M449, M485, M804 projectiles can be utilized using one latch rod assembly (Type I pallet), while the M483A1, M549, M718/M741, M692/M731, M864, M795, M825 and the M898 can be utilized using the other latch rod assembly (Type II pallet).

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of this specification.
b. Type of pallet (see 1.2).
c. Quantity required and delivery schedules.
d. Certificates of conformance for each lot or shipment of product.
e. First Article Sample requirements.
f. Quality Conformance Inspection, if other than specified in section 4 of this specification.
g. Packaging requirements, if other than specified in section 5 of this specification.
h. Applicable stock number.
i. Serialization requirements, if applicable.
j. AIE (see 6.4)

6.3 Submission of alternative quality conformance provisions. Unless otherwise specified in the contract, proposed alternative quality conformance provisions will be submitted by the contractor for evaluation by the technical activity responsible for the preparation of this specification.

6.4 Submission of contractor acceptance inspection equipment (AIE) designs for approval. Submit copies of designs as required to: Commander, U.S. Army RDECOM-ARDEC, ATTN: AMSRD-AAR-QEM-A, Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract.

6.5 Approval of equivalent test methods. Prior approval of the Contracting Officer is required for use of equivalent test methods. A description of the proposed method should be submitted through the Contracting officer to: Commander, U.S. Army Armament Research, Development and Engineering Center, ATTN: AMSRD-AAR-QEM-A, Picatinny Arsenal, NJ 07806-5000. This description should include but not be limited to the accuracy and precision and drawings of any special equipment required.

6.7 Inspection lots. It is noted that the size of inspection lots of components, assemblies or items of delivery may differ from the actual quantities contractually scheduled for delivery. However, in order to facilitate scheduling of tests or deliveries, inspection lots of items of

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

delivery may be equivalent to such contract quantities provided all of the lot formation criteria per MIL-STD-1168 and sampling provisions of this specification are maintained.

6.8 Visual examination qualification. When compliance with the applicable requirement is in doubt as a result of visual examination the characteristic may be measured or gaged to determine acceptability.

6.9 Tool control. Where destruction of components is necessary to inspect these dimensions, measurements of the tool may be substituted provided that the contractor has established a correlation between the tool dimensions and the components dimensions prior to the start of production. The contractor should be responsible for maintaining adequate surveillance to assure the drawing requirements are being met throughout the life of the tools.

6.10 Shipping. The FAPP should be assembled in accordance with drawing 12926862, except the latch rod assembly should be attached but shipped with the FAPP to minimize cube and packed as a single unit in accordance with ASTM D 3951, unless otherwise specified in the contract or by the procuring contracting officer.

6.11 Definitions

a. Acceptance Inspection Equipment (AIE). Any measuring device that is traceable to the national or international standard which is used to assure conformance of material to the contract requirements.

b. Heat treatment. Heat treatment is understood to be any thermal process which brings about a modification in the mechanical and metallurgical properties of the metal involved.

6.12 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

6.13 Subject term (keyword) listing.

Ammunition
Metal
Unit load
Welding

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

APPENDIX A

FIELD ARTILLERY PROJECTILE PALLET REFURBISHMENT

A.1 SCOPE

A.1.1 Scope. This appendix provides the provisions for the refurbishment of the Field Artillery Projectile Pallet. This appendix is a mandatory part of the specification. The information contained herein is intended for compliance when refurbishing the pallets.

A.2 REQUIREMENTS

A.2.1 Welds. Welds shall be in accordance with good commercial practices.

A.2.2 Stackability. The pallet shall not be deformed to the extent that it affects safely stacking of pallet in storage.

A.2.3 Workmanship. See 3.7 unless otherwise specified below.

a. Deformation or damage that does not affect stacking, slinging, or assembly of the pallet is allowed.

b. Damage or deformation to the pallet legs that does not allow entry or prevents the pallet from resting evenly on a level surface is not allowed.

A.2.4 Packing and marking 155mm projectile pallet. The components and assemblies shall comply with all requirements specified on drawing 12914619.

A.3 VERIFICATION

A.3.1 Examination. Unless otherwise specified, the attributes sampling inspection shall be in accordance with 4.3.2.a for the examination and tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

APPENDIX A

Conformance inspection by classification of characteristics

PARAGRAPH A.3.1.1	**TITLE** Packing and marking 155mm projectile pallet (Field Artillery Projectile Pallet assembly)	**SHEET** 1 **OF** 1	**DRAWING NUMBER** 12914619
			NEXT HIGHER ASSEMBLY -

CLASSIFICATION	**EXAMINATION OR TEST**	**CONFORMANCE CRITERIA**	**REQUIREMENT PARAGRAPH**	**INSPECTION METHOD REFERENCE**
Critical	None defined			
Major				
101	Weld missing or broken	Level IV	A.2.1	Visual
102	Stacking surface deformed	Level IV	A.2.2	Visual
103	Protective finish damaged	Level IV	3.7.2	Visual/Measure
Minor				
201	Marking missing, incorrect or illegible	Level II	A.2.4	Visual
202	Evidence of poor workmanship	Level II	A.2.3	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.

A.4 NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

A.4.1 Refurbishment.

A.4.1.1 Cleaning. Loose paint, dirt, grease and rust should be removed (See 3.7.3).

A.4.1.2 Refinish. The parts should be finished in accordance with the applicable drawings.

Preparing Activity:
Army – AR

(Project 8140–2007-004)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:15Z
Check the source to verify that this is the current version before use.