INCH-POUND

MIL-M-50974C(AR)
AMENDMENT 2
8 September 1992
SUPERSEDING
AMENDMENT 1
14 October 1988

MILITARY SPECIFICATION

MOTOR-DETONATOR ASSEMBLY, ROCKET, LOADING, ASSEMBLING AND PACKING (FOR DEOMLITION KIT, CRATERING: M180)

This Amendment forms a part of MIL-M-50974C(AR), dated 19 March 1983, and is approved for use by the U.S. Army Armament, Munitions, and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

3.6.1: Delete "0.520" and replace with "0.760".

3.6.2: Delete "0.520" and replace with "0.760".

PAGE 13

* 4.4.2.3: Delete "Minor 206" in it entirety.

PAGE 15 & 16

* 4.4.2.5: Delete 4.4.2.5 in its entirety and substitute with new 4.4.2.5 included.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:46Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Flange, Rocket	1 OF 2	9244447
			NEXT HIGHER ASSEMBLY 9329588

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Salt spray test	(a)		3.2	4.5.1
102	Largest outside diameter		0.40%	3.2	Gage
103	Second Largest outside diameter		0.40%	3.2	Gage
104	True position of second largest outside diameter		0.40%	3.2	Gage
105	Third largest outside diameter		0.40%	3.2	Gage
106	Diameter of protector body flange counterbore		0.40%	3.2	Gage
107	Diameter of protector bodyhole		0.40%	3.2	Gage
108	Runout of protector bodyhole		0.40%	3.2	Gage
109	Total thickness		0.40%	3.2	Gage
110	Depth of body protector flange counterbore		0.40%	3.2	Gage
111	Angle of tapered surface		0.40%	3.2	Gage
112	Basic distance on tapered surface		0.40%	3.2	Gage
113	Distance from flange forward mating surface to top of insert		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:46Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.5	Flange, Rocket	2	2	9244447
				NEXT HIGHER ASSEMBLY: 9329588

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
114	Width of insert		0.40%	3.2	Gage
115	Diameter of screw holes, max (6)		0.40%	3.2	Gage
116	True position of screw holes (6)		0.40%	3.2	Gage
117	Width of slot		0.40%	3.2	Gage
118	Depth of slot		0.40%	3.2	Gage
119	True position of small hole		0.40%	3.2	Gage
120	Depth of screw counterbore		0.40%	3.2	Gage
Minor					
201	Protective finish missing or damaged (bare spot)		0.65%	3.2	Visual
202	Paint missing or damaged		0.65%	3.2	Visual
203	Poor workmanship		1.0%	3.9	Visual

NOTES:
4. Five(5) flanges shall be selected from each lot for this test. Lot formation provisions shall be as specified in the applicable finish specification. If one sample shows evidence or corrosion or salt deposits, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:46Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modification, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1375-A490)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:46Z
Check the source to verify that this is the current version before use.