MILITARY SPECIFICATION

INDICATORS, POSITION, CONTROL, SURFACES, 28 VOLT DC, GENERAL SPECIFICATION FOR

This amendment forms a part of Military Specification MIL-I-7062C dated 8 April 1975, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1, delete first sentence and substitute:

"2.1 Government documents

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation."

At bottom of page add:

"AMSC N/A

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: ASD/ENES, Wright-Patterson AFB OH 45433-6503 by using the self-addressed Standardization Document Improvement proposal (DD Form 1426) appearing at the end of this document or by letter.

PAGE 2

Under STANDARDS, Military: delete "MIL-STD-100" and substitute "DOD-STD-100".

Source paragraph, delete and substitute:

(Copies of specifications and standards required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)"

FSC 6610

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:53Z
Check the source to verify that this is the current version before use.

Add:

"2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in the specification, however, shall supersede applicable laws or regulations unless a specific exemption has been obtained.

3.2, delete and substitute:

"3.2 First article. When specified in the contract or purchase order, a sample shall be subject to first article inspection (see 4.4 and 6.6)."

PAGE 7

3.7: delete "MIL-STD-100" and substitute "DOD-STD-100".

PAGE 8

4.1, delete and substitute:

"4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of section 3 and 5. The inspection set forth in this specification shall become part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material."

4.2 delete and substitute:

"4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4)

b. Quality conformance inspection (see 4.5)."

Source: https://assist.dla.mil -- Downloaded: 20260-17T07:53Z
Check the source to verify that this is the current version before use.

PAGE 9

4.4, delete and substitute:

"4.4 First article inspection".

4.4.3, delete and substitute:

"4.4.3 First article inspection tests. The first article inspection tests shall consist of all the tests specified under 4.6.

PAGE 16

5, delete and substitute:

"5. PACKAGING"

PAGE 17

6.6, delete and substitute:

"6.6 First article. When a first article inspection is required, the items should be a first article sample as specified in 4.2. The first article should consist of 2 complete indicators. The contracting officer should include specific instructions in acquisition documents regarding arrangement for examinations, approval of first article test results and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract.

Custodians:
Army - AV
Navy - AS
Air Force - 11

Review activity:
Air Force - 71

User activity:
Army - ME

Preparing activity:
Air Force - 11

Project 6610- 0188

Source: https://assist.dla.mil -- Downloaded: 202610-17T07:53Z
Check the source to verify that this is the current version before use.