MILITARY SPECIFICATION

INDICATOR, POSITION, RUDDER TRIM TAB

This amendment forms a part of MIL-I-7063B, dated 20 April 1979, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Delete "2.1" and add:
"2.1 Government documents."

Add:
"2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation."

Add boxed paragraph to bottom center of page.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Oklahoma City Air Logistics Center/MMEDO, Tinker AFB OK 73145-5990 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

PAGE 2

Under STANDARDS, Military delete "MS 33680" and add: "MIL-STD-1651 Insert Arrangements For MIL-C-5015, MIL-C-22992 and MIL-C-83723 Electrical Connectors".

Add:
"2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment document which is current on the date of the solicitation.

ASTM-D-3951 Packaging, Comercial - 29 Jan 82.

(Application for copies should be addressed to: ASTM, 1916 Race St, Philadelphia PA 19103.)

(Nongovernment standards and other publications are normally available from the organization which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services."

AMSC N/A FSC 6610
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:53Z
Check the source to verify that this is the current version before use.

Add:
3.3.1 Recovery materials. Recovered materials shall be used to the maximum extent possible without jeopardizing the end use of the item.

PAGE 3

3.4.3 Line 3 delete "MS33680" and add: "MIL-STD-1651".

PAGE 6

Delete section 5 in its entirety and add:

"5. PACKAGING

5.1 Preservation-packaging. Preservation-packaging shall be level A, C, or Industrial as specified. (see 6.2)

5.1.1 Level A.

5.1.1.1 Cleaning. Indicators shall be cleaned in accordance with process C-1 of MIL-P-116.

5.1.1.2 Drying. Indicators shall be dried in accordance with process D-4 of MIL-P-116.

5.1.1.3 Preservation application. Not applicable.

5.1.1.4 Unit packaging. Unless otherwise specified by the contracting activity, each indicator shall be packaged in quantity unit packs of one each in accordance with Method 1C1 of MIL-P-116. Overbox completed pack in PPP-B-636 container. Apply sufficient cushioning material between bag and unit container of a type, density, and thickness to insure shock transmission does not exceed peak values in G's established for the gyroscope when completed packs are subjected to the rough handling drop tests of MIL-P-116.

5.1.2 Level C. Indicators shall be clean, dry, and individually packaged in a manner that will afford adequate protection against corrosion, deterioration, and physical damage during shipment from supply source to the first receiving activity.

5.1.3 Industrial. The industrial preservation of indicators shall be in accordance with ASTM-D-3951

5.2 Packing. Packing shall be level A, B, C, or Industrial as specified (see 6.2).

5.2.1 Level A. Indicators packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-601, Styles A or B, class overseas, unless otherwise specified by the contracting activity. Insofar as practical, exterior shippping container shall be of uniform shape, size, minimum tare and cube consistent with the protection required.

5.2.2 Level B. Indicators packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-636, class weather-resistant, unless otherwise specified by the contracting activity. Other requirements as specified in 5.2.1 apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:53Z
Check the source to verify that this is the current version before use.

5.2.3 Level C. Packing shall be applied which affords adequate protection during domestic shipment from the supply source to first receiving activity for immediate use. This level shall conform to applicable carrier rules and regulations.

5.2.4 Industrial. The packaged indicator shall be packed in accordance with ASTM-D-3951 .

5.3 Marking. In addition to any other markings required by the contract or order (see 6.2), interior and exterior containers shall be marked in accordance with MIL-STD-129.

PAGE 8

Paragraph 6.3 lines 12 and 13 delete "HQ AFLC CASO/LODS, Federal Center, Battle Creek MI 49016 and add: "OC-ALC/MMEDO, Tinker AFB OK 73145-5990.

Delete "6.4".

Delete "6.5".

Custodians:
Air Force - 99
Navy - AS
Army - AV

Preparing Activity:
Air Force - 71

Project Number:
6610 - 0112

Source: https://assist.dla.mil -- Downloaded: 202610-17T07:53Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T07:53Z
Check the source to verify that this is the current version before use.