MIL-I-7070B
Amendment 1
21 January 1972

MILITARY SPECIFICATION

INDICATOR, TEMPERATURE, ELECTRICAL RESISTANCE, HERMETICALLY SEALED, GENERAL SPECIFICATION FOR

This amendment forms a part of Military Specification MIL-I-7070B, 29 June 1970, and is mandatory for use by all Departments and Agencies of the Department of Defense.

Page 3, paragraph 3.4.2.2, last line: Delete "approximately 1 atmosphere" and substitute "12 to 14.7 psi".

Page 10, paragraph 4.6.3, last line: Delete "on-scale" and substitute "off-scale".

Page 12, paragraph 4.6.13, add: "When pointer oscillation and pointer variation are noted, the vibration frequency shall be 5 to 500 Hz at double amplitudes that produce a vibration level of 1.4 ±0.1g."

Page 12, add:

"4.6.13.3 Vibration failure. At the conclusion of the vibration test, the indicator shall be subjected to the scale error at room temperature test. The scale errors shall not exceed the tolerances specified in the detail specification. No looseness in the mechanism nor damage to any part of the indicator shall result from the vibration."

Page 15, add:

"6.5 Supersession data. This issue of MIL-I-7070 supersedes all previous issues of MIL-I-7070 for new design. Previous issues remain in effect to cover reprocurement of previously designed indicators."

Custodians:
Army - AV
Navy - AS
Air Force - 11

Review activities
Army -
Navy -
Air Force - 82

Preparing activity:
Air Force - 11

Project No. 6685-0427

FSC 6685

Source: https://assist.dla.mil -- Downloaded: 202610-17T07:55Z
Check the source to verify that this is the current version before use.