MIL-C-0050007C(MU)
3 July 1973
USED IN LIEU OF
MIL-C-50007B
21 August 1968

MILITARY SPECIFICATION

CHUTE, CONTAMINATED CLOTHING, M1

This limited coordination Military specification has been prepared by Edgewood Arsenal based upon currently available technical information, but it has not been approved for promulgation as a coordinated revision of Military Specification MIL-C-50007B. It is subject to modification. However, pending its promulgation as a coordinated Military specification, it may be used in procurement.

1. SCOPE

1.1 This specification covers one type of clothing chute for protective shelters.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

U-T-30	-	Talcum; Powder, Plain or Borated.
FF-N-105	-	Nails, Wire, Brads, and Staples.
FF-S-111	-	Screw, Wood.
QQ-S-781	-	Strapping, Steel, Flat and Seals.
UU-P-271	-	Paper, Wrapping, Waterproofed Kraft.
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner.
PPP-C-843	-	Cushioning Material, Cellulosic.
PPP-F-320	-	Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes.
PPP-T-60	-	Tape: Pressure-Sensitive Adhesive, Waterproof, for Packaging.

FSC 4240

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:13Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-731 - Quality of Wood Members for Containers and Pallets.

DRAWINGS

US ARMY MUNITIONS COMMAND

Edgewood Arsenal

E5-79-3 - Chute, Contaminated Clothing, M1.
D150-2-1 - Marking Diagram for Shipping Containers.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing E5-79-3 or on the subsidiary drawings shall conform to the specifications listed thereon or to specific characteristics set forth on the drawings.

3.1.2 Components. All components of the chute shall conform to the specifications and drawings listed on Drawing E5-79-3 and on subsidiary drawings.

3.2 Assembly. The chute shall be assembled as shown on Drawing E5-79-3.

3.3 Performance. The chute shall satisfy the following requirements when tested as specified in 4.2.4:

(a) The door shall be in positive contact with the gasket at least 90% of periphery when the discharge end of the chute is resting on a horizontal surface. Maximum gap permitted on 10% of the periphery is 0.020 inch.

Source: https://assist.dla.mil -- Downloaded: 20260-22T20:13Z
Check the source to verify that this is the currentversion before use.

(b) A force of 2.2 to 2.7 pounds when applied at the center of the door and 1/2 inch above the lip touching the front of the door.

3.4 Workmanship. The chute shall be free from contamination (foreign matter) and damage such as dents, cracks or deformation which would impair its use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Quality conformance inspection.

4.2.1 Lotting. A lot shall consist of the chutes produced by one manufacturer, at one plant, from the same materials, and under essentially the same manufacturing conditions.

4.2.2 Sampling for examination and nondestructive tests. Sampling shall be conducted in accordance with MIL-STD-105.

4.2.3 Inspection procedure for examination and nondestructive tests. Sample chutes and the level A preparation for delivery shall be examined and tested in accordance with the classification of defects and with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 20261O-22T20:13Z
Check the source to verify that this is the current version before use.

4.2.3.1 Classification of defects.

(a) Front (Dwg D5-79-5).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	0.249 diameter holes incorrect
102	Location of 0.249 diameter holes incorrect

(b) Body (Dwg E5-79-4).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Size of wire bead incorrect
102	Location of wire bead incorrect
103	Body height incorrect
104	Body width incorrect

(c) Chute, contaminated clothing, M1 (Dwg E5-79-3).

Categories	Defects	Acceptance standards
Critical:	None defined	
Major:	AQL 1.5 percent defective	
101	Performance	4.2.4
	AQL 1.0 percent defective	
102	Component missing or incorrectly assembled	
103	Welding incorrect or inadequate	
104	Protective finish missing, incorrect or inadequate	
105	Workmanship (3.4)	
Minor:	AQL 2.5 percent defective	
201	Transition piece incorrect	

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:13Z
Check the source to verify that this is the currentversion before use.

4.2.3.1 Classification of defects (continued).

(d) Preparation for delivery (section 5).

Categories		Defects
Critical:		None defined
Major:		AQL 4.0 percent defective
	101	Chute assembly not packaged as specified
	102	Class or style of shipping container incorrect
	103	Chute incorrectly packed in shipping container

4.2.4 Performance test. The painted and assembled chute shall be tested as follows:

(a) With the discharge end of the chute resting on a horizontal surface, push the lower edge of the door inward a few inches, allow it to return slowly to the closed position and examine for compliance with 3.3(a).

(b) With the chute oriented as in (a), apply a force with a Pelouze Tension Testing Scale - Model No. 5-T to the door at place located on the vertical centerline and 1/2 inch above the lip touching the front of the door. Observe and record the pressure necessary to open the door 1/4 inch at the bottom. The recorded pressure per door shall be the average of 10 readings.

5. PREPARATION FOR DELIVERY

5.1 Packaging, level A. The surface of the transition piece shall be sprinkled with talcum powder conforming to U-T-30. The transition piece shall be tucked within the body of the chute assembly. Cellulosic cushioning material conforming to type II, Class B of PPP-C-843 shall be placed between the mounting screws and the butyl cloth transition piece to prevent rupture of the cloth. The cushioned transition piece shall be held in place with 2 inch wide pressure sensitive tape conforming to Class 1 of PPP-T-60. The door on the chute shall be secured in a closed position with Class 1, minimum 2 inch wide, pressure sensitive tape conforming to PPP-T-60.

5.2 Packing. Packing shall be level A, B or C as specified (see 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:13Z
Check the source to verify that this is the current version before use.

5.2.1 Level A. A nailed wood frame shall be fabricated of nominal 2 x 6 inch material having outside dimensions in inches of 17-7/8 (+0 - 1/16) by 23 (+0 - 1/16) and placed over the door frame. The lumber used to fabricate the frame shall conform to the requirements of MIL-STD-731. The frame shall be fastened at each of the corners with two ninepenny cement coated or chemically etched cooler, sinker or standard box nails conforming to FF-N-105. The chute mounting flange shall be fastened to the wood base at each corner by 1-1/2 inch, No. 10 wood screws conforming to style 2S of FF-S-111. Chute and base shall be separated by paper conforming to Class E-1 of UU-P-271. The chute assembly, fastened to the wood frame and packaged as specified in 5.1, shall then be packed in a nailed wood box conforming to class 2, style 4, Grade A of PPP-B-621 having inside dimensions in inches of 29 by 18 by 26-3/4. Fiberboard pads conforming to type CF or SF, class domestic, variety SW, minimum grade 200 of PPP-F-320 shall be placed between the item and the top, bottom, sides and ends of the box to prevent movement of the item within the box. The box shall be closed and strapped in accordance with the appendix thereto. Strapping conforming to type I, Class B of QQ-S-781 shall be used.

5.2.2 Level B. The chute assembly shall be packed as specified in 5.2.1, except that the box shall conform to Class 1 style 4, Grade B of PPP-B-621. Strapping conforming to type I, Class A of QQ-S-781 shall be used.

5.2.3 Interplant shipment (see 6.2). The chute assembly shall be packaged as specified in 5.1 and packed to prevent damage in shipment from the supply source to the first receiving activity. Shipping containers shall be in compliance with the rules and regulations applicable to the mode of transportation.

5.3 Marking. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129. All markings on the shipping containers shall be clear, legible and permanent after the application of the wood preservative required on level A shipping containers, paragraph 5.2.1.

6. NOTES

6.1 Intended use. The chute is intended for conveying contaminated clothing from the undressing area of a protective shelter without loss of static pressure or re-introduction of contaminants.

6.2 Interplant shipment defined. Packing for supplies and materials that does not enter the military supply system. Typical are shipments from a vendor to a contractor, a subcontractor, or a supplier to a military arsenal or plant.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:13Z
Check the source to verify that this is the current version before use.

6.3 Ordering data. Procurement documents should specify the following:

(a) The title, number and date of this specification.
(b) The level of packing required.

Custodians:

Army - MU

Preparing activity:

Army - MU(EA)

Project No. 4240-A619

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:13Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:13Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 68 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 20261O-22T20:13Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

OFFICIAL BUSINESS

Commanding Officer
Edgewood Arsenal
ATTN: SMUEA-TS-S
Edgewood Arsenal, MD 21010

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:13Z
Check the source to verify that this is the current version before use.