INCH-POUND

MIL-C-48670 (AR)
AMENDMENT 3
23 February 1989
SUPERSEDING
AMENDMENT 2
18 November 1987

MILITARY SPECIFICATION

CHARGE ASSEMBLY FOR M207E5 OR M207E6 WARHEADS
INERT PARTS, FOR

This Amendment forms a part of Military Specification MIL-W-48670 (AR) dated 21 March 1986 and is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

In the specification wherever "M207E5" appears add "or M207E6."

PAGE 1

* 2.1.1, Specifications, Military: Add the following:

"MIL-C-48659 - Charge Assembly for M207E5 Warhead Loading, Assembling and Packing"

PAGE 2

* 2.2, Add: "ASTM E 348 Microhardness of Materials"

PAGE 3

* 3.5.1, Delete paragraph in its entirety and substitute the following:

"3.5.1 Process documentation. Concurrent with submission of the First Article Sample (see paragraph 4.3) the contractor shall submit a written description of the manufacturing process used for the body and liner. As a minimum, the process description shall include intermediate steps in press operations and specifics of the heat treatment process used together with the means by which the process can be verified in production. The method of verification shall be reviewed by and must be acceptable to the Government. The contractor's written plan of process and process controls shall be prepared in accordance

AMSC N/A FSC 1336

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

with Data Item Description DI-P-1604 (Tailored). Proposed changes to the process which produced the accepted First Article Sample shall be submitted to the government prior to actual implementation of the change. A new First Article Sample may be required for each proposed process change as determined by the Government."

PAGE 4

* 4.3.1, After first sentence, add the following:

"The first article sample shall be manufactured using the same materials, equipment, processes, and procedures as will be used in regular production. All parts and materials, including packing shall be the same as used in regular production and shall be obtained from the same source of supply. A First Article Sample of portion thereof, as directed by the procuring agency shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing processes, materials used, drawings, specifications or source of supply, such as to significantly affect product uniformity or quality as determined by the Contracting Officer (see 3.5.1)."

* 4.3.1, Liner quantity: Delete "20" and substitue "30."
Plate quantity: Delete "20" and substitute "10."
Pad, Compression quantity: Delete "20" and substitute "10."

* 4.3.2, Delete paragraph in its entirety and add the following:

* "4.3.2 Testing

* 4.3.2.1 Starting material. Sample material of the starting stock for the liner, shall be selected prior to fabrication and used for hardness, chemical composition and grain size tests.

* 4.3.2.2 Finished machine liners. Ten finished machine liners from a single annealed batch shall be used for testing for grain size and hardness.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

* 4.3.2.3 Static penetration. Twenty finished machined liners will be delivered to a designated government facility for loading and testing in accordance with 4.4.3.2. This test is for information only."

* 4.3.5 Delete paragraph in its entirety and substitute the following:

"4.3.5 Completion. Upon completion of the first article testing, sample disposition procedure shall be in accordance with 6.5."

PAGE 5

Delete Note 1 in its entirety and substitute the following:

"1. Upon completion of Examination of Defects select ten (10) of the twenty (20) liners for hardness of the finished liner. These same liners shall then be used for grain size of the finished liner."

* Table I

Liner: Examination of defects, delete "20" and substitute "30"

Liner: Add "Penetration (see note 2) 20 3.1 4.4.3.2"

Plate: Examination of defects, delete "20" and substitute "10"

Pad Compression: Examination of defects, delete "20" and substitute "10"

Add Note: "2. For informational purposes only."

PAGE 6

* 4.4.1, Delete the first sentence in its entirety and substitute the following:

"Inspection lots for the liner, body, plate, PIC, and compression pad shall be identified with a lot number in accordance with provisions of MIL-A-48078 and MIL-STD-1168. The contractor shall request the initial lot interfix number from the government procuring activity."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

PAGE 7 & 8

Delete 4.4.2.1 in its entirety and substitute included revised 4.4.2.1.

PAGE 9 & 9a

Delete 4.4.2.2 in its entirety and substitute included revised 4.4.2.2.

PAGE 10

Delete 4.4.2.3 in its entirety and substitute included revised 4.4.2.3.

PAGE 11

Delete 4.4.2.4 in its entirety and substitute included revised 4.4.2.4.

PAGE 12

Delete 4.4.2.5 in its entirety and substitute included revised 4.4.2.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER 9387148
4.4.2.1	Liner				NEXT HIGHER ASSEMBLY 9399673
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Outside diameter (O.D)		0.40%	3.2	Gage
102	Inside diameter		0.40%	3.2	Gage
103	Total runout of O.D. with datums A and B		0.40%	3.2	Gage
104	Depth of datum A from base		0.40%	3.2	Gage
105	Length of datum A to datum B		0.40%	3.2	Gage
106	Inside spherical radius		0.40%	3.2	Gage
107	Wall thickness at apex end (See note 7 on dwg.)		0.40%	3.2	Gage
108	Wall thickness between datum A and datum B		0.40%	3.2	Gage
109	Perpendicularity of base of liner with datums A and B		0.40%	3.2	Gage
110	Straightness between datum A and datum B (See note 5 on dwg.)		0.40%	3.2	Gage
111	Length from datum A to inside spherical radius		0.40%	3.2	Gage
112	Wall thickness variation between datum A and datum B (See note 4 on dwg.)		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 2 OF 2	DRAWING NUMBER 9387148
4.4.2.1	Liner (continued)		NEXT HIGHER ASSEMBLY 9399673

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
MAJOR					
113	Hardness of starting stock (See note 1)	Mat'l Sample		3.2	4.6.1
114	Chemical composition of starting stock (See note 1)	Mat'l Sample		3.2	4.6.2
115	Grain size of starting stock (See note 1)	Mat'l Sample		3.2	4.6.3
116	Hardness of finished liner (See note 11B on dwg.)	4.4.3	1.1	3.2	4.6.4
117	Grain size of finished liner (See note 11A on dwg.)	4.4.3	1.1	3.2	4.6.5
118	Evidence of discontinuity of machined surface (See note 10 on dwg.)		0.40%	3.2	Visual
MINOR					
201	63 Finish (See note 6 on dwg.)		0.65%	3.2	Gage
202	Workmanship		0.65%	3.6	Visual

NOTES:
1. Starting stock - See note 2 of drawing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.2	Body				9387149
					NEXT HIGHER ASSEMBLY 9399673
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Wall thickness		0.40%	3.2	Gage
102	Total length		0.40%	3.2	Gage
103	Large inside diameter (I.D.)		0.40%	3.2	Gage
104	Middle I.D.		0.40%	3.2	Gage
105	True position of middle I.D.		0.40%	3.2	Gage
106	Small I.D.		0.40%	3.2	Gage
107	Total runout of small I.D.		0.40%	3.2	Gage
108	Depth of middle I.D. to small I.D.		0.40%	3.2	Gage
109	Small outside diameter (O.D.)		0.40%	3.2	Gage
110	Runout small O.D.		0.40%	3.2	Gage
111	Large O.D.		0.40%	3.2	Gage
112	Runout large O.D.		0.40%	3.2	Gage
113	Parallelism of small face to datum B		0.40%	3.2	Gage
114	Perpendicularity of datum B to datum A		0.40%	3.2	Gage
115	Improper taper angle		0.40%	3.2	Gage
116	Incorrect depth of large inside diameter		0.40%	3.2	Gage
117	Improper length to rear basic diameter		0.40%	3.2	Gage

NOTES:

Source: http://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.2	Body				9387149
					NEXT HIGHER ASSEMBLY
					9399673
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
MINOR					
201	125 Finish (See note 3 on dwg.)		0.65%	3.2	Gage
202	Protective finish (see note 4 on dwg.)		0.65%	3.2	Visual
203	Workmanship		0.65%	3.6	Visual
204	Improper chamfer at front end		0.65%	3.2	Visual
205	Lot identification illegible		0.65%	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9387158
4.4.2.3	Plate				NEXT HIGHER ASSEMBLY 9399673
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Inside diameter		0.40%	3.2	Gage
102	True position of inside diameter		0.40%	3.2	Gage/Visual
103	Large outside diameter		0.40%	3.2	Gage
104	Depth, inside diameter		0.40%	3.2	Gage
MINOR					
201	Overall thickness		0.65%	3.2	Gage
202	Presence of chamfer		0.65%	3.2	Gage/Visual
203	Thickness of outside diameter		0.65%	3.2	Gage
204	125 Finish (See note 4 on dwg.)		0.65%	3.2	Gage
205	Protective finish (See note 5 on dwg.)		0.65%	3.2	Visual
206	Workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9399691
4.4.2.4	Body, PIC				NEXT HIGHER ASSEMBLY 9399689
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Large inside diameter		0.40%	3.2	Gage
102	Small inside diameter		0.40%	3.2	Gage
103	Length large inside diameter		0.40%	3.2	Gage
104	True position large inside diameter		0.40%	3.2	Gage
105	Outside diameter		0.40%	3.2	Gage
106	True position, outside diameter		0.40%	3.2	Gage
MINOR					
201	Overall length		0.65%	3.2	Gage
202	Protective finish (See note 4 on dwg.)		0.65%	3.2	Visual
203	Workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER 9387189
4.4.2.5	Pad, Compression		NEXT HIGHER ASSEMBLY 9399687

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Outside diameter		0.40%	3.2	Gage
102	Material (See note 2 on dwg.)				Certification
MINOR					
201	Inside diameter		0.65%	3.2	Gage
202	Thickness		0.65%	3.2	Gage
203	Workmanship		0.65%	3.6	Visual

NOTES:

Source: http://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

PAGE 13

4.4.3.1.1.b, Delete the paragraph in its entirety and substitute with the following:

"If five consecutive annealed batches meet the heat treatment requirements reduce the sampling to a minimum of one liner per week's production of annealed batches or one liner from the last annealed batch producing a total of no more than 5000 pieces whichever occurs first. Test results must be submitted to and accepted by the government."

4.4.3.2, Add the following:

"4.4.3.2 Static penetration test. Sampling shall be in accordance with the following:

1. Ten (10) tip charge assemblies will be loaded at a designated government facility in accordance with the assembly procedures specified in MIL-C-48659 using liners provided in para. 4.3.1.

2. Static penetration testing of these assemblies will be conducted at a designated government facility using the test methods and target materials as specified in MIL-C-48659.

3. If penetration results of the 10 samples meets the requirements of MIL-C-48659 the remaining liners will be held for future reference.

4. If any sample from step 4 fails the specified penetration requirement, the remaining 10 liners will be loaded and step 2 repeated.

5. All penetration results shall be submitted in accordance with DI-T-5247 (Tailored) (see 6.4)."

PAGE 14

4.6, Delete the paragraph in its entirety and substitute the following:

"4.6 Metallurgical and chemical tests. The following tests shall be performed using equipment and procedures prescribed by the cited ASTM."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

4.6.1, Include the following at the end of the first sentence: "in accordance with ASTM B 248."

4.6.2, Include the following at the end of the first sentence: "in accordance with ASTM B 248."

4.6.3, Include the following at the end of the first sentence: "in accordance with ASTM B 248."

4.6.4, Delete the second sentence and substitute the following:

"The hardness of the finished liner shall be determined in accordance with ASTM-E-384. Three 1000g Knoop microhardness measurements shall be taken at the following locations: 0.10 inch, 0.80 inch, and 1.5 inches from the base (See Figure 1)."

Lines 7 and 8: Delete "for the finished liners." and substitute "per sample liner."

PAGE 15

4.6.5, Delete the first and second sentence and substitute the following:

"Two quarter test sections, 90 degree apart, from 4.6.4 shall be utilized for taking grain size. Examination shall be made at the same three locations which were hardness tested (see Figure 1)."

6.3, At end of paragraph delete "Dover, New Jersey 07801-5001" and substitute "Picatinny Arsenal, N.J. 07806-5000."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

6.4, Delete and substitute as follows:

"6.4 Data requirements - Deliverable data required by the specification is cited in the following paragraphs:

Paragraph	Data Requirement	Applicable DID
3.3	Ammunition Data	DI-L-1410
3.5.1 & 3.5.2	Manufacturing Methods Report	DI-P-1604 (Tailored) (see note 1)
4.4.3.2, 4.6.1, 4.6.2, 4.6.3, 4.6.4, 4.6.5	Test Report	DI-T-5247 (Tailored)

The above data items shall be delivered to the following:

Commander
U.S. Army Armament Research, Development
and Engineering Center
ATTN: AMSMC-QAT-B (D)
Picatinny Arsenal, N.J. 07806-5000

Note 1: One copy shall also be sent to Commander, U.S. Army Armament Research, Development and Engineering Center, ATTN: SMCAR-CCH-A, Picatinny Arsenal, NJ 07806-5000."

PAGE 15a

* Add new figure included.


PAGE 17

* 6.5, Add new paragraph as follows:

"6.5 Submission of test hardware. Upon completion of First Article Testing, all samples shall be sent to Commander, ARDEC, ATTN: SMCAR-CCH-A, Picatinny Arsenal, NJ 07806-5000."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

SCHEMATIC OF SECTIONED LINER



□→ Designates the cross-section of each required section to be tested.

Figure 1

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1336-A582)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.