MIL-I-81577A (AS)
24 September 1974
SUPERSEDING
MIL-I-81577 (AS)
9 April 1968

MILITARY SPECIFICATION

IGNITION ELEMENT, ELECTRIC, MARK 17 MOD 0

This specification is approved by the Naval Air Systems Command, Department of the Navy.

1. SCOPE

1.1 This specification governs the manufacture, assembly and preparation for delivery of the Ignition Element, Electric, Mark 17 Mod 0. (See 6.1.)

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issues in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-P-116	Preservation, Methods of
MIL-I-23659	Initiators, Electric, Design and Evaluation of

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:43Z
Check the source to verify that this is the current version before use.

MIL-STD-129	Marking for Shipment and Storage
MIL-STD-414	Sampling Procedures and Tables for Inspection by Variables for Percent Defective

DRAWINGS AND ASSOCIATED LISTS

Naval Air Systems Command (Code Ident 30003)

LD 537927	Container, Inner, for Cartridges, Power Source
LD 537928	Container, Outer, for Cartridges, Power Source
LD 613468	Ignition Element, Electric, Mark 17 Mod 0
2302224	Ignition Element, Electric, Mark 17 Mod 0, Assembly
2519610	Primer Assembly

PUBLICATIONS

Naval Ordnance Systems Command (Code Ident 10001)

OP 5	Ammunition Ashore (This publication is not furnished to bidders and contractors by the procuring activity. Contractors should contact the Government Inspector for use of the publication.)
WR-43A	Preparation of Quality Assurance Provisions (Including Classification of Characteristics)

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 **Other publications.** The following document forms a part of this specification. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

Source: https://assist.dla.mil -- Downloaded: 202610-23T05:43Z
Check the source to verify that this is the current version before use.

Code of Federal Regulations

49 CFR 171-178	Hazardous Materials Regulations, Department of Transportation

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, D. C. 20402. Orders for the above publication should request the latest edition and supplements thereto.)

3. REQUIREMENTS

3.1 **Preproduction sample.** When specified by the procuring activity, a preproduction sample of 137 ignition elements shall be manufactured using the same methods and procedures proposed for the production lot. The sample shall be tested as specified in 4.3.2 and is for the purpose of determining that the contractor, prior to starting production, is capable of producing items which comply with the technical requirements of the contract.

3.2 **Conformance to documents.** The Ignition Element, Electric, Mark 17 Mod 0, covered by this specification shall be manufactured in accordance with the drawings listed on LD 613468.

3.3 **Materials.** All materials used in the manufacture of the ignition elements shall conform strictly with the specifications referred to on the respective drawings, unless specific approval in writing covering a departure therefrom has been obtained from the Navy cognizant field activity for cartridges prior to manufacture. When alternate materials or methods of manufacture are specified on the drawings, the bidder's selections shall be clearly stated in the proposal.

3.4 **Primary components.** For the purposes of this specification the ignition compositions, primer composition, and main propellant charge are defined as primary components. (See 4.3.3.)

3.5 **Cleanliness and condition of parts.** All parts shall be free of chips, dirt, grease, rust and all other foreign materials. There shall be no burrs nor other imperfections of manufacture which would harmfully affect either the assembly or the functioning of the product. The cleaning methods which are used shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agents which are used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:43Z
Check the source to verify that this is the current version before use.

3.6 **Explosive components, volatiles.** The ignition compositions and the primer composition shall have a maximum moisture content of 0.5 percent at the time of loading, as determined in accordance with 4.7.1. After consolidation of the primer composition, the subassembly shall be dried in accordance with Drawing 2302224.

3.7 **Insulation resistance.** The insulation resistance between shorted electrodes (connector pins) and receptacle of each completely assembled ignition element shall be a minimum of 20 megohms when tested in accordance with 4.7.3 at a relative humidity of 80 percent or less.

3.8 **Ignition and primer compositions, compounding and loading.** The ignition compositions and the primer composition shall be compounded in accordance with the applicable drawings, and shall be loaded in accordance with Drawings 2519610 and 2302224, respectively.

3.9 **Propellant charges.**

3.9.1 **Quantity.** All propellant charges shall be as specified on Drawing 2302224. Charges shall be determined by weight rather than by volume measurements.

3.9.2 **Smokeless powder, handling and loading.** Do not subject the smokeless powder to unnecessary handling or exposure to the atmosphere. The handling and loading of smokeless powder exposed to the atmosphere shall be performed only under conditions that do not permit the relative humidity to exceed 75 percent.

3.9.2.1 **Smokeless powder, condition.** The smokeless powder utilized shall exhibit no evidence of decomposition. (See 4.7.2.)

3.10 **Ignition element inspection.**

3.10.1 **Visual inspection.** Ignition elements shall be free of the following visible defects: chips, burrs, rough edges, incomplete threads, improper crimp, perforated closure disc, or any other imperfections which could harmfully affect either assembly or functioning. (See 4.7.6.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:43Z
Check the source to verify that this is the current version before use.

3.10.2 **Bridge circuit resistance.** The resistance of the bridge circuit in each completely assembled ignition element, when measured electrically as specified in 4.7.5. shall be not less than 1.0 ohm nor more than 1.2 ohms.

3.10.3 **Leakage.** Ignition element leakage rate shall not exceed 10^{-5} cc of air or gas per second, when tested in accordance with 4.7.7.

3.10.4 **X-ray.** Ignition elements shall be free of the following defects when examined by X-ray in accordance with 4.7.4: improper assembly of components. charges or inert components missing. or any other imperfections which could adversely affect performance.

3.11 **Tests.**

3.11.1 **Electric sensitivity.**

3.11.1.1 **No-fire.** The ignition element shall not fire when an electric current of $1.0 \begin{smallmatrix}+0.10\\-0.00\end{smallmatrix}$ ampere is applied in accordance with 4.7.8.1.

3.11.1.2 **All-fire.** The ignition element shall fire within 0.025 second when an electric current of $4.0 \begin{smallmatrix}+0.10\\-0.00\end{smallmatrix}$ amperes is applied in accordance with 4.7.8.2.

3.11.2 **Ballistic requirements.** Ignition elements from each production lot. selected in accordance with 4.7.9. shall meet the requirements listed below when subjected to the tests prescribed in 4.7.9.

3.11.2.1 **Chamber pressure.** The upper (U) and lower (L) limits of maximum chamber pressure, in pounds per square inch (psi), shall be 1800 psi and 1200 psi. respectively.

3.11.2.2 **Response time.** The time from application of firing current to start of pressure rise shall not exceed 0.025 second. The time from start of pressure rise to maximum pressure shall not exceed 0.015 second.

3.11.2.3 **Misfire.** There shall be no misfires. (See 4.7.9.2.3.)

Source: https://assist.dla.mil -- Downloaded: 202610-23T05:43Z
Check the source to verify that this is the current version before use.

3.12 Workmanship. Ignition elements shall be constructed and finished in a manner to assure compliance with all requirements of this specification. Particular attention should be directed to dimensions, finishes and coatings.

4. QUALITY ASSURANCE PROVISIONS

4.1 **Responsibility for inspection.** Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 **Sampling.** Unless otherwise specified, and when applicable, the sampling plans and procedures used in the determination of the acceptability of products submitted by a supplier shall be in accordance with the provisions of MIL-STD-414 or MIL-STD-105, whichever applies.

4.3 **Lots.**

4.3.1 **Inspection lots.** Inspection lot definition, formation, and size shall be in accordance with MIL-STD-414 or MIL-STD-105, whichever applies.

4.3.2 **Preproduction sample.** When specified by the procuring activity and before entering into quantity production, an acceptable preproduction sample of 137 ignition elements shall be prepared. Of these ignition elements, 127 shall be expended in the tests listed below and ten shall be retained for investigative purposes. A preproduction sample acceptable for environmental and functional testing shall be defined as a sample which has met the requirements of 3.4 through 3.10.4 of this specification. Preproduction sample acceptance shall consist of the following tests, which, except as otherwise specified herein, shall be conducted in accordance with MIL-I-23659: 40-foot drop (6) (nonfiring test); temperature and humidity cycling (THC) (36); vibration (12); high temperature (12); low temperature (12); untreated (12). The numbers in parentheses denote the allocation of ignition elements for the tests. After exposure to the specified environmental treatment, the units from THC and the vibration tests, together with the 12 untreated units, shall be conditioned for a minimum of 6 hours at 70° ± 5° F and fired in the test set as specified in 4.7.9.1. All of these units shall fire and produce results within the limits set forth in 3.11.2.1 and 3.11.2.2. The units allocated for the high temperature and low temperature tests shall be conditioned at 225° ± 5° F and -80° ± 5° F, respectively, for not less than 6

Source: https://assist.dla.mil -- Downloaded: 202610-23T05:43Z
Check the source to verify that this is the current version before use.

nor more than 24 hours and fired in the test set as specified in 4.7.9.1. All of these units shall fire and produce results within the limits set forth in 3.11.2.1 and 3.11.2.2 except that the upper and lower limits of maximum pressure for these units shall be 1900 psi and 1000 psi, respectively. In addition, 25 ignition elements shall be subjected to the no-fire and all-fire tests. None of these 25 units shall fire when temperature conditioned and tested in accordance with 4.7.8.1, and all of these same 25 units shall fire within 0.025 second when temperature conditioned and tested in accordance with 4.7.8.2. Additionally, 12 ignition elements shall be subjected to an electrostatic sensitivity test. Each of these 12 units shall withstand the stimulus from an electrically charged capacitor without firing when tested as specified in the applicable paragraph under the electrical tests of MIL-I-23659. All of the specified firings and tests shall be conducted within 3 minutes after removal of the units from the specified temperature conditioning. The failure of any ignition element to meet the requirements as stated above shall cause rejection of the preproduction sample.

4.3.3 **Production lot.** The suggested ignition element production lot size is 1301 minimum and 3200 maximum. Only primary components from a single lot or batch shall be used in a production lot of ignition elements; however, one primary component production lot may be used in more than one ignition element production lot.

4.4 **Gages.** The contractor shall provide gages as necessary to insure that the material to which this specification applies will meet the dimensional requirements shown on the applicable drawings.

4.5 **Classification of characteristics.** The characteristics verified by the tests and examinations herein are classified as critical, major or minor in accordance with WR-43A. Tests and examinations that verify critical characteristics are identified by the symbol (C) and major characteristics by the symbol (M). The number following the classification symbol indicates the serial number of test or examination. Tests and examinations which are not annotated with a classification code are classified minor.

4.6 **Quality conformance inspection.** Quality conformance inspection shall consist of verification of the characteristics classified on the drawings of LD 613468 and verification of the following requirements and tests:

Source: https://assist.dla.mil -- Downloaded: 202640-23T05:43Z
Check the source to verify that this is the current version before use.

Item	Nature of Requirement Verification	Applicable Paragraphs	Classification (WR-43A)
Primary Component	Single lot or batch	3.4, 4.3.3	(M101)
Ignition and Primer Compositions	Moisture content	3.6, 4.7.1	(M102)
Ignition and Primer Compositions (loaded)	Drying	3.6	(M103)
Ignition Element	Insulation resistance	3.7, 4.7.3	(M104)
Ignition and Primer Compositions	Compounding and loading	3.8	(M105)
Propellant Charge	Type and weight	3.9.1	(M106)
Smokeless Powder	Condition	3.9.2.1, 4.7.2	(M107)
Ignition Element	Visual inspection	3.10.1, 4.7.6	(M108)
Ignition Element	Bridge circuit resistance	3.10.2, 4.7.5	(C1)
Ignition Element	Leakage	3.10.3, 4.7.7	(C2)
Ignition Element	X-ray	3.10.4, 4.7.4	(C3)
Ignition Element	Electric sensitivity	3.11.1, 4.7.8	(C4)
Ignition Element	Ballistic requirements	3.11.2, 4.7.9	(M109)
Ignition Element	Packaging, packing and container markings	4.6.1	(M110)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:43Z
Check the source to verify that this is the current version before use.

4.6.1 **Packing, packaging, and marking.** Quality conformance inspection shall be conducted in accordance with the inspection criteria on the applicable drawings referenced in section 5.

4.7 **Tests.**

4.7.1 **Determining moisture content.** Transfer approximately 2 grams of the ignition composition to be used in loading to a tared weighing dish, weigh to the nearest 0.1 milligram, calculate the weight of the sample, transfer weighing dish and sample to a vacuum drying oven, dry at 160° ± 5° F and 28 ± 2 inches of mercury vacuum until constant weight is obtained. The loss of weight represents the percentage of moisture in the original sample. Use the same procedure for the primer composition.

4.7.2 **Smokeless powder, condition.** Smokeless powder shall be inspected in accordance with the applicable paragraphs of OP 5. Evidence of decomposition shall be cause for rejection.

4.7.3 **Insulation resistance.** The insulation resistance of each completely assembled ignition element shall be checked with an applied voltage of 350 ± 10 volts D.C. This measurement shall be made between shorted electrodes (connector pins) and receptacle. Units which fail to meet the requirements of 3.7 shall be rejected.

4.7.4 ***X-ray of ignition element.*** Examine all ignition elements by X-ray and reject those having any of the defects of 3.10.4. Ignition elements shall be mounted in suitable racks or frames and laid on their side so that the most revealing exposure can be obtained. Pressure-sensitive tape may be used as an aid in positioning the ignition elements.

4.7.5 **Bridge circuit resistance.** Conformance with the bridge circuit resistance of 3.10.2 shall be ascertained by means of a test circuit which limits the bridge current to 25 milliamperes, maximum. The test circuit shall be connected to the ignition element through a number PTO6E-8-2S Bendix connector, or equivalent. A new connector shall be used after a maximum of 500 connections. A safety chamber with an interlock switch shall be used to protect the operator during the application of current. A suitable bridge which is known to be accurate within 1 percent in the range of resistance specified shall be used to determine whether or not the requirement is being met. Units which fail to meet the requirements of 3.10.2 or fail to assemble completely, by hand, with the specified connector, with ignition element lugs locked in connector detents, shall be rejected. The results of bridge circuit resistance measurements shall not be affected by resistance of the test circuit or connector.

Source: https://assist.dla.mil -- Downloaded: 202640-23T05:43Z
Check the source to verify that this is the current version before use.

4.7.6 Visual inspection. Examine all ignition elements visually and reject those having any of the defects of 3.10.1.

4.7.7 Leakage. Each ignition element in the preproduction sample or production lot sample shall be leak tested in a dry gas or dry air leak tester. Ignition elements which exhibit a leak rate in excess of 10^{-5} cc/sec gas or air at a pressure differential of 1.0 ± 0.1 atmosphere shall be considered defective. Ignition elements of the preproduction sample which exhibit a leakage defect shall be rejected. If one or more ignition elements of the production lot sample exhibit a leakage defect, then a 100 percent leak test of the lot being tested shall be required at no additional expense to the government. Ignition elements which exhibit a leak rate in excess of that specified above shall be rejected.

4.7.8 Electric sensitivity tests.

4.7.8.1 No-fire test. The number of ignition elements selected from each production lot for the no-fire test shall be in accordance with the requirements of table I of MIL-STD-105. Inspection Level I. Each ignition element shall be conditioned at 70° ± 5° F for a minimum of 6 hours and then tested. During this test insure that the ignition element is sufficiently shielded to prevent personnel injury or material damage in the event an ignition element fires. The firing circuit shall contain a resistor in series sufficient to regulate the current to $1.0\ ^{+0.10}_{-0.00}$ ampere measured to within an accuracy of 1 percent. This current shall be applied to the ignition element for a period of not less than 5 nor more than 5.1 minutes. An ignition element which fires shall be considered defective and shall cause rejection of the lot represented. If the ignition elements pass this test they shall then be subjected to the test of 4.7.8.2.

4.7.8.2 All-fire test. The ignition elements shall be conditioned at 70° ± 5° F for a minimum of 6 hours and then tested. During this test insure that the ignition element is sufficiently shielded to prevent personnel injury or material damage. The firing circuit shall contain a resistor in series sufficient to regulate the current to $4\ ^{+0.10}_{-0.00}$ amperes measured to within an accuracy of 1 percent. Any ignition element which fails to fire within 0.025 second after current application shall be considered defective and shall cause rejection of the lot represented. As a precaution against obtaining an apparent defective element due to high internal circuit resistance, it is recommended that the resistance of each element be measured prior to conducting the test.

4.7.9 Ballistic tests.

4.7.9.1 The number of ignition elements selected from each production lot for the ballistic tests shall be in accordance with the requirements of table A-2 of MIL-STD-414.

Source: https://assist.dla.mil -- Downloaded: 202610-23T05:43Z
Check the source to verify that this is the current version before use.

Inspection Level IV and AQL of 0.10, but shall never be less than 15. The ignition elements shall be conditioned for a minimum of 6 hours at 70° ± 5°F and fired in a closed chamber having an internal volume, exclusive of ignition element volume, of 10 cubic centimeters and adapted for measurement of time from application of current to start of pressure rise and maximum pressure. The ratio of length to diameter of the closed chamber shall be approximately 1:1. The firing current shall be 5 ± 0.10 amperes. In addition to the sample of ignition elements for the above test, 10 additional ignition elements shall be furnished from the production lot for investigative purposes.

4.7.9.2 **Criteria of acceptability.**

4.7.9.2.1 **Chamber pressure.** The chamber pressure shall meet the requirements of 3.11.2.1. Lot acceptability shall be determined in accordance with the applicable provisions of MIL-STD-414 at an AQL of 0.10.

4.7.9.2.2 **Response time.** The failure of any ignition element to meet the response time requirements of 3.11.2.2 shall cause rejection of the lot represented.

4.7.9.2.3 **Misfire.** The failure of any ignition element to fire shall result in rejection of the lot represented, unless such failure is plainly attributable to faulty test equipment or procedure.

4.8 **Retest.** There shall be no retests.

4.9 **Test failure.** If test failure is attributable to an assignable cause, excluding the test ignition element, original test results should be discarded and that part of the test reconducted.

5. PREPARATION FOR DELIVERY

5.1 **Preservation and packaging.** For definitions of packaging levels, see 6.4.

5.1.1 **Level A.** Level A packaging shall be used for packaging of all production lots for service use. Four ignition elements shall be packaged in an inner container in accordance with the drawings listed on LD 537927.

Source: https://assist.dla.mil -- Downloaded: 202610-23T05:43Z
Check the source to verify that this is the current version before use.

5.1.2 **Level B.** Not applicable.

5.1.3 **Level C.** When directed by the procuring activity, those ignition elements which are intended for expenditure in preproduction sample testing and for production lot acceptance tests, or shipment to point of assembly into cartridges, shall be packaged in accordance with method III of MIL-P-116 and with the Code of Federal Regulations 49 CFR 171-178.

5.2 **Packing.** For definitions of packing levels, see 6.4.

5.2.1 **Level A.** Level A packing shall be used for packing of all production lots for service use. Twelve inner containers as described in 5.1.1 shall be packed in accordance with the drawings listed on LD 537928.

5.2.2 **Level B.** Not applicable.

5.2.3 **Level C.** When directed by the procuring activity, ignition elements intended for expenditure in preproduction sample testing and for production lot acceptance tests, or shipment to point of assembly into cartridges, and are packaged in accordance with 5.1.3 shall be packed to afford protection against damage during direct shipment from the supply source to the first receiving activity for immediate use. Shipping containers shall be in accordance with the Code of Federal Regulations 49 CFR 171-178.

5.3 **Markings.**

5.3.1 **Special markings.** Marking of exterior containers shall be in accordance with the Code of Federal Regulations 49 CFR 171-178.

5.3.2 **Normal markings.** Unless otherwise specified in the contract or order, the marking information on unit packages and shipping containers shall be in accordance with the drawings listed on LD 537927 and LD 537928, respectively. The specified marking information shall be applied to the containers in accordance with the applicable provisions of MIL-STD-129.

6. NOTES

6.1 **Intended use.** The Mark 17 Mod 0 ignition element is intended for use as (1) an igniter for power source cartridges, and (2) the power source for the operation of an aircraft store jettison mechanism.

Source: https://assist.dla.mil -- Downloaded: 202640-23T05:43Z
Check the source to verify that this is the currentversion before use.

6.2 **Ordering information.** Procurement documents should specify the following:

a. Title, number and date of this specification

b. Whether preproduction inspection is required and, if so, specify the test activity

c. Production lot size and test activity (see 4.3.3)

d. Items of data required for each preproduction and production lot (see 6.3)

e. Level of packaging and packing desired (see 5.1.3 and 5.2.3)

f. That the safety precaution requirements of the "Contractors' Safety Manual for Ammunition, Explosives, and Related Dangerous Material," DOD 4145.26M are applicable. NOTE: When this purchase description is used as part of the description of work to be accomplished by a Government activity, the safety precaution requirements of 'Ammunition Ashore," OP 5, are applicable.

6.3 **Data.** For the information of contractors and contracting officers, any of the data specified in (a) subparagraphs below, (b) applicable documents listed in section 2 of this specification or (c) referenced lower-tier documents need not be prepared for the Government and shall not be furnished to the Government unless specified in the contract or order.

6.3.1 **Test report.** The contract or order should specify that results of ballistic tests are to be forwarded to the Naval Ordnance Station, (5012), Indian Head, Maryland and the procuring activity.

6.3.2 **Data cards.** The contract or order should specify the format, quantity and destination of data cards.

6.4 **Definitions.** For purposes of this specification, the following definitions apply.

6.4.1 **Level A packaging.** The degree of preservation and packaging which will afford adequate protection against corrosion, deterioration and physical damage during handling, shipment, indeterminate storage and world-wide redistribution.

Source: https://assist.dla.mil -- Downloaded: 202640-23T05:43Z
Check the source to verify that this is the currentversion before use.

6.4.1.1 **Level C packaging.** The degree of preservation and packaging which will afford adequate protection against corrosion, deterioration and physical damage during shipment from supply source to the first receiving activity for immediate use. This level may conform to supplier's commercial practice when such meets the requirements of this level.

6.4.2 **Level A packing.** The degree of packing which will afford adequate protection during shipment, handling, indeterminate storage and world-wide redistribution.

6.4.2.1 **Level C packing.** The degree of packing which will afford protection against damage during direct domestic shipment from the supply source to the first receiving activity for immediate use. This level, in general, will conform to applicable carrier rules and regulations and may be the supplier's commercial practice when such meets the requirements of this level.

Preparing Activity:
NAVY-AS
(Project No. 1377-N590)

Source: https://assist.dla.mil -- Downloaded: 202640-23T05:43Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-I-81577A(AS) IGNITION ELEMENT, ELECTRIC MK 17 MOD 0

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

S/N 0102-014-1802

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:43Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
Naval Air Systems Command
Washington, D.C. 20361

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID

DOD 316

NAVAL AIR SYSTEMS COMMAND(AIR-52021)
DEPARTMENT OF THE NAVY
WASHINGTON, D.C. 20361

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:43Z
Check the source to verify that this is the current version before use.