MILITARY SPECIFICATION
EJECTOR, PARACHUTE, CARTRIDGE ACTUATED: XM7 ASSEMBLY

1. SCOPE

1.1 This specification covers Ejector, Parachute, Cartridge Actuated: XM7, Assembly, loaded with Cartridge, Impulse, XM267, for use in conjunction with Ballistically Deployed Troop Chest Reserve-Type Parachute.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein:

SPECIFICATIONS

Military

MIL-A-2550	- Ammunition and Special Weapons, General Specification for

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	- Quality Assurance Terms and Definitions

DRAWINGS

Munitions Command

F10551541	- Ejector, Parachute, Cartridge Actuated, XM7, Assembly
C9257363	- Carton, Packing, Ammunition, Fiber for Ejector, Parachute Cartridge Actuated, XM7
C9257364	- Box, Packing, Ammunition for Ejector, Parachute, Cartridge Actuated, XM7 in Fiber Container
IEL-10551541	- Inspection Equipment List for Ejector, Parachute, Cartridge Actuated, XM7, Assembly

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:36Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 General.-Material, parts and assemblies shall comply with all the requirements specified on the applicable drawings and specifications.

3.2 Torque.-Torque requirements shall be as specified in Table I. No movement or deformation shall occur upon application of the breakway torque.

Table I

Components	A Run on (Min. inch pounds)	B (including A) Seating or Bottoming Torque (inch pounds)	C Breakaway Torque (inch pounds)
Head and Inside Tube	40	300 + 15	200 + 20
T-Bar and Outside Tube	40	300 + 15	200 + 20

3.3 Functional Requirements.

3.3.1 The Ejector shall not fail to fire.

3.3.2 The Ejector shall function without mechanical failure (See 6.2).

3.3.3 No load.-The Ejector fired with no load on the T-bar shall complete its stroke of 15 7/16 inches minimum, and the tubes shall not separate (See 6.3).

The test fixture shall be such that the ejector head will not be restrained from moving out of the fixture.

3.3.4 Load.-The Ejector fired under load shall perform as follows: With the T-bar connected to a 10.75 pound weight, the Ejector shall propel the weight along a horizontal path of travel, and shall complete its

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:36Z
Check the source to verify that this is the current version before use.

3.3.4 (Cont'd)

stroke of 15 7/16 inches, minimum. The velocity of the mass upon reaching end of stroke shall be 57 feet per second (fps) minimum. The thrust shall not exceed 1700 lbs. maximum. The ejector shall not be restrained by the fixture.

3.3.5 Temperature.-The thruster shall comply with all the ballistic requirements throughout the temperature range of minus 65 degrees to plus 160 degrees Fahrenheit (F).

3.4 Workmanship.-The requirements for workmanship are as specified on the applicable drawings, referenced specifications and the following:

3.4.1 Metal defects.-All components shall be free from cracks, splits, cold shuts, inclusions, porosity or any similar defects.

3.4.2 Burr.-No part shall have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.4.3 Foreign matter.-No part or assembly shall contain chips, dirt, grease, rust, corrosion or other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the government. The government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions.-Reference shall be made to MIL-STD-109 to define quality assurance terms used.

4.1.2 Inspection.-Inspection shall be in accordance with MIL-A-2550, except as specified herein.

Source: https://assist.dla.mil -- Downloaded: 20260-22T20:36Z
Check the source to verify that this is the current version before use.

4.2 Inspection provisions.

4.2.1 Submission of product.-The product shall be submitted in accordance with MIL-STD-105.

4.2.2 Examination.-One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a defect basis in accordance with the classification of defects contained herein, using the sampling plan and associated criteria in Table II. The total number of allowable defects per class for either the major or minor classification shall not exceed the acceptance number of Table II. Four power (4X) magnification may be used in performing visual examination for such defects as burr and foreign matter.

Table II

Lot Size	Sample Size	Major		Minor	
		Accept	Reject	Accept	Reject
1 - 300	100% Examination				
301 - 800	50	0	1	1	2
801 - 1800	90	1	2	2	3
1801 - 10,000	200	2	3	3	4

4.2.2.1 Cartridge, Impulse, XM267, Dwg. D10551458, covering a detail of Dwg. F10551541.

Defect	Method of Inspection
CRITICAL	
1. Mixed cartridges	Visual
2. Metal defective	Visual
3. Marking missing, incorrect or illegible	Visual
MAJOR	
101. Foreign matter	Visual
MINOR	
201. Case scratched, wrinkled, bulged or dented	Visual
202. Varnish missing or inadequate	Visual

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:36Z
Check the source to verify that this is the current version before use.

4.2.2.2 Head, Sub-Assembly consisting of 10551449, 10551445, MS29513004, 10551450, and 10551448.

Defect	Method of Inspection
CRITICAL	
1. Any part missing	Visual
MAJOR	
101. Safety pin between cable strands	Visual
102. Striker hole obstructed	Visual
103. Foreign matter	Visual
MINOR	
None defined	

4.2.2.3 Assembly Dwg. F10551541.

CRITICAL	
1. Any part missing as detected by x-ray	X-ray
2. Improper assembly	X-ray
3. Metal defective	Visual
MAJOR	
101. Burr	Visual
102. Foreign matter	Visual
103. Marking missing, incorrect or illegible	Visual
MINOR	
201. Total length	Gage
202. Location of labels, incorrect	Visual
203. Tag missing or inadequate	
204. Protective finish inadequate or defective	Visual
205. Varnish missing or inadequate	Visual

4.2.2.4 Packing Container Dwg. C9257363.

CRITICAL	
None defined	

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:36Z
Check the source to verify that this is the currentversion before use.

4.2.2.4 (Cont'd)

Defect	Method of Inspection
MAJOR	
None defined	
MINOR	
201. Cap between body and cover, max.	Manual
202. Contents loose	Manual
203. Metal ends loose or distorted	Manual
204. Cut or damaged through all impregnated layers	Visual
205. Marking missing, incorrect or illegible	Visual
206. Tape incomplete or badly wrinkled	Visual
207. Length of tear tab, min.	Visual
208. Color of tape incorrect	Visual

4.2.2.5 Box, Packing, Dwg. 0925736A.

CRITICAL	
None defined	
MAJOR	
None defined	
MINOR	
201. Contents loose	Manual
202. Hardware missing, loose, broken or improperly engaged	Manual & Visual
203. Strapping missing, loose, broken or improperly assembled	Manual & Visual
204. Contents of box exposed	Visual
205. Box damaged	Visual
206. Marking misleading or unidentifiable	Visual
207. Number of units incorrect	Visual
208. Car seal missing, unsealed or improperly positioned	Visual

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:36Z
Check the source to verify that this is the current version before use.

4.2.3 Inspection testing.-The following tests shall be performed in accordance with 4.3.

4.2.3.1 Torque inspection.

4.2.3.1.1 Head and inside tube.-Each head and inside tube shall be subjected to a breakaway torque application. Failure of any sub-assembly to comply with the requirements of column "C", Table I in 3.2 shall be cause for rejection of the subassembly.

4.2.3.1.2 T-Bar and Outside Tube.-Each T-Bar and Outside Tube shall be subjected to a breakaway torque application. Failure of any assembly to comply with the requirements of column "C", Table I in 3.2 shall be cause for rejection of the assembly.

4.2.3.2 Head, Inside Tube, T-Bar and Outside Tube.-Each head and inside tube, T-bar and outside tube shall be subjected to a seating or bottoming torque application. Failure of any assembly to comply with the requirements of column B, Table I in 3.2 shall be cause for rejection of the assembly.

4.2.3.3 Functional tests.-The following tests shall be performed by the Government:

4.2.3.3.1 Ballistics.-Twenty-one units shall be tested to determine compliance with the requirements of 3.3.1 through 3.3.5. The units shall be temperature conditioned as provided in Table III and 4.3.3.1.1. Failure of any unit to comply with the requirements shall be cause for rejection of the lot.

Table III

Sample Size	Method	Temperature
6	Load (See 3.3.4)	-65° to -70°F
6	Load (See 3.3.4)	+65° to +75°F
6	Load (See 3.3.4)	+160° to +165°F
1	No Load (See 3.3.3)	-60° to -70°F
1	No Load (See 3.3.3)	+65° to +75°F
1	No Load (See 3.3.3)	+160° to +165°F

4.2.4 Inspection equipment.-The examination and tests shall be made using equipment listed on IEL-10551541.

4.3 Test methods and procedures.

4.3.1 Breakaway torque.-A torque wrench, capable of measuring the torque requirements specified in 3.2, shall be used with an appropriate adapter to determine the adequacy of the joints. The torque shall be applied to the head after application of proper bottoming torque.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

4.3.2 Bottoming torque.-A torque wrench set at the bottoming torque as specified in 3.2, Table I, Column B shall be used in conjunction with an adapter to determine the adequacy of the joint.

4.3.3 Functional.

4.3.3.1 Ballistics.-The test samples shall be supported so that the entire thrust is borne by the ejector inside tube. The samples shall be tested within 10 minutes after removal from the temperature conditioning chamber. When this time limit is exceeded, the sample units shall be reconditioned at the original temperature.

4.3.3.1.1 Temperature conditioning time.-The ejectors for ballistic tests shall be temperature conditioned for a minimum of 3 hours.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking.-Level A - Packing and marking shall be in accordance with Drawings C9257363 and C9257364.

6. NOTES

6.1 Ordering data.-Procurement document should specify the title, number, and date of this specification.

6.2 A "mechanical failure" is defined as any deformation or breakage of a part, the occurrence of which is other than a design function.

6.3 No load.-Permanent yielding of the inside tube shall not be cause for rejection when ejectors are tested with no load on the T-Bar.

6.4 Load.-The expected performance of the ejector under conditions simulating those existing in actual firing is obtained when the ejectors satisfactorily meets conditions of the "load" firing.

6.5 Explosive hazard classification of material.

6.5.1 Ejector, Parachute, Cartridge Actuated, XM7 Assembly.

"Explosive Hazard Classification - Class 1"
"Storage Compatibility Grouping - Group B, E, or N"
"Department of Transportation - (DOT) Hazard Class - Class C"
"DOT Marking: Explosive Power Device - Class C"
"Handle Carefully - Keep Fire Away"

Custodian:

Army - MU

Preparing activity:

Army - MU(FA)

Project No. 1377-A492

Source: https://assist.dla.mil -- Downloaded: 20261O-22T20:36Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

YES NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

5. SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
Department of the Army

OFFICIAL BUSINESS

Commanding Officer
Frankford Arsenal
ATTN: SMUFA-J4000
Philadelphia, Pa. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:36Z
Check the source to verify that this is the current version before use.