MIL-F-60342A (MU)
6 November 1972
SUPERSEDING
MIL-F-60342
25 May 1965

MILITARY SPECIFICATION

FUZE, POINT DETONATING, M525
LOADING, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification covers the loading, assembling and packing for one type of fuze designated as Fuze, Point Detonating, M525.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition and Special Weapons, General Specification for
MIL-D-1000 - Drawings, Engineering and Associated Lists
MIL-I-45607 - Inspection Equipment, Supply and Maintenance of
MIL-P-60312 - Parts, Molded, Plastic Foam, Polystyrene (for use with ammo)

STANDARDS

MILITARY

MIL-STD-100 - Engineering Drawing Practices
MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-331 - Fuze and Fuze Components, Environmental and Performance Tests for
MIL-STD-1167 - Ammunition Data Card
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes
MIL-HDBK-204 - Inspection Equipment Design

FSC: 1390

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:30Z
Check the source to verify that this is the current version before use.

DRAWINGS

ORDNANCE CORPS

8800197 - Fuze, PD, M525, Assembly
8835933 - Box, Packing, Ammunition for Fuze, PD, M525, M525A1, M525A2E1, M527, M527A1, M527B1, M527A2E1, M717 and XM719
8835934 - Container, Ammunition, Packing for Fuze, PD, M525, M525A1, M525A2E1, M527, M527A1, M527B1, M527A2E1, M717 and XM719

PUBLICATIONS

ORDNANCE CORPS

ET-8800197 - Index of Inspection Equipment Lists

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

3. REQUIREMENTS

3.1 Material. - Materials shall be in accordance with applicable drawings and specifications.

3.2 Fuzes. - The fuzes shall comply with all requirements specified on drawing (dwg.) 8800197 and with all requirements specified in applicable specifications.

3.3 Jolt and Jumble. - The loaded fuze assemblies shall have no explosive elements explode, shall have its slider assembly remain in the unarmed position (firing pin point seated in the slider relief hole), shall not cause the head assembly to arm, shall not come apart and shall have no parts broken, deformed or displaced in such a manner as to render the fuze unsafe to handle or dangerous to fire when subjected to the jolt test, Number 101, specified in Standard MIL-STD-331 and a jumble test, Number 102, of same specification. These tests shall be performed as specified in 4.3.2.

3.4 Proving Ground. - The fuzes shall comply with the following requirements when tested as specified in 4.3.3.

3.4.1 Premature Burst. - No fuze shall show evidence of premature burst (see 6.3).

3.4.2 Functioning. - No fuze shall fail to cause the projectile to function upon impact.

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:30Z
Check the source to verify that this is the currentversion before use.

3.4.3 Arming Safety. - The fuze shall not function on impact against a plywood screen when tested as specified in 4.3.3.2.

3.5 Specific Gravity of Booster Pellet. - The booster pellet (see dwg. 8798659) shall meet a specific gravity of 1.45 to 1.60 when tested as specified in 4.3.5.

3.6 Transportation Vibration. - The fuze assembly shall comply with the requirements of MIL-STD-331. The test shall be performed as specified in 4.3.6.

3.7 Polystyrene Container Component Water Loss Test (dwg. 8835934). - Polystyrene containers shall meet the requirements as specified in MIL-P-60312A.

3.8 Booster Lead Cup Assembly Density Test. - The tetryl pellet of the booster lead cup assembly shall meet a specific gravity of 1.46 to 1.63 when tested as specified in 4.3.7.

3.9 Workmanship. - All parts and assemblies shall be fabricated and loaded in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, rust and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection. - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define the terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 Submission of Product. - At the time each completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:30Z
Check the source to verify that this is the current version before use.

a. A statement that the lot complies with all of the quality assurance provisions specified in this specification.

b. Drawing and specification number and date, together with identification and date of changes thereto.

c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.

d. Number of items in the lot.

e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 Inspection Provisions

4.2.1 Lot Formation. - The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection has been produced by one manufacturer, in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to the process, specification or drawing not affecting safety, performance, interchangeability or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each lot shall contain:

a. Parts and assemblies of one lot interfix number from one manufacturer.

b. Detonator assemblies of one lot interfix number from one manufacturer.

c. Booster cup assemblies of one lot interfix number from one manufacturer.

Source: https://assist.dla.mil -- Downloaded: 20260-23T00:30Z
Check the source to verify that this is the current version before use.

d. Booster lead cup assemblies of one lot interfix number from one manufacturer.

e. Tetryl of one lot interfix number from one manufacturer.

4.2.2 Examination. - The examinations listed in the following subparagraphs shall be performed on inspection lots (see 4.2.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for Critical Defects (and Major Defects when so specified) shall be 100 percent. Sampling plans for Major and Minor Defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of Major and Minor defects listed, the contractor may elect to apply AQL's to individual defects using an AQL of 0.40 percent for each Major Defect and an AQL of 0.65 percent for each Minor Defect. When this method is elected, it shall be applied to all of the Major and Minor Defects listed in the applicable subparagraph of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.2.4.

4.2.2.1 Assembly, Prior to Cementing of Slider Plug or Booster Cup Assembly, or Staking of Head Assembly, or Depressing Firing Pin (see dwg. 8800197).

Categories	Defects	Method of Inspection	Code No. (see 6.5)
Critical:	None defined.		
Major:	AQL 1.00 percent		
101.	Detonator loose	Manual	01001
102.	Slider not free	Manual	01002
103.	Detonator inverted	Visual	01003
104.	Guide pin bent or broken	Visual	01004
105.	Firing pin damaged	Visual	01005
106.	Any component missing	Visual	01006
Minor:	AQL 1.50 percent		
201.	Booster charge cracked, broken	Visual	01007
202.	Booster lead cup charge cracked, broken or above flush	Visual	01008
203.	Evidence of poor workmanship (see 3.9)	Visual	01009

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:30Z
Check the source to verify that this is the current version before use.

4.2.2.2 Assembly, After Positioning Firing Pin in Slider but Prior to Cementing Slider Plug (see dwg. 8800197).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Slider spring missing	Visual	02001
Minor:	AQL 0.65 percent		
201.	Pettman cement missing from threads	Visual	02002

4.2.2.3 Assembly (see dwg. 8800197)

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Safety wire missing or loose	Visual-Manual	03001
2.	Safety pin missing	Visual	03002
Major:	AQL 0.65 percent		
101.	Total length, max.	Gage	03003
102.	Length from rearward face to shoulder, max.	Gage	03004
103.	Torque failure (head must withstand an assembly test torque of 30 - 5.0 in-lbs.	Test	03005
Minor:	AQL 2.50 percent		
201.	Any component loose	Manual	03006
202.	Cord missing or insecure	Visual-Manual	03007
203.	Threads damaged	Visual	03008
204.	Marking misleading or unidentifiable	Visual	03009
205.	Evidence of poor workmanship (see 3.9)	Visual	03010

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:30Z
Check the source to verify that this is the currentversion before use.

4.2.2.4 Polystyrene Container (see dwg. 8835934).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Sealing strip incomplete, loose or badly wrinkled	Visual	04001
102.	Container cut or damaged	Visual	04002
Minor:	AQL 1.00 percent, AQL 0.65 percent (applicable when 201 not applicable)		
201.	Marking missing, misleading or unidentifiable (overseas shipment only)	Visual	04003
202.	Contents loose	Manual	04004

4.2.2.5 Bag, Barrier, Sealed (when applicable) (see dwg. 8835934).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Waterproofness destroyed by rip, tear, puncture or separation of seal	Visual	05001
102.	Marking missing, misleading or unidentifiable	Visual	05002
Minor:	None defined.		

4.2.2.6 Box, Packing, Wood (see dwg. 8835933).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.0 percent		
101.	Box damaged exposing contents	Visual	06001
102.	DOD symbol missing or incorrect	Visual	06002

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:30Z
Check the source to verify that this is the current version before use.

103.	Strapping missing, loose or broken	Visual-Manual	06003
104.	Hardware missing, loose or broken	Visual-Manual	06004
105.	Board loose, broken or nail protruding	Visual-Manual	06005
Minor:	AQL 2.50 percent		
201.	Car seal missing, unsealed or improperly positioned	Visual	06006
202.	Marking missing, misleading or unidentifiable	Visual	06007
203.	Hardware improperly engaged	Visual-Manual	06008
204.	Strapping improperly assembled	Visual-Manual	06009
205.	Contents loose	Manual	06010

4.2.2.7 Box, Packing, Wirebound (Alternative) (see dwg. 8835933).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Box damaged exposing contents	Visual	07001
102.	Wire missing, broken or loose	Visual-Manual	07002
103.	Board broken or split	Visual	07003
104.	DOD symbol missing or incorrect	Visual	07004
Minor:	AQL 1.50 percent		
201.	Car seal missing, unsealed or improperly positioned	Visual	07005
202.	Marking missing, misleading or unidentifiable	Visual	07006
203.	Contents loose	Manual	07007

4.2.3 Testing

4.2.3.1 Jolt and Jumble (see 3.3) - Critical Defect - Code No. 03011. - The test shall be performed as specified in 4.3.2 using equipment in accordance with 4.2.4. Critical Defects shall include the following as a minimum:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:30Z
Check the source to verify that this is the current version before use.

a. The detonation of any of the explosive material.
b. The arming or partial arming of either the body assembly or the head assembly.
c. The failure of the safety wire to be engaging the setback pin in the body assembly.
d. The complete or partial ejection of the safety pin from the body assembly.
e. The failure of the slider to remain in the unarmed position.
f. Any evidence of dusting of explosive material.
g. The failure of the firing pin to be engaging the slider as evidenced by the retraction of the firing pin collar.
h. The failure of the upper pull wire to be engaging the setback detent.

4.2.3.1.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the acceptance criteria specified herein, 36 fuze assemblies shall be selected from each lot for these tests. If one or more fuze assembly fails to comply with the requirement specified, the lot shall be rejected.

4.2.3.1.2 After three consecutive lots have complied with the criteria of 4.2.3.1.1, twelve (12) fuze assemblies shall be selected for these tests. If any fuze assembly fails to comply with the requirements specified, the lot shall be reiected.

4.2.3.2 Proving Ground (see 3.4)

4.2.3.2.1 Premature Burst - Critical Defect - Code No. 03012, Failure to function - Major Defect - Code No. 03013.

4.2.3.2.1.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirement specified, 100 samples shall be selected for this test. If a premature burst occurs or if four or more assemblies fail to comply with the applicable functioning requirements, the lot shall be rejected. The test shall be performed as specified in 4.3.3.

4.2.3.2.1.2 After three consecutive lots have complied with the criteria of 4.2.3.2.1.1, a sample of fifty-four (54) fuz es shall be selected from each lot for this test. If three or more fuzes fail to comply with the applicable functioning requirement, or if a premature burst occurs, the lot shall be rejected. The test shall be performed as specified in 4.3.3.

4.2.3.2.2 Arming Safety - Critical Defect - Code No. 03014

4.2.3.2.2.1 Eighty (80) samples shall be selected from each lot for this test. If one sample fails to comply with the specified requirements, the lot shall be rejected. The test shall be performed as specified in 4.3.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:30Z
Check the source to verify that this is the current version before use.

4.2.3.3 Check Test for Deterioration of Detonators - Major Defect - Code No. 08001. - If the total time between original acceptance of any detonator lot and the assembly of that lot into fuzes exceeds two years, or if the detonators have been subjected to adverse conditions, however brief, at any time since previous tests, the detonator lot shall be subjected to and must satisfactorily pass the check test for deterioration specified in the applicable specification immediately before the detonator lot is assembled into the fuzes. This test shall be performed by the contractor on detonators selected by the Government inspector at the facility assembling the detonators into the fuzes (see 6.4).

4.2.3.4 Graphite Content - Major Defect - Code No. 08002; and Binding Lubricant Content - Major Defect - Code No. 08003. - The graphite content of tetryl shall be determined for each lot at the time of loading. A sample of 15 grams shall be selected and tested as specified in 4.3.4. If the graphite content of the booster lead cup charge is in excess of the percentage specified on dwg. 8798674 or the binding lubricant content of the booster pellet is in excess of the percentage specified on dwg. 8798659 and if loading has not begun, the lot of tetryl shall be rejected until proper corrective action has been accomplished as verified by repeating the graphite content test specified in 4.3.4. If loading has begun, action on the unloaded tetryl shall be as specified above and all components loaded with the questionable tetryl shall be rejected.

4.2.3.5 Specific Gravity of Booster Pellet (see 3.5) - Major Defect - Code No. 08004. - A sample of thirteen (13) booster pellets shall be selected from each lot for this test. If one or more pellets fails to meet the specified requirement, the lot shall be rejected. The test shall be performed as specified in 4.3.5.

4.2.3.6 Positioning (see dwg. 8800197) - Critical Defect - Code No. 03015. - This test shall be performed 100%. Assemblies failing to meet the applicable requirement shall be classed defective and removed from the lot. The test shall be performed as specified in 4.3.1.

4.2.3.7 Transportation Vibration (see 3.6) - Critical Defect for Safety Deficiency - Code No. 03016 - Major Defect for Operational Defect - Code No. 03017. - This test shall be performed as specified in 4.3.6. The Critical Defect criteria shall be as specified in 4.2.3.1.

4.2.3.7.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the specified requirements, thirty (30) fuze assemblies shall be selected from each lot for this test. If one or more assemblies fail to comply with the specified requirements, the lot shall be rejected.

4.2.3.7.2 After three consecutive lots have complied with the criteria of 4.2.3.8.1, ten (10) assemblies shall be selected from each lot for this

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:30Z
Check the source to verify that this is the current version before use.

test. If one or more assemblies fail to comply with the applicable requirements, the lot shall be rejected.

4.2.3.8 Booster Lead Cup Assembly Density Test (see 3.8) - Major Defect - Code No. 08005.

4.2.3.8.1 One Increment Consolidation Method

4.2.3.8.1.1 Beginning with the first lot produced and continuing until: (1) the requirements of 3.8 have been met, and (2) the requirement that the standard deviation of the density measurements, when multiplied by the factor 0.84, shall not exceed 0.033 has been met, the sample size shall be 80. If one or more samples does not comply with the applicable requirements, when tested as specified in 4.3.7, the lot shall be rejected.

4.2.3.8.1.2 After three lots have complied with the criteria of 4.2.3.8.1.1, the sample size shall be 32. If one or more samples fail to comply with the requirements of 3.8, or if the standard deviation, when multipled by the factor 0.76 exceeds 0.033, the lot shall be rejected.

4.2.3.8.2 Two or More Increment Consolidation Method

4.2.3.8.2.1 The sample size shall be 32. If one or more samples fail to comply with the requirements of 3.8, the lot shall be rejected.

4.2.4 Inspection Equipment. - Index of Inspection Equipment List Number ET-8800197 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions of Paragraph 6.2.

4.2.4.1 Government Rights to Documentation. - Inspection equipment drawings and lists provided and revised in accordance with the requirements of the ET may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.2.4.2 Government Use of Contractor's Inspection and Test Equipment. - The contractor shall make available to the Government all inspection and test equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment, and verification of its accuracy, shall be supplied by the contractor for the performance of examination or test by the Government.

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:30Z
Check the source to verify that this is the current version before use.

4.3 Test Methods and Procedures

4.3.1 Positioning of Firing Pin. - After mounting the assembly in a suitable test fixture, a power operated ram shall exert the specified load (50 + 5.0 lbs.) to the striker to seat the firing pin against the slider in the required position. The rate at which the load is applied shall not exceed 0.25 inch per second.

4.3.2 Jolt and Jumble. - The loaded fuze assemblies shall be subjected to jolt test in accordance with MIL-STD-331. After completion of the jolt test, the assemblies shall not be disassembled but shall be subjected to the jumble test in accordance with MIL-STD-331. The loaded fuze assemblies shall be jumble tested in a jumble fixture in accordance with 4.2.4. Disassembly and examination of the assemblies shall be accomplished after both jolt and jumble tests have been completed. Examination shall be made to determine compliance with 3.3.

4.3.3 Proving Ground

4.3.3.1 Premature Burst - Functioning. - The test shall be performed at a Government Proving Ground. The fuze assembly shall be assembled to a 60MM Cartridge, Smoke, WP, M302 or Cartridge, HE, M49A4, and fired from a 60MM Mortar for which the round is standard. The mortar tube shall be elevated 45 degrees (°) or greater for impact on firm ground. One half of the sample fuzes shall be assembled to cartridges assembled with an ignition cartridge (Charge Zone 0) and one half of the sample fuzes shall be assembled with an ignition cartridge and four propellant increments (Charge Zone 4).

4.3.3.2 Arming Safety. - The fuze assembly shall be assembled as specified in 4.3.3.1 (Charge Zone 0) and fired against a 1/4 inch plywood screen set at a distance of 150 + 5 ft. from the muzzle of the mortar.

4.3.3.3 Test Validity. - If for any reason the proving ground considers that the test conditions have detrimentally affected the test results, the test shall be declared invalid and a new test shall be performed with additional samples.

4.3.4 Determination of Graphite Content of Tetryl. - A sample of approximately five grams of the tetryl shall be transferred to a 250 ml. beaker. Add 100 ml. of acetone and heat to dissolve the tetryl. Filter the solution through a weighed, tarred filtering crucible and wash the residue in the crucible with two 25 ml. portions of acetone. Dry the crucible at 100°C for one hour, cool in a dessicator and weigh. For the tetryl used for the booster lead cup charge, calculate the increase in weight of the crucible as percentage of graphite; and, for the tetryl used for the booster pellet, calculate the increase in weight of the crucible as percentage of binding lubricant.

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:30Z
Check the source to verify that this is the current version before use.

4.3.5 Specific Gravity of Booster Pellet. - The booster pellet shall be weighed on a balance, and the weight recorded as dry weight. The pellet shall then be weighed while completely submerged in water. The temperature of the water shall be 68 degrees Fahrenheit (F) plus or minus 20 degrees F. This weight shall be recorded as weight under water. Specific gravity of the pellet shall be calculated as follows:

$$\text{Specific Gravity} = \frac{A}{A - B}$$

where:

A = Dry weight of pellet.
B = Weight of pellet under water.

4.3.6 Transportation Vibration. - The loaded fuze assemblies shall be tested in accordance with MIL-STD-331 for compliance with the requirements.

4.3.7 Booster Lead Cup Assembly Test. - The booster lead assembly shall be weighed on a balance and the weight recorded as dry weight. The assembly shall then be weighed while completely submerged in water and the weight recorded as weight under water. After both these operations have been completed, the tetryl shall be dissolved from the assembly using acetone. Then the booster lead cup shall be weighed on a balance and the weight recorded as dry weight. Then the booster lead cup shall be weighed while completely submerged in water and the weight recorded as weight under water. The temperature of the water shall be 68 degrees F plus or minus 5 degrees F. Specific gravity of the pellet shall be calculated as follows:

$$\text{Specific Gravity} = \frac{A - C}{(A-C) - (B-D)}$$

where:

A = Dry weight of assembly.
B = Weight under water of assembly.
C = Dry weight of cup only.
D = Weight under water of cup only.

The result shall be corrected to 4°C using appropriate tables.

5. PREPARATION FOR DELIVERY

5.1 Preservation and Packaging

5.1.1 Level C. - The fuzes shall be preserved and packaged in accordance with dwg. 8835933.

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:30Z
Check the source to verify that this is the currentversion before use.

5.1.2 Level A. - The fuzes shall be preserved and packaged in accordance with dwg. 8835933.

5.2 Packing

5.2.1 Level C. - The fuzes in polystyrene containers shall be packed in accordance with dwg. 8835934.

5.2.2 Level A. - The fuzes in polystyrene containers shall be packed in accordance with dwg. 8835934.

5.3 Marking. - Marking shall be as specified on dwgs. 8835933 and 8835934.

5.4 Data Cards. - Data cards shall be prepared for each lot in accordance with the information specified in MIL-A-2550.

6. NOTES

6.1 Ordering Data. - Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. Data cards. - Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

6.2 Inspection Equipment Designs. - Inspection equipment designs are of two types: Government Special Inspection Equipment (SIE) designs and contractor designs. SIE designs are designated by drawing numbers on the Equipment Lists referenced on the Equipment Tabulation. Design responsibility for all other inspection equipment is assigned to the contractor. Equipment to be designed by the contractor is designated "CD". The contractor need not furnish any design when a complete Government SIE design is provided. Unless otherwise specified, however, the contractor may submit alternate or modified contractor designs of SIE in accordance with 6.2.2 and 6.2.3 should he elect to do so.

6.2.1 SIE Designs. - SIE designs may consist of any of the following:

a. Detailed drawings which completely depict all information necessary for the fabrication and use of the item of inspection equipment.
b. A source control drawing or specification control drawing as defined in MIL-STD-100.
c. An envelope drawing, as defined in MIL-STD-100, which establishes the criteria which a detail design shall meet. When envelope drawings are specified, the contractor shall prepare designs which comply with the criteria therein.

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:30Z
Check the source to verify that this is the currentversion before use.

6.2.2 Contractor designs. - Contractor designs are required for all inspection equipment for which SIE designs are not specified and may include commercial equipment which the contractor proposes to use. (Commercial equipment is defined as unmodified equipment which is cataloged and available for purchase by the general public.) Contractor designs shall include appropriate operating instructions, calibration procedures and maintenanceprocedures. Commercial equipment shall be fully described by catalog listings or other means which provide sufficient information to permit identification and evaluation by the Government and may include illustrations and engineering data. Designs shall be prepared for any special fixture(s) required to be used with commercial equipment, or with SIE designs if not otherwise covered thereby (see 6.2.1.c). Designs shall be of the category and form (per MIL-D-1000) specified in the Contract Data Requirements List (DD Form 1423). The contractor is referred to MIL-HDBK-204 "Inspection Equipment Design" for guidance. The specification number and the applicable five-digit defect code number (or other specific identifying information) from Section 4 of this specification shall be referenced on each contractor design together with the component or assembly drawing number or revision letter to which the specific design applies.

6.2.3 Submission of Designs for Approval. - Contractor designs shall be approved by the Government prior to fabricating or procuring the equipment. Designs shall be submitted for approval in accordance with the stipulations, time frame and distributed as specified in the Contract Data Requirements List (DD Form 1423) or in the contract. Partial submission of inspection equipment designs is permissible and encouraged. However, the completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will normally be accomplished within one month after receipt.

6.3 Premature Burst. - Premature burst is defined as the functioning of the fuze in the weapon bore in flight before impact.

6.4 Check Test. - The Contracting Officer will arrange for the contractor to be reimbursed for the expense incurred in the performance of the detonator assembly check test. The test shall be conducted at Government expense without cost to the contractor who loaded the detonators or the contractor assembling the detonators into the fuzes, and shall not constitute a basis for rejection against either contractor except where deterioration has occurred as a direct result of carelessness in handling, storage, etc. permitted while the detonator lot was under their jurisdiction.

6.5 Inspection Code Numbers. - The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:30Z
Check the source to verify that this is the currentversion before use.

6.6 Proving Ground Testing Requirements

6.6.1 Acceptance Criteria. - Acceptance criteria will be in accordance with the following table:

TABLE I

Test	Initial Production		Regular Production	
	Sample Size	Reject With	Sample Size	Reject With
Functioning (upon impact on firm ground)*	100**	1 Premature 4 or more Non-Function	54**	1 Premature 3 or more Non-Function
Arming Safety (fired against 1/4 inch plywood screen at distance of 150 + 5 feet)*	80***	1 Functioning on Screen	80***	1 Functioning on Screen

* Test vehicle either 60MM Ctg, Smk, WP, M302 or Ctg, HE, M49A4 fired from a 60MM Mortar.

** One half of sample fuzes shall be assembled to cartridges assembled with Charge Zone 0 and one half shall be assembled to cartridges with four propellant increments (Charge Zone 4).

*** All of the sample fuzes shall be assembled to cartridges assembled with Charge Zone 0.

Custodian:
Army-MU

Preparing Activity:
Army-MU

Project Number: 1390-A-004

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:30Z
Check the source to verify that this is the current version before use.