MIL-M-48836(PA)
9 June 1975
SUPERSEDING
See Section 6

MILITARY SPECIFICATION
MOTOR, SERVO, for M5 BAROSWITCH

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of two-phase, six-pole, 26 volt, 400 Hertz (Hz) servo motor which is used in the Nike Hercules warhead section.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-E-5272	- Environmental Testing, Aeronautical and Associated Equipment, General Specification For.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-130	- Identification and Marking for U.S. Government Property.
MIL-STD-810	- Environmental Test Methods.
MIL-STD-1167	- Ammunition Data Card.
MIL-STD-1168	- Lot Numbering of Ammunition.
MIL-STD-1169	- Packaging, Packing and Marking of Inert Ammunition Components.
MIL-STD-1460	- Soldering of Electrical Connections and Printed Wiring Assemblies, Procedure For.

FSC 1190

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

DRAWINGS

ORDNANCE CORPS

8803809 - Motor, Servo.
EL-8871262 - Equipment List.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The servo motor shall comply with all requirements specified on drawing (dwg) 8803809, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 First article testing. Requirements for the submission of first article samples by the contractor shall be as specified in the contract (see 4.2).

3.4 Serialization. A six letter serial number shall be assigned to the item. Serial numbers required on these items shall be obtained by means of a letter addressed to: Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTENTION: SARPA-QA-T-M. The letter of request shall include:

a. Exact nomenclature of the item as specified on the applicable drawing.
b. Name of the contractor.
c. Contract number or procurement request order number.
d. Number of serial numbers required.

3.5 Insulation resistance. The insulation resistance shall be a minimum of 25 megohms with an applied potential of 500 ± 50 volts direct current (vdc) when tested as specified in 4.4.1.

3.6 Direction of rotation. The servo motor shall be capable of operating in a clockwise or counterclockwise direction when connected to a 26 ± 1 volt, 400 Hertz (Hz) power supply when tested as specified in 4.4.2.

3.7 No-load speed. The no-load speed shall be 5000 revolutions per minute (rpm) minimum at room temperature when operated at 26 ± 1 volts when tested as specified in 4.4.3.

3.8 Stalling torque. The stalling torque shall be 0.5 ounce-inch minimum in either direction when operated at 26 ± 1 volts when tested as specified in 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

3.9 Shaft end play. The shaft end play parallel to the longitudinal axis of the servo motor shall be 0.002 to 0.007 inch total indicator reading maximum when tested as specified in 4.4.5.

3.10 Radial play. The radial play perpendicular to the longitudinal axis of the servo motor shall be within 0.001 inch total indicator reading maximum when tested as specified in 4.4.6.

3.11 Operating life. The servo motor shall be capable of operating continuously for 55 hours without damage when tested as specified in 4.4.7.

3.12 Environmental testing (see 4.4.8). The servo motor shall comply with MIL-STD-810, visual inspection and failure criteria, section 3. The servo motor shall also comply with 3.5 through 3.8 before and after each environmental test. Testing shall be as specified in 4.4.8. Tests shall be conducted in the order specified.

3.12.1 Vibration. The servo motor shall show no evidence of damage such as cracking, splitting, etc., when vibrated in any direction through the frequency ranges, accelerations, and times when tested as specified in 4.4.8.1.

3.12.2 Acceleration. The servo motor shall show no evidence of damage after being subjected to 50 gravity (g) in any direction when tested as specified in 4.4.8.2.

3.12.3 Mechanical shock. The servo motor shall show no evidence of damage when subjected to impact shocks of 50 g in any direction when tested as specified in 4.4.8.3.

3.12.4 Pull test. The leads shall withstand a 6-pound pull when attached to the servo motor when tested as specified in 4.4.8.5.

3.12.5 Low temperature. There shall be no evidence of damage and the servo motor shall be capable of operating at a temperature of -65 $\pm$ 5° Fahrenheit (F) when tested as specified in 4.4.8.5.

3.12.6 High temperature. There shall be no evidence of damage and the servo motor shall be capable of operating at a temperature of +300 $\pm$ 5°F when tested as specified in 4.4.8.6.

3.12.7 Pressure, The servo motor shall be capable of operation at pressures ranging from 8 to 800 millimeters (mm) mercury (Hg) absolute when tested as specified in 4.4.8.7.

3.12.8 Fungus. The servo motor shall show no evidence of fungus growth when subjected to the fungus test of MIL-E-5272, when tested as specified in 4.4.8.8.

3.13 Marking. The servo motors shall be marked in accordance with MIL-STD-130, 1.2.1 and 3.2.1 with the manufacturer's name or symbol, type designation, and terminal identification.

3.14 Soldering. Soldering shall be in accordance with MIL-STD-1460.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

3.15 Workmanship.

3.15.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.15.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.15.3 Burrs. Parts shall be free from burrs.

3.15.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.15.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

3.15.6 Electrical. Cable assemblies and wires shall be dressed in such a manner as to prevent pinching or chafing of the wire insulation. Ends of wires shall be free from burrs, sharp edges, or points. All parts shall be free from flux, chips, dirt, grease, rust or foreign material.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.

4.2.1 Quantity to be submitted. When the contract requires first article inspection, the contractor shall submit 3 complete assemblies (see dwg 8803809) for first article testing to the testing facility designated in the invitation for bids or request for proposal.

4.2.2 Inspection and testing to be performed. The first article inspection sample shall be subjected to the inspections and tests specified in Table I. Tests shall be conducted in order specified in Table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Table I
First article inspection and tests

Inspection or Test	Dest	Non Dest
1. Classification of characteristics (see 4.3.2.1)		X
2. Insulation resistance (see 3.5)		X
3. Direction of rotation (see 3.6)		X
4. No-load speed (see 3.7)		X
5. Stalling torque (see 3.8)		X
6. Shaft end play (see 3.9)		X
7. Radial play (see 3.10)		X
8. Operating life (see 3.11)	X	
9. Vibration (see 3.12.1)	X	
10. Acceleration (see 3.12.2)		X
11. Mechanical shock (see 3.12.3)		X
12. Pull test (see 3.12.4)	X	
13. Low temperature (see 3.12.5)		X
14. High temperature (see 3.12.6)		X
15. Pressure (see 3.12.7)		X
16. Fungus (see 3.12.8)		X

4.2.3 Inspection equipment. The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.1.

4.2.4 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Quality conformance inspection.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

4.3.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table II and Table III), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-72	all	140-141	124	256-259	177	541-549	230
73	72	142	125	260-262	178	550-559	231
74	73	143-144	126	263-265	179	560-569	232
75	74	145	127	266-268	180	570-579	233
76	75	146-147	128	269-271	181	580-590	234
77	76	148-149	129	272-275	182	591-601	235
78	77	150	130	276-278	183	602-613	236
79	78	151-152	131	279-282	184	614-625	237
80	79	153-154	132	283-285	185	626-637	238
81-82	80	155-156	133	286-289	186	638-649	239
83	81	157	134	290-293	187	650-662	240
84	82	158-159	135	294-296	188	663-676	241
85	83	160-161	136	297-300	189	677-690	242
86	84	162-163	137	301-304	190	691-704	243
87	85	164-165	138	305-308	191	705-719	244
88-89	86	166-167	139	309-312	192	720-735	245
90	87	168	140	313-316	193	736-751	246
91	88	169-170	141	317-320	194	752-768	247
92	89	171-172	142	321-324	195	769-785	248
93	90	173-174	143	325-329	196	786-804	249
94-95	91	175-176	144	330-333	197	805-823	250
96	92	177-178	145	334-338	198	824-842	251
97	93	179-180	146	339-342	199	843-863	252
98	94	181-182	147	343-347	200	864-884	253
99-100	95	183-184	148	348-352	201	885-907	254
101	96	185-187	149	353-356	202	908-930	255
102	97	188-189	150	357-361	203	931-955	256
103	98	190-191	151	362-366	204	956-981	257
104-105	99	192-193	152	367-372	205	982-1008	258
106	100	194-195	153	373-377	206	1009-1036	259
107	101	196-197	154	378-382	207	1037-1066	260
108-109	102	198-200	155	383-388	208	1067-1098	261
110	103	201-202	156	389-393	209	1099-1131	262
111	104	203-204	157	394-399	210	1132-1166	263
112-113	105	205-207	158	400-405	211	1167-1204	264
114	106	208-209	159	406-411	212	1205-1243	265
115	107	210-212	160	412-417	213	1244-1285	266
116-117	108	213-214	161	418-424	214	1286-1330	267
118	109	215-217	162	425-430	215	1331-1378	268
119	110	218-219	163	431-437	216	1379-1429	269
120-121	111	220-222	164	438-443	217	1430-1483	270
122	112	223-224	165	444-450	218	1484-1542	271
123-124	113	225-227	166	451-457	219	1543-1605	272
125	114	228-230	167	458-465	220	1606-1673	273
126-127	115	231-232	168	466-472	221	1674-1747	274
128	116	233-235	169	473-480	222	1748-1827	275
129-130	117	236-238	170	481-488	223	1828-1914	276
131	118	239-241	171	489-496	224	1915-2010	277
132-133	119	242-243	172	497-504	225	2011-2115	278
134	120	244-246	173	505-513	226	2116-2232	279
135-136	121	247-249	174	514-521	227	2233-2361	280
137	122	250-252	175	522-530	228	over 2361	298
138-139	123	253-255	176	531-540	229		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Table III
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Servo motor (see dwg 8803809).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Shaft diameter incorrect	Gage
	102. Length of lead, min	Gage
	103. Total indicator reading,max	Gage
	104. Marking misleading or unidentifiable	Visual
	105. Damaged lead such as a break, split, etc	Visual
	106. Retaining ring loose or missing	Visual/Manual
	107. Shaft not free to turn	Visual/Manual
	108. Lead loose or missing	Visual/Manual
	109. Objective evidence relative to material missing or improper (see 3.1)	Visual
	110. Serialization improper or missing (see 3.4)	Visual
Minor:		
	201. Lead not stripped and tinned	Visual
	202. Finish damaged to the extent of exposing base metal	Visual
	203. Evidence of a burr or a sharp edge	Visual
	204. Paint on machined surfaces	Visual
	205. Evidence of poor workmanship (see 3.15)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

4.3.2.1.2 Preparation for delivery (see 5).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Preservation and packaging in accordance with MIL-STD-1169 (see 5.1)	Visual
102.	Packing in accordance with MIL-STD-1169 (see 5.2)	Visual
103.	Marking in accordance with MIL-STD-1169 (see 5.3)	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.15)	Visual

4.3.3 Testing. All tests shall be performed. Tests shall be performed in the order specified below:

	Test	Test Classification
a.	Insulation resistance	Major
b.	Direction of rotation	Major
c.	No-load speed	Major
d.	Stalling speed	Major
e.	Shaft end play	Major
f.	Radial play	Major
g.	Low temperature	Major
h.	High temperature	Major
i.	Operating life	Major
j.	Vibration	Major
k.	Pull test	Major

Of these tests, i, j and k are considered destructive and samples so tested shall not be returned to the lot. Destructive samples are over and above the deliverable quantity of items required by the contract.

4.3.3.1 Insulation resistance, direction of rotation, no-load speed, stalling torque, shaft end play, and radial play. Each servo motor shall be tested in accordance with 4.4.1 through 4.4.6. If any item fails to comply with 3.5 through 3.10, the item shall be rejected and removed from the lot.

4.3.3.2 Operating life, vibration, pull test, low temperature and high temperature. A sample shall be selected at random in accordance with Table IV. The sample shall be tested in accordance with 4.4.7, 4.4.8.1, 4.4.8.4 through 4.4.8.6. If any item fails to comply with 3.11, 3.12.1, 3.12.4 through 3.12.6, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Table IV

Sample sizes for destructive testing

Number Required to be Delivered	Sample Size for No Failures
1-10	15
11-18	16
19-25	17
26-37	18
38-57	19
58-105	20
106-249	21
250 and over	22

Lot Size Required = Number Required to be Delivered + Sample Size.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL) (see EL-8871262). When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.4.1 Insulation resistance. The insulation resistance shall be a minimum of 25 megohms when a potential of 500 ± 50 vdc is applied for 5 seconds. All leads shall be connected together, and the insulation resistance measured to case ground.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

4.4.2 Direction of rotation. The servo motor shall be connected to a 26 ± 1 volt, 400 Hz power supply as shown on dwg 8803809. When the white and yellow leads are energized with the primary phase, the servo motor shall rotate clockwise when viewed from the shaft end. When the white and red leads are energized, the servo motor shall rotate counterclockwise when viewed from the shaft end.

4.4.3 No-load speed. The no-load speed shall be 5000 rpm minimum in each direction at room temperature 75 ± 10°F when measured with a tachometer or equivalent apparatus and operated at 26 ± 1 volts, 400 Hz in the test circuit as shown on dwg 8803809.

4.4.4 Stalling torque. The stalling torque shall be 0.5 ounce-inch minimum in each direction when the servo motor is operated at 26 ± 1 volts, 400 Hz as shown on the test circuit on dwg 8803809. The stalling torque shall be measured with a dynamometer or its equivalent.

4.4.5 Shaft end play. An 8-ounce reversing gage load shall be applied to the end of the shaft in a direction parallel to the longitudinal axis of the rotor with the rotor axis in its horizontal position. When shaft movement has ceased, the direction of the applied load shall be reversed. The rotor shaft shall be observed for maximum movement when the load is applied.

4.4.6 Radial play. An 8-ounce reversing gage load shall be applied to the shaft 1/8-inch from the bearing, perpendicular to the longitudinal axis. Measurements shall be taken 1/8-inch from the bearing and shall not exceed 0.001 inch total indicator reading when the direction of the load is reversed.

4.4.7 Operating life. The servo motor shall be mounted on an aluminum plate 3 by 3 by 1/16 inches and enclosed in a sealed aluminum container, the walls of which shall be 1/32 to 1/16 inch thick with a free air volume of 25 ± 5 cubic inches. The servo motor shall be operated as shown on dwg 8803809 and operated at no load for 55 hours at normal room temperature 75 ± 10°F. One half of the time the servo motor shall operate in a clockwise direction and one half of the time in a counterclockwise direction. After completion of this test, the servo motor shall be tested as specified in 4.4.1 through 4.4.4.

4.4.8 Environmental testing (see 3.12).

4.4.8.1 Vibration. The servo motor shall be mounted on a vibration table and vibrated in each of three mutually perpendicular planes under the following conditions. Duration of the test shall be 2 hours in each plane.

Frequency Range (Hz)	Double Amplitude (Inches) or Acceleration (g)	Length of Cycle (Minutes)
10-30-10	0.109 inch	4
30-80-30	10. g	4
80-500-80	6. g	16

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

After completion of this test the servo motor shall be tested as specified in 4.4.1 through 4.4.5.

4.4.8.2 Acceleration. The servo motor shall be mounted on the apparatus (centrifuge) and subjected to an acceleration of 50 g in each direction along its three mutually perpendicular axes, one of which is its axis of rotation. This acceleration shall be stabilized and maintained for a period of not less than 1 minute for each of the six directions. After completion of this test, the servo motor shall be tested as specified in 4.4.1 through 4.4.4. There shall be no evidence of mechanical failures or malfunctions due to the applied acceleration.

4.4.8.3 Mechanical shock. The servo motor shall be subjected to 12 impact shocks of 50 g, each shock impluse having a time duration of 11 ± 1 milliseconds. The maximum g shall be reached in 5-1/2 milliseconds. The intensity shall be within ± 10 percent when measured with a filter having a band width of 5 to 100 Hz. The shocks shall be applied in the following directions.

a. Vertically: two shocks in each direction.
b. Parallel to the major horizontal axis: two shocks in each direction.
c. Parallel to the minor horizontal axis: two shocks in each direction.

After completion of this test, the servo motor shall be tested as specified in 4.4.1 through 4.4.4.

4.4.8.4 Pull test. A force shall be applied at a point 1 inch from the free end of each lead. This force shall be applied in any direction, including the weakest, and shall be increased gradually to 6 pounds and held at this value for at least 30 seconds. There shall be no evidence of damage to the leads or solder connections. After completion of this test, the servo motor shall be tested as specified in 4.4.1 through 4.4.5.

4.4.8.5 Low temperature. The servo motor shall be placed in a suitable chamber and the temperature stabilized (see 6.4) at -65 ± 5°F. While at this temperature the servo motor shall operate as in the test circuit of dwg 8803809. A minimum no-load speed of 5000 rpm in each direction of rotation shall be attained within 1 minute of voltage application to the circuit. After completion of this test, the temperature of the servo motor shall be raised to room temperature (75 ± 10°F) and tested as in 4.4.1 through 4.4.4.

4.4.8.6 High temperature. The servo motor shall be placed in a suitable temperature chamber and the temperature stabilized at 300 ± 5°F (see 6.4). While at this temperature the servo motor shall operate as in the test circuit of dwg 8803809. A minimum no-load speed of 5000 rpm in each direction of rotation shall be attained within 1 minute of voltage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

application to the circuit. After completion of this test, the temperature of the servo motor shall be decreased to room temperature (75 ± 10°F) and tested as specified in 4.4.1 through 4.4.4.

4.4.8.7 Pressure. The servo motor shall meet the requirements of the altitude test in accordance with procedure III of MIL-E-5272. The maximum altitude shall be 8 mm Hg or approximately 105,000 feet. The servo motor shall be tested as specified in 4.4.1 through 4.4.4 during this test.

4.4.8.8 Fungus. The servo motor shall be subjected to the action of fungi in accordance with MIL-E-5272, section 4.8 for a period of 50 hours. At the end of the test period, the servo motor shall be disassembled and carefully examined to ascertain that no fungus growth has occurred.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The servo motor shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169.

5.1.2 Level C. The servo motor shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169.

5.2 Packing.

5.2.1 Levels A and C. The servo motor shall be packed in accordance with the applicable instructions contained in MIL-STD-1169.

5.3 Marking. Marking shall be in accordance with MIL-STD-1169.

5.4 Data cards. Data cards shall be prepared in accordance with MIL-STD-1167.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.3.4.1). Data specified in 4.3.4.1 and 5.4 will be delivered as identified on a numbered DD Form 1664 when required on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SARPA-QA-T.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

6.4 Temperature stabilization. The temperature is considered stabilized when the greatest peaks (both highest and lowest) continually observed over 5 minutes min. do not exceed the nominal temperature plus tolerance specified.

6.5 Supersession data. This specification supersedes the requirements of Purchase Description -PA-PD-1162 (Rev. 1) dated 28 September 1962.

Custodian:
Army - PA

Preparing activity:
Army - PA

Project No.1190-A084

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
Picatinny Arsenal
ATTN: SARPA-QA-N-Q
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.