MILITARY SPECIFICATION

PRESSURE RELIEF DEVICES, OVERPRESSURIZATION PREVENTION, WHEEL/TIRE, AIRCRAFT

This specification has been approved by the Naval Air Systems Command, Department of the Navy.

1. SCOPE

1.1 Scope - This specification covers the requirements for an overpressurization relief device to replace standard inflation valves for aircraft pneumatic tubeless wheel/tires.

1.2 Classification

1.2.1 Types - This specification covers pressure relief devices of the types shown below:

Type	Tire Working Pressure Range (psig)
I	80-129
II	130-199
III	200-284
IV	285-399
V	400-679

2. APPLICABLE DOCUMENTS

2.1 Government documents normally furnished - The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

Federal

QQ-P-416	Plating, Cadmium (Electrodeposited)
PPP-B-566	Boxes, Folding, Paperboard
PPP-B-636	Box, fiberboard

FSC 1630

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:29Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

Military

MIL-P-116	Preservation, Methods of
MIL-S-8879	Screw Threads, Controlled Radius Root with Increased Minor Diameter, General Specification for

STANDARDS

Military

MIL-STD-129	Marking for Shipment and Storage
MIL-STD-143	Specifications and Standards, Order of Precedence for the Selection of
MIL-STD-810	Environmental Test Methods
MIL-STD-889	Dissimilar Metals
MS33649	Bosses, Fluid Connection-Internal Straight Thread

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Qualification - The pressure relief devices furnished under this specification shall be products which are qualified for listing on the applicable qualified products list, at the time set for opening of the bids (See 4.3.1 and 6.3).

3.1.1 Retention of qualification - To maintain status on a Qualified Products List, certification shall be submitted at two year intervals to indicate continued compliance with the requirements of this specification (See 4.3.2 and 6.3).

3.2 Selection of specifications and standards - Specifications and standards for necessary commodities and services not specified herein shall be selected in accordance with MIL-STD-143.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:29Z
Check the source to verify that this is the current version before use.

3.3 Materials - Materials shall conform to the applicable specifications. Materials for which there are no applicable specifications, or which are not specifically described herein, shall be of the best quality, of the lightest practical weight and suitable for the purposes intended. Materials used shall be compatible with titanium, magnesium, aluminum, steel, and plastic wheel materials.

3.3.1 Dissimilar metals - Unless suitably protected against electrolytic corrosion, dissimilar metals, as defined in MIL-STD-889 shall not be used in intimate contact with each other.

3.3.2 Plating - All steel except corrosion resisting steel shall be cadmium plated in accordance with Type II, Class 2 plating of QQ-P-416.

3.3.3 Age - Elastomer components, except silicone, shall not be more than 12 months old from the cure date of manufacture to the date of delivery to Government procuring activity.

3.3.4 Fungus-proof materials - Materials which are not nutrients for fungi shall be used to the greatest extent practicable. External materials which are nutrients for fungi shall be treated with a fungicidal agent approved by the procuring activity (see 4.6.14).

3.4 Design and construction

3.4.1 General - The devices shall be designed to function so as to preclude the possibility of pressurizing an aircraft tubeless wheel/tire beyond the specified pressure limits for the applicable tire type when using an inflation source to 5000 psig. The devices shall not permit the pressure contained in the wheel/tire to exceed the rated relief pressure (see 3.4.3) at operating temperatures and shall reseat automatically after relief (See 3.4.4). They shall be designed so as to prevent the installation of a device with an incorrect pressure relief setting. The devices shall maintain tire pressure under service use conditions.

3.4.2 Threads - The pressure relief devices shall be designed to mount on wheel bosses conforming to MS33649 and have threads in accordance with MIL-S-8879 in the sizes and thread designations listed below:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:29Z
Check the source to verify that this is the current version before use.

Type	Thread Designation
I	.5625-18UNJF-3A
II	.5000-20UNJF-3A
III	.4375-20UNJF-3A
IV	.3750-24UNJF-3A
V	.3125-24UNJF-3A

3.4.3 Relief pressure - The devices shall be designed to relieve at the wheel/tire pressures specified below for the types indicated at operating temperatures of from -65°F to 350°F.

Type	Relief Pressure (psig) ±15%
I	200
II	310
III	460
IV	640
V	930

3.4.4 Reseating pressure - Type I devices shall reseat at 50 psig minimum following relief, Types, II, III, IV, and V shall reseat at 100 psig minimum.

3.4.5 Weight - Unless otherwise specified, the devices shall not exceed .30 pounds each in weight (See 6.2).

3.4.6 Length - The devices shall not exceed 1.75 inches in overall length, including inflation stem.

3.4.7 Environmental conditions - The device shall meet the performance requirements of this specification under the following environmental conditions when subjected to the tests specified herein.

3.4.7.1 Temperatures - Design operating and nonoperating temperatures range from -65°F to 350°F and storage temperatures from -65°F to 180°F.

3.4.7.2 Ambient pressures - Ambient pressures to be encountered during operation range from 2.13 inches Hg to 31 inches Hg.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:29Z
Check the source to verify that this is the current version before use.

3.4.7.3 Humidity - The device shall not be adversely affected by and shall function properly while being exposed to 95 percent relative humidity, including conditions wherein condensation takes place in the form of water, frost, icing or a combination thereof (see 4.6.15).

3.4.7.4 Sand, dust, mud, water and slush - The device shall be designed to operate in atmospheres containing any of the above contaminants and shall be capable of operating following the combination of tests specified in 4.6.11 and 4.6.12.

3.4.7.5 Salt spray - The device shall function properly following exposure to salt-saturated, moisture laden air when tested as specified in 4.6.13.

3.5 Performance - The device shall be capable of successfully conforming to the following performance requirements:

3.5.1 High pressure - The device shall not permanently distort or structurally fail when an internal pressure of 6500 psig is applied pneumatically or hydraulically from the inflation end as specified in the burst pressure test of 4.6.5.

3.5.2 Acceleration - The device shall show no evidence of leakage while being subjected to the acceleration test under pressure as specified in 4.6.8.

3.5.3 Shock - The device shall show no evidence of leakage while being subjected to the shock test under pressure as specified in 4.6.9.

3.5.4 Vibration - The device shall show no evidence of leakage while being subjected to the vibration test under pressure as specified in 4.6.10.

3.6 Shelf life - The manufacturer shall provide certification that the devices furnished in each lot shall be capable of successfully meeting the leakage requirements of 4.6.3 when tested following storage for a maximum of 24 months under the conditions of 3.4.7 (See 6.2.1).

3.7 Identification of product - Unless otherwise specified, each device shall be identified by part number, type, and nominal relief pressure electrochemically etched or metal stamped on an easily visible external surface protected from normal wear and damage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:29Z
Check the source to verify that this is the current version before use.

3.8 Workmanship - The relief devices shall be fabricated so as to be uniform in quality, and shall be free from cracks, sharp edges, burrs and other defects that affect safety, serviceability and appearance.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspections - The inspection requirements specified herein are classified as follows:

a. Qualification inspection (See 4.3)

b. Quality conformance inspection (See 4.4)

4.3 Qualification inspection - Qualification inspection shall consist of all the examinations and tests of this specification conducted in the order listed under 4.6 and Table I.

TABLE I

Qualification and Quality Conformance Requirements, Tests, and Testing Sequence

Examination	Requirement	Test Procedure	Qualification	Quality Conformance	
				Individual	Sampling
Inspection of Product	3.4	4.6.1	X	X	X
Examination of Preperation for Delivery	Sect. 5	4.6.2	X		X
Operation	3.4.1	4.6.3	X	X	X
Pressure Cycling	-	-	-	-	-
Impulse Cycling	3.4	4.6.4.1	X		X
Relief Cycling	3.4	4.6.4.2	X		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:29Z
Check the source to verify that this is the current version before use.

TABLE I (Cont.)

Qualification and Quality Conformance Requirements, Tests, and Testing Sequence

Examination	Requirement	Test Procedure	Qualification	Quality Conformance	
				Individual	Sampling
Pressure endurance	3.4.1	4.6.4.3	X		
Burst Pressure	3.5.1	4.6.5	X		
Simulated in-flight braking	3.4.1	4.6.6	X		X
Extreme temperature	-	-	-	-	-
High temperature	3.4.3	4.6.7.1	X		
Low temperature	3.4.3	4.6.7.2	X		
Acceleration	3.5.2	4.6.8	X		
Shock	3.5.3	4.6.9	X		
Vibration	3.5.4	4.6.10	X		
Sand and dust	3.4.7.4	4.6.11	X		
Mud and slush	3.4.7.4	4.6.12	X		
Salt Spray	3.4.7.5	4.6.13	X		
Fungus	3.3.4	4.6.14	X		
High humidity	3.4.7.3	4.6.15	X		
Icing	3.4.7.3	4.6.16	X		
Government flight service	3.4.1	4.6.17	X		

4.3.1 Sampling for qualification inspection - Qualification samples shall consist of the following:

a. 20 samples of each of the types to be qualified.

b. One cutaway sample of each of the types to be qualified.

Samples minimally shall be identified by the type, nominal relief pressure, sample number and manufacturer's identification number and forwarded to the activity responsible for testing as designated in the letter of authorization (see 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:29Z
Check the source to verify that this is the current version before use.

4.3.2 Retention of qualification - To comply with the requirements specified in 3.1.1, the manufacturer shall forward a qualification certification to the Commander, Naval Air Systems Command (AIR-530321C), Department of the Navy, Washington, D.C. 20361. This certification, signed by a responsible official of management shall attest that the manufacturer has the capability to produce pressure relief devices under conditions equal to those existing at the time of the original approved listing.

4.4 Quality conformance inspection - The quality conformance inspection shall consist of the individual inspection and the sampling inspection.

4.4.1 Individual inspection - Each device shall be subjected to the following inspection and test. Any device containing a defect or failing to pass the inspection or test shall be rejected.

a. Inspection of product (4.6.1)

b. Operation (4.6.3)

4.4.2 Sampling inspection -

4.4.2.1 Lot - A lot shall consist of 500 devices of each type, or any fraction thereof, manufactured under the same conditions and of the same material and submitted for acceptance at the same time.

4.4.2.2 Sampling - Twenty-five devices shall be selected at random from each lot specified in 4.4.2.1. A sample unit for all tests, except for examination for preparation for delivery, shall be one device. A sample unit for preparation for delivery (4.6.2) shall be one fully packaged shipping container with devices preserved, packaged and packed as specified herein, except that the container shall not be sealed prior to examination. Failure of any device to pass any test specified in 4.4.2.3 and Table I, except preparation for delivery, shall be cause for rejecting the lot.

4.4.2.3 Sampling tests - Samples selected as specified in 4.4.2.2 shall be subjected to the following tests in addition to the individual inspections.

a. Pressure cycling (4.6.4) which includes

(1) Impulse cycling (4.6.4.1)

(2) Relief cycling (4.6.4.2)

b. Examination of preparation for delivery (4.6.2)

Source: https://assist.dla.mil -- Downloaded: 202610-23T06:29Z
Check the source to verify that this is the current version before use.

4.5 Test conditions -

4.5.1 Temperature, pressure and humidity - Whenever the pressure, temperature and humidity existing at the time of test are not specified definitely the test shall be conducted at an ambient barometric pressure of 28.5 +2, -4.5 inches of mercury and an ambient temperature of 73 ±18°F and a relative humidity of 50 ±30%. When tests are conducted with conditions differing materially from the preceding values, proper allowance shall be made for the difference from the specified condition.

4.5.2 Test set-up - Unless otherwise specified for the particular test, the pressure relief device may be mounted either on a rim and tire assembly when suitable, or on a one half cubic foot maximum volume pressure bottle. The bottle shall be equipped to permit the introduction of pressure from either the inflation side or the tire side of the pressure relief device.

4.5.3 Test fluid - Unless otherwise specified in a particular test, the test fluid may be either air or an inert gas.

4.5.4 Test and inspection records - Test and Inspection Records shall be maintained by the contractor for review by the procuring activity, as required, unless specifically required by the contract to be furnished as a data item (see Section 6). Test and Inspection Records shall shall include complete identification of all test equipment and accessories. The data shall include the actual test sequence used, measured ambient conditions recorded periodically during the test period, measured characteristics of the unit under test, the date of test and signature of the test conductor.

4.6 Test methods

4.6.1 Inspection of product - Each relief device shall be inspected to determine compliance with the requirements specified herein with respect to materials, size, design, construction, marking, workmanship and other requirements not covered by tests.

4.6.2 Examination of preparation for delivery - The packings shall be examined to ascertain that the preparation for delivery conforms to the requirements of Section 5 of this specification and as required by the specifications referenced herein.

4.6.3 Operation - A relief device shall have a pressure introduced from the inflation end by a 5000 psig minimum source and maintained for a minimum of 30 seconds, followed by a pressure cut off. The device shall relieve within the relief range for the type being tested (See 3.4.3) and shall reseat, at or above the

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:29Z
Check the source to verify that this is the current version before use.

minimum reseating pressure (See 3.4.4) with no leakage as determined by chemical means. "Chemical means" indicates use of soap solution or other bubble forming liquid.

4.6.4 Pressure cycling

4.6.4.1 Impulse cycling - A device shall be subjected to 25 impulse cycles with the pressure introduced through the tire side of the device. Each cycle, of 17 seconds maximum duration, shall consist of an increase from the minimum tire working pressure to 75 percent of the rated relief pressure of the type device being tested (see 3.4.3) in a maximum of 2 seconds, dwell for 3 seconds, decay in a maximum of 2 seconds to minimum tire working pressure and dwell for 10 seconds. During the 10 second dwell period the inflation end of the device shall show no visible evidence of leakage when tested by chamical means.

4.6.4.2 Relief cycling - A device shall be subjected to 5 relief cycles with pressure introduced through the inflation end of the device. Each cycle shall consist of inflation, by a source of 5000 psig minimum, maintained for a minimum of 30 seconds, followed by pressure cutoff. The device shall relieve within the relief range for the device being tested (See 3.4.3) and shall reseat, at or above the minimum reseating pressure (See 3.4.4) for each cycle with no leakage as determined by chemical means. Readings shall be taken of the relief pressure and the reseating pressure reached for each cycle.

4.6.4.3 Pressure endurance - A device shall be subjected to a pressure, introduced from the tire side, of 80 percent of the rated relief pressure of the device being tested, for a period of 10 days. Leakage during this test shall not exceed five percent of the original inflation pressure.

4.6.5 Burst pressure - A device shall be plugged on the outlet end and a pneumatic or hydraulic pressure of 6500 psig introduced into the inlet end, held for two seconds, then released. The device shall not distort or structurally fail during this test.

4.6.6 Simulated in-flight braking - A device shall be mounted either on a wheel and brake assembly or on a pressure bottle with the device situated so as to simulate a normal wheel mounting with a 6-inch radius to the device mounting. The assembly shall be pressurized to the tire working pressure, of the device being tested, and run through an in-flight test of equal dynamic loading to 3000 rpm and stopping in 0.5 second. Following this test, no leakage shall be evident as determined by chemical means when the assembly pressure is increased to 75 percent of the rated relief pressure of the device being tested.

Source: https://assist.dla.mil -- Downloaded: 202640-23T06:29Z
Check the source to verify that this is the currentversion before use.

4.6.7 Extreme temperature

4.6.7.1 High temperature - A device shall be mounted on a one half cubic foot volume maximum pressure bottle and subjected to a 24 hour heat soak at 350°F while maintaining 75 percent of the rated relief pressure, of the device being tested, applied from the tire side. The pressure loss shall not exceed 1.5 percent during the 24 hour test. While still at temperature in the chamber, repeat two cycles each of impulse cycling test (4.6.4.1) and relief cycling test (4.6.4.2). The device shall satisfactorily meet the leakage requirement of each test.

4.6.7.2 Low temperature - Following the high temperature test, the same device shall be mounted as noted for the high temperature test and subjected to a 24 hour cold soak at -65°F while maintaining 75 percent of the rated relief pressure, of the device being tested, applied from the tire side. The pressure loss shall not exceed 1.5 percent during the 24 hour test. While still at temperature in the chamber, repeat two cycles each of impulse cycling test (4.6.4.1) and relief cycling test (4.6.4.2). The device shall satisfactorily meet the leakage requirement of each test.

4.6.8 Acceleration - A device shall be mounted either on a wheel/tire assembly or on a 50 cubic inch volume maximum pressure bottle and pressurized from the inflation side of the device to 75 percent of the rated relief pressure of the device being tested. The assembly shall be accelerated to 25 G's and maintained for 10 seconds with the G forces parallel to the axis of the device and in a direction to actuate the device. Repeat the 25 G's acceleration and maintain it for 10 seconds with the G forces perpendicular to the device axis. There shall be no indication of leakage due to the device unseating evidenced by a drop in pressure as measured by a recorder.

4.6.9 Shock - A device shall be mounted on a 50 cubic inch volume maximum pressure bottle and pressurized from the tire side to 75 percent of the rated relief pressure of the device being tested. The assembly shall be subjected to three shocks in each direction along each of the three mutually perpendicular axes of the test device. Each shock shall be of 15 G peak acceleration for a time consistant with testing equipment capabilities but not to exceed 500 milliseconds approximately of a half sine wave type. There shall be no indication of leakage due to the device unseating evidenced by a drop in pressure as measured by a recorder.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:29Z
Check the source to verify that this is the current version before use.

4.6.10 Vibration - A device shall be mounted on a 50 cubic inch volume maximum pressure bottle and pressurized from the tire side to 75 percent of the rated relief pressure of the device being tested. The assembly shall be subjected to vibrations of from 5 Hz to 200 Hz frequency at 0.025 inch double amplitude sine wave for five minutes along each of the three mutually perpendicular axes of the test device. There shall be no indication of leakage due to the device unseating evidenced by a drop in pressure as measured by a recorder.

4.6.11 Sand and dust - A device shall have both ends capped and shall be subjected to a dust test in accordance with MIL-STD-810, Method 510, Procedure I, Steps 1, 2, 3 and 4. The device shall then be removed from the dust chamber and, without cleaning, installed and tested as required for the relief cycling test of 4.6.4.2 and shall satisfactorily meet the leakage requirements of this test.

4.6.12 Mud and slush - A device shall be installed in an inflation test set-up with both ends capped or protected and dipped until fully covered in a standard bentonite casting slip. The device shall then be allowed to air-dry for 12 hours and shall then be submerged in slush for 15 minutes at a constant temperature. The device shall be removed from the slush and immediately tested as required for the relief cycling test of 4.6.4.2 and shall satisfactorily meet the leakage requirements of this test.

4.6.13 Salt spray - A device shall be capped on the tire side and subjected to a salt spray test in accordance with MIL-STD-810, Method 509, Procedure I, except that the exposure to the salt spray shall continue for 30 days. After both the 30 day exposure and the 48 hour drying periods, the device shall be installed and tested as required for the relief cycling test of 4.6.4.2 and shall satisfactorily meet the leakage requirements of this test.

4.6.14 Fungus - A device shall be capped on the tire side and subjected to a fungus test in accordance with MIL-STD-810, Method 508, Procedure I. The device shall not support fungus growth as defined by this test.

4.6.15 High humidity - A device shall have both ends capped and shall be subjected to the humidity test in accordance with MIL-STD-810, Method 507, Procedure I. Test steps 1 through 6 shall be conducted. Following Step 6, the end caps shall be removed and the device installed in the applicable test set-up for the relief cycling test (4.6.4.2). The device shall satisfactorily meet the leakage requirements of 4.6.4.2 following the completion of this test.

Source: https://assist.dla.mil -- Downloaded: 202610-23T06:29Z
Check the source to verify that this is the current version before use.

4.6.16 Icing - A device shall be installed in an inflation test set-up with both ends capped or protected and submerged in water for 24 hours. Upon removal from the water, the device shall be subjected to a temperature of -65°F for one hour. While still at this temperature, a gas, from a 5000 psig source, shall be introduced through the inflation end at a rate sufficient to cause the device to relieve within two seconds. The flow shal be maintained for a period of 15 seconds. The device shall prevent the pressure buildup in the test set-up from exceeding the maximum rated relief pressure for the device type being tested.

4.6.17 Government flight service - Upon the successful completion of all the above tests, the qualification samples, of the type specified by the procuring activity, shall be forwarded as directed for Government flight service testing. Successful completion of flight tests, under service operating conditions, conducted for a period of three months, by the Navy, are required to fully qualify the devices.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging - Preservation and packaging shall be level A or C as specified (See 6.2).

5.1.1 Level A

5.1.1.1 Unit package - Pressure relief devices shall be individually packaged in accordance with MIL-P-116, Method 1C-1.

5.1.1.2 Intermediate package - Ten devices packaged individually in accordance with 5.1.1.1 shall be packaged in a container conforming to PPP-B-566.

5.1.2 Level C - Devices shall be preserved and packaged in a manner to prevent deterioration and damage during shipment from the supply source to the first receiving activity.

5.2 Packing - Packing shall be level A, B, or C as specified.

5.2.1 Level A - Devices packaged in accordance with 5.1.1 shall be packed in containers conforming to PPP-B-636, type CF, class-weather resistant.

5.2.2 Level B - Devices packaged in accordance with 5.1.1 shall be packed in containers conforming to PPP-B-636, type CF, class domestic.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:29Z
Check the source to verify that this is the current version before use.

5.2.3 Level C - Devices that require packing for acceptance by the carrier shall be packed in exterior type shipping containers in a manner that will ensure safe transportation at the lowest rate to the point of delivery, and shall meet, as a minimum, the requirements of the rules and regulations, as applicable to the mode of transportation to be utilized.

5.3 Marking - All containers shall be marked in accordance with MIL-STD-129. Packages containing devices with elastomeric components shall bear the cure date of these components.

6. NOTES

6.1 Intended use - The pressure relief devices are intended to prevent overpressurization of tubeless aircraft wheels/tires due to overinflation.

6.2 Ordering data - Procurement documents should specify:

6.2.1 Procurement requirements

a. Title, number and date of this specification

b. Quantity desired.

c. Type device required

d. Report verifying cure date of elastomer components (see 3.3.3).

e. Whether differing maximum weight is to be permitted (See 3.4.5)

f. Whether additional product marking is required (See 3.7)

g. Level of preservation and packaging required (See 5.1 and 5.2)

h. Certificate of elastomer storage capability (See 3.6)

i. Types of devices and forwarding information required for qualification samples for Government flight service test (see 4.6.17, and 6.3.1)

j. Items of data required (See 6.3.2 and 6.4)

6.3 Qualification - With respect to products requiring qualification, awards will be made only for products which are at the time set for opening of bids, qualified for inclusion in the applicable Qualified Products List whether or not such products have actually been so listed by that date. The attention of the suppliers is called to this requirement, and manufacturers are urged to

Source: https://assist.dla.mil -- Downloaded: 202640-23T06:29Z
Check the source to verify that this is the currentversion before use.

arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. The activity responsible for the Qualified Products List is the Commander, Naval Air Systems Command, (AIR-530321C), Department of the Navy, Washington, D.C. 20361.

6.3.1 Government flight service test waiver - When devices of one type of one manufacturer have successfully completed the Government flight service test, consideration should be given to waive this qualification requirement for other types of similar design, materials and fabrication methods by the same manufacturer.

6.3.2 Drawings and reports - When requested, the manufacturer shall submit drawings and inspection reports in accordance with SD6, Provisions Governing Qualification.

6.4 Data - For the information of contractors and contracting officers, any of the data specified in applicable documents listed in Section 2 of this specification or referenced in lower-tier documents need not be prepared for the Government and will not be required by the Government unless specified in the contract or order. The data to be furnished will be listed on DD Form 1423 (Contractor Data Requirement List), which will be attached to and made a part of the contract or order. NAVAIR Form 4200/25 (Drawings, Lists and Specifications Required) shall be attached where applicable.

Preparing Activity
Navy - AS
(Project No.1630-N166)

☆ U. S. GOVERNMENT PRINTING OFFICE: 1974-713-164/1216

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:29Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE MIL-P-81958(AS) PRESSURE RELIEF DEVICES, OVER-PRESSURIZATION PREVENTION, WHEEL/TIRE, AIRCRAFT

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO (If "Yes", in what way?)

4. REMARKS

SUBMITTED BY (Printed or typed name and address - Optional)

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:29Z
Check the source to verify that this is the current version before use.