MIL-STD-1158A
5 December 1978
SUPERSEDING
MIL-STD-1158
5 May 1966

MILITARY STANDARD

CUSTODIAL CLEANING SERVICES

FSC 7930

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:20Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF DEFENSE

Washington, DC 20301

CUSTODIAL CLEANING SERVICES

MIL-STD-1158A

1. This Military Standard is approved for use by all Departments and Agencies of the Department of Defense.

2. Recommended comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: US Army Natick Research and Development Command, Natick, MA 01760, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:20Z
Check the source to verify that this is the current version before use.

FOREWORD

This standard outlines the items, procedures, and frequencies of custodial cleaning services for posts, camps, and stations. The standard also provides a basis for procuring these services, the use of which should result in longer life for floors, walls, furnishings, equipment and office furniture.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:20Z
Check the source to verify that this is the current version before use.

CONTENTS

	Page
1. SCOPE	1
2. REFERENCED DOCUMENTS	1
3. DEFINITIONS	2
3.1 Floor care	2
3.2 Care of walls and ceilings	3
3.3 Care of lavatory equipment, sinks, and drinking fountains	4
3.4 Care of furniture	4
4. GENERAL REQUIREMENTS	4
5. DETAILED REQUIREMENTS	4
5.1 Daily services .	4
5.2 Weekly services	7
5.3 Quarterly services	8
5.4 Third of year services	8
5.5 Semi-annual services	9
5.6 Annual services	10
6. NATIONAL STOCK NUMBERS FOR CHEMICALS AND EQUIPMENT	11

Source: https://assist.dla.mil -- Downloaded: 202640-23T23:20Z
Check the source to verify that this is the currenversion before use.

1. SCOPE

1.1 Purpose. The purpose of this standard is to outline in detail the frequencies, items, and procedures necessary to accomplish satisfactory custodial cleaning based on average conditions and activity. It is to be referenced in custodial services contracts initiated by Military installations. The specified frequencies should be adjusted, as required, to meet the needs of each installation based on geographical location, climate, degree of soiling and obstruction, health requirements, and amount of traffic.

2. REFERENCED DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this standard to the extent specified herein.

FEDERAL SPECIFICATIONS

O-S-642	-	Sodium Phosphate, Tribasic, Anhydrous; Dodecahydrate and Monohydrate; Technical
P-C-447	-	Cleaning Compound, Toilet Bowl
P-C-1632	-	Cleaning Compound, Rug and Upholstery
P-D-215	-	Deodorant, Toilet, Cake
P-D-220	-	Detergent, General Purpose
P-D-1747	-	Detergent, General Purpose (Spray-On, Wipe-Off)
P-F-430	-	Finish, Floor, Water-Emulsion (For Use on Light Colored Floors)
P-G-406	-	Glass Cleaner, Liquid
P-P-553	-	Polish, Furniture
P-P-556	-	Polish, Metal
P-R-1760	-	Remover, Floor Polish (Resin-Type and Wax)
P-S-311	-	Scouring Powder
P-S-609	-	Soap, Saddle (Leather Goods)
P-S-620	-	Soap, Toilet (Cake and Powdered)
P-S-624	-	Soap, Toilet (Liquid and Paste)
P-S-625	-	Soap, Borax (Powdered)
P-S-863	-	Sweeping Compound
P-W-155	-	Wax, Floor, Water-Emulsion
FF-W-1825	-	Wool, Metallic
OO-P-40	-	Pad, Floor Polishing Machine: and Holder, Floor Polishing Machine Pad
TT-S-176	-	Sealer, Surface, Varnish Type, Floor Wood and Cork
UU-P-556	-	Paper, Toilet Tissue
UU-T-591	-	Towels, Paper

Source: https://assist.dla.mil -- Downloaded: 202610-23T23:20Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.

3. DEFINITIONS

3.1 Floor care.

3.1.1 Sweeping. Sweeping is the accumulation and removal of all litter adjacent to and under furniture, fixtures, in corners, and on a floor by use of a vacuum cleaner, brush, broom, or a dry or treated sweeping mop.

3.1.2 Dustless sweeping. Dustless sweeping is the cleaning of floors using a sweeping compound which has been applied prior to sweeping. Dustless sweeping reduces dustiness and leaves a film of wax on the floor.

3.1.3 Mopping. Mopping is the removal of dirt on a floor leaving the floor dirt free and evenly cleaned. Mopping may be substituted for sweeping where a minimum amount of dust raising is desired.

3.1.4 Wet-mopping. Wet-mopping is the removal of dirt on a floor leaving the floor dirt free and evenly cleaned, with baseboards unsplashed, and no mop strings remaining on the floor. Wet-mopping requires the use of a clean mop, a detergent, and a minimum of water followed by a clear water rinse. Wet-mopping is utilized when dirt cannot be removed by sweeping or mopping.

3.1.5 Dry-cleaning. Dry-cleaning is the cleaning of floors using a cylinder-type machine equipped with a grade one steel wool conforming to type I, class 0 or class 1 of FF-W-1825 and a vacuum attachment, or a disk-type machine with a steel wool pad or a nylon pad conforming to type I, class 1 or class 2 or type II, class 1 or class 2 of 00-P-40. Dry-cleaning is frequently preferred to wet-mopping for the removal of stubborn dirt. (Generally, cylinder-type machines have a wax bar which rides on the steel wool or brush cylinder, thus the floor can be cleaned, waxed, and buffed in the same operation.)

3.1.6 Scrubbing. Scrubbing is the cleaning of floors, using a brush, detergent, and a minimum of water followed by a clear water rinse. Scouring powder shall be used only when absolutely necessary and care shall be taken to prevent damage to surface cleaned. On wooden floors the brush shall be moved with the grain. Scrubbing shall be utilized when wet-mopping or dry-cleaning does not suffice. Scrubbing may also be accomplished by using a rotary disk-type machine and scrubbing pad conforming to type I, class 2 or type II, class 2 of 00-P-40.

Source: https://assist.dla.mil -- Downloaded: 20260-23T23:20Z
Check the source to verify that this is the current version before use.

3.1.7 Wax stripping. Wax stripping is the removal of old, dirty, built-up wax by a liquid wax remover in conjunction with a floor stripping machine equipped with an abrasive pad conforming to type I, class 3 or type II, class 3 of OO-P-40 or a steel wool pad conforming to type I, class 1 of FF-W-1825. The floor will be left wax free and uniformly clean by using a mop and water to remove uplifted wax.

3.1.8 Waxing. Waxing is the treatment of floors for preserving the finish and improving the appearance by increasing gloss or sheen and uniformity. Waxing may be accomplished by a machine using bar wax, by mop using a water emulsion wax, or by an electric-waxing machine using a liquid wax. To prevent buildup of successive layers, wax should not be applied closer than 6 inches (152 mm) adjacent to walls or partitions.

3.1.9 Buffing. Buffing is the treatment of waxed floors using a machine fitted with a brush or wool pad, leaving the floors lustrous, with a uniform sheen, and with no visible swirl or brush marks.

3.2 Care of walls and ceilings (including doors, windows, blackboards, railings, balusters, radiators, venetian blinds, and light fixtures).

3.2.1 Wall washing. Wall washing is the cleaning of walls leaving them uniformly clean with no streaks or smudge marks visible at meeting point of upper and lower cleaned sections. In the process of cleaning, care shall be exercised so that no water is spilled on floors or furnishings.

3.2.2 Dusting. Dusting is the removal of dust with a treated cloth or yarn duster. Dusting with brush or feather duster is not recommended as it only spreads more dust. When dusting with a treated cloth, care shall be taken not to leave oil spots.

3.2.2.1 High dusting. High dusting is the removal of dust from walls, ceilings, and such appurtenances as pipes and mouldings, leaving them free of dust and smudges.

3.2.2.2 Low dusting. Low dusting is the removal of dust from woodwork leaving it bright in appearance with no smudge marks on adjacent walls.

3.2.3 Window washing. Window washing is the cleaning of windows leaving them bright and free of streaks with no water on the sill or around the window. Use of a glass cleaner is more effective than soap and water and is less likely to leave streaks.

3.2.4 Solid unlacquered brassware cleaning. This process is the cleaning and polishing of brassware, using specified cleaner and polish, leaving the brassware highly lustrous with no dull patches, scratches, or evidence of spilled cleaner or polish on fixtures, floor, or adjoining surfaces.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:20Z
Check the source to verify that this is the current version before use.

3.2.5 Light fixture cleaning. This process is the cleaning of bulbs, tubes, or globes leaving them bright and clean and their supports and other parts free of a film residue, dust, dirt, lint, and streaks.

3.3 Care of lavatory equipment (wash bowls, toilet bowls and seats, water closets, urinals, and exposed attached plumbing), sinks, and drinking fountains.

3.3.1 Cleaning of lavatory equipment. This process is the cleaning of enamel, porcelain, and wood and the cleaning and polishing of all metal surfaces, leaving them bright and without streaks, stains, or unpleasant odors.

3.3.2 Cleaning of sinks. This process is the cleaning of sinks leaving them clean and stain free and the metalware shiny. There shall be no evidence of water or soap solutions spilled on the floor and on the wall behind or adjacent to the fixtures.

3.3.3 Cleaning of drinking fountains. This process is the cleaning of drinking fountains leaving them clean with no evidence of water splashed on walls or floor and with the metalware bright and shiny.

3.3.4 Polishing chromium or nickel-plated ware. This process is the polishing of chromium and nickel-plated fixtures leaving them clean and bright with no polish remaining on fixtures and floors.

3.4 Care of furniture (including ash trays, sand urns, waste receptacles, book cases, desks, and chairs).

3.4.1 Dusting (office). Office dusting is the removal of dust from office furniture by use of a treated cloth or yarn duster leaving the furniture clean and orderly with no oily surfaces.

4. GENERAL REQUIREMENTS

4.1 The general requirements comprise the established frequencies listed and modified in 5.1 Daily services, 5.2 Weekly services, 5.3 Quarterly services, 5.4 Third of the year services, 5.5 Semi-annual services, and 5.6 Annual services.

5. DETAILED REQUIREMENTS

5.1 Daily services (work is to be performed each day per 5 day week).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:20Z
Check the source to verify that this is the current version before use.

5.1.1 Floor care.

5.1.1.1 Carpeted areas and rugs.

a. All rugs are to be vacuumed a minimum of every two days depending upon soiling. Heavy traffic areas shall be vacuumed daily.

5.1.1.2 Other surfaces.

a. Sweep all floor areas including offices, lavatories, hallways, stairways, entrances, stoops, landings, and outside platforms. As required, furniture and equipment shall be carefully moved and returned to their original position.

1. Waxed floors - Use a soft bristle floor brush or untreated sweeping mop.
2. Unwaxed floors - Use a treated sweeping mop or a bristle floor brush with a sweeping compound conforming to type I of P-S-863.
3. Dust-sensitive areas (for critical areas bearing equipment which might be damaged or whose operation might be impaired by dust from normal sweeping). - Sweep using a non-combustible sweeping compound conforming to type II of P-S-863. Do not use oiled sawdust or other flammable sweeping compounds prohibited by fire protection regulations.

b. Clean all entrance and exit mats.
c. Sweep exterior surfaces using straw or rigid plastic bristle brooms.
d. Collect debris and remove to point of disposal.
e. Wet-mop lavatory floors and floor areas subject to heavy traffic.
f. Wipe clean any spillage on floors adjacent to sinks and fountains with a mop or dampened cloth.
g. Remove all stubborn spots or stains by using scouring powder conforming to type I of P-S-311.

5.1.2 Care of walls and ceilings (including doors, windows, and blackboards).

a. Clean all building entrances especially areas around handles and kickplates of doors with a warm solution of detergent conforming to type I or type II of P-D-220 or a spray cleaner conforming to P-D-1747, and all glass parts with a window cleaner conforming to type I of P-G-406 to remove all handmarks, fingerprints, grease, dirt, stains, and foreign matter.

1. Remove all stubborn spots and stains by using scouring powder conforming to type I of P-S-311.

b. Dust shelves and window sills using a dry cloth, treated cloth, or yarn duster.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:20Z
Check the source to verify that this is the current version before use.

c. Erase blackboards of all markings then wipe with a clean cloth wetted in clear water and allow to air-dry. Wipe stands and dust trays with a clean cloth or sponge and clear water. Remove chalk dust from erasers outside of building.

1. If diagrams, drawings, sketches, mathematical formulas or figures are present, do not erase unless directed.

d. Spot clean all latrine walls to remove stains and discolorations using a cloth dampened with a solution of water and detergent conforming to type I or type II of P-D-220 or a spray cleaner conforming to P-D-1747.

e. Remove stains from latrine wainscots and stall partitions (including shower stalls) using a cloth dampened with a solution of water and detergent conforming to type I or type II of P-D-220 or a spray cleaner conforming to P-D-1747.

5.1.3 Care of lavatory equipment (wash bowls, toilet bowls, toilet seats, water closets, urinals, and exposed plumbing), sinks, drinking fountains, and water coolers.

a. Clean wash bowls, outside of toilet bowls, toilet seats, water closets, urinals, exposed plumbing, sinks, drinking fountains and water coolers using a warm solution of water and detergent conforming to type I or type II of P-D-220.

b. Spot clean latrines to remove stains and discolorations.

1. Remove stains and hardwater deposits on plumbing or ceramic tile using a scouring powder conforming to type I of P-S-311 or a solution of trisodium phosphate conforming to type I (approximately 1 tablespoon per gallon (3.8 L) of water) or type II (approximately 2 tablespoons per gallon (3.8 L) of water) of O-S-642.

c. Clean the inside of toilet bowls with a cleaner conforming to type I or type II of P-C-447.

d. Clean the inside of urinal troughs with a pine oil solution or approved disinfectant.

e. Wipe clean any spillage on floors and walls adjacent to sinks and fountains with a dampened cloth.

f. Fill all dispensers and receptacles.

1. Fill toilet paper dispensers with paper conforming to type I, grade A or B or type II, single or double fold of UU-P-556.
2. Fill towel dispensers with paper towels conforming to any type or size of UU-T-591.
3. Fill soap dispensers and receptacles with soap conforming to type I, class 1 or 2, or type II of P-S-620, type I or type II of P-S-624, or class 1 or class 2 of P-S-625, as applicable.

Source: https://assist.dla.mil -- Downloaded: 202610-23T23:20Z
Check the source to verify that this is the current version before use.

4. Place deodorant blocks conforming to type I or type II of P-D-215 in urinal troughs and toilet bowls.

5.1.4 Care of furniture (including ash trays, sand urns, and waste receptacles).

a. Dust all tables, desks, cabinets, chairs, book cases, and telephones using a treated cloth or yarn duster.

b. Empty and clean ash trays. Clean all sand urns and replace sand if required.

1. Smouldering cigarettes should be extinguished before disposal.
2. Dispose of ash tray and urn waste by using metal containers provided by the Government for transport of waste to outside collection facility.

c. Empty waste baskets. Do not pull contents out with your hands.

5.2 Weekly services (to be performed one specified day each week).

5.2.1 Floor care.

a. Wet-mop all floors, other than wood, but including entrances, reception areas, hallways, corridors, conference rooms, lavatories, and areas subject to heavy traffic, using a minimum of warm water and a detergent conforming to type I or type II of P-D-220. Rinse with a clean mop and clean water. When dry, wax with a water-emulsion wax conforming to P-W-155 or P-F-430 for light colored surfaces. Buff well and replace all equipment and furniture in original location.

b. Wet-mop all wooden floors using a minimum of warm water and if required to remove stubborn soil, a detergent conforming to type I or type II of P-D-220. Rinse with a clean mop and a minimum of clear water. Seal wooden floors with a penetrating sealer conforming to class 1 or class 2 of TT-S-176. Wax with a water-emulsion wax conforming to P-W-155. Buff well with palmetto brushes or electric buffer. Replace all equipment and furniture in original location.

c. Vacuum all rugs or carpets to remove surface dirt, dust, and foreign matter. All spills or spots are to be spot cleaned as they occur.

5.2.2 Care of walls and ceilings.

a. Dust all window surfaces, railings, balusters, and radiators using a treated cloth.

b. Clean all glass mirrors, partitions, baseboards, and woodwork near the floor using appropriate cleaning solutions and clear water.

Source: https://assist.dla.mil -- Downloaded: 202610-23T23:20Z
Check the source to verify that this is the currentversion before use.

c. Clean and polish all brass fixtures (door knobs, push plates, etc.).
d. Wash all wainscots, toilet stall partitions, and doors with a sponge and water solution of detergent conforming to type I or type II of P-D-220. Rinse with clean water and dry with a clean cloth. Wipe clean any marks, spots, or spillage with a damp cloth.

5.2.3 Care of furniture.

a. Clean all glass cases using appropriate cleaning solution and water.

5.3 Quarterly services (to be performed on specified week and month every 3 months).

5.3.1 Care of walls and ceilings.

a. Dust venetian blinds with chemically treated cloth, or vacuum.

5.3.2 Care of furniture.

a. Polish high gloss wooden furniture with a silicone wax furniture polish conforming to type II, class 2 of P-P-553. Before polishing, wash the wooden furniture with an aqueous solution of detergent conforming to type I or type II of P-D-220 using a minimum of warm water. Immediately wipe dry with a clean cloth.

1. Remove heavy stains as soon as possible to prevent permanent staining.

5.4 Third of year services (to be performed one specified week every 4 months).

5.4.1 Care of furniture.

a. Polish satin-finish wood furniture with a wax-emulsion furniture polish conforming to type II, class 1 of P-P-553 for normal luster or with a silicone wax furniture polish conforming to type II, class 2 of P-P-553 to yield a higher luster.

1. Before polishing, very soiled furniture shall be cleaned with an aqueous solution of detergent conforming to type I or type II of P-D-220 using a sponge. Avoid the use of excessive water.
2. Slightly soiled furniture shall be cleaned by wiping with a dampened clean cloth or sponge before polishing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:20Z
Check the source to verify that this is the current version before use.

b. Polish low-gloss wood furniture with a wax-emulsion furniture polish conforming to type II, class 1 of P-P-553.

1. Before polishing, very soiled furniture shall be cleaned with an aqueous solution of detergent conforming to type I or type II of P-D-220. Avoid use of excessive water.
2. Slightly soiled furniture shall be cleaned by wiping with a damp cloth or sponge before polishing.

5.5 Semi-annual services (to be performed every 6 months).

5.5.1 Floor care.

a. Strip all wax from wood, resilient, and oxychloride or otherwise impermeable floor surfaces using a wax remover conforming to P-R-1760. Dry cleaning is preferred for wooden floors.
b. When dry, wax the floor using a bar wax or a water-emulsion wax conforming to P-W-155. On light colored floors, a detergent resistant, floor finish conforming to P-F-430 may be used.
c. Buff well leaving the floor with a uniform sheen.

5.5.1.1 Care of rugs and carpets. All rugs in heavy traffic areas shall be thoroughly cleaned using steam or other current industry practice measures of shampooing. Plastic or foil strips shall be placed under furniture legs to prevent staining. All furniture shall be returned to its original position.

5.5.2 Care of walls and ceilings.

a. Dust air conditioning grilles, heaters, convectors, radiators, and fans with a yarn duster, radiator brush, cloth, or vacuum cleaner attachment. If present, radiator covers shall be removed before dusting the radiators.
b. Dust electric fixtures (including flourescent light reflectors and globes, as applicable) and bulbs or tubes, as applicable.
c. Wash the inside and outside of all accessible windows not bearing screens or bars with a suitable squeegee. Use an aqueous solution (1 to 2 teaspoons per gallon (3.8 L) of water) of trisodium phosphate conforming to type I or type II of O-S-642.

5.5.3 Care of furniture.

a. Wipe painted metal furniture with a damp cloth or sponge. Clean badly soiled areas with a clean cloth and a warm aqueous solution of a detergent conforming to type I or type II of P-D-220 or spray cleaner conforming to P-D-1747. (Easiest cleaning is accomplished immediately after soiling occurs.)

Source: https://assist.dla.mil -- Downloaded: 202640-23T23:20Z
Check the source to verify that this is the current version before use.

b. Polish linoleum desk and table tops with a wax-emulsion polish conforming to type II, class 1 of P-P-553. Before polishing severely soiled tops, clean with a warm solution of detergent conforming to type I or type II of P-D-220. Immediately wipe dry with a clean dry cloth.

1. Do not use scouring powder or an oily furniture polish on linoleum desk tops.

c. Clean badly soiled plastic and imitation leather coverings with an aqueous solution of detergent conforming to type I or type II of P-D-220 or with cleaning compound conforming to type II or type III of P-C-1632 and wipe with a cloth dampened in clean water. Clean leather coverings with saddle soap conforming to P-S-609 and a dry cloth. Wipe away any spillage with a damp cloth leaving furniture surfaces free of streaks, film, or deposits of dirt.

d. Apply polish conforming to type II, class 2 or type III, class 2 of P-P-556 to impart luster to any metal furniture, such as desks, chairs, and book cases.

5.6 Annual services.

5.6.1 Care of walls and ceilings.

a. Dust high walls and ceilings.
b. Clean all electric light fixture components.

1. Remove reflectors from fluorescent fixtures and clean by soaking or wiping with a sponge and a warm solution of detergent conforming to type I or type II of P-D-220. Wipe cool fluorescent tubes with cloth dampened in clear water. When dry, replace tubes and reflectors securely in original position.
2. Where applicable, remove globes and wipe with a sponge and warm solution of detergent conforming to type I or type II of P-D-220. Remove bulbs, if cool, wipe with cloth dampened in clear water and replace in original position when finished. Wipe globes dry with a clean, dry cloth and replace securely.

c. Remove window screens, brush them clean, and replace when finished.
d. Wash all venetian blinds with a clean cloth dampened in warm solution of detergent conforming to type I or type II of P-D-220. Rinse with clear water and dry with a clean cloth.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:20Z
Check the source to verify that this is the current version before use.

5.6.2 Care of furniture.

a. Wash all receptacles with a warm solution of detergent conforming to type I or type II of P-D-220. Brush to remove deposits, dirt, and odors. Rinse well with clear water and rest upside down to dry.

b. Clean all leather upholstery.

1. Clean slight soils using a saddle soap conforming to P-S-609 and a dampened cloth or sponge.
2. Clean severely soiled areas with a warm solution of detergent conforming to type I or type II of P-D-220. Wipe dry with a clean cloth. Avoid the use of excessive water.
3. Do not apply wax.

c. Clean vinyl upholstery with a dampened cloth or sponge to remove slight soils; clean severely soiled areas with a minimum of warm aqueous solution of detergent conforming to type I or type II of P-D-220 or cleaning compound conforming to type II or type III of P-C-1632. Do not apply wax.

6. NATIONAL STOCK NUMBERS FOR CHEMICALS AND EQUIPMENT

6.1 Cleaning compound toilet bowl - P-C-447.

Type I	Liquid	
	7930-00-234-1945	1 qt. (0.95 L) bottle
Type II	Solid	
	7930-00-559-9481	20 oz. (567 g) container

6.2 Cleaning compound, rug and upholstery - P-C-1632.

Type II	Liquid cleaner	
	7930-00-113-1913	1/2 gal. (1.9 L) bottle
Type III	Aerosol cleaner	
	7930-00-724-9556	24 oz. (680 g) can

6.3 Deodorant, toilet, cake - P-D-215.

Type I	Cake, without holder	No stock No. Buy commercial.
Type II	Cake, with holder	No stock No. Buy commercial.

6.4 Detergent, general purpose - P-D-220.

Type I	Powder, flake or granular	
	7930-00-249-8036	5 lbs. (2.3 kg) can
	7930-00-634-136	25 lbs. (11.3 kg) drum
	7930-00-634-1363	300 lbs. (136 kg) drum

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:20Z
Check the source to verify that this is the current version before use.

Type II Liquid

7930-00-634-4784	1 gal. (3.8 L) can
7930-00-634-3441	5 gal. (18.9 L) pail
7930-00-527-1237	55 gal. (208 L) drum

6.5 Detergent, general purpose (spray on wipe-off) - P-D-1747.

7930-00-926-5280	1 pt. (0.47 L) bottle
7930-00-068-1669	1/2 gal. (1.9 L) bottle
7930-00-177-5243	1 gal. (3.8 L) bottle

6.6 Finish, floor, water-emulsion - P-F-430.

7930-00-926-1689	5 gal. (18.9 L) can
7930-00-926-1687	55 gal. (208 L) drum

6.7 Glass cleaner - P-G-406.

Type I -	7930-00-664-6910	8 oz. (237 ml) bottle
	7930-00-184-9423	1 gal. (3.8 L) bottle

6.8 Pad, floor polishing - 00-P-40.

Type I - Class 1, 2, or 3

Type II - Class 1, 2, or 3

Stock numbers for the various types, classes and sizes are too numerous to list. Sizes range from 14 to 20 inches (356 to 508 mm) in diameter in increments of 1 inch (25 mm). FSC is 7910, and listing is contained in the GSA catalog.

6.9 Paper, toilet tissue - UU-P-556.

Type I	- Roll tissue	
	Grade A 8540-00-143-1030	Box of 96 rolls
	Grade B 8540-00-530-3770	Box of 96 rolls
Type II	- Sheet tissue	
	Single fold	No stock No.
	Double fold 8540-00-170-8792	Box of 100 packages

6.10 Polish, furniture, liquid - P-P-553.

Type II	- Class 1	
	7930-00-576-2031	1 qt. (0.95 L) bottle
Type II	- Class 2	
	7930-00-985-6893	1 qt. (0.95 L) bottle

Source: https://assist.dla.mil -- Downloaded: 202640-23T23:20Z
Check the source to verify that this is the current version before use.

6.11 Polish, metal - P-P-556.

Type II - Class 2 (liquid)	
7930-00-995-7572	1 qt. (0.95 L) can
Type III - Class 2 (paste)	
7930-00-995-7573	1 lb. (0.45 kg) can

6.12 Remover, floor polish - P-R-1760.

7930-00-045-6912	5 gal. (18.9 L) can
7930-00-045-6931	55 gal. (208 L) drum

6.13 Scouring powder - P-S-311.

Type I - 7930-00-205-2868	14 oz. (397 g) can
7930-00-721-8592	21 oz. (595 g) can

6.14 Sealer, surface, varnish type - TT-S-176.

Class 1 8010-00-243-0962	5 gal. (18.9 L) pail
Class 2 8010-00-597-8210	1 gal. (3.8 L) can

6.15 Soap, saddle (leather goods) - P-S-609.

7930-00-170-5467	1 lb. (0.45 kg) can

6.16 Soap, toilet (cake and powdered) - P-S-620.

Type I - Class 1 (white floating cake)	
8520-00-551-0376	Box of 500 cakes
Type I - Class 2 (milled cake)	
8520-00-634-0336	Box of 144 cakes
Type II - Powdered	
8520-00-228-0985	5 lb. (2.3 kg) box

6.17 Soap, toilet (liquid and paste) - P-S-624.

Type I - (liquid)	
8520-00-228-0598	6 gal. (23 L) can
8520-00-141-2519	55 gal. (208 L) drum
Type II (paste)	
8520-00-261-8273	8 lb. (3.6 kg) can
8520-00-231-2997	120 lb. (54 kg) drum

Source: https://assist.dla.mil -- Downloaded: 202610-23T23:20Z
Check the source to verify that this is the current version before use.

6.18 Soap, borax (powdered) - P-S-625.

Class 1 (regular)	
8520-00-270-0258	5 lb. (2.3 kg) box
Class 2 (with lanolin)	
8520-00-270-0065	5 lb. (2.3 kg) box

6.19 Sodium phosphate - O-S-642.

Type I - 6810-00-664-7487	100 lb. (45 kg) drum
Type II - 6810-00-240-2116	100 lb. (45 kg) drum

6.20 Sweeping compound - P-S-863.

Type I - 7930-00-132-5265	100 lb. (45 kg) drum
Type II - 7930-00-633-9849	100 lb. (45 kg) drum

6.21 Towel, paper - UU-T-591.

Type I - Singlefold	
8540-00-262-7178	Box of 50 packages
Type II - Multifold	
Size 1 8540-00-291-0389	Box of 30 packages
Size 2 8540-00-291-0390	Box of 30 packages
Type III - C-fold 8540-00-291-0392	Box of 30 packages
Type IV - Roll towels 8540-00-291-0391	Box of 25 rolls

6.22 Wax, floor, water-emulsion - P-W-155.

7930-00-141-5888	5 gal. (18.9 L) pail
7930-00-205-2871	55 gal. (208 L) drum

6.23 Wool, metallic - FF-W-1825.

Type I - Class 0	
5350-00-242-4405	1 lb. (0.45 kg) package
Type I - Class 1	
5350-00-242-4404	1 lb. (0.45 kg) package

Source: https://assist.dla.mil -- Downloaded: 202610-23T23:20Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Air Force - 99

Review activities:

Army - MD, EA

User activities:

Army - AL
Navy - YD

Preparing activity:

Army - GL

Project No. 7930-0339

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:20Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-STD-1158A CUSTODIAL CLEANING SERVICES

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:20Z
Check the source to verify that this is the current version before use.