INCH-POUND

MIL-STD-1488H
02 February 2021
SUPERSEDING
MIL-STD-1488G
30 March 1990

DEPARTMENT OF DEFENSE
STANDARD PRACTICE

PROVISIONS FOR EVALUATING OF QUALITY

OF TROUSERS

AMSC N/A

FSC 8405

DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

FOREWORD

1. This standard is approved for use by the Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

2. This standard is intended to provide standard practice for quality inspections of men's trousers. This standard provides the following information:

- A standard method for visually inspecting and evaluating the quality of trousers
- Standard descriptions for trousers defects
- Standardized examination requirements for trousers

3. Trousers covered by this document are designated as Dress, Semi-Dress and Utility. Semi-dress trousers are sometimes referred to as "Service Uniform" trousers. If an end-item specification includes a list of defects or exceptions to this standard, the end-item specification shall prevail. For provisions for evaluating quality of women's slacks MIL-STD-656 should be used.

4. Comments, suggestions, or questions on this document should be addressed to: Attn: DLA Troop Support, 700 Robbins Street, Philadelphia, PA 19111-5096. Since contact information can change, you may want to verify the currency of this address information using Acquisition Streamlining and Standardization Information System (ASSIST) online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

CONTENTS

PARAGRAPH		PAGE
	FOREWORD	ii
1.	SCOPE	1
1.1	Scope	1
1.2	Purpose	1
1.3	Applicability	1
1.4	Classification	1
2.	APPLICABLE DOCUMENTS	1
2.1	General	1
2.2	Government documents	1
2.3	Non-Government publications	1
2.4	Order of precedence	2
3.	DEFINITIONS	2
3.1	Defective button	2
3.2	End-item	2
3.3	Fabric defects	2
3.4	Inside and outside	2
3.5	Knots and slubs	2
3.6	Major defect	2
3.7	Minor defect	2
3.8	Puckering	3
3.9	Quality assurance terms and procedures	3
3.10	Raw edge	3
3.11	Seams and stitching	3
3.11.1	Open seam	3
3.12	Trousers	3
4.	GENERAL REQUIREMENTS	3
4.1	General	3
4.2	Normal viewing conditions	3
5.	DETAILED REQUIREMENTS	3
5.1	Sampling and acceptance criteria	3
5.2	End-item dimensional examination	4
5.3	End-item visual examination	4
5.4	Shade variation examination	18
5.4.1	Shade match and appearance examination	18

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

CONTENTS

PARAGRAPH		PAGE
6.	NOTES ……	18
6.1	Intended use ……..	18
6.2	Acquisition requirements ……..	18
6.3	Subject term (key word) listing ……	18
6.4	Changes from previous issue ……..	18
TABLE I.	End-item defects ……..	5-17

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 Scope. This standard covers the inspection provision requirements for trousers worn by members of the military.

1.2 Purpose. The purpose of this document is to provide standardized examination provisions for evaluating the quality of trousers. It is intended to, in a single document, list defects irrespective of fabrics used.

1.3 Applicability. This standard is applicable to contracts by reference in the appropriate trousers specifications.

1.4 Classification. The trousers will be of the following types:

D - Dress
SD - Semi-Dress
U - Utility

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3, 4 or 5 of this standard. This section does not include documents cited in other sections of this standard or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3, 4 and 5 of this standard, whether or not they are listed.

2.2 Government documents. No Government documents are currently specified in this standard.

2.3 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

AMERICAN ASSOCIATION OF TEXTILE CHEMISTS AND COLORISTS

68373A: AATCC Photographic Seam Smoothness Scales

(Scales are available at https://www.aatcc.org)

AMERICAN SOCIETY FOR QUALITY

ASQ/ANSI Z1.4 - Sampling Procedures and Tables for Inspection by Attributes

(Copies of this document are available online at https://www.asq.org.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

ASTM INTERNATIONAL

ASTM D3990 - Standard Terminology Relating to Fabric Defects
ASTM D6193 - Standard Practice for Stitches and Seams

(Copies of these documents are available online at https://www.astm.org.)

Fabric Defect Replica Scales

(For information on obtaining copies of the Fabric Defect Replica Scales please contact U.S. Army Combat Capabilities Development Command (CCDC), Soldier Center, ATTN: FCDD-SCD-PE, 10 General Greene Avenue, Natick, MA 01760-5019.)

2.4 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document or end-item specific documents supersedes applicable laws and regulations, unless a specific exemption has been obtained.

3. DEFINITIONS

3.1 Defective button. A button will be considered defective when it is broken or cracked; has sharp, rough or split edges; has scratches or dents, blemishes or foreign matter embedded or is unevenly shaded. Additional button defects may be found in the defects tables in section 5 of this standard or in applicable button specifications.

3.2 End-item. End-item refers to finished trousers ready for inspection and acceptance.

3.3 Fabric defects. Fabric defects specified in Table I are defined in ASTM D3990. Fabric defects not specified in Table I are specified in the appropriate fabric specification.

3.4 Inside and outside. The term “inside” refers to any part of the trousers that are not visible when completely closed and fastened, while the term “outside” refers to any part of the trousers that are visible when the completely closed and fastened.

3.5 Knots and slubs. Only knots and slubs on the outside of the trousers that exceed the limits in the basic cloth specification will be scored as defects in evaluating quality of the finished trousers. Knots and slubs are rated using Fabric Defect Replica Scales (see 2.3).

3.6 Major defect. A departure of a quality characteristic from its intended level of the specification that occurs with a severity sufficient that is likely to result in a failure, or to reduce considerably the usability of the trousers for its intended purpose.

3.7 Minor defect. A departure of a quality characteristic from its intended level of the specification but the trousers are still considered serviceable. (Multiple minor defects may render trousers or production lot unserviceable).

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

3.8 Puckering. Refers to the gathering of a seam/stitches during sewing, after sewing and after laundering causing unacceptable seam appearance when compared to the 68373A; AATCC Photographic Seam Smoothness Scales (see 2.3). Puckering on major portions of the suspected seam that has a rating of less than "4" will be scored as a puckered seam.

3.9 Quality assurance terms and procedures. Definitions of quality assurance terms and procedures, where applicable, will be in accordance with ASQ/ANSI Z1.4.

3.10 Raw edge. Raw edge is defined as any fabric edge not serged or otherwise finished to prevent raveling.

3.11 Seams and stitching. Unless otherwise specified, seams and stitching will be as defined in ASTM D6193. Open seam defects will be as defined in 3.11.1.

3.11.1 Open seam. A seam will be considered open when stitching joining the seam area are broken, skipped or missing stitches. (Seams with multiple rows of stitching are considered open when any of the criteria in this section are met by any one or more of the rows.)

3.12 Trousers. The term "trousers" refers to "an outer garment covering the body from the waist to the ankles, with a separate part for each leg". Trousers typically refers to items meeting this description that are worn by men, but many unisex items are also referred to with the term trousers.

4. GENERAL REQUIREMENTS

4.1 General. This standard contains provisions and terminology for end-item inspection of dress, semi-dress and utility trousers. If there are any inconsistencies between the requirements of the appropriate end-item specification and the provisions of this standard, the end-item specification shall govern.

4.2 Normal viewing conditions. Normal viewing conditions for the inspection of trousers is three (3) feet from the surface being examined. Unless otherwise specified, trousers shall be examined while laid flat on a suitable table using the following illumination criteria. The overhead direct lighting source shall be parallel to the viewing surface so as to illuminate with direct perpendicular impinging light rays. The surface illumination level shall be a minimum of 1075 lux (100 foot candles). The lights shall be cool white preheat rapid start fluorescent lamps with white reflectors and without baffles or glass.

5. DETAILED REQUIREMENTS

5.1 Sampling and acceptance criteria. The sample unit shall be one pair of finished trousers and lot size shall be expressed in the number of sample units. The sample size and Acceptance Quality Limits (AQLs) shall be as specified in the contract or purchase order. Sampling for inspection shall be conducted in accordance with ASQ/ANSI Z1.4 – Sampling Procedures and Tables for Inspection by Attributes. Sampling shall represent all

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

types, classes, and styles included in the production lot, and shall include samples from the beginning, middle and end of production of the end specification.

5.2 End-item dimensional examination. Finished trousers shall be examined for conformance to the finished measurements as stated in the end item specification. The sample size for end item dimensional examination shall be as specified in the contract or purchase order.

5.3 End-item visual examination. The trousers shall be examined for the defects stated in Table I of this document. Defects are assigned as “Major” or “Minor”. The sample unit shall be one pair of finished trousers.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects.

Defect description	Defect Category					
	Dress		Semi-Dress		Utility	
	Major	Minor	Major	Minor	Major	Minor
I. MATERIAL DEFECT AND DAMAGE:						
Any hole, cut, tear, smash, burn, drill hole, scorched area and/or multiple float:						
- Up to ¼-inch, inclusive	101		101			201
- More than ¼-inch in any direction	102		102		101	
Any knot and/or slub 1/		201		201		202
Misweave, area of poor/no dye (print) penetration, dye streak, missing yarn, broken yarn, visible mend, thin place, shade bar and barre		202		202		203
Loose yarn, snag and/or coarse yarn more than ½-inch in any direction on outside	103			203		204
Woven in debris and/or waste on outside visible at 3-feet		203		204		205
II. SHADED PARTS						
Variation and shade within a part or between parts	104		103			206
III. STITCHING AND SEAM DEFECTS						
Needle chew:						
- Up to ¼-inch, inclusive, in any direction		204		205		207
- More than ¼-inch in any direction	105		104		102	
Seam allowance not as specified		205		206		208
Raw edge of fabric not as specified (except where pinking is required)		206		207		209
Seams irregular, twisted, wavy and/or pleated	106			208		210
Wrong seam and/or stitch type	107		105		103	

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Defect Category					
	Dress		Semi-Dress		Utility	
	Major	Minor	Major	Minor	Major	Minor
III. STITCHING AND SEAM DEFECTS (continued)						
Any line of stitching omitted	108		106		104	
Any line of stitching not starting and/or ending where specified		207		209		211
Basting stitch visible on outside of the finished trousers		208		210		212
Gauge irregular and/or not within range specified (score only when condition exists on more than ½-inch the length of the seam)		209		211		213
Stitches per inch incorrect		210		212		214
Loose stitch tension:						
- Up to ½-inch inclusive		211		213		215
- More than ¾-inch	109		107		105	
Tight stitch tension (all seams)	110		108		106	
Seam puckered 2/ (score only on major portion of seam)	111		109			216
Any part of trousers caught in an unrelated operation and/or stitching	112		110		107	
End of stitching, when not caught in another seam, not backstitched as specified		212		214		217
Thread break not repaired by backstitching at least ½-inch		213		215		218
Ends of a continuous line of stitching not overlapped by at least ½-inch		214		216		219
Open seam (see 3.11.1) and/or runoff:						
- Up to and including ½-inch		215		217		220
- Greater than ½-inch	113		111		108	

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. - Continued

Defect description	Defect Category					
	Dress		Semi-Dress		Utility	
	Major	Minor	Major	Minor	Major	Minor
III. STITCHING AND SEAM DEFECTS (continued)						
Inseam and/or outseam not lapped as specified	114			218		221
Ends of inseams staggered at crotch more than ½-inch (center to center)	115			219		222
Pleated and/or twisted at base of pocket and/or placket opening	116			220	--	--
Front and seat seams not joined in one continuous operation (when applicable)		216		221		223
Seat seam outlet omitted		217		222		224
IV. COMPONENTS						
Any component omitted and/or part not as specified and/or twisted, unless otherwise specified below	117		112		109	
Thread/gimp color not as specified	118		113			225
Button not as specified, broken, bent, cracked		218		223		226
Snap fastener						
Not as specified	--	--	114		110	
Non-functioning (broken, bent, cracked)	--	--	115		111	
Hook and eye/bar fastener						
Not as specified	119		116		112	
Non-functioning (broken, bent, cracked)	120		117		113	
Hook and loop fastener						
Not as specified	--	--	--	--	114	
Non-functioning	--	--	--	--	115	
Slide fastener						
Not as specified	121		118		116	

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Defect Category					
	Dress		Semi-Dress		Utility	
	Major	Minor	Major	Minor	Major	Minor
IV. COMPONENTS (continued)						
Slide fastener (continued)						
Cut, hole and/or tear in tape	122		119		117	
Slider does not operate smoothly (binds, catches or sticks)		219		224		227
Drawcord(s)						
Not as specified	--	--	--	--		228
End(s) not finished as specified	--	--	--	--		229
Binding						
Material type and/or color not as specified		220		225		230
Not cut as specified (e.g., on the bias)		221		226		231
Width of finished binding not as specified		222		227		232
Waistband						
Waistband gripper tape not as specified		223		228		233
Label						
Not as specified (material)		224		229		234
Missing, incorrect and/or illegible information	123		120		118	
Braid/cord						
Braid/cord/stripes not as specified	124		121		--	--
Fusing material						
Not as specified	125		122		--	--

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Defect Category					
	Dress		Semi-Dress		Utility	
	Major	Minor	Major	Minor	Major	Minor
V. CONSTRUCTION						
Unless otherwise specified, items intended to be equal length and/or in alignment that differ by more than ½-inch and ⅛-inch respectively	126		123		119	
Any component part not cut and/or sewn in accordance with specified directional lines, twill lines and/or fabric grain not parallel between parts	127		124		120	
Excessive bulging, twisting, pulling and/or puckering at closures when fasteners and/or closure devices are properly positioned according to marks on patterns	128		125		121	
Notch exposed at pocket opening	129		126		122	
Top of pocketing not securely inserted under waistband causing bulge and distortion on the outside	130		127		123	
Pocketing caught in unrelated stitching	131		128		124	
Buttonhole						
Not as specified, misplaced, omitted, added, not finished as specified	132		129		125	
Gimp omitted, uncut buttonhole, incomplete stitching	133		130		126	
Two (2) or more skipped or loose stitches		225		230		235
Button						
Misplaced, missing, insecurely and/or improperly sewn		226		231		236
Location not as specified		227		232		237
Number of buttons not as specified		228		233		238
Snap fastener						
Not attached as specified, missing	--	--	131		127	
Male and female sides misaligned by more than ⅛-inch when trousers are properly oriented	--	--		234		239

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Defect Category					
	Dress		Semi-Dress		Utility	
	Major	Minor	Major	Minor	Major	Minor
V. CONSTRUCTION (continued)						
Hook and eye/bar fastener						
Not attached as specified	134		132		128	
Not positioned as specified causing bulging, puckering, twisting and/or pulling	135		133		129	
Male and female sides misaligned:						
- Misaligned by ≥ ¼-inch	136		134		130	
Hook and loop fastener						
Not attached as specified	--	--	--	--	131	
Hook and loop sides misaligned:						
- Misaligned by ≥ ¾-inch	--	--	--	--	132	
Bartack or tack						
Missing, insecure, misplaced, not serving intended purpose and/or not specified size and/or type:						
- Bartack for attachment	137		135		133	
- Bartack for reinforcement		229		235		240
Incorrect number of stitches		230		236		241
Loose and/or tight stitch tension		231		237		242
Waist adjustment strap or tab						
Not attached and/or finished as specified, missing	--	--	136		134	
Slide fastener						
Not attached as specified	138		137		135	
Opening greater than ⅛-inch at top when fully secured		232		238		243
Uneven at top by more than ¼-inch	139		138		136	
Bottom stop not positioned within ⅜-inch of front seam		233		239		244

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Defect Category					
	Dress		Semi-Dress		Utility	
	Major	Minor	Major	Minor	Major	Minor
V. CONSTRUCTION (continued)						
Slide fastener (continued)						
Stitching too close to chain not permitting slider to pass freely	140		139		137	
Slide fastener thong missing and/or incorrectly attached	--	--	--	--		245
Bottom stop not securely stapled	141		140		138	
Slide fastener thong						
Length of thong not as specified	--	--		240		246
End of thong not finished as specified	--	--		241		247
Drawcord(s)						
Finished length not as specified		234		242		248
Eyelet misplaced and/or not positioned as specified		235		243		249
Stay stitch omitted		236		244		250
Drawcord does not move freely		237		245		251
Binding						
Not attached or finished as specified	142		141		139	
Tight and/or twisted, causing puckering and/or pleating		238		246		252
More splices than specified		239		247		253
Waistband						
Width of finished waistband and linings not as specified		240		248		254
Waistband not uniformly stitched to top of trousers causing waviness, pleats, twist of waistband, lining visible on outside	143		142		140	
Joining seam (center back) not aligned with seat seam by ⅛-inch or more	144		143			255
Bottom edges of waistband extensions not in line with waistband joining seam by more than ¼-inch, when trousers are buttoned		241		249		256

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Defect Category					
	Dress		Semi-Dress		Utility	
	Major	Minor	Major	Minor	Major	Minor
V. CONSTRUCTION (continued)						
Waistband (continued)						
Waistband extension not specified distance from fold and/or welt to point of tab or underside exposed by ⅛-inch.		242		250		257
Linings not as specified and exposed on outside		243		251	--	--
Non-slip tape as specified	145		--	--	--	--
Waistband interlining/fusing not as specified, bubbling, delamination	146		--	--	--	--
Waist adjustment strap and/or tab missing	--	--	--	--	141	
Belt loops						
Belt loops missing, and/or incorrect number	147		144		142	
Finished width and length not as specified		244		252		258
Not attached and/or finished as specified		245		253		259
Placement more than ¼-inch from specified location		246		254		260
Opening differs from specified by more than ⅛-inch		247		255		261
Center back loop not centered on seat seam by more than ¼-inch		248		256		262
Bartacks not as specified		249		257		263
Darts (if applicable)						
Not type specified; not properly tapered causing bulging, twist, fullness, and/or opening	148			258		264
Lower end not extending into pocket opening, incomplete		250		259		265
Length of darts differs by more than ¼-inch	149		145			266
Front opening						
Opening orientation incorrect	150		146		143	
J stitch not as specified		251		260		267

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Defect Category					
	Dress		Semi-Dress		Utility	
	Major	Minor	Major	Minor	Major	Minor
V. Construction (continued)						
Front opening (continued)						
Left fly facing exposed when slide fastener is closed	151		147			268
Right fly facing exposed when slide fastener is closed		252		261		269
Fly attachment seam visible on outside of trousers	152		148			270
Slide fastener tapes show when the trousers are fully closed	153		149			271
Fly tab not positioned as specified		253		262		272
Pockets or flap:						
General pocket information:						
Pocket or flap out of alignment from each other by more than ½-inch when intended to be in corresponding locations	154		150		144	
Poor pocket construction causing fullness and/or distortion	155		151		--	--
Pocket openings uneven in length up to ¼-inch		254		263		273
Raw edge of pocket opening exposed	156			264		274
Pocket flap not as specified, crooked, poorly shaped and/or constructed, not covering pocket opening	157		152			275
Pocket bag material not as specified		255		265		276
Depth of pocket not as specified by more than ½-inch	158		153		145	
Pocket bag improperly sewn, causing fullness, twisting and/or bunching	159			266		277
Pocket bag material caught in an unrelated operation	160			267		278
Welt pocket information:						
Pocket opening welt not as specified	161		154		--	--
Poorly shaped and/or not uniform in shape or size	162		155		--	--
Irregular in-width by more than 3/16-inch	163		156		--	--

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Defect Category					
	Dress		Semi-Dress		Utility	
	Major	Minor	Major	Minor	Major	Minor
V. Construction (continued)						
Welt pocket information (continued)						
Welts out of horizontal alignment with waistband when measured from bottom of waistband to top corners of welt up to ¼-inch:	164		157		--	--
Finish depth and width of welt not as specified	165		158		--	--
Welts out of alignment from each other when measured from the bottom waistband straight down to top edge of outside and inside end of welt by ¼-inch	166		159		--	--
Hip pocket information:						
Cord and/or welt not as specified width	--	--		268		279
Hip pocket cord and/or bearer not caught in the edge stitching of pocketing	--	--		269		280
Side pocket and/or hanging type pocket information:						
Pocketing facing too tight and/or loose causing edge of pocket opening to be wavy		256		270	--	--
Facing or bearer not caught in bartack at each end of opening; facing and/or bearer not extending below bottom bartack and above top bartack	167		160			281
Pocketing notched more than ¼-inch beyond width of outseam allowance on the underside		257		271		282
Bartack extends beyond outseam no more than ⅛-inch	--	--		272		283
Cargo pocket information:						
Shape not as specified	--	--	--	--	146	
Pleats not as specified	--	--	--	--	147	

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Defect Category					
	Dress		Semi-Dress		Utility	
	Major	Minor	Major	Minor	Major	Minor
V. Construction (continued)						
Cargo pocket information (continued)						
Center of button out of alignment with buttonhole in flap causing distortion, bunching and/or twisting when buttoned.	--	--	--	--		284
Bellows shape and/or size not as specified	--	--	--	--	148	
Cargo pockets do not align (right and left leg)	--	--	--	--		285
Drawcord lock/toggle missing and/or not functioning	--	--	--	--	149	
Eyelets omitted	--	--	--	--	150	
Eyelets not as specified	--	--	--	--	151	
Fabric inside of eyelet not completely cut and/or removed	--	--	--	--		286
Eyelet stitches not securely caught in fabric	--	--	--	--	152	
Shin/lower leg pocket						
Shape not as specified	--	--	--	--	153	
Center of button out of alignment with buttonhole in flap causing distortion, bunching and/or twisting when buttoned.	--	--	--	--		287
Bellow shape or size not as specified	--	--	--	--	154	
Eyelets not as specified	--	--	--	--	155	
Drawcord lock/toggle missing and/or not functioning	--	--	--	--	156	
Pockets do not align (right and left leg)	--	--	--	--		288
Seat patch						
Missing, not properly placed	--	--	--	--	157	
Knee patch						
Misplaced (i.e. not serving intended purpose)	--	--	--	--		289
Omitted or not securely caught in either inseam /outseam	--	--	--	--	158	

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Defect Category					
	Dress		Semi-Dress		Utility	
	Major	Minor	Major	Minor	Major	Minor
V. Construction (continued)						
Hem/leg bottom						
Not finished as specified		258		273		290
Unhemmed bottoms uneven by more than ½-inch at inseams and outseams		259		274	--	--
Width of hem not as specified and/or irregular by more than ¼-inch		260		275		291
Leg tie tape						
Length not as specified	--	--	--	--		292
Ends not finished as specified	--	--	--	--		293
Not attached as specified	--	--	--	--		294
Label						
Not as specified, missing, incorrect and/or illegible	168		161		159	
Braid/stripes (when required)						
Not as specified, missing,	169		162		--	--
Not completely caught in waistband seam	170		163		--	--
Twisted, bulging, bunched and/or puckered	171		164		--	--
Stripes not centered over outseam and not even with edge of side pocket	172		165		--	--
VI. PRESSING AND CLEANING EFFECTS						
Pressing omitted and/or poorly pressed, or exhibiting a double crease line:						
- On permanent crease and/or durable press	173		166		160	
- On other than permanent crease and/or durable press	174			276		295

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

TABLE I. End-item defects. – Continued

Defect description	Defect Category					
	Dress		Semi-Dress		Utility	
	Major	Minor	Major	Minor	Major	Minor
VI. PRESSING AND CLEANING EFFECTS (continued)						
Pressing not seam on seam by more than ½-inch:						
- On permanent crease or durable press	175		167			296
- On other than permanent crease and/or durable press		261		277		297
Permanent crease omitted:						
- ≤1-inch	176		168			298
Permanent crease line not ending within specified limits	177		169			299
Seam allowance not pressed open		262		278	--	--
Burned and/or scorched in pressing	178		170		--	--
Gloss and/or impressions not removed		263		279	--	--
Any spot and/or stain that cannot be completely removed with a clean cloth moistened with water:						
- 1/16 to ⅜-inch, inclusive		264		280		300
- >⅜-inch up to and including ¾-inch	179		171			301
Three (3) or more thread ends on the outside greater than and/or equal to ½-inch		265		281		302
Re-sewn and/or re-stitched seams not cleaned	180		172			303
Thread end caught in a line of stitching on the outside for more than ¼-inch		266		282		304

1/ Knots and slubs shall be rated in accordance with the Fabric Defect Replica Scales.
2/ Puckering shall be rated in accordance with the AATCC Photographic Seam Smoothness Scales (see 2.3).
Puckering on major portions of the suspected seam that has a rating of less than “4” shall be scored as a puckered seam.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

5.4 Shade variation examination. During the examination, each pair of trousers in the sample shall be examined for shade variation. Any trouser in the sample containing uneven shade or shade variation, within a part or between parts, shall be cause for rejection of entire lot represented by the sample.

5.4.1 Shade match and appearance examination. The shade match and appearance examination shall be conducted as specified in the material specification, contract or purchase order.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. To provide a standardized examination procedure for evaluating quality of men's trousers that are worn by members of the military as part of dress, semi-dress and utility uniforms. These defects are typical of those included in quality inspections of trousers.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this standard
b. Type of material defects allowed.
c. The specific issue of individual documents referenced (see 2.3)
d. Acceptance Quality Levels (AQLs)
e. Sample size

6.3 Subject term (key word) listing.

Defect
Dress uniform
Examination
Inspection
Semi-Dress uniform
Utility uniform

6.4 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.

Custodians:
Army – GL
Navy – NU
Air Force – 11

Preparing activity:
DLA - CT

(Project 8405- 2021-003)

Review activities:
Army – MD
Navy – AS, CG1, MC

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using ASSIST online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T00:30Z
Check the source to verify that this is the current version before use.