MIL-S- 50563 (AR)
7 July 1977
SUPERSEDING
See Section 6

MILITARY SPECIFICATION

SUPPORT, ADAPTION KIT COMPONENTS: XM9

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of kit entitled Support, Adaption Kit Components: XM9 which is used with the Sprint warhead.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

QQ-M-56 - Magnesium Alloy, Sand Castings.

MILITARY

MIL-C-6021 - Castings, Classification and Inspection of.
MIL-T-12076 - Tin, Strip and Sheet.
MIL-I-45932 - Insert, Screw Thread, Thin Wall, Locked in; General Specification For.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-1168 - Lot Numbering of Ammunition.
MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components.

Beneficial comments (recommendations, additions, deletions), and any pertinent data which may be of use in improving this document, should be addressed to: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAN-Q, Dover, New Jersey 07801, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426), appearing at the end of this document, or by letter.

FSC 1135

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

DRAWINGS

ORDNANCE CORPS

8888398	- Gasket, Inner.
9234436	- Cover.
9234966	- Gasket, Outer.
9268963	- Support, Adaption Kit Components: XM9.
9271630	- Support, Assembly, Adaption Kit.
9274351	- Box, Fiberboard, Packing for Support, A.K. Casting XM9.
9277416	- Support, Machined, Adaption Kit.
EL-8888398	- Equipment List.
EL-9234436	- Equipment List.
EL-9234966	- Equipment List.
EL-9271630	- Equipment List.
EL-9277416	- Equipment List.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The kit shall comply with all requirements specified on the drawing (dwg) 9268963, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 First article testing. Requirements for the submission of first article samples by the contractor shall be as specified in the contract (see 4.2).

3.4 Serialization. The contractor shall assign serial numbers as required by drawings. The contractor may select any number which complies with the drawing requirement. These numbers shall not be duplicated.

3.5 Conductivity (Support, Machined Adaption Kit). The resistance between surfaces, around holes 57, 58, 59, 60, 61, 62 and any part on the inner and outer mounting surfaces (see dwg 9271630) shall not exceed 50 milliohms when tested as specified in 4.4.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

3.6 Tensile test bars. Test bars shall be supplied for each melt from which castings are poured and shall be in accordance with QQ-M-56.

3.6.1 Identification. All castings and related test bars shall be impression marked by the contractor. Location of impression markings on the casting shall be specified by the procuring activity.

3.7 Plating. A plated coupon from each batch of castings plated at one time shall be furnished by the contractor. The base material of the coupon shall be of the same composition as the castings. All castings and related coupons shall be identified utilizing a system which will have no deleterious effect on the plated surfaces.

3.8 Workmanship.

3.8.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.8.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.8.3 Burrs. Parts shall be free from burrs.

3.8.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.8.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.

4.2.1 Quantity to be submitted. When the contract requires first article inspection, the contractor shall submit 2 complete assemblies (see dwg 9268963) for first article testing to the testing facility designated in the invitation for bids or request for proposal.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

4.2.2 Inspection and testing to be performed. The first article inspection sample shall be subjected to the inspections and tests specified in Table I. Tests shall be conducted in order specified in Table I.

Table I

First article inspection and tests

Inspection or Test	Dest	Non-Dest
1. Classification of characteristics/ defects (see 4.3.2.1)		X
2. Conductivity (see 3.5)		X

4.2.3 Inspection equipment. The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.1.

4.2.4 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Quality conformance inspection.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor defects/characteristics table (see Table II and Table III), and inspected for all defects/characteristics in the applicable classification. Any defects/characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of defects/characteristics in each classification need not be followed as long as all defects/characteristics inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

Table II
Major Defects/Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Table III
Minor Defects/Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

4.3.2.1 Classification of defects/characteristics (see 3.2). Critical, major and minor defects/characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Support, machined, adaption kit (see dwg 9277416) before installing inserts.

Categories	Defects/Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Outer ring surface not flat (Sec A-A)	Gage
	102. Inner ring surface not flat (Sec A-A)	Gage
	103. Distance between outer ring surface and inner ring surface incorrect (Sec A-A)	Gage
	104. Thickness of inner ring incorrect (Sec A-A)	Gage
	105. Thickness and radial width of outer ring incorrect (Sec A-A)	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

Categories	Defects/Characteristics	Method of Inspection
106.	Length of holes at inner ring incorrect (12 places) (Sec A-A)	Gage
107.	Typical wall thickness incorrect (Sec A-A)	Gage
108.	Depth of well from spotface incorrect (Sec D-D)	Gage
109.	Distance between exterior of well and outer ring surface incorrect (Sec D-D)	Gage
110.	Wall thickness at well incorrect (Sec D-D)	Gage
111.	Incorrect minor diameter (19 places) (Sec E-E) and MIL-I-45932/1-7)	Gage
112.	Location of threaded holes incorrect (19 places) (Sec E-E)	Gage
113.	Drill depth incorrect (19 places) (Sec E-E)	Gage
114.	Depth and diameter of C'bore incorrect (19 places) (Sec E-E and MIL-I-45932/1-7)	Gage
115.	Depth of thread incorrect (19 places) (Sec E-E and MIL-I-45932/1-7)	Gage
116.	Incorrect pitch diameter of threaded hole (max) (1 place) (Sec F-F)	Gage
117.	Incorrect minor diameter (min) (1 place) (Sec F-F)	Gage
118.	Location of threaded hole incorrect (1 place) (Sec F-F)	Gage
119.	Drill depth incorrect (1 place) (Sec F-F)	Gage
120.	Depth of thread incorrect (1 place) (Sec F-F)	Gage
121.	Incorrect minor diameter (min) (8 places) (Sec G-G) (See MIL-I-45932/1-7)	Gage
122.	Location of threaded holes incorrect (8 places) (Sec G-G)	Gage
123.	Drill depth incorrect (min) (8 places) (Sec G-G) (See MIL-I-45932/1-3)	Gage
124.	Depth of thread incorrect (8 places) (Sec G-G) (See MIL-I-45932/1-3)	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

Categories	Defects/Characteristics	Method of Inspection
125.	Diameter and depth of C'bore incorrect (8 places) (Sec G-G) (See MIL-I-45932/1-3)	Gage
126.	Incorrect thickness (2 places) (Sec H-H)	Gage
127.	Incorrect minor diameter (min) (24 places) (Sec J-J) (See MIL-I-45932/1-3)	Gage
128.	Location of threaded holes incorrect (24 places) (Sec J-J)	Gage
129.	Depth and diameter of C'bore incorrect (24 places) (Sec J-J) (See MIL-I-45932/1-3)	Gage
130.	Radius at inner ring incorrect (Sec K-K)	Gage
131.	Incorrect inside diameter and location of well (2 places) (Sec L-L)	Gage
132.	Wall thickness at wells (side and bottom) incorrect (Sec L-L)	Gage
133.	Depth of wells incorrect (2 places) (Sec L-L)	Gage
134.	Distance between exterior of wells and outer ring surface incorrect (Sec L-L)	Gage
135.	Height of bosses around wells incorrect (12 places) (Sec L-L)	Gage
136.	Height of bosses incorrect (8 places) (Sec N-N)	Gage
137.	Wall thickness at spot faces incorrect (4 places) (Sec N-N)	Gage
138.	Wall thickness around spotfaces incorrect (Sec N-N)	Gage
139.	Incorrect minor diameter (min) (4 places) (Sec P-P)	Gage
140.	Location of threaded holes incorrect (4 places) (Sec P-P)	Gage
141.	Drill depth incorrect (4 places) (Sec P-P)	Gage
142.	Depth of thread incorrect (4 places) (Sec P-P) (See MIL-I-45932/1-9)	Gage
143.	Diameter and depth of C'bore incorrect (4 places) (Sec P-P) (See MIL-I-45932/1-9)	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

Categories	Defects/Characteristics	Method of Inspection
144.	Diameter of thru holes incorrect (holes 25, 26, 28, 30, 31, 33, 35, 36, 38, 40, 41, 42 and 44)	Gage
145.	Location of thru holes incorrect (holes 25, 26, 28, 30, 31, 33, 35, 36, 38, 40, 41, 42 and 44)	Gage
146.	Diameter of spotface incorrect (holes 64 and 65)	Gage
147.	Location of spotface incorrect (holes 64 and 65)	Gage
148.	Diameter of hole incorrect (hole 62)	Gage
149.	Location of hole incorrect (hole 62)	Gage
150.	Width across flat incorrect (hole 62)	Gage
151.	Diameter and depth of C'bore incorrect (hole 62)	Gage
152.	Location of spotface incorrect (hole 62)	Gage
153.	Incorrect radius at bottom of relief in casting lip (3 places)	Gage
154.	Incorrect location of radius at bottom of relief (3 places)	Gage
155.	Width of relief incorrect (3 places)	Gage
156.	Location of relief incorrect (3 places)	Gage
157.	Incorrect diameter of thru holes (holes 46, 47, 48, 49)	Gage
158.	Location of thru holes incorrect (holes 46, 47, 48, 49)	Gage
159.	Diameter and location of hole incorrect (hole 57)	Gage
160.	Hole size from flat incorrect (hole 57)	Gage
161.	Angular location of flat incorrect (hole 57)	Gage
162.	Diameter and location of C'bore incorrect (hole 57)	Gage
163.	Diameter and location of hole incorrect (hole 58)	Gage
164.	Hole size from flat incorrect (hole 58)	Gage
165.	Angular location of flat incorrect (hole 58)	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

Categories	Defects/Characteristics	Method of Inspection
166.	Diameter and location of C'bore incorrect (holes 58 and 59)	Gage
167.	Hole size from flat incorrect (hole 59)	Gage
168.	Angular location of flat incorrect (hole 59)	Gage
169.	Diameter and location of hole incorrect (hole 60)	Gage
170.	Hole size from flat incorrect (hole 60)	Gage
171.	Angular location of flat incorrect (hole 60)	Gage
172.	Diameter and location of C'bore incorrect (hole 60)	Gage
173.	Inside diameter of inner ring incorrect	Gage
174.	Location of inner ring inside diameter incorrect	Gage
175.	Location of hole incorrect (hole 59)	Gage
176.	Diameter of pad around inner ring incorrect (2 places)	Gage
177.	Location of pad around inner ring incorrect (2 places)	Gage
178.	Diameter of pads in well incorrect (8 places)	Gage
179.	Pad wall thickness between thread minor diameter & pad outside diameter incorrect	Gage
180.	Outside diameter of outer ring incorrect	Gage
181.	Specified height of webs and outside bosses incorrect	Gage
182.	Diameter and position of boss incorrect (Sec P-P) (4 places)	Gage
183.	Radii of bosses incorrect (67 thru 78)	Gage
184.	Location of bosses incorrect (67 thru 78)	Gage
185.	Thickness of webs incorrect (33 places)	Gage
186.	Webs missing or incorrect (30 places)	Visual/Gage
187.	Webs missing or incorrect (20 places)	Visual/Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

Categories	Defects/Characteristics	Method of Inspection
188.	Diameter and depth of spot faces incorrect (4 places)	Gage
189.	Diameter of C'bores incorrect (12 places)	Gage
190.	Outside diameter of inner ring face incorrect	Gage
191.	Location of inner ring face outside diameter incorrect	Gage
192.	Distance between inner ring inside diameter and webs incorrect (4 places)	Gage
193.	Insufficient, incorrect or missing web or fillet (all over)	Visual/Gage
194.	Objective evidence that casting complies with MIL-C-6021 (see 6.2)	Visual
195.	Protective finish missing or incomplete	Visual
196.	Thickness of protective finish incorrect	Gage
197.	Tensile test bars missing (see 3.6)	Visual
198.	Plating coupons missing (see 3.7)	Visual
199.	Incorrect inside diameter and position of well (2 places) (Sec D-D)	Gage
200.	Location of outer ring incorrect	Gage
101a.	Incorrect minor diameter (min) (1 place) (Sec M-M) (See MIL-I-45932/1-3)	Gage
102a.	Location of threaded hole incorrect (1 place) (Sec M-M)	Gage
103a.	Drill depth incorrect (1 place) (Sec M-M) (See MIL-I-45932/1-3)	Gage
104a.	Depth of thread incorrect (1 place) (Sec M-M) (See MIL-I-45932/1-3)	Gage
Minor:		
201.	Evidence of poor workmanship (see 3.8)	Visual
202.	Machined surface finish incorrect	Visual
203.	Draft angles incorrect	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

4.3.2.1.2 Support assembly adaption kit (see dwg 9271630) inserts installed.

Categories	Defects/Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Depth of installed inserts incorrect (56 places)	Gage
102.	Backout torque of installed inserts below minimum (56 places) (See note 3)	Gage
103.	Incorrect type of inserts installed in holes 83, 84, 85 and 86	Visual
104.	Primer coating missing or inserts	Visual
105.	Web or rib missing or broken	Visual
106.	Protective finish missing or incorrect (see note 8)	Visual
Minor:		
201.	Characters missing, improper, illegible or misplaced (see dwg note 4)	Visual
202.	Evidence of poor workmanship (see 3.8)	Visual
203.	Damaged or insufficient protective finish exposing base material	Visual
204.	Identification plate missing or improperly positioned	Visual

4.3.2.1.3 Cover (see dwg 9234436).

Categories	Defects/Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Incorrect outside diameter	Gage
102.	Concentricity of outside diameter incorrect	Gage
103.	Diameter of hole incorrect	Gage
104.	Inside diameter of well incorrect	Gage
105.	Concentricity of well to hole incorrect	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

Categories	Defects/Characteristics	Method of Inspection
	106. Incorrect overall height of cover	Gage
	107. Incorrect thickness of cover stock	Gage
	108. Diameter of holes incorrect (24 holes)	Gage
	109. Location of holes incorrect (24 holes)	Gage
	110. Diameter of countersunk hole incorrect (8 holes)	Gage
	111. Diameter of countersink incorrect (8 holes)	Gage
	112. Location of countersunk holes incorrect (8 holes)	Gage
	113. Diameter of holes incorrect (13 holes)	Gage
	114. Location of holes incorrect (13 holes)	Gage
	115. Incorrect width of recesses (3 places)	Gage
	116. Incorrect location of recesses (3 places)	Gage
	117. Incorrect distance from outside diameter to flat	Gage
	118. Dimension from bottom of recesses to outside diameter incorrect (3 places)	Gage
	119. Position of recess to flat on outside diameter incorrect	Gage
	120. Radii incorrect (12 places)	Gage
Minor:		
	201. Damaged or insufficient protective finish exposing base material	Visual
	202. Evidence of poor workmanship (see 3.8)	Visual

4.3.2.1.4 Gasket, inner (see dwg 8888398).

Categories	Defects/Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Width of gasket incorrect (Sec A-A)	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

Categories	Defects/Characteristics	Method of Inspection
	102. Diameter of holes incorrect (21 holes)	Gage
	103. Location of holes incorrect (21 holes)	Gage
	104. Inside diameter of gasket incorrect	Gage
	105. Objective evidence that gasket material complies with MIL-T-12076	Visual
Minor:		
	201. Evidence of poor workmanship (see 3.8)	Visual

4.3.2.1.5 Gasket, outer (see dwg 9234966).

Categories	Defects/Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Outside diameter incorrect	Gage
	102. Diameter of holes incorrect (24 holes)	Gage
	103. Position of holes incorrect (24 holes)	Gage
	104. Width of recesses incorrect (3 places)	Gage
	105. Location of recesses incorrect (3 places)	Gage
	106. Incorrect dimension from outside diameter to flat	Gage
	107. Width of gasket incorrect	Gage
	108. Objective evidence that gasket material complies with drawing	Visual
	109. Height of inserts incorrect (24 places)	Gage
	110. Radii incorrect (12 places)	Gage
Minor:		
	201. Evidence of poor workmanship (see 3.8)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

4.3.2.1.6 Preparation for delivery (see 5).

Categories	Defects/Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Conformance of packaging, packing and marking with MIL-STD-1169 and dwg 9274351	Visual
102.	Improper or insufficient strapping of loaded pallet (if applicable)	Visual
103.	Weight or height of loaded pallet (if applicable)	Gage
Minor:		
201.	Evidence of poor workmanship (see 3.8)	Visual

4.3.3 Testing. The contractor shall perform the test listed in this paragraph.

Test	Test Classification
a. Conductivity	Major

This test is not considered destructive and samples so tested may be returned to the lot.

4.3.3.1 Conductivity. Each Support, Machined, Adaption Kit shall be tested in accordance with 4.4.1. If any item fails to comply with 3.5, the item shall be rejected and removed from the lot.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Major defects/characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL) (see EL-8888398; 9234436; 9234966; 9271630; and 9277416). When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

4.3.4.2 Minor defects/characteristics and tests. Acceptance inspection equipment for minor defects/characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.4.1 Conductivity. A suitable electrical resistance measuring instrument with blunt probes shall be applied at random to the areas specified in 3.5. In the performance of this test the surface finish shall not be penetrated, marred or damaged.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The support assembly AK, and kit shall be packaged in accordance with dwg 9274351 and MIL-STD-1169 (as applicable) using the specified moisture barrier.

5.1.2 Level C. The support assembly AK, and kit shall be packaged in accordance with dwg 9274351 and MIL-STD-1169 (as applicable) except that the moisture barrier may be omitted.

5.2 Packing.

5.2.1 Level A and C. The support assembly AK, and kit shall be packed in accordance with dwg 9274351 (as applicable).

5.3 Marking. Marking shall be as specified in accordance with dwg 9274351 and MIL-STD-1169.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.3.2.1). Data specified in 4.3.2.1 will be delivered as identified on a numbered DD Form 1664 when required on a DD Form 1423 incorporated in the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAN-I, Dover, New Jersey 07801.

6.4 Supersession data. This specification supersedes the requirements of Purchase Description PA-PD-2229 dated 10 October 1972 and SCN No. 1 dated 2 October 1973.

Custodian:
Army - AR

Preparing Activity:
Army - AR

Project No. 1135-A225

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Armament R&D Command
ATTN: DRDAR-QAN-Q
Dover, NJ 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. *REMARKS*

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:29Z
Check the source to verify that this is the current version before use.