MIL-S-52159B
27 September 1971
SUPERSEDING
MIL-S-52159A
17 December 1963

MILITARY SPECIFICATION

SLING, MULTIPLE LEG:

5/8-INCH BY 6-FOOT CHAIN;

WITH SPECIAL HOOKS AND RING

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers a two-leg chain sling equipped with special hooks and a connecting ring.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-621	- Boxes, Wood, Nailed and Lock-Corner.

Military

MIL-C-16173	- Corrosion Preventive Compound, Solvent Cutback, Cold-Application.

FSC 5420

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:09Z
Check the source to verify that this is the currentversion before use.

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.

DRAWINGS

ME

DL13212E7099	- Sling, Multiple Leg.

(Copies of specifications, standards, and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Tariff Publishing Officer, Room 202, Union Station, 516 West Jackson Boulevard, Chicago, Illinois 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Tariff Order Section, 1616 P Street NW, Washington, D.C. 20036.)

3. REQUIREMENTS

3.1 Description. The sling shall be as shown on DL13212E7099 and as specified herein.

3.1.1 Drawings. The drawings forming a part of this specification are engineering design drawings. No deviation from the prescribed dimensions

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:09Z
Check the source to verify that this is the current version before use.

or tolerances is permissible without prior approval of the contracting officer. Any data (e.g., shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the supplier or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

3.2 First article (preproduction model). The supplier shall furnish a sling for examination and testing within the time frame specified to prove, prior to starting production, that his production methods will produce slings that comply with the requirements of this specification. Examination and tests shall be as specified in section 4 and shall be subject to surveillance and approval by the Government (see 6.3).

3.3 Material. Material shall be as specified herein and as shown on the drawings. Materials not specified shall be selected by the supplier and shall be subject to all provisions of this specification.

3.4 Performance. The assembled sling shall lift a load of 22,000 pounds for 5 minutes without rupture or permanent deformation in any of the chain links, hooks, connecting links, and the connecting ring. The included angle between the legs of the sling shall be 60 degrees plus or minus 5 degrees when lifting the load.

3.5 Workmanship. All surfaces shall be rounded and free from sharp edges, slivers, or burrs.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The supplier is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards.

4.1.2 Parts and components. Parts and components detailed on the drawings shall be inspected in accordance with the supplementary quality assurance

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:09Z
Check the source to verify that this is the current version before use.

provisions (SQAP) shown on the drawings. The drawings specify the characteristics requiring SQAP inspection, the sampling plan, and the basis for acceptance or rejection (see 6.4 and 6.5).

4.2 Classification of inspection. Inspection shall be classified as follows:

(a) Preproduction inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).
(c) Inspection of preparation for delivery (see 4.6).

4.3 Preproduction inspection.

4.3.1 Examination. The sling shall be examined for the defects specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Test. The sling shall be tested as specified in 4.5.2. Failure of the test shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for examination and test shall be in accordance with MIL-STD-105.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined for the major and minor defects specified in 4.5.1. AQL shall be 2.5 percent defective for major defects and 4.0 percent defective for minor defects.

4.4.3 Test. Samples selected in accordance with 4.4.1 shall be tested as specified in 4.5.2. AQL shall be 0.65 percent defective, inspection level III.

4.5 Inspection procedure.

4.5.1 Examination. The slings shall be examined for the following defects:

Major

101. Material not as specified.
102. Workmanship not as specified.
103. Incomplete or incorrect assembly.
104. Any part or component not in accordance with the SQAP requirements as shown on the drawings.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:09Z
Check the source to verify that this is the currentversion before use.

Minor

201. Identification marking incorrect, missing or illegible.
202. Dimensions other than those identified by SQAP data not as specified.

4.5.2 Test. Suspend an 11,000-pound load for 5 minutes from each hook of the sling while the legs of the sling form an included angle of 60 degrees plus or minus 5 degrees. Any evidence of breakage or permanent deformation shall constitute failure of this test.

4.6 Inspection of preparation for delivery.

4.6.1 Quality conformance inspection of pack.

4.6.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.6.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.6.1.3 Examination. Samples selected in accordance with 4.6.1.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

105. Slings not coated with the preservative specified.
106. Boxes not as specified for level A or B.
107. Blocking and bracing not adequate to prevent movement for level A or B.
108. Quantities packed together exceed limitations of the box for level A or B.
109. Strapping not zinc coated for level A.
110. Marking missing, illegible, incorrect, or incomplete.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging (see 6.6). Each complete sling shall be coated with preservative conforming to MIL-C-16173, grade 1.

5.2 Packing. Packing shall be level A, B, or C as specified.

5.2.1 Level A. The slings shall be packed together in a close-fitting box conforming to PPP-B-601, overseas type, style optional or PPP-B-621, class 2, style optional, in quantities not to exceed the weight limitation

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:09Z
Check the source to verify that this is the current version before use.

of the box. The contents shall be blocked and braced to prevent free movement. Closure shall be in accordance with the appendix to the applicable box specification. Strapping shall be zinc coated.

5.2.2 Level B. Packing shall be as specified in 5.2.1 for level A except boxes shall be domestic type or class as applicable and strapping shall not be required to be zinc coated.

5.2.3 Level C. The slings shall be packed to assure carrier acceptance and safe delivery to destination at lowest ratings in fiberboard or wooden containers complying with Uniform Freight Classification rules or National Motor Freight Classification rules.

5.3 Marking. Shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The two-leg chain sling is intended for use in the erection of fixed and floating bridges.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Time frame required for submission of preproduction model (see 3.2).
(c) Level of packing required (see 5.2).

6.3 Preproduction model. Any changes or deviations of production slings from the approved preproduction model during production will be subject to the approval of the contracting officer. Approval of the preproduction model will not relieve the supplier of his obligation to furnish slings conforming to this specification.

6.4 Supplementary Quality Assurance Provisions (SQAP). The contracting officer should require the supplier to maintain records of all SQAP inspections. A suggested paragraph is as follows:

"The supplier shall maintain complete records of all examinations and tests performed to verify the requirements of classified SQAP characteristics. The records shall include as a minimum, lot size, sample size, drawing requirement, actual measurement, number and type of deficiencies found, quantity approved, quantity rejected, corrected action taken when applicable."

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:09Z
Check the source to verify that this is the current version before use.

6.5 Definitions.

6.5.1 Supplementary Quality Assurance Provisions (SQAP). A SQAP is a contractual requirement that supplements section 4 of the specification. SQAP indicates the minimum requirements which must be inspected on the product drawings to verify the design objectives of the product and assure interchangeability of repair parts.

6.6 Levels of preservation have not been included as the preservation specified is the minimum acceptable for any level.

Custodians:

Army - ME

User activity:

Navy - MC

Preparing Activity:

Army - ME

Project No. 5420-0096

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:09Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:09Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION: MIL-S-52159B, Sling, Multiple Leg: 5/8 Inch by 6-Foot Chain; with Special Hooks and Ring

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:09Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
U. A. ARMY MOBILITY EQUIPMENT COMMAND
RESEARCH, DEVELOPMENT AND ENGINEERING DIRECTORATE
ATTN: AMSME-RZG
FORT BELVOIR, VIRGINIA 22060

OFFICIAL BUSINESS

POSTAGE AND FEES PAID

DEPARTMENT OF THE ARMY
U. S. ARMY MOBILITY EQUIPMENT COMMAND
RESEARCH, DEVELOPMENT AND ENGINEERING DIRECTORATE
ATTN: AMSME-RZG
FORT BELVOIR, VIRGINIA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:09Z
Check the source to verify that this is the current version before use.