INCH-POUND

MS90557J
w/AMENDMENT 3
10 April 2024
SUPERSEDING
MS90557J
w/AMENDMENT 2
24 February 2017

MILITARY SPECIFICATION SHEET

CONNECTOR, RECEPTACLE, ELECTRICAL, CABLE CONNECTING, (WITHOUT COUPLING RING), CLASS L

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-22992.




FIGURE 1. Dimensions and configuration.

AMSC N/A

FSC 5935

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:38Z
Check the source to verify that this is the current version before use.





FIGURE 1. Dimensions and configuration - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:38Z
Check the source to verify that this is the current version before use.



ACCESSORY INTERFACE DIMENSIONS

FIGURE 1. Dimensions and configuration - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:38Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm	Inches	mm
.001	0.03	.016	0.41	.120	3.05	.380	9.65
.002	0.05	.020	0.51	.130	3.30	.381	9.68
.005	0.13	.022	0.56	.135	3.43	.500	12.70
.006	0.15	.025	0.64	.142	3.61	.531	13.49
.008	0.20	.031	0.79	.164	4.17	.750	19.05
.010	0.25	.047	1.19	.217	5.51	1.125	28.58
.014	0.36	.062	1.57	.322	8.18	2.0	50.8
.015	0.38	.100	2.54	.375	9.53		

Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm
.005	0.13	1.138	28.91	1.935	49.15	2.678	68.02	3.156	80.16
.137	3.48	1.156	29.36	1.937	49.20	2.685	68.20	3.174	80.62
.143	3.63	1.281	32.54	1.938	49.23	2.687	68.25	3.185	80.90
.187	4.75	1.405	35.69	1.943	49.35	2.689	68.30	3.187	80.95
.198	5.03	1.514	38.46	2.015	51.18	2.693	68.40	3.193	81.10
.223	5.66	1.531	38.89	2.026	51.46	2.744	69.70	3.265	82.93
.229	5.82	1.539	39.09	2.104	53.44	2.765	70.23	3.276	83.21
.275	6.99	1.562	39.67	2.125	53.97	2.776	70.51	3.406	86.51
.286	7.26	1.655	42.04	2.188	55.58	2.781	70.64	3.646	92.61
.322	8.18	1.674	42.52	2.239	56.87	2.789	70.84	3.656	92.86
.338	8.59	1.685	42.80	2.354	59.79	2.905	73.79	3.667	93.14
.406	10.31	1.687	42.85	2.405	61.09	2.924	74.27	3.896	98.96
.417	10.59	1.693	43.00	2.428	61.67	2.935	74.55	3.917	99.49
.510	12.95	1.733	44.02	2.439	61.95	2.937	74.60	4.146	105.31
.526	13.36	1.765	44.83	2.494	63.35	2.943	74.75	4.167	105.84
.594	15.09	1.776	45.11	2.531	64.29	3.015	76.58		
.605	15.37	1.781	45.24	2.539	64.49	3.026	76.86		
.663	16.84	1.789	45.44	2.655	67.44	3.031	76.99		
.913	23.19	1.926	48.92	2.674	67.92	3.039	77.19		

FIGURE 1. Dimensions and configuration - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:38Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm
.001	0.03	1.130	28.70	1.609	40.87	2.453	62.31	8.688	220.68
.010	0.25	1.135	28.83	1.672	42.47	2.545	64.64	9.688	246.08
.011	0.28	1.187	30.15	1.692	42.98	2.692	68.38	10.125	257.18
.020	0.51	1.217	30.91	1.703	43.26	2.750	69.85	10.688	271.48
.035	0.89	1.250	31.75	1.734	44.04	2.755	69.98	11.062	280.97
.273	6.93	1.259	31.98	1.750	44.45	2.854	72.49	12.688	322.28
.523	13.28	1.312	33.32	1.786	45.36	2.875	73.02	13.688	347.68
.562	14.27	1.313	33.35	1.797	45.64	2.911	73.94	14.188	360.38
.672	17.07	1.342	34.09	1.867	47.42	2.953	75.01	17.188	436.58
.719	18.26	1.375	34.93	1.942	49.33	3.005	76.33	18.188	461.98
.742	18.85	1.391	35.33	2.000	50.80	3.161	80.29		
.844	21.44	1.438	36.53	2.183	55.45	3.250	82.55		
.922	23.42	1.516	38.51	2.250	57.15	6.688	169.88		
1.005	25.53	1.536	39.01	2.308	58.62	7.188	182.58		
1.047	26.59	1.547	39.29	2.328	59.13	8.156	207.16		
		1.558	39.57	2.448	62.18	8.188	207.98		

NOTES:

1. All dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified tolerances are ± .016 (0.41 mm).
4. Mates with plugs shown on MS90558.
5. Inserts and contacts are removable.
6. Normal keyway position. For alternate keyway positions, see figure 2.
7. G dimension from the front of the shell to the shoulder in the shell.
8. This depth is the point at which the square-ended gauge pin, of the same basic diameter as the mating pin, first engages the spring of the socket contact.

FIGURE 1. Dimensions and configuration - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:38Z
Check the source to verify that this is the current version before use.

TABLE I. Receptacle dimensions.

Shell size	M thread	S max	R thread class 2 left hand	DD dia basic	GG dia	HH thread class 2B
28	.164-32UNC	1.817	1.8750-16UN	2.104	2.439 2.428	.164-32UNC
32	.164-32UNC	1.817	1.8750-16UN	2.354	2.689 2.678	.164-32UNC
44	.250-28UNF	1.943	1.3125-16UNS	3.156	3.667 3.646	.250-28UNF
48	.250-28UNF	2.130	2.7500-16UN	3.406	3.917 3.896	.250-28UNF
52	.250-28UNF	2.193	3.0000-16UN	3.656	4.167 4.146	.250-28UNF

TABLE I. Receptacle dimensions - Continued.

Shell size	KK thread		JJ dia	EE dia	FF dia
	Class 2B	Modified minor dia			
28	.164-32UNC	.143/.137	.198 .187	1.693 1.687	1.776 1.765
32	.164-32UNC	.143/.137	.198 .187	1.943 1.937	2.026 2.015
44	.250-28UNF	.229/.223	.286 .275	2.693 2.687	2.776 2.765
48	.250-28UNF	.229/.223	.286 .275	2.943 2.937	3.026 3.015
52	.250-28UNF	.229/.223	.286 .275	3.193 3.187	3.276 3.265

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:38Z
Check the source to verify that this is the current version before use.

TABLE I. Receptacle dimensions - Continued.

Shell size	B dia max	G ± .005	C maximum		Packing preformed size 3/
			Phase and neutral	Ground	
28	1.281	1.514	.913	.913	MS29513-128
32	1.562	1.514	.913	.913	MS29513-132
44	2.239	1.733	1.138	.663	MS29513-144
48	2.494	1.733	1.156	.663	MS29513-148
52	2.744	1.733	1.156	.663	MS29513-151

TABLE I. Receptacle dimensions - Continued.

Shell size	Hex socket head size	AA dia	BB dia	CC dia min	LL	MM
28	9/64	1.685 1.674	1.539 1.531	1.405	.417 .406	.338 .322
32	9/64	1.935 1.924	1.789 1.781	1.655	.417 .406	.338 .322
44	3/16	2.685 2.674	2.539 2.531	2.405	.605 .594	.526 .510
48	3/16	2.935 2.924	2.789 2.781	2.655	.605 .594	.526 .510
52	3/16	3.185 3.174	3.039 3.031	2.905	.605 .594	.526 .510

TABLE II. "U" diameter by contact size.

Contact size	"U" diameter (metric equivalent in parentheses)
4/0	.510/.515 (12.95/13.08)
2/0	.416/.421 (10.57/10.69)
1/0	.367/.372 (9.32/9.45)
4	.235/.240 (5.97/6.10)
6	.188/.193 (4.78/4.90)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:38Z
Check the source to verify that this is the current version before use.

TABLE III. Accessory interface dimensions.

Shell size	Arrangement no.	E cable range	K approx free length	H + .001 - .010	L max free length	N dia + .011 -.020	F +.011 -.005	YY dia + .010 - .006	ZZ ± .035 free length
28	-02, -04 -03, -05, -06 -07, -12, -13	.844 / .719 .969 / .844 1.047 / .922 1.130 / 1.005	6.688 7.188 7.188 7.188	1.750	8.156	2.000	2.448	1.692	.562
32	-02, -04 -03, -05, -12 -06 -07 -13	.969 / .844 1.130 / 1.005 1.047 / .992 1.259 / 1.135 1.342 / 1.217	7.188 7.188 7.188 8.188 8.688	1.750	8.156	2.000	2.448	1.942	.562
44 1/ 2/	-02, -04 -03, -05 -06 -12 -13 -51	1.312 / 1.187 1.438 / 1.313 1.375 / 1.250 1.516 / 1.391 1.672 / 1.547 1.734 / 1.609	10.688 9.688 9.688 10.688 12.688 11.688	2.250	10.125	2.500	2.854	2.692	.672
48	-13	2.000 / 1.867	14.188	2.750	10.688	2.953	2.854	2.911	.672
52	-02 -06 -12 -13	1.703 / 1.558 1.797 / 1.652 2.328 / 2.183 2.453 / 2.308	13.688 13.688 17.188 18.188	2.875	11.062	3.250	2.854	3.161	.672

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:38Z
Check the source to verify that this is the current version before use.

TABLE III. Accessory interface dimensions - Continued.

Shell size	Arrangement no.	E cable range	K approx free length	A thread class 2A	D dia +-005 -.010	J +.020 - .030	
						Phase and neutral	Ground
28	-02, -04 -03, -05, -06 -07, -12, -13	.844 / .719 .969 / .844 1.047 / .922 1.130 / 1.005	6.688 7.188 7.188 7.188	2.0000- .1428P-2857L	1.536	.523	.523
32	-02, -04 -03, -05, -12 -06 -07 -13	.969 / .844 1.130 / 1.005 1.047 / .992 1.259 / 1.135 1.342 / 1.217	7.188 7.188 7.188 8.188 8.688	2.250- .1428P-.2857L	1.786	.523	.523
44 1/ 2/	-02, -04 -03, -05 -06 -12 -13 -51	1.312 / 1.187 1.438 / 1.313 1.375 / 1.250 1.516 / 1.391 1.672 / 1.547 1.734 / 1.609	10.688 9.688 9.688 10.688 12.688 11.688	3.000-.1428P-2857L	2.545	.742	.273
48	-13	2.000 / 1.867	14.188	3.250-.1428P-.2857L	2.755	.742	.273
52	-02 -06 -12 -13	1.703 / 1.558 1.797 / 1.652 2.328 / 2.183 2.453 / 2.308	13.688 13.688 17.188 18.188	3.500- 1428P-.2857L	3.005	.742	.273

1/ Arrangements 44-52 and 44-56 are for stub cable application only; they are not to be used in a cable.

2/ Arrangement 44-56 to include 4 each MS3348-1-6L contact bushings.

3/ SAE-AS29513 dash numbers are for dimensions only. Packing material utilized for specified O-rings shall meet the performance requirements of MIL-DTL-22992.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:38Z
Check the source to verify that this is the current version before use.

TABLE IV. Insert arrangements, crimp bushings, and contacts.

Insert arrangement	Contacts 1/		Cable conductors 1/		Contact bushing required	
	Quantity	Size	Quantity	Size	Quantity	PIN MS3348-
28-02	2	6	2	8	2	6-8L
28-04	2	6	2	8	2	6-8L
	1	6 (G)	2	10 (G)	---	---
28-06	3	6	3	8	3	6-8L
	1	4 (G)	3	12 (G)	1	4-8L
28-07	3	6	3	8	---	---
	1	4 (G)	3	10 (G)	4	4-5L
28-12	4	6	4	8	4	6-8L
	1	6 (G)	4	12 (G)	---	---
32-02	2	4	2	6	2	4-6L
32-04	2	4	2	6	2	4-6L
	2	6 (G)	2	10 (G)	2	4-10L
32-05	2	4	2	4	---	---
	2	6 (G)	2	8 (G)	2	6-8L
32-06	3	4	3	6	3	4-6L
	1	4 (G)	3	12 (G)	1	4-8L
32-12	4	4	4	6	4	4-6L
	1	6 (G)	4	12 (G)	---	---
44-02	2	1/0	2	2	2	1-2L
44-04	2	1/0	2	2	2	1-2L
	2	4 (G)	2	6 (G)	2	4-6L
44-05	2	1/0	2	1	---	---
	2	4 (G)	2	5 (G)	2	4-5L
44-06	3	1/0	3	2	3	1-2L
	3	6 (G)	3	8 (G)	3	6-8L
44-12	4	1/0	4	2	4	1-2L
	4	6 (G)	4	9 (G)	4	6-9L
44-13	4	1/0	4	1	---	---
	4	6 (G)	4	8 (G)	4	6-8L
44-52	3	1/0	3	2	3	1-2L
	1	1/0 (G)	1	2 (G)	1	1-2L
44-56	3	1/0	3	6	3	1-6L
	1	1/0 (G)	1	6 (G)	1	1-6L
52-02	2	4/0	2	2/0	2	4/0-2/0L
52-06	3	4/0	3	2/0	3	4/0-2/0L
	3	4 (G)	3	5 (G)	3	4-5L


1/ (G) designates grounding.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:38Z
Check the source to verify that this is the current version before use.


REQUIREMENTS:

Dimensions and configurations: See figures 1 and 2, and tables I, II, III and IV.
Mating: See MS90558 for mating plugs.
Inserts and contacts: Removable.
For final installation: Contacts will be assembled in all insert holes.
Shell and nut finish: See MIL-DTL-22992.
Normal keyway position: See figure 1.
Alternate keyway position: See figure 2.
Insert arrangements: See MS90565, MS14054. MS14055, and MS14057.
Cover: In accordance with MS90563. Cover shall be attached to cap screw on body.
Crimp bushings: Crimp contact bushings in accordance with SAE-AS39029/112 and table IV herein shall be supplied with the contacts.
Cable sealing gland: In accordance with MS23747. Shall be supplied with each connector.
Cable grip: In accordance with MS90561. Shall be supplied with each connector.
Socket contact: In accordance with SAE-AS39029/49.

PIN example:



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:38Z
Check the source to verify that this is the current version before use.



Finish N (non-grounding assemblies)

Shell size	Shell main keyway positions 2 wire, 28 Vdc
28	N (105°)
32	N (105°)
46	N (105°)
48	N (105°)
52	N (105°)

FIGURE 2. Alternate keyway position.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:38Z
Check the source to verify that this is the current version before use.

Finishes, conductive (grounding assemblies)

Shell size	Shell main keyway position (see note 3)						
	60 Hz and 400 Hz (see note 1)						
	1 ∅			3 ∅			3 ∅ (see note 2)
	2 wire		3 wire	4 wire			3 wire
	120 V	240 V	120/240 V	120/208 V	240/416 V	277/480 V	450/480 V
28	4 (120°)	5 (135°)	4 (120°)	4 (120°)	5 (135°)	6 (150°)	---
32	4 (120°)	5 (135°)	4 (120°)	4 (120°)	5 (135°)	6 (150°)	---
44	4 (120°)	---	4 (120°)	4 (120°)	5 (135°)	6 (150°)	1 (60°)
48	---	---	4 (120°)	4 (120°)	5 (135°)	6 (150°)	---
52	---	---	4 (120°)	4 (120°)	5 (135°)	6 (150°)	---

NOTES:

1. Discrimination of 60 Hz and 400 Hz assemblies is accomplished by alternate positioning of inserts. See applicable insert drawing for keying.
2. For Navy ground support equipment use only.
3. Shell main keyway positions 2 and 3 are not used.

FIGURE 2. Alternate keyway position - Continued.

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-DTL-22992, this document references the following:

MS14054
MS14055
MS14057
MS23747
MS90558
MS90561
MS90563
MS90565
SAE-AS29513
SAE-AS39029/49
SAE-AS39029/112

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:38Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – EC
Air Force – 85
DLA – CC

Preparing activity:
DLA – CC

(Project 5935-2024-124)

Review activities:
Army – AV, MI
Navy – AS, CG, MC, OS
Air Force – 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:38Z
Check the source to verify that this is the current version before use.