MILITARY SPECIFICATION

PILOCARPINE OPHTHALMIC DISKS

This specification is approved for use by the Defense Personnel Support Center, Defense Logistics Agency and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers Pilocarpine Ophthalmic Disks.

1.2 Classification. The ophthalmic disks covered by this specification shall be of the following strengths (see 6.2):

Strength 1 - 5 mg
Strength 2 - 11 mg

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-C-186 - Containers, Packaging and Packing for Drugs, Chemicals and Pharmaceuticals.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Hq, Defense Personnel Support Center, ATTN: Directorate of Medical Materiel, DPSC-ATT, 2800 S. 20th St., Phila., PA 19101, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document, or by letter.

FSC 6505

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:29Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposals shall apply.

U. S. DEPARTMENT OF HEALTH, EDUCATION, AND WELFARE, FOOD AND DRUG ADMINISTRATION (FDA)

Federal Food, Drug, and Cosmetic Act and Regulations Promulgated Thereunder.

(Application for copies should be addressed to the Food and Drug Administration, Washington, DC 20204.)

U. S. PHARMACOPEIAL CONVENTION, INC.

The United States Pharmacopeia (USP).

(Application for copies should be addressed to the Mack Publishing Company, Easton, PA 18042.)

The National Formulary (NF).

(Applications for copies should be addressed to the Mack Publishing Company, Easton, PA 18042.)

3. REQUIREMENTS

3.1 Material. The disk shall be a sterile, clear, elliptically shaped wafer with a white annular ring containing pilocarpine in the quantities specified herein. The disk (wafer) shall be designed for insertion into the cul-de-sac of the eye for continuous release of the pilocarpine following placement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:29Z
Check the source to verify that this is the current version before use.

Strength 1 - shall contain 5 mg pilocarpine per disk within the designated assay limits for the disks.

Strength 2 - shall contain 11 mg pilocarpine per disk within the designated assay limits for the disks.

3.1.1 Structure and components of the disk.

3.1.1.1 Strength 1. The disk shall contain a core reservoir consisting of 5 mg pilocarpine and alginic acid. The mixture of pilocarpine and alginic acid is prepared by casting into a film by a suitable method. The core shall be surrounded by an ethylene-vinyl acetate copolymer membrane which controls the diffusion of the pilocarpine into the eye. The disk shall measure nominally 5.7 mm (minor axis length) by 13.4 mm (major axis length) and 0.3 mm in thickness. The disk shall be surrounded by a white border consisting of ethylene-vinyl acetate copolymer membrane with titanium dioxide in the approximate quantities of 95 percent w/w ethylene-vinyl acetate copolymer and 5 percent w/w titanium dioxide.

3.1.1.2 Strength 2. The disk shall contain a core reservoir consisting of 11 mg pilocarpine and alginic acid. The mixture of pilocarpine and alginic acid is prepared by casting into a film by a suitable method. The core shall be surrounded by an ethylene-vinyl acetate copolymer membrane containing 20 percent w/w di (2-ethylhexyl) phthalate which controls the diffusion of the pilocarpine into the eye. The disk shall measure nominally 5.7 mm (minor axis length) by 13.4 mm (major axis length) and 0.5 mm in thickness. The disk shall be surrounded by a white border consisting of ethylene-vinyl acetate copolymer membrane with titanium dioxide in the approximate quantities of 95 percent w/w ethylene-vinyl acetate copolymer and 5 percent w/w titanium dioxide.

3.1.2 Assay and content uniformity.

3.1.2.1 Strength 1. Disks shall contain not less than 4.25 mg and not more than 5.75 mg per unit (disk) of pilocarpine when assayed as specified in 4.5.1.1 and shall comply with the requirements in the USP content uniformity test for capsules.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:29Z
Check the source to verify that this is the current version before use.

3.1.2.2 Strength 2. Disks shall contain not less than 9.4 mg and not more than 12.6 mg per unit (disk) of pilocarpine when assayed as specified in 4.5.1.2 and shall comply with the requirements in the USP content uniformity test for capsules.

3.1.3 Release rate. Strength 1 disks shall have a release rate of not less than 16 and not more than 24 mcg per hour of pilocarpine over a seven day period and strength 2 disks shall have a release rate of not less than 32 and not more than 48 mcg per hour of pilocarpine over a seven day period, when determined as specified in 4.5.2.

3.1.4 Identity. The pilocarpine in the ophthalmic disks shall comply with the following identification test. The infrared spectrum shall exhibit maxima only at the same wavelengths as a pilocarpine standard measured concomitantly when determined as specified in 4.5.3.

3.1.5 Sterility. The ophthalmic disks shall be sterile when tested in accordance with the USP sterility test method for parenteral devices except that Trypticase Soy Broth shall be used instead of Soybean-Casein Digest.

3.1.6 Impurities. The ophthalmic disks shall contain not more than 2 percent impurity when determined as specified in 4.5.4.

3.2 Ingredients.

3.2.1 Pilocarpine. The pilocarpine used in the manufacture of the ophthalmic disks shall comply with the following requirements.

3.2.1.1 Refractive index. Shall be not less than 1.5170 and not more than 1.5210 at 25°C using the USP method.

3.2.1.2 Specific rotation. Shall have a specific rotation of not less than + 102° and not more than + 106° at 25°C, calculated on the anhydrous basis using the USP method except 200 mg of pilocarpine is dissolved in 10 ml of pH 6.0 phosphate buffer.

3.2.1.3 Water. Shall have not more than 0.5 percent when tested using the USP Karl Fischer titrimetric method.

3.2.1.4 Sulfate. Shall have not more than 40 ppm when tested using the USP Sulfate method.

3.2.1.5 Nitrate. Shall have not more than 50 ppm when determined as specified in 4.5.5.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:29Z
Check the source to verify that this is the current version before use.

3.2.1.6 Impurities. Shall not be more than 2 percent when determined as specified in 4.5.5.2.

3.2.1.7 Isopilocarpine. Shall have not more than 2 percent isopilocarpine when tested by a suitable accurate reproducible high-pressure liquid chromatographic method using 20 ul of solution prepared by dissolving 200 mg pilocarpine in 10 ml of 1 percent pH 6.0 phosphate buffer. The peak area corresponding to the isopilocarpine in the sample is no more than 2 percent of the peak area corresponding to the pilocarpine sample.

3.2.1.8 Identity. The infrared absorption spectrum prepared by spreading one drop of pilocarpine base over a salt crystal (NaCl plate) exhibits maxima and minima only at the same wavelengths as that of a similar preparation of a pilocarpine standard measured concomitantly.

3.2.1.9 Assay. Shall assay to contain not less than 99.0 percent and not more than 100.5 percent of pilocarpine, calculated on the anhydrous basis when determined as specified in 4.5.5.3.

3.3 Ingredients. All ingredients used in the manufacture of the ophthalmic disks shall be in accordance with the tests, standards, and requirements of the USP or NF, including any supplements or revisions thereto; or, if not included in either of these compendia, the ingredients shall be of the highest pharmaceutical grade.

3.4 Expiration dating period. The expiration dating period shall be not less than 24 months.

3.4.1 Delivery. Not more than 3 months of the expiration dating period shall have elapsed at the time of delivery to the Government.

3.5 Workmanship. The material and its containers shall be free from defects which detract from their appearance or may impair their serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Supplier responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities

Source: https://assist.dla.mil -- Downloaded: 202610-21T11:29Z
Check the source to verify that this is the current version before use.

suitable for the performance of the inspection requirements specified herein, unless disapprcved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government, upon the Government's request, at any time, or from time to time, during the performance of the contract and, (i) as to any expiration dated item, for the expiration dating period specified by the contractor for such item, or such longer period as may be required by regulation of any federal agency; or (ii) as to non-dated items, for not less than 3 years after delivery of the item to the Government.

4.1.2 No company supplying any ingredient(s) to the contractor will be considered an acceptable facility for the performance of any inspection requirements specified herein.

4.2 Lot. For purposes of this specification, a lot, batch, or control is that single, uniform, and homogeneous quantity of ophthalmic disks produced from one formulation, subjected to the same compounding and manufacturing operation, and filled into final containers.

4.3 Sampling. Sampling shall be conducted in accordance with MIL-STD-105.

TABLE I. Sampling.

For visual examination	Inspection level	AQL (percent defective)	Unit of product
Major	S-2	1.0	Filled immediate container
Minor	II	2.5	Filled immediate container

Source: https://assist.dla.mil -- Downloaded: 202610-21T11:29Z
Check the source to verify that this is the currentversion before use.

4.3.1 Raw material and end item testing. Noncompliance with any of the following is cause for rejection.

TABLE II. Criteria for raw material and end item testing.

Characteristic	Requirement paragraph	Inspection level 1/	Minimum sample
Assay and Content Uniformity	3.1.2	S-2	5 Composite
Release Rate	3.1.3		
Identity	3.1.4		
Impurities	3.1.6		
Sterility	3.1.5	USP	USP
Ingredient: Pilocarpine	3.2.1	2/	

1/ Where possible, the sample shall be used for two or more tests.
2/ Sufficient quantities of each of the raw materials shall be selected from each lot to perform tests indicated in applicable test methods. Failure of any sample to comply with test requirements shall be cause for rejection of the lot represented.

4.4 Examination. The finished ophthalmic disks shall be examined to determine compliance with all requirements of this specification. Non-conformance will be permitted to the extent indicated in 4.3 and 4.3.1.

4.4.1 Classification of defects. Examination will be conducted in accordance with the following classification of defects:

TABLE III. Classification of defects.

Categories	Defects 1/
Major	
101	Disks not free from foreign matter.
102	Disks do not have required dimensions.
103	Core of disks is not clear.
104	Lack of white annular ring surrounding core.
Minor	
201	Exterior of immediate container is not free from contents or foreign matter.
202	Label not free from defacing marks and tears.

1/ Inspection is not restricted to the classified possible defects listed above.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:29Z
Check the source to verify that this is the current version before use.

4.5 Tests.

4.5.1 Test for ophthalmic disks.

4.5.1.1 Assay and content uniformity for strength 1.

Select 10 disks and transfer each disk to individual 250 ml volumetric flasks. Add 5.0 ml of menthanol to each flask. The flasks are heated until the disks break apart (do not heat for more than 1 hour) and then cool to room temperature. Add purified water to dissolve the pilocarpine, then add sufficient purified water to make up to volume and filter. Prepare a standard containing about 23 mcg per ml of Pilocarpine Hydrochloride working standard, previously dried to constant weight in vacuum at 80°C, accurately measured, in purified water containing 5.0 ml of methanol in each 250 ml of purified water. This standard solution and each test sample solution are concomitantly measured at the peak of maximum absorption, at about 215 nm in a suitable spectrophotometer in 1 cm cell, using purified water containing 2 percent methanol as the blank. The average content of the 10 samples shall be within the limits as specified in 3.1.2.1. In addition, the 10 samples shall comply with the limits and the requirements of the USP Content Uniformity Test for Capsules. The content of pilocarpine in the samples is calculated as follows:

$$\text{mg Pilocarpine/disk} = \frac{Au}{As} \times 0.851\ C \times .25$$

Where Au = abosrbance of the sample solution.
As = absorbance of the standard solution.
C = concentration of the standard, mcg/ml.
0.851 = conversion factors.

4.5.1.2 Assay and content uniformity for strength 2.

Select 10 disks and transfer each disk to individual 100 ml volumetric flasks each containing about 10 ml of purified water. The flasks are heated until the disks break apart (do not heat for more than 1 hour) and then cool to room temperature. Add purified water to make up to volume and filter. Prepare a standard containing about 120 mcg per ml of Pilocarpine Hydrochloride working standard previously

Source: https://assist.dla.mil -- Downloaded: 202640-21T11:29Z
Check the source to verify that this is the current version before use.

dried to constant weight in vacuum at 80°C, accurately measured, in purified water. This standard solution and each test sample solution are concomitantly measured at the peak of maximum absorption, at about 215 nm in a suitable spectrophotometer in 2 mm cell, against a reagent blank (purified water). The average content of the 10 samples shall be within the limits specified in 3.1.2.2. In addition the 10 samples shall comply with the limits and the requirements of the USP Content Uniformity Test for Capsules. The content of pilocarpine in the sample is calculated as follows:

$$\text{mg Pilocarpine/disk} = \frac{Au}{As} \times 85.1\ C$$

Where: Au = absorbance of the sample solution.
As = absorbance of the standard solution.
C = concentration of the standard in mg/ml.
85.1 = conversion factor.

4.5.2 Release rate of Pilocarpine for strength 1 and strength 2 disks.

Place each of 10 disks into separate suitable porous holders made of an inert material and suspend each from a nickel wire. To the upper end of the wire attach a tag identifying the sample. Put each assembly into a test tube containing 27.0 ml of 0.9 percent aqueous NaCl solution so that the disk lies at the bottom of the tube and the identifying tag extends from the open top of the tube. Put the loaded tubes into a horizontally reciprocating shaker in which the temperature is controlled at 37° + 1° C. Agitate the tubes with a horizontal amplitude of about 4 cm and a frequency of about 35 cycles per minute. At time intervals of 0-7 hours, 7-24 hours, 24-48 hours, 48-72 hours, 72-96 hours and 96-168 hours remove the assemblies from their tubes and place them in tubes containing 27.0 ml of fresh 0.9 percent NaCl solution. Assay the solutions for pilocarpine content after adjusting the volume to make up for any evaporative losses. For strength 1 disks, concomitantly measure the ultraviolet absorption of a solution of pilocarpine hydrochloride working standard (previously dried to constant weight in vacuum at 80°C, containing about 20 mcg in each ml

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:29Z
Check the source to verify that this is the current version before use.

of 0.9 percent NaCl solution accurately measured) and the sample solutions at the peak of maximum absorption, at about 215 nm in a suitable spectrophotometer in 1 cm cells against aqueous 0.9 percent NaCl solution as the blank. For strength 2 disks concomitantly measure the ultraviolet absorption of a solution of pilocarpine hydrochloride working standard, (previously dried to constant weight in vacuum at 80°C, containing about 46 mcg in each of 0.9 percent NaCl solution accurately measured) and the sample solutions at the peak of maximum absorption, at about 215 nm in a suitable spectrophotometer in 2 mm cells against aqueous 0.9 percent NaCl solution as the blank.

Note: The sample solutions and standard solution may be appropriately diluted and read in 1 cm cells. For strength 1 and strength 2 disks, the quantities of Pilocarpine released in 0-24 hours, 24-96 hours, and 96-168 hours are calculated. The average release rate for strength 1 disks from 0-24 hours is 30 $\pm$ 6 mcg/hour, from 24-96 hours is 20 $\pm$ 4 mcg/hour and from 96-168 hours is 15 $\pm$ 3 mcg/hour. The average release rate for strength 2 disks from 0-24 hours is 68 $\pm$ 14 mcg/hour, from 24-96 hours is 42 $\pm$ 8 mcg/hour and from 96-168 hours is 34 $\pm$ 7 mcg/hour. The average release rate of the ten (10) strength 1 and strength 2 disks over 168 hours (seven days) shall be within the limits specified in 3.1.3.

Calculate the pilocarpine released in the solutions as follows:

$$\text{mcg pilocarpine released} = \frac{Au \times 0.851\ C \times 27}{As}$$

Where: Au = absorbance of the sample solution.
As = absorbance of the standard solution.
C = concentration of the standard in mcg/ml.
0.851 = conversion factor.

4.5.3 Identity for pilocarpine in strength 1 and strength 2 disks. Cut one disk around the inside of the white annular ring so that a smaller ellipse remains consisting of two layers of outer film sandwiching the inner drug core. The three film layers are vigorously shaken in a small capped vial with 0.5 ml of anhydrous methanol for 1 or 2 minutes. The methanol solution is evaporated on a NaCl plate and the infrared spectrum of the residue is recorded. Concomitantly record the infrared spectrum of pilocarpine standard similarly prepared.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:29Z
Check the source to verify that this is the current version before use.

4.5.4 Impurities for strength 1 and strength 2 disks. Transfer two (2) strength 1 disks or one (1) strength 2 disk which are/is cut in half, to a small stoppered flask with 2.0 ml of methanol. Shake for about 3 minutes to dissolve the pilocarpine (Solution A). Dilute this solution 1 to 10 with methanol (Solution B). Divide a 20 cm x 20 cm TLC plate, coated with a 250 micron layer of silica gel, into 10 sections 2 cm apart. In the first section, on a line 2 cm from the lower edge of the plate, spot 40 ul of the solvent (methanol) and in subsequent sections spot 40, 20, 10, and 2 ul of Solution A, then spot 10, 8, 4, 2, and 1 ul of Solution B. Develop the plate in a suitable pre-equilibrated TLC chamber with a solvent system consisting of methanol - 1 percent pH 6.0 phosphate buffer (pHydrion buffer concentrate), 9:1 (v/v), until the solvent front has traveled 10 cm above the point of application of the spots. Remove the plate and air dry. Spray the dried plate with Dragendorff's Reagent(modified). Any impurities seen in the 40 ul spot are, in total, no greater in size or intensity than the major spot produced by the 8 ul sample.

4.5.5 Test for pilocarpine.

4.5.5.1 Nitrate. Prepare a standard solution of pilocarpine nitrate in purified water containing 43 mcg per ml. This solution contains the equivalent of 10 mcg of nitrate ion (NO_3) in each ml. Prepare a sample solution of pilocarpine in purified water containing 200 mg per ml. Transfer 0.5 ml of the sample and the standard each to separate small test tubes and to each tube add 1 drop of a 1 percent sulfanilic acid solution in 30 percent acetic acid and 1 drop of a 0.3 percent solution of N-(1-naphthyl) ethylenediamine dihydrochloride in 30 percent acetic acid. Add a few granules of nitrate-free zinc to each solution and 1 to 2 drops of 1:1 hydrochloric acid. Allow five minutes for the development of a pink color. Any pink color observed in the sample is no greater than that in the standard.

4.5.5.2 Impurities. Dissolve 100 mg of pilocarpine, accurately weighed, in 10 ml of methanol (Solution A) and dilute 1.0 ml of this solution to 20 ml with methanol (Solution B). Divide a 20 cm x 20 cm TLC plate, coated with a 250 micron layer of silica gel, into 10 sections, 2 cm apart. In the first section, on a line 2 cm from the lower edge of the plate and parallel to it, spot 10 ul of the solvent (methanol) and in subsequent sections spot 10, 5 and 1 ul of Solution A and then 10, 4, 2 and 1 ul of Solution B equivalent to 100, 50, 10, 5, 2, 1 and 0.5 mcg of pilocarpine. Develop the plate in a suitable pre-equilibrated TLC chamber with a solvent system consisting of methanol - 1 percent pH 6.0 phosphate buffer (pHydrion buffer concentrate, pH 6.0) 9:1 (v/v), until the solvent front has traveled 15 cm above the point of application of the spots. Remove the plate and air dry. Spray the dried plate with Dragendorff's Reagent (modified). Any impurities seen in the

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:29Z
Check the source to verify that this is the current version before use.

200 mcg spot are, in total, no greater in size or intensity than the major spot produced by the 2 mcg sample.

4.5.5.3 Assay. Dissolve about 100 mg, accurately weighed, in 25 ml of glacial acetic acid. Titrate potentiometrically with 0.05N perchloric acid in glacial acetic acid. Perform a blank titration and make any necessary correction. Calculate the percentage of pilocarpine in the sample taken by the following formula:

$$\text{percent pilocarpine} = \frac{V \times N \times 2.08 \times 10^4}{W}$$

Where: V = ml of perchloric acid required to titrate the sample.
N = normality of the perchloric acid.
W = weight of the sample in mg.

4.6 Packaging inspection. The inspection of the intermediate package, packing and marking for shipment and storage shall be in accordance with quality assurance provisions of the applicable container specification and the marking requirements of MIL-STD-129.

4.7 Labeling inspection. Sampling shall be in accordance with MIL-STD-150 and the unit of product shall be the unit of issue. The inspection lot shall be the number of units of issue of each batch, lot, control number, etc., offered for inspection at one time. The inspection level for labeling shall be S-2 and the acceptance number shall be zero.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with all applicable requirements of PPP-C-186, and as specified herein.

5.2 Packaging. Packaging shall be level A or C, as specified (see 6.1).

5.2.1 Unit of issue. One box containing eight ophthalmic disks, as specified, constitutes one unit of issue.

5.2.2 Level A.

5.2.2.1 Immediate container. The immediate container shall be a commercially available immediate container considered acceptable by the Food and Drug Administration (FDA) for the product contained therein and shall be of such compatibility that neither the contents nor the container are altered in any way by each other.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:29Z
Check the source to verify that this is the current version before use.

5.2.2.2 Unit package. Each unit shall be packaged as specified in 5.2.5 of PPP-C-186.

5.2.2.3 Intermediate package. Twelve (12) units of issue of strength 1 or strength 2 shall be packaged as specified in 5.2.9 of PPP-C-186.

5.2.3 Level C. Units shall be packaged in standard commercial containers of the size and kind commonly used, which will afford the degree of protection required for shipment and use of the product for its intended purpose.

5.3 Packing. Packing shall be level A, B or C, as specified (see 6.1).

5.3.1 Level A. Thirty-six (36) units of issue of strength 1 or strength 2 shall be packed as specified in 5.4.4 of PPP-C-186.

5.3.2 Level B. Thirty-six (36) units of issue of strength 1 or strength 2 shall be packed as specified in 5.4.3.2 of PPP-C-186.

5.3.3 Level C. The subject commodity shall be packed in substantial commercial containers of the type, size, and kind commonly used for the purpose, so constructed as to insure acceptance and safe delivery by common or other carriers, at the lowest rate, to point of delivery called for in the contract or purchase order.

5.4 Marking.

5.4.1 Labeling. Labeling shall be in accordance with the requirements of the Federal Food, Drug and Cosmetic Act and shall include the information required below:

5.4.1.1 Immediate container: Each immediate container label shall bear the following information:

(a) label information in accordance with commercial practice.

5.4.1.2 Unit package. Each unit package label shall bear the following information:

(a) label information in accordance with commercial practice.

(b) the National Stock Number.

(c) the expiration date.

Source: https://assist.dla.mil -- Downloaded: 202610-21T11:29Z
Check the source to verify that this is the currentversion before use.

NOTES: (1) The National Stock Number shall not be preceded by any prefix.
(2) Strip labeling may be used.
(3) Label adhesion test shall not apply.

5.4.2 Intermediate package. Each intermediate package shall be marked as specified in 5.5.3 of PPP-C-186. Type I shelf life markings shall be shown as specified in MIL-STD-129. Marking shall include the legend:

"STORE BETWEEN 2°-8°C (35°-46°F)".

5.4.3 Exterior container. Exterior container shall be marked as specified in 5.5.4 of PPP-C-186. Type I shelf life marking shall be shown as specified in MIL-STD-129. Marking shall include the legend:

"STORE BETWEEN 2°-8°C (35°-46°F)".

NOTE: Subject material shall be shipped under constant chill 2°-8°C (35°-46°F)".

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) National Stock Number.
(c) Selection of applicable levels of packaging and packing (see 5.2 and 5.3).

6.2 This specification covers the following items:

National Stock Number	Item Identification	Specification Designation
6505-01-032-1330	PILOCARPINE OPHTHALMIC DISKS, 5 mg, 8s	Strength 1
6505-01-032-1331	PILOCARPINE OPHTHALMIC DISKS, 11 mg, 8s	Strength 2

Preparing activity:
DLA-DM

Project No. 6505-1930

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:29Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL	OMB Approval No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE
MIL-P-37764(DLA-DM) PILOCARPINE OPHTHALMIC DISKS

NAME OF ORGANIZATION AND ADDRESS	CONTRACT NUMBER
	MATERIAL PROCURED UNDER A ☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

YES NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-21T11:29Z
Check the source to verify that this is the current version before use.

FOLD

DEFENSE PERSONNEL SUPPORT CENTER
2800 SOUTH 20TH STREET
PHILADELPHIA, PA. 19101

POSTAGE AND FEES PAID
DEFENSE SUPPLY AGENCY
DoD - 304

U.S. MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

HEADQUARTERS, DEFENSE PERSONNEL SUPPORT CENTER
ATTN: DIRECTORATE OF MEDICAL MATERIEL, CODE ATT
2800 SOUTH 20TH STREET
PHILADELPHIA, PA. 19101

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:29Z
Check the source to verify that this is the current version before use.