INCH-POUND

MIL-DTL-41819/24F
3 January 2018
SUPERSEDING
MIL-DTL-41819/24E
25 February 2013

DETAIL SPECIFICATION SHEET

RIBBON ATTACHMENT, BRAVERY U.S. NAVY

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-R-41819.

MATERIAL: Red Brass 85/15 (UNS Alloy No.C-230) or Nickel Silver 65/15 (UNS Alloy C-752)

FINISH: Nickel Plated (C-230 only), Silver Plated, Oxidized, Buffed Relieved, Matte Finish, Polished Highlights (Letters) and shall match The Institute of Heraldry Metal Finish Chip Number 15.

DIMENSIONS:
HEIGHT: 9/32 inch (REF)
WIDTH: 1- 3/8 inches (REF)
THICKNESS (On letters): 0.070 ± 0.005 inch

ATTACHMENT DEVICE:
The attaching device shall be located on the horizontal center line of the ribbon attachment with the prongs equidistant from the edges and 7/8 inch ± 1/32 inch apart.

NOTES:
The term (REF) refers to the measurements taken from the Government furnished hub or die.

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:53Z
Check the source to verify that this is the current version before use.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Navy - NU

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2018-092)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:53Z
Check the source to verify that this is the current version before use.