NOT MEASUREMENT SENSITIVE

MIL-DTL-41819/26E
30 September 1996
SUPERSEDING
MIL-R-41819/26D
1 November 1994

DETAIL SPECIFICATION SHEET

RIBBON ATTACHMENT, ADDITIONAL AWARDS (LAMP), JROTC, ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-41819 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

MATERIAL:
-1, -3: Red Brass or Gilding Metal
-2: Red Brass or Nickel Silver

DASH NO.
-1: Bronze (2nd Award)
-2: Silver (3rd Award)
-3: Gold (4th Award)

DIMENSIONS:
HEIGHT: 9/64 inch (0.36 cm) (REF)
WIDTH: 1/4 inch (0.64 cm) (REF)
THICKNESS (At Thickest Point): 0.050 inch ± 0.005 inch (0.127 cm ± 0.012 cm)

FINISH:
-1: Copper Flash (Red Brass Only), Oxidized, Relieved.
-2: Nickel Plated (Red Brass Only), Mirror-like Polished and shall match TIOH Metal Finish Chip Number 16.
-3: Gold Polished, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:54Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The attaching device shall be a staple type prong. The prong shall be located on the vertical center line on the reverse side of the ribbon attachment.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0863)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:54Z
Check the source to verify that this is the current version before use.