NOT MEASUREMENT SENSITIVE

MIL-DTL-41819/29C
30 September 1996
SUPERSEDING
MIL-R-41819/29B
1 November 1994

DETAIL SPECIFICATION SHEET

RIBBON ATTACHMENT, AFROTC DRILL TEAM AND COLOR GUARD BARS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-41819 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

-1

-2

MATERIAL: Red Brass or Gilding Metal

DASH NO.
-1: Drill Team Bar
-2: Color Guard Bar

DIMENSIONS:
HEIGHT (Overall): 1/8 inch (0.32 cm) (REF)
WIDTH (Overall): 13/16 inch (2.06 cm) (REF)
THICKNESS (At Thickest Point): 0.050 inch + 0.010 inch - 0 (0.127 cm ± 0.025 cm - 0)

FINISH: Copper Flash (Red Brass only), Oxidized, Relieved, Matte Finish.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The attaching device shall be two prongs. The prongs shall be located on the reverse side of the ribbon attachment at the horizontal center line of the bar equidistant from each end and 5/8 inch ± 1/32 inch (1.59 cm ± 0.08 cm) apart.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:55Z
Check the source to verify that this is the current version before use.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
Air Force - 45

Preparing activity:
Army - IH

Review activities:
Air Force - 32, 82, 99
DLA - CT

(Project No. 8455-0863)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:55Z
Check the source to verify that this is the current version before use.