NOT MEASUREMENT SENSITIVE

MIL-DTL-41819/31C
30 September 1996
SUPERSEDING
MIL-R-41819/31B
1 November 1994

DETAIL SPECIFICATION SHEET

RIBBON ATTACHMENT, NAVY “E”

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-41819 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

-1

-2

MATERIAL: Red Brass or Nickel Silver

DASH NO.
-1: Letter E
-2: Letter E with Wreath

DIMENSIONS:
HEIGHT (Overall):
-1: 3/16 inch (0.48 cm) (REF)
-2: 1/4 inch (0.64 cm) (REF)
WIDTH (Overall):
-1: 1/8 inch (0.32 cm) (REF)
-2: 1/4 inch (0.64 cm) (REF)
THICKNESS (At Thickest Point): 0.055 inch ± 0.005 inch (0.140 cm ± 0.012 cm)

FINISH: Nickel Plated (Red Brass Only), Silver Plated, Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Number 14.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:56Z
Check the source to verify that this is the current version before use.

2. The attaching device shall be a staple type prong located on the horizontal center line of the reverse side of the ribbon attachment.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
Navy - NU

Preparing activity:
Army - IH

Review activities:
Navy - MC
DLA - CT

(Project No. 8455-0863)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:56Z
Check the source to verify that this is the current version before use.