NOT MEASUREMENT SENSITIVE

MIL-DTL-41819/33C
30 September 1996
SUPERSEDING
MIL-R-41819/33B
1 November 1994

DETAIL SPECIFICATION SHEET

RIBBON ATTACHMENT, LETTER "E"

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-41819 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.



MATERIAL: Red Brass

DIMENSIONS:
HEIGHT (Overall): 5/16 inch ± 1/64 inch (0.79 cm ± 0.04 cm)
WIDTH (Overall): 5/16 inch ± 1/64 inch (0.79 cm ± 0.04 cm)
THICKNESS: 0.050 inch ± 0.005 inch (0.127 cm ± 0.012 cm)

FINISH: Oxidized, Relieved Matte Finish and shall match TIOH Metal Finish Chip Number 4.

NOTES:
1. Ribbon attachment "E" shall be die cut.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:57Z
Check the source to verify that this is the current version before use.

2. This ribbon attachment is intended to be worn on the Navy Rifle and Pistol Marksmanship Ribbon and National Oceanographic and Atmospheric Association (NOAA) Engineering Award.

3. The attaching device shall be a staple type prong. The prong shall be centered on the reverse side of the ribbon attachment at the short middle leg of the "E".

3. The attaching device shall be a staple type prong. The prong shall be centered on the reverse side of the ribbon attachment.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
Navy - NU

Preparing activity:
Army - IH

Review activities:
Navy - MC
Coast Guard - CG
DLA - CT

(Project No. 8455-0863)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:57Z
Check the source to verify that this is the current version before use.