NOT MEASUREMENT SENSITIVE


MIL-DTL-41819/33E
3 February 2021
SUPERSEDING
MIL-DTL-41819/33D
23 March 2016

DETAIL SPECIFICATION SHEET

RIBBON ATTACHMENT, LETTER “E”

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-R-41819.



MATERIAL: Red Brass 85/15 (UNS Alloy No.C-230)

FINISH: Brass, Oxidized, Buffed Relieved and shall match TIOH Metal Finish Chip Number 4.

DIMENSIONS:
HEIGHT (Overall): 5/16 inch (REF)
WIDTH (Overall): 5/16 inch (REF)
THICKNESS (At thickest point): 0.050 inch ± .005 inch

ATTACHING DEVICE:
1: The attaching device shall be a staple type prong

2: The prong shall be centered on the reverse side of the ribbon attachment at the short middle leg of the "E".

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:56Z
Check the source to verify that this is the current version before use.

NOTES:
1: The term (REF) refers to the measurements taken from the Government furnished hub or die.

2: Ribbon attachment "E" shall be die cut.

3: Ribbon attachment is intended to be worn on the Navy Rifle and Pistol Marksmanship ribbon. And intended to be worn on the NOAA Engineering award.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Navy - MC

Preparing activity:
Army - IH

Review activities:
Navy - CG1
DLA - CT

(Project No. 8455-2021-188)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:56Z
Check the source to verify that this is the current version before use.