NOT MEASUREMENT SENSITIVE

MIL-DTL-41819/36D
12 April 2021
SUPERSEDING
MIL-DTL-41819/36C
28 March 2016

DETAIL SPECIFICATION SHEET

RIBBON ATTACHMENT, EXCELLENCE IN COMPETITION, PISTOL SHOT, U.S. COAST GUARD

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-R-41819.



DASH NO.
-1: Bronze, 1ST Award
-2: Silver, 2nd Award

MATERIAL: Red Brass 85/15 (UNS Alloy No.C-230)

FINISH:
-1: Brass, Oxidized, Buffed Relieved and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 4.

-2: Silver Plated, Oxidized, Buffed Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14.

DIMENSIONS:
HEIGHT: 9/32 inch (REF)
WIDTH: 15/32 inch (REF)
THICKNESS (At thickest point): 0.080 inch $\pm$ .005 inch

ATTACHING DEVICE:
1: The attaching device shall be a staple type prong.

2: The prong shall be centered on the reverse side of the ribbon attachment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:57Z
Check the source to verify that this is the current version before use.

NOTE:
The term (REF) refers to the measurements taken from the Government furnished hub or die.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Navy - CG1

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2021-327)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:57Z
Check the source to verify that this is the current version before use.