MILITARY SPECIFICATION

RAINCOAT, MAN'S, LIGHTWEIGHT, COATED

This amendment forms a part of Military Specification MIL-R-29103B dated 12 February 1980

Page 1

2.1, SPECIFICATIONS, Federal
Add "V-T-276, Thread, Cotton"

Page 2

2.1, SPECIFICATIONS, Military - Delete "MIL-C-326-Cloth, Silesia, Cotton" and substitute "MIL-C-43718, Cloth, Twill, Polyester; Polyester and Cotton; Polyester and Rayon".
MIL-T-43548 - After "Cotton-covered" add "and Rayon covered"

Page 3

3.3.3, At the end of paragraph add "As an alternate, the binding cloth may be woven of type 66 nylon and 70 denier yarns conforming to the following minimum requirements:

Weight, oz. per sq. yd	- 1.8
Yarns per inch	
Warp	- 102
Filling	- 86
Colorfastness to:	
Perspiration	- Good
Wet dry cleaning	- Good
Crocking	- Good
Laundering	- Good

3.3.4, line 2 - Delete "type I of MIL-C-326" and substitute "class 1 of MIL-C-43718"

Page 4

3.3.6, line 1 - Following "cotton covered" add "and rayon covered"

Line 10 - Add "as alternates the thread for buttonholes may be type I, IC2, size A, 3 ply and the thread for the buttons may be type I, IB3, size 30, 4 ply of V-T-276. The shade for both alternate threads shall be Black AA, Cable No. 66043

FSC 8405

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:28Z
Check the source to verify that this is the current version before use.

Page 5

3.3.11.1, line 2 - Delete "type I" and substitute "type VI".
3.3.11.2, line 2 - Delete "type I" and substitute" type VI".

Page 12

Table I, op. 8b - Delete in its entirety and substitute:

"8b Join the topsleeve and undersleeve at the inseam. The folded edge shall face towards the back of the sleeve.

301	or	LSq-2	or,	8-10	,	70	,	70
401		LSr-2	or,			70	,	80 ".
		LSc-2						

Table I, op. 9a - Under Seam and Stitching Type add "or LSc-2".

Page 17

Table I, op. 13d, line 4 - Delete "underside" and substitute "upperside". Under their respective columns add " or 401, -, -, 70, 80"

Add new operation "Stitch top edge of tab to facing with stitchline superimposed on the edge stitching of tab.

301,	-	8-10,	70,	70".

Page 19

Table I, op. 18b - Description of Operation - Add new sentence "As an alternate, the eyelet reinforcement piece may be cemented into position".

Table I, op. 18c - Description of Operation - Add new sentence "As an alternate, the raw edge of the sleeve may be bound before setting the sleeve in the armhole".

Table I, oper 18d - Description of Operation -

Line 1 - Delete "and shoulder strap"
Line 4 - Delete "shoulder strap and binding" and substitute "binding and, when applicable, the armhole seam allowance."
Line 6 - Delete "strap" and substitute "shoulder".
At end of paragraph add "The shoulder straps shall not be caught in the topstitching".

Page 20

Table I, op. 20a - Delete description of operation and substitute:

"a. Position bottom stitched raw edge of assembled collar between the outershell (back with yoke) and facing and stitch to neckline 3/16 to 1/4 inch from raw edges. Notching the seam allowance is permitted."

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:28Z
Check the source to verify that this is the current version before use.

op. 20b - Delete operation in its entirety and substitute:

"b. Turn collar and body to finished position. Turn seam allowances of neckline seam towards bottom of raincoat and topstitch body 1/16 to 1/8 inch from folded edge. The folded edge of seam shall finish towards the collar. (see operation 5b)."

Page 22

Table I, op. 24b - Under "Thread" add "or A/3"

Page 23

Table I, op. 25 , line 2 - following word "top" add ", center,". At end of paragraph add "The top and bottom tacks shall catch both plys of the pocket and the center tack shall catch only the inner ply (next to facing) of the pocket.

op. 27a,b,c, and d - Under "Thread" add "or 30"

Page 32

5.2.1, line 3 - Delete "SF" and substitute "CF". Following word "resistant" add "variety DW"
line 4 - Delete "V2s" and substitute "V15c"

5.2.2, line 3 - Following word "to" add "type CF, class domestic, variety DW," Following "MIL-B-17757" add new sentence: "The fiberboard for the liner shall be type CF, class domestic, in accordance with the requirements specified in MIL-B-17757".

Custodian:
Navy - NU

Preparing activity:
Navy - NU

Project No. 8405-N928

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:28Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:28Z
Check the source to verify that this is the current version before use.